

300-710 Dumps

Securing Networks with Cisco Firepower (SNCF)

<https://www.certleader.com/300-710-dumps.html>



NEW QUESTION 1

Which two conditions are necessary for high availability to function between two Cisco FTD devices? (Choose two.)

- A. The units must be the same version
- B. Both devices can be part of a different group that must be in the same domain when configured within the FMC.
- C. The units must be different models if they are part of the same series.
- D. The units must be configured only for firewall routed mode.
- E. The units must be the same model.

Answer: AE

NEW QUESTION 2

What are the minimum requirements to deploy a managed device inline?

- A. inline interfaces, security zones, MTU, and mode
- B. passive interface, MTU, and mode
- C. inline interfaces, MTU, and mode
- D. passive interface, security zone, MTU, and mode

Answer: C

NEW QUESTION 3

Which two deployment types support high availability? (Choose two.)

- A. transparent
- B. routed
- C. clustered
- D. intra-chassis multi-instance
- E. virtual appliance in public cloud

Answer: AB

NEW QUESTION 4

Which protocol establishes network redundancy in a switched Firepower device deployment?

- A. STP
- B. HSRP
- C. GLBP
- D. VRRP

Answer: A

NEW QUESTION 5

Which interface type allows packets to be dropped?

- A. passive
- B. inline
- C. ERSPAN
- D. TAP

Answer: B

NEW QUESTION 6

Which two dynamic routing protocols are supported in Firepower Threat Defense without using FlexConfig? (Choose two.)

- A. EIGRP
- B. OSPF
- C. static routing
- D. IS-IS
- E. BGP

Answer: CE

NEW QUESTION 7

Which two OSPF routing features are configured in Cisco FMC and propagated to Cisco FTD? (Choose two.)

- A. OSPFv2 with IPv6 capabilities
- B. virtual links
- C. SHA authentication to OSPF packets
- D. area boundary router type 1 LSA filtering
- E. MD5 authentication to OSPF packets

Answer: BD

NEW QUESTION 8

When creating a report template, how can the results be limited to show only the activity of a specific subnet?

- A. Create a custom search in Firepower Management Center and select it in each section of the report.
- B. Add an Input Parameter in the Advanced Settings of the report, and set the type to Network/IP.
- C. Add a Table View section to the report with the Search field defined as the network in CIDR format.
- D. Select IP Address as the X-Axis in each section of the report.

Answer: B

NEW QUESTION 9

Which two routing options are valid with Cisco Firepower Threat Defense? (Choose two.)

- A. BGPv6
- B. ECMP with up to three equal cost paths across multiple interfaces
- C. ECMP with up to three equal cost paths across a single interface
- D. BGPv4 in transparent firewall mode
- E. BGPv4 with nonstop forwarding

Answer: AC

NEW QUESTION 10

Which object type supports object overrides?

- A. time range
- B. security group tag
- C. network object
- D. DNS server group

Answer: C

NEW QUESTION 10

Which Cisco Firepower rule action displays an HTTP warning page?

- A. Monitor
- B. Block
- C. Interactive Block
- D. Allow with Warning

Answer: C

NEW QUESTION 14

Which Firepower feature allows users to configure bridges in routed mode and enables devices to perform Layer 2 switching between interfaces?

- A. FlexConfig
- B. BDI
- C. SGT
- D. IRB

Answer: D

NEW QUESTION 16

In which two places can thresholding settings be configured? (Choose two.)

- A. on each IPS rule
- B. globally, within the network analysis policy
- C. globally, per intrusion policy
- D. on each access control rule
- E. per preprocessor, within the network analysis policy

Answer: AC

NEW QUESTION 21

In which two ways do access control policies operate on a Cisco Firepower system? (Choose two.)

- A. Traffic inspection can be interrupted temporarily when configuration changes are deployed.
- B. The system performs intrusion inspection followed by file inspection.
- C. They can block traffic based on Security Intelligence data.
- D. File policies use an associated variable set to perform intrusion prevention.
- E. The system performs a preliminary inspection on trusted traffic to validate that it matches the trusted parameters.

Answer: AC

NEW QUESTION 22

Which command is run at the CLI when logged in to an FTD unit, to determine whether the unit is managed locally or by a remote FMC server?

- A. system generate-troubleshoot
- B. show configuration session
- C. show managers
- D. show running-config | include manager

Answer: C

NEW QUESTION 24

How many report templates does the Cisco Firepower Management Center support?

- A. 20
- B. 10
- C. 5
- D. unlimited

Answer: D

NEW QUESTION 28

Which report template field format is available in Cisco FMC?

- A. box lever chart
- B. arrow chart
- C. bar chart
- D. benchmark chart

Answer: C

NEW QUESTION 29

Which group within Cisco does the Threat Response team use for threat analysis and research?

- A. Cisco Deep Analytics
- B. OpenDNS Group
- C. Cisco Network Response
- D. Cisco Talos

Answer: D

NEW QUESTION 31

Which CLI command is used to generate firewall debug messages on a Cisco Firepower?

- A. system support firewall-engine-debug
- B. system support ssl-debug
- C. system support platform
- D. system support dump-table

Answer: A

NEW QUESTION 35

Which command must be run to generate troubleshooting files on an FTD?

- A. system support view-files
- B. sudo sf_troubleshoot.pl
- C. system generate-troubleshoot all
- D. show tech-support

Answer: B

NEW QUESTION 40

When do you need the file-size command option during troubleshooting with packet capture?

- A. when capture packets are less than 16 MB
- B. when capture packets are restricted from the secondary memory
- C. when capture packets exceed 10 GB
- D. when capture packets exceed 32 MB

Answer: D

NEW QUESTION 41

A network engineer is configuring URL Filtering on Firepower Threat Defense. Which two port requirements on the Firepower Management Center must be validated to allow communication with the cloud service? (Choose two.)

- A. outbound port TCP/443
- B. inbound port TCP/80
- C. outbound port TCP/8080
- D. inbound port TCP/443

E. outbound port TCP/80

Answer: AE

NEW QUESTION 44

Which limitation applies to Cisco Firepower Management Center dashboards in a multidomain environment?

- A. Child domains can view but not edit dashboards that originate from an ancestor domain.
- B. Child domains have access to only a limited set of widgets from ancestor domains.
- C. Only the administrator of the top ancestor domain can view dashboards.
- D. Child domains cannot view dashboards that originate from an ancestor domain.

Answer: D

NEW QUESTION 49

What is a valid Cisco AMP file disposition?

- A. non-malicious
- B. malware
- C. known-good
- D. pristine

Answer: B

NEW QUESTION 53

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 300-710 Exam with Our Prep Materials Via below:

<https://www.certleader.com/300-710-dumps.html>