



Amazon-Web-Services

Exam Questions ANS-C01

AWS Certified Advanced Networking Specialty Exam

About ExamBible

[Your Partner of IT Exam](#)

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

A network engineer needs to update a company's hybrid network to support IPv6 for the upcoming release of a new application. The application is hosted in a VPC in the AWS Cloud. The company's current AWS infrastructure includes VPCs that are connected by a transit gateway. The transit gateway is connected to the on-premises network by AWS Direct Connect and AWS Site-to-Site VPN. The company's on-premises devices have been updated to support the new IPv6 requirements.

The company has enabled IPv6 for the existing VPC by assigning a new IPv6 CIDR block to the VPC and by assigning IPv6 to the subnets for dual-stack support. The company has launched new Amazon EC2 instances for the new application in the updated subnets.

When updating the hybrid network to support IPv6 the network engineer must avoid making any changes to the current infrastructure. The network engineer also must block direct access to the instances' new IPv6 addresses from the internet. However, the network engineer must allow outbound internet access from the instances.

What is the MOST operationally efficient solution that meets these requirements?

- A. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- B. Create a new VPN connection that supports IPv6 connectivity
- C. Add an egress-only internet gateway
- D. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices
- E. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- F. Update the existing VPN connection to support IPv6 connectivity
- G. Add an egress-only internet gateway
- H. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- I. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- J. Create a new VPN connection that supports IPv6 connectivity
- K. Add an egress-only internet gateway
- L. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- M. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- N. Create a new VPN connection that supports IPv6 connectivity
- O. Add a NAT gateway
- P. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.

Answer: B

NEW QUESTION 2

A company has deployed a software-defined WAN (SD-WAN) solution to interconnect all of its offices. The company is migrating workloads to AWS and needs to extend its SD-WAN solution to support connectivity to these workloads.

A network engineer plans to deploy AWS Transit Gateway Connect and two SD-WAN virtual appliances to provide this connectivity. According to company policies, only a single SD-WAN virtual appliance can handle traffic from AWS workloads at a given time.

How should the network engineer configure routing to meet these requirements?

- A. Add a static default route in the transit gateway route table to point to the secondary SD-WAN virtual appliance
- B. Add routes that are more specific to point to the primary SD-WAN virtual appliance.
- C. Configure the BGP community tag 7224:7300 on the primary SD-WAN virtual appliance for BGP routes toward the transit gateway.
- D. Configure the AS_PATH prepend attribute on the secondary SD-WAN virtual appliance for BGP routes toward the transit gateway.
- E. Disable equal-cost multi-path (ECMP) routing on the transit gateway for Transit Gateway Connect.

Answer: A

NEW QUESTION 3

A software-as-a-service (SaaS) provider hosts its solution on Amazon EC2 instances within a VPC in the AWS Cloud. All of the provider's customers also have their environments in the AWS Cloud.

A recent design meeting revealed that the customers have IP address overlap with the provider's AWS deployment. The customers have stated that they will not share their internal IP addresses and that they do not want to connect to the provider's SaaS service over the internet.

Which combination of steps is part of a solution that meets these requirements? (Choose two.)

- A. Deploy the SaaS service endpoint behind a Network Load Balancer.
- B. Configure an endpoint service, and grant the customers permission to create a connection to the endpoint service.
- C. Deploy the SaaS service endpoint behind an Application Load Balancer.
- D. Configure a VPC peering connection to the customer VPC
- E. Route traffic through NAT gateways.
- F. Deploy an AWS Transit Gateway, and connect the SaaS VPC to it
- G. Share the transit gateway with the customer
- H. Configure routing on the transit gateway.

Answer: AB

Explanation:

NLB for creating the private link which solves the overlapping IP address issue and the SaaS service endpoint behind it. (the SaaS endpoint could be an ALB)
<https://aws.amazon.com/about-aws/whats-new/2021/09/application-load-balancer-aws-privatelink-static-ip>

NEW QUESTION 4

A company is using an AWS Site-to-Site VPN connection from the company's on-premises data center to a virtual private gateway in the AWS Cloud. Because of congestion, the company is experiencing availability and performance issues as traffic travels across the internet before the traffic reaches AWS. A network engineer must reduce these issues for the connection as quickly as possible with minimum administration effort.

Which solution will meet these requirements?

- A. Edit the existing Site-to-Site VPN connection by enabling acceleration
- B. Stop and start the VPN service on the customer gateway for the new setting to take effect.
- C. Configure a transit gateway in the same AWS Region as the existing virtual private gateway

- D. Create a new accelerated Site-to-Site VPN connectio
- E. Connect the new connection to the transit gateway by using a VPN attachmen
- F. Update the customer gateway device to use the new Site to Site VPN connectio
- G. Delete the existing Site-to-Site VPN connection
- H. Create a new accelerated Site-to-Site VPN connectio
- I. Connect the new Site-to-Site VPN connection to the existing virtual private gatewa
- J. Update the customer gateway device to use the new Site-to-Site VPN connectio
- K. Delete the existing Site-to-Site VPN connection.
- L. Create a new AWS Direct Connect connection with a private VIF between the on-premises data center and the AWS Clou
- M. Update the customer gateway device to use the new Direct Connect connectio
- N. Delete the existing Site-to-Site VPN connection.

Answer: B

NEW QUESTION 5

A network engineer must provide additional safeguards to protect encrypted data at Application Load Balancers (ALBs) through the use of a unique random session key.

What should the network engineer do to meet this requirement?

- A. Change the ALB security policy to a policy that supports TLS 1.2 protocol only
- B. Use AWS Key Management Service (AWS KMS) to encrypt session keys
- C. Associate an AWS WAF web ACL with the ALB
- D. and create a security rule to enforce forward secrecy (FS)
- E. Change the ALB security policy to a policy that supports forward secrecy (FS)

Answer: D

NEW QUESTION 6

A company has deployed an application in a VPC that uses a NAT gateway for outbound traffic to the internet. A network engineer notices a large quantity of suspicious network traffic that is traveling from the VPC over the internet to IP addresses that are included on a deny list. The network engineer must implement a solution to determine which AWS resources are generating the suspicious traffic. The solution must minimize cost and administrative overhead.

Which solution will meet these requirements?

- A. Launch an Amazon EC2 instance in the VP
- B. Use Traffic Mirroring by specifying the NAT gateway as the source and the EC2 instance as the destinatio
- C. Analyze the captured traffic by using open-source tools to identify the AWS resources that are generating the suspicious traffic.
- D. Use VPC flow log
- E. Launch a security information and event management (SIEM) solution in the VP
- F. Configure the SIEM solution to ingest the VPC flow log
- G. Run queries on the SIEM solution to identify the AWS resources that are generating the suspicious traffic.
- H. Use VPC flow log
- I. Publish the flow logs to a log group in Amazon CloudWatch Log
- J. Use CloudWatch Logs Insights to query the flow logs to identify the AWS resources that are generating the suspicious traffic.
- K. Configure the VPC to stream the network traffic directly to an Amazon Kinesis data strea
- L. Send the data from the Kinesis data stream to an Amazon Kinesis Data Firehose delivery stream to store the data in Amazon S3. Use Amazon Athena to query the data to identify the AWS resources that are generating the suspicious traffic.

Answer: C

NEW QUESTION 7

A company's network engineer needs to design a new solution to help troubleshoot and detect network anomalies. The network engineer has configured Traffic Mirroring. However, the mirrored traffic is overwhelming the Amazon EC2 instance that is the traffic mirror target. The EC2 instance hosts tools that the company's security team uses to analyze the traffic. The network engineer needs to design a highly available solution that can scale to meet the demand of the mirrored traffic.

Which solution will meet these requirements?

- A. Deploy a Network Load Balancer (NLB) as the traffic mirror targe
- B. Behind the NL
- C. deploy a fleet of EC2 instances in an Auto Scaling grou
- D. Use Traffic Mirroring as necessary.
- E. Deploy an Application Load Balancer (ALB) as the traffic mirror targe
- F. Behind the ALB, deploy a fleet of EC2 instances in an Auto Scaling grou
- G. Use Traffic Mirroring only during non-business hours.
- H. Deploy a Gateway Load Balancer (GLB) as the traffic mirror targe
- I. Behind the GL
- J. deploy a fleet of EC2 instances in an Auto Scaling grou
- K. Use Traffic Mirroring as necessary.
- L. Deploy an Application Load Balancer (ALB) with an HTTPS listener as the traffic mirror targe
- M. Behind the AL
- N. deploy a fleet of EC2 instances in an Auto Scaling grou
- O. Use Traffic Mirroring only during active events or business hours.

Answer: A

NEW QUESTION 8

A company uses a 4 Gbps AWS Direct Connect dedicated connection with a link aggregation group (LAG) bundle to connect to five VPCs that are deployed in the us-east-1 Region. Each VPC serves a different business unit and uses its own private VIF for connectivity to the on-premises environment. Users are reporting slowness when they access resources that are hosted on AWS.

A network engineer finds that there are sudden increases in throughput and that the Direct Connect connection becomes saturated at the same time for about an

hour each business day. The company wants to know which business unit is causing the sudden increase in throughput. The network engineer must find out this information and implement a solution to resolve the problem.
Which solution will meet these requirements?

- A. Review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observe
- B. Create a new 10 Gbps dedicated connectio
- C. Shift traffic from the existing dedicated connection to the new dedicated connection.
- D. Review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observe
- E. Upgrade the bandwidth of the existing dedicated connection to 10 Gbps.
- F. Review the Amazon CloudWatch metrics for ConnectionBpsIngress and ConnectionPpsEgress to determine which VIF is sending the highest throughput during the period in which slowness is observe
- G. Upgrade the existing dedicated connection to a 5 Gbps hosted connection.
- H. Review the Amazon CloudWatch metrics for ConnectionBpsIngress and ConnectionPpsEgress to determine which VIF is sending the highest throughput during the period in which slowness is observe
- I. Create a new 10 Gbps dedicated connectio
- J. Shift traffic from the existing dedicated connection to the new dedicated connection.

Answer: A

Explanation:

To meet the requirements of finding out which business unit is causing the sudden increase in throughput and resolving the problem, the network engineer should review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observed (Option B). After identifying the VIF that is causing the issue, they can upgrade the bandwidth of the existing dedicated connection to 10 Gbps to resolve the problem (Option B).

NEW QUESTION 9

A security team is performing an audit of a company's AWS deployment. The security team is concerned that two applications might be accessing resources that should be blocked by network ACLs and security groups. The applications are deployed across two Amazon Elastic Kubernetes Service (Amazon EKS) clusters that use the Amazon VPC Container Network Interface (CNI) plugin for Kubernetes. The clusters are in separate subnets within the same VPC and have a Cluster Autoscaler configured.

The security team needs to determine which POD IP addresses are communicating with which services throughout the VPC. The security team wants to limit the number of flow logs and wants to examine the traffic from only the two applications.
Which solution will meet these requirements with the LEAST operational overhead?

- A. Create VPC flow logs in the default forma
- B. Create a filter to gather flow logs only from the EKS nodes.Include the srcaddr field and the dstaddr field in the flow logs.
- C. Create VPC flow logs in a custom forma
- D. Set the EKS nodes as the resource Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.
- E. Create VPC flow logs in a custom forma
- F. Set the application subnets as resource
- G. Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.
- H. Create VPC flow logs in a custom forma
- I. Create a filter to gather flow logs only from the EKS nodes.Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.

Answer: D

NEW QUESTION 10

An organization launched an IPv6-only web portal to support IPv6-native mobile clients. Front-end instances launch in an Amazon VPC associated with an appropriate IPv6 CIDR. The VPC IPv4 CIDR is fully utilized. A single subnet exists in each of two Availability Zones with appropriately configured IPv6 CIDR associations.

Auto Scaling is properly configured, and no Elastic Load Balancing is used.

Customers say the service is unavailable during peak load times. The network engineer attempts to launch an instance manually and receives the following message: "There are not enough free addresses in subnet 'subnet-12345677' to satisfy the requested number of instances."

What action will resolve the availability problem?

- A. Create a new subnet using a VPC secondary IPv6 CIDR, and associate an IPv6 CID
- B. Include the new subnet in the Auto Scaling group.
- C. Create a new subnet using a VPC secondary IPv4 CIDR, and associate an IPv6 CID
- D. Include the new subnet in the Auto Scaling group.
- E. Resize the IPv6 CIDR on each of the existing subnet
- F. Modify the Auto Scaling group maximum number of instances.
- G. Add a secondary IPv4 CIDR to the Amazon VP
- H. Assign secondary IPv4 address space to each of the existing subnets.

Answer: B

NEW QUESTION 10

An international company provides early warning about tsunamis. The company plans to use IoT devices to monitor sea waves around the world. The data that is collected by the IoT devices must reach the company's infrastructure on AWS as quickly as possible. The company is using three operation centers around the world. Each operation center is connected to AWS through Its own AWS Direct Connect connection. Each operation center is connected to the internet through at least two upstream internet service providers.

The company has its own provider-independent (PI) address space. The IoT devices use TCP protocols for reliable transmission of the data they collect. The IoT devices have both landline and mobile internet connectivity. The infrastructure and the solution will be deployed in multiple AWS Regions. The company will use Amazon Route 53 for DNS services.

A network engineer needs to design connectivity between the IoT devices and the services that run in the AWS Cloud.

Which solution will meet these requirements with the HIGHEST availability?

- A. Set up an Amazon CloudFront distribution with origin failove

- B. Create an origin group for each Region where the solution is deployed.
- C. Set up Route 53 latency-based routing.
- D. Add latency alias record.
- E. For the latency alias records, set the value of Evaluate Target Health to Yes.
- F. Set up an accelerator in AWS Global Accelerator.
- G. Configure Regional endpoint groups and health checks.
- H. Set up Bring Your Own IP (BYOIP) addresses.
- I. Use the same IP addresses for each Region where the solution is deployed.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/iot/automate-global-device-provisioning-with-aws-iot-core-and-amazon-route-53>

NEW QUESTION 11

A company has deployed a critical application on a fleet of Amazon EC2 instances behind an Application Load Balancer. The application must always be reachable on port 443 from the public internet. The application recently had an outage that resulted from an incorrect change to the EC2 security group. A network engineer needs to automate a way to verify the network connectivity between the public internet and the EC2 instances whenever a change is made to the security group. The solution also must notify the network engineer when the change affects the connection. Which solution will meet these requirements?

- A. Enable VPC Flow Logs on the elastic network interface of each EC2 instance to capture REJECT traffic on port 443. Publish the flow log records to a log group in Amazon CloudWatch Log.
- B. Create a CloudWatch Logs metric filter for the log group for rejected traffic.
- C. Create an alarm to notify the network engineer.
- D. Enable VPC Flow Logs on the elastic network interface of each EC2 instance to capture all traffic on port 443. Publish the flow log records to a log group in Amazon CloudWatch Log.
- E. Create a CloudWatch Logs metric filter for the log group for all traffic.
- F. Create an alarm to notify the network engineer.
- G. Create a VPC Reachability Analyzer path on port 443. Specify the security group as the source.
- H. Specify the EC2 instances as the destination.
- I. Create an Amazon Simple Notification Service (Amazon SNS) topic to notify the network engineer when a change to the security group affects the connection.
- J. Create an AWS Lambda function to start Reachability Analyzer and to publish a message to the SNS topic in case the analyses fail.
- K. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke the Lambda function when a change to the security group occurs.
- L. Create a VPC Reachability Analyzer path on port 443. Specify the internet gateway of the VPC as the source.
- M. Specify the EC2 instances as the destination.
- N. Create an Amazon Simple Notification Service (Amazon SNS) topic to notify the network engineer when a change to the security group affects the connection.
- O. Create an AWS Lambda function to start Reachability Analyzer and to publish a message to the SNS topic in case the analyses fail.
- P. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke the Lambda function when a change to the security group occurs.

Answer: C

NEW QUESTION 16

An Australian ecommerce company hosts all of its services in the AWS Cloud and wants to expand its customer base to the United States (US). The company is targeting the western US for the expansion.

The company's existing AWS architecture consists of four AWS accounts with multiple VPCs deployed in the ap-southeast-2 Region. All VPCs are attached to a transit gateway in ap-southeast-2. There are dedicated VPCs for each application service. The company also has VPCs for centralized security features such as proxies, firewalls, and logging.

The company plans to duplicate the infrastructure from ap-southeast-2 to the us-west-1 Region. A network engineer must establish connectivity between the various applications in the two Regions. The solution must maximize bandwidth, minimize latency and minimize operational overhead.

Which solution will meet these requirements?

- A. Create VPN attachments between the two transit gateways.
- B. Configure the VPN attachments to use BGP routing between the two transit gateways.
- C. Peer the transit gateways in each Region.
- D. Configure routing between the two transit gateways for each Region's IP addresses.
- E. Create a VPN server in a VPC in each Region.
- F. Update the routing to point to the VPN servers for the IP addresses in alternate Regions.
- G. Attach the VPCs in us-west-1 to the transit gateway in ap-southeast-2.

Answer: B

Explanation:

Peering the transit gateways in each region would establish a private network connection between the two regions, allowing the company to route traffic between the VPCs in different regions without going over the public internet. This would help minimize latency and maximize bandwidth while reducing the operational overhead of managing multiple VPN connections.

NEW QUESTION 17

A company has deployed an AWS Network Firewall into a VPC. A network engineer needs to implement a solution to deliver Network Firewall flow logs to the company's Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster in the shortest possible time.

Which solution will meet these requirements?

- A. Create an Amazon S3 bucket.
- B. Create an AWS Lambda function to load logs into the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster.
- C. Enable Amazon Simple Notification Service (Amazon SNS) notifications on the S3 bucket to invoke the Lambda function.
- D. Configure flow logs for the firewall.
- E. Set the S3 bucket as the destination.
- F. Create an Amazon Kinesis Data Firehose delivery stream that includes the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster as the destination.
- G. Configure flow logs for the firewall. Set the Kinesis Data Firehose delivery stream as the destination for the Network Firewall flow logs.

- H. Configure flow logs for the firewall
- I. Set the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster as the destination for the Network Firewall flow logs.
- J. Create an Amazon Kinesis data stream that includes the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster as the destination
- K. Configure flow logs for the firewall
- L. Set the Kinesis data stream as the destination for the Network Firewall flow logs.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/networking-and-content-delivery/how-to-analyze-aws-network-firewall-logs-usin>

NEW QUESTION 20

A company is planning to create a service that requires encryption in transit. The traffic must not be decrypted between the client and the backend of the service. The company will implement the service by using the gRPC protocol over TCP port 443. The service will scale up to thousands of simultaneous connections. The backend of the service will be hosted on an Amazon Elastic Kubernetes Service (Amazon EKS) cluster with the Kubernetes Cluster Autoscaler and the Horizontal Pod Autoscaler configured. The company needs to use mutual TLS for two-way authentication between the client and the backend.

Which solution will meet these requirements?

- A. Install the AWS Load Balancer Controller for Kubernetes
- B. Using that controller, configure a Network Load Balancer with a TCP listener on port 443 to forward traffic to the IP addresses of the backend service Pods.
- C. Install the AWS Load Balancer Controller for Kubernetes
- D. Using that controller, configure an Application Load Balancer with an HTTPS listener on port 443 to forward traffic to the IP addresses of the backend service Pods.
- E. Create a target group
- F. Add the EKS managed node group's Auto Scaling group as a target Create an Application Load Balancer with an HTTPS listener on port 443 to forward traffic to the target group.
- G. Create a target group
- H. Add the EKS managed node group's Auto Scaling group as a target
- I. Create a Network Load Balancer with a TLS listener on port 443 to forward traffic to the target group.

Answer: B

Explanation:

<https://docs.aws.amazon.com/elasticloadbalancing/latest/application/load-balancer-target-groups.html#target-gro>

NEW QUESTION 22

A company uses a hybrid architecture and has an AWS Direct Connect connection between its on-premises data center and AWS. The company has production applications that run in the on-premises data center. The company also has production applications that run in a VPC. The applications that run in the on-premises data center need to communicate with the applications that run in the VPC. The company is using corp.example.com as the domain name for the on-premises resources and is using an Amazon Route 53 private hosted zone for aws.example.com to host the VPC resources.

The company is using an open-source recursive DNS resolver in a VPC subnet and is using a DNS resolver in the on-premises data center. The company's on-premises DNS resolver has a forwarder that directs requests for the aws.example.com domain name to the DNS resolver in the VPC. The DNS resolver in the VPC has a forwarder that directs requests for the corp.example.com domain name to the DNS resolver in the on-premises data center. The company has decided to replace the open-source recursive DNS resolver with Amazon Route 53 Resolver endpoints.

Which combination of steps should a network engineer take to make this replacement? (Choose three.)

- A. Create a Route 53 Resolver rule to forward aws.example.com domain queries to the IP addresses of the outbound endpoint.
- B. Configure the on-premises DNS resolver to forward aws.example.com domain queries to the IP addresses of the inbound endpoint.
- C. Create a Route 53 Resolver inbound endpoint and a Route 53 Resolver outbound endpoint.
- D. Create a Route 53 Resolver rule to forward aws.example.com domain queries to the IP addresses of the inbound endpoint.
- E. Create a Route 53 Resolver rule to forward corp.example.com domain queries to the IP address of the on-premises DNS resolver.
- F. Configure the on-premises DNS resolver to forward aws.example.com queries to the IP addresses of the outbound endpoint.

Answer: BCE

Explanation:

To replace the open-source recursive DNS resolver with Amazon Route 53 Resolver endpoints in a hybrid architecture where on-premises applications need to communicate with applications running in a VPC, a network engineer should take the following steps:

- Create a Route 53 Resolver inbound endpoint and a Route 53 Resolver outbound endpoint. (Option C)
- Configure the on-premises DNS resolver to forward aws.example.com domain queries to the IP addresses of the inbound endpoint. (Option B)
- Create a Route 53 Resolver rule to forward corp.example.com domain queries to the IP address of the on-premises DNS resolver. (Option E)

These steps will allow for seamless replacement of the open-source recursive DNS resolver with Amazon Route 53 Resolver endpoints and enable communication between on-premises and VPC applications.

NEW QUESTION 23

A company has deployed Amazon EC2 instances in private subnets in a VPC. The EC2 instances must initiate any requests that leave the VPC, including requests to the company's on-premises data center over an AWS Direct Connect connection. No resources outside the VPC can be allowed to open communications directly to the EC2 instances.

The on-premises data center's customer gateway is configured with a stateful firewall device that filters for incoming and outgoing requests to and from multiple VPCs. In addition, the company wants to use a single IP match rule to allow all the communications from the EC2 instances to its data center from a single IP address.

Which solution will meet these requirements with the LEAST amount of operational overhead?

- A. Create a VPN connection over the Direct Connect connection by using the on-premises firewall
- B. Use the firewall to block all traffic from on premises to AWS
- C. Allow a stateful connection from the EC2 instances to initiate the requests.
- D. Configure the on-premises firewall to filter all requests from the on-premises network to the EC2 instance
- E. Allow a stateful connection if the EC2 instances in the VPC initiate the traffic.
- F. Deploy a NAT gateway into a private subnet in the VPC where the EC2 instances are deployed

- G. Specify the NAT gateway type as private
- H. Configure the on-premises firewall to allow connections from the IP address that is assigned to the NAT gateway.
- I. Deploy a NAT instance into a private subnet in the VPC where the EC2 instances are deployed. Configure the on-premises firewall to allow connections from the IP address that is assigned to the NAT instance.

Answer: C

NEW QUESTION 27

A company delivers applications over the internet. An Amazon Route 53 public hosted zone is the authoritative DNS service for the company and its internet applications, all of which are offered from the same domain name.

A network engineer is working on a new version of one of the applications. All the application's components are hosted in the AWS Cloud. The application has a three-tier design. The front end is delivered through Amazon EC2 instances that are deployed in public subnets with Elastic IP addresses assigned. The backend components are deployed in private subnets from RFC1918.

Components of the application need to be able to access other components of the application within the application's VPC by using the same host names as the host names that are used over the public internet. The network engineer also needs to accommodate future DNS changes, such as the introduction of new host names or the retirement of DNS entries.

Which combination of steps will meet these requirements? (Choose three.)

- A. Add a geoproximity routing policy in Route 53.
- B. Create a Route 53 private hosted zone for the same domain name. Associate the application's VPC with the new private hosted zone.
- C. Enable DNS hostnames for the application's VPC.
- D. Create entries in the private hosted zone for each name in the public hosted zone by using the corresponding private IP addresses.
- E. Create an Amazon EventBridge (Amazon CloudWatch Events) rule that runs when AWS CloudTrail logs a Route 53 API call to the public hosted zone.
- F. Create an AWS Lambda function as the target of the rule.
- G. Configure the function to use the event information to update the private hosted zone.
- H. Add the private IP addresses in the existing Route 53 public hosted zone.

Answer: BCD

NEW QUESTION 32

A company hosts an application on Amazon EC2 instances behind an Application Load Balancer (ALB). The company recently experienced a network security breach. A network engineer must collect and analyze logs that include the client IP address, target IP address, target port, and user agent of each user that accesses the application.

What is the MOST operationally efficient solution that meets these requirements?

- A. Configure the ALB to store logs in an Amazon S3 bucket.
- B. Download the files from Amazon S3, and use a spreadsheet application to analyze the logs.
- C. Configure the ALB to push logs to Amazon Kinesis Data Stream.
- D. Use Amazon Kinesis Data Analytics to analyze the logs.
- E. Configure Amazon Kinesis Data Streams to stream data from the ALB to Amazon OpenSearch Service (Amazon Elasticsearch Service). Use search operations in Amazon OpenSearch Service (Amazon Elasticsearch Service) to analyze the data.
- F. Configure the ALB to store logs in an Amazon S3 bucket.
- G. Use Amazon Athena to analyze the logs in Amazon S3.

Answer: D

Explanation:

The most operationally efficient solution to collect and analyze logs that include the client IP address, target IP address, target port, and user agent of each user that accesses the application would be to configure the ALB to store logs in an Amazon S3 bucket and use Amazon Athena to analyze the logs in Amazon S3 (Option D). This solution allows for quick and easy analysis of log data without requiring manual download or manipulation of log files.

NEW QUESTION 35

A network engineer needs to set up an Amazon EC2 Auto Scaling group to run a Linux-based network appliance in a highly available architecture. The network engineer is configuring the new launch template for the Auto Scaling group.

In addition to the primary network interface the network appliance requires a second network interface that will be used exclusively by the application to exchange traffic with hosts over the internet. The company has set up a Bring Your Own IP (BYOIP) pool that includes an Elastic IP address that should be used as the public IP address for the second network interface.

How can the network engineer implement the required architecture?

- A. Configure the two network interfaces in the launch template.
- B. Define the primary network interface to be created in one of the private subnets.
- C. For the second network interface, select one of the public subnets.
- D. Choose the BYOIP pool ID as the source of public IP addresses.
- E. Configure the primary network interface in a private subnet in the launch template.
- F. Use the user data option to run a cloud-init script after boot to attach the second network interface from a subnet with auto-assign public IP addressing enabled.
- G. Create an AWS Lambda function to run as a lifecycle hook of the Auto Scaling group when an instance is launched.
- H. In the Lambda function, assign a network interface to an AWS Global Accelerator endpoint.
- I. During creation of the Auto Scaling group, select subnets for the primary network interface.
- J. Use the user data option to run a cloud-init script to allocate a second network interface and to associate an Elastic IP address from the BYOIP pool.

Answer: D

Explanation:

During creation of the Auto Scaling group, select subnets for the primary network interface. Use the user data option to run a cloud-init script to allocate a second network interface and to associate an Elastic IP address from the BYOIP pool.

This solution meets all of the requirements stated in the question. The primary network interface can be configured in a private subnet during creation of the Auto Scaling group. The user data option can be used to run a cloud-init script that will allocate a second network interface and associate an Elastic IP address from the BYOIP pool with it.

NEW QUESTION 37

All IP addresses within a 10.0.0.0/16 VPC are fully utilized with application servers across two Availability Zones. The application servers need to send frequent UDP probes to a single central authentication server on the Internet to confirm that is running up-to-date packages. The network is designed for application servers to use a single NAT gateway for internal access. Testing reveals that a few of the servers are unable to communicate with the authentication server.

- A. The NAT gateway does not support UDP traffic.
- B. The authentication server is not accepting traffic.
- C. The NAT gateway cannot allocate more ports.
- D. The NAT gateway is launched in a private subnet.

Answer: C

Explanation:

Ref: <https://docs.aws.amazon.com/vpc/latest/userguide/vpc-nat-gateway.html>

"A NAT gateway can support up to 55,000 simultaneous connections to each unique destination. This limit also applies if you create approximately 900 connections per second to a single destination (about 55,000 connections per minute). If the destination IP address, the destination port, or the protocol (TCP/UDP/ICMP) changes, you can create an additional 55,000 connections. For more than 55,000 connections, there is an increased chance of connection errors due to port allocation errors. These errors can be monitored by viewing the ErrorPortAllocation CloudWatch metric for your NAT gateway. For more information, see Monitoring NAT Gateways Using Amazon CloudWatch."

NEW QUESTION 38

A Network Engineer is provisioning a subnet for a load balancer that will sit in front of a fleet of application servers in a private subnet. There is limited IP space left in the VPC CIDR. The application has few users now but is expected to grow quickly to millions of users.

What design will use the LEAST amount of IP space, while allowing for this growth?

- A. Use two /29 subnets for an Application Load Balancer in different Availability Zones.
- B. Use one /29 subnet for the Network Load Balance
- C. Add another VPC CIDR to the VPC to allow for future growth.
- D. Use two /28 subnets for a Network Load Balancer in different Availability Zones.
- E. Use one /28 subnet for an Application Load Balance
- F. Add another VPC CIDR to the VPC to allow for future growth.

Answer: C

NEW QUESTION 40

You deploy an Amazon EC2 instance that runs a web server into a subnet in a VPC. An Internet gateway is attached, and the main route table has a default route (0.0.0.0/0) configured with a target of the Internet gateway.

The instance has a security group configured to allow as follows:

- Protocol: TCP
- Port: 80 inbound, nothing outbound

The Network ACL for the subnet is configured to allow as follows:

- Protocol: TCP
- Port: 80 inbound, nothing outbound

When you try to browse to the web server, you receive no response. Which additional step should you take to receive a successful response?

- A. Add an entry to the security group outbound rules for Protocol: TCP, Port Range: 80
- B. Add an entry to the security group outbound rules for Protocol: TCP, Port Range: 1024-65535
- C. Add an entry to the Network ACL outbound rules for Protocol: TCP, Port Range: 80
- D. Add an entry to the Network ACL outbound rules for Protocol: TCP, Port Range: 1024-65535

Answer: D

Explanation:

To enable the connection to a service running on an instance, the associated network ACL must allow both inbound traffic on the port that the service is listening on as well as allow outbound traffic from ephemeral ports. When a client connects to a server, a random port from the ephemeral port range (1024-65535) becomes the client's source port. The designated ephemeral port then becomes the destination port for return traffic from the service, so outbound traffic from the ephemeral port must be allowed in the network ACL. <https://aws.amazon.com/premiumsupport/knowledge-center/resolve-connection-sg-acl-inbound/>

NEW QUESTION 41

An AWS CloudFormation template is being used to create a VPC peering connection between two existing operational VPCs, each belonging to a different AWS account. All necessary components in the 'Remote' (receiving) account are already in place.

The template below creates the VPC peering connection in the Originating account. It contains these components:

AWSTemplateFormation Version: 2010-09-09 Parameters:

Originating VPCId: Type: String RemoteVPCId: Type: String

RemoteVPCAccountId: Type: String Resources:

newVPCPeeringConnection:

Type: 'AWS::EC2::VPCPeeringConnection' Properties:

VpcId: !Ref OriginatingVPCId PeerVpcId: !Ref RemoteVPCId PeerOwnerId: !Ref RemoteVPCAccountId

Which additional AWS CloudFormation components are necessary in the Originating account to create an operational cross-account VPC peering connection with AWS CloudFormation? (Select two.)

- A. Resources:NewEC2SecurityGroup:Type: AWS::EC2::SecurityGroup
- B. Resources:NetworkInterfaceToRemoteVPC:Type: "AWS::EC2NetworkInterface"
- C. Resources:newEC2Route:Type: AWS::EC2::Route
- D. Resources:VPCGatewayToRemoteVPC:Type: "AWS::EC2::VPCGatewayAttachment"
- E. Resources:newVPCPeeringConnection:Type: 'AWS::EC2VPCPeeringConnection'PeerRoleArn: !Ref PeerRoleArn

Answer: CE

Explanation:

https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/AWS_EC2.html

NEW QUESTION 44

A network engineer is designing a hybrid architecture that uses a 1 Gbps AWS Direct Connect connection between the company's data center and two AWS Regions: us-east-1 and eu-west-1. The VPCs in us-east-1 are connected by a transit gateway and need to access several on-premises databases. According to company policy, only one VPC in eu-west-1 can be connected to one on-premises server. The on-premises network segments the traffic between the databases and the server.

How should the network engineer set up the Direct Connect connection to meet these requirements?

- A. Create one hosted connectio
- B. Use a transit VIF to connect to the transit gateway in us-east-1. Use a private VIF to connect to the VPC in eu-west-1. Use one Direc
- C. Connect gateway for both VIFs to route from the Direct Connect locations to the corresponding AWS Region along the path that has the lowest latency.
- D. Create one hosted connectio
- E. Use a transit VIF to connect to the transit gateway in us-east-1. Use a private VIF to connect to the VPC in eu-west-1. Use two Direct Connect gateways, one for each VIF, to route from the Direct Connect locations to the corresponding AWS Region along the path that has the lowest latency.
- F. Create one dedicated connectio
- G. Use a transit VIF to connect to the transit gateway in us-east-1. Use a private VIF to connect to the VPC in eu-west-1. Use one Direct Connect gateway for both VIFs to route from the Direct Connect locations to the corresponding AWS Region along the path that has the lowest latency.
- H. Create one dedicated connectio
- I. Use a transit VIF to connect to the transit gateway in us-east-1. Use a private VIF to connect to the VPC in eu-west-1. Use two Direct Connect gateways, one for each VIF, to route from the Direct Connect locations to the corresponding AWS Region along the path that has the lowest latency.

Answer: B

Explanation:

This solution meets the requirements of the company by using a single Direct Connect connection with two VIFs, one connected to the transit gateway in us-east-1 and the other connected to the VPC in eu-west-1. Two Direct Connect gateways are used, one for each VIF, to route traffic from the Direct Connect location to the corresponding AWS Region along the path that has the lowest latency. This setup ensures that traffic between the VPCs in us-east-1 and on-premises databases is routed through the transit gateway, while traffic between the VPC in eu-west-1 and the on-premises server is routed directly through the private VIF.

NEW QUESTION 48

A bank built a new version of its banking application in AWS using containers that content to an on-premises database over VPN connection. This application version requires users to also update their client application. The bank plans to deprecate the earlier client version. However, the company wants to keep supporting earlier clients through their on-premises version of the application to serve a small portion of the customers who haven't yet upgraded.

What design will allow the company to serve both newer and earlier clients in the MOST efficient way?

- A. Use an Amazon Route 53 multivalue answer routing policy to route older client traffic to the on-premises application version and the rest of the traffic to the new AWS based version.
- B. Use a Classic Load Balancer for the new applicatio
- C. Route all traffic to the new application by using an Elastic Load Balancing (ELB) load balancer DN
- D. Define a user-agent-based rule on the backend servers to redirect earlier clients to the on-premises application.
- E. Use an Application Load Balancer for the new applicatio
- F. Register both the new and earlier applications as separate target groups and use path-based routing to route traffic based on the application version.
- G. Use an Application Load Balancer for the new applicatio
- H. Register both the new and earlier application backends as separate target group
- I. Use header-based routing to route traffic based on the application version.

Answer: D

NEW QUESTION 50

A company is planning a migration of its critical workloads from an on-premises data center to Amazon EC2 instances. The plan includes a new 10 Gbps AWS Direct Connect dedicated connection from the on-premises data center to a VPC that is attached to a transit gateway. The migration must occur over encrypted paths between the on-premises data center and the AWS Cloud.

Which solution will meet these requirements while providing the HIGHEST throughput?

- A. Configure a public VIF on the Direct Connect connectio
- B. Configure an AWS Site-to-Site VPN connection to the transit gateway as a VPN attachment.
- C. Configure a transit VIF on the Direct Connect connectio
- D. Configure an IPsec VPN connection to an EC2 instance that is running third-party VPN software.
- E. Configure MACsec for the Direct Connect connectio
- F. Configure a transit VIF to a Direct Connect gateway that is associated with the transit gateway.
- G. Configure a public VIF on the Direct Connect connectio
- H. Configure two AWS Site-to-Site VPN connections to the transit gatewa
- I. Enable equal-cost multi-path (ECMP) routing.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/networking-and-content-delivery/adding-macsec-security-to-aws-direct-connect-c>

NEW QUESTION 52

A company is using a NAT gateway to allow internet connectivity for private subnets in a VPC in the us-west-2 Region. After a security audit, the company needs to remove the NAT gateway.

In the private subnets, the company has resources that use the unified Amazon CloudWatch agent. A network engineer must create a solution to ensure that the unified CloudWatch agent continues to work after the removal of the NAT gateway.

Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Validate that private DNS is enabled on the VPC by setting the enableDnsHostnames VPC attribute and the enableDnsSupport VPC attribute to true.

- B. Create a new security group with an entry to allow outbound traffic that uses the TCP protocol on port 443 to destination 0.0.0.0/0
- C. Create a new security group with entries to allow inbound traffic that uses the TCP protocol on port 443 from the IP prefixes of the private subnets.
- D. Create the following interface VPC endpoints in the VPC: com.amazonaws.us-west-2.logs and com.amazonaws.us-west-2.monitorin
- E. Associate the new security group with the endpoint network interfaces.
- F. Create the following interface VPC endpoint in the VPC: com.amazonaws.us-west-2.cloudwatch. Associate the new security group with the endpoint network interfaces.
- G. Associate the VPC endpoint or endpoints with route tables that the private subnets use.

Answer: BDF

NEW QUESTION 57

A company is deploying a new application on AWS. The application uses dynamic multicasting. The company has five VPCs that are all attached to a transit gateway. Amazon EC2 instances in each VPC need to be able to register dynamically to receive a multicast transmission. How should a network engineer configure the AWS resources to meet these requirements?

- A. Create a static source multicast domain within the transit gateway
- B. Associate the VPCs and applicable subnets with the multicast domain
- C. Register the multicast senders' network interface with the multicast domain
- D. Adjust the network ACLs to allow UDP traffic from the source to all receivers and to allow UDP traffic that is sent to the multicast group address.
- E. Create a static source multicast domain within the transit gateway
- F. Associate the VPCs and applicable subnets with the multicast domain
- G. Register the multicast senders' network interface with the multicast domain
- H. Adjust the network ACLs to allow TCP traffic from the source to all receivers and to allow TCP traffic that is sent to the multicast group address.
- I. Create an Internet Group Management Protocol (IGMP) multicast domain within the transit gateway. Associate the VPCs and applicable subnets with the multicast domain
- J. Register the multicast senders' network interface with the multicast domain
- K. Adjust the network ACLs to allow UDP traffic from the source to all receivers and to allow UDP traffic that is sent to the multicast group address.
- L. Create an Internet Group Management Protocol (IGMP) multicast domain within the transit gateway. Associate the VPCs and applicable subnets with the multicast domain
- M. Register the multicast senders' network interface with the multicast domain
- N. Adjust the network ACLs to allow TCP traffic from the source to all receivers and to allow TCP traffic that is sent to the multicast group address.

Answer: C

NEW QUESTION 58

A company hosts a web application on Amazon EC2 instances behind an Application Load Balancer (ALB). The ALB is the origin in an Amazon CloudFront distribution. The company wants to implement a custom authentication system that will provide a token for its authenticated customers. The web application must ensure that the GET/POST requests come from authenticated customers before it delivers the content. A network engineer must design a solution that gives the web application the ability to identify authorized customers. What is the MOST operationally efficient solution that meets these requirements?

- A. Use the ALB to inspect the authorized token inside the GET/POST request payload
- B. Use an AWS Lambda function to insert a customized header to inform the web application of an authenticated customer request.
- C. Integrate AWS WAF with the ALB to inspect the authorized token inside the GET/POST request payload
- D. Configure the ALB listener to insert a customized header to inform the web application of an authenticated customer request.
- E. Use an AWS Lambda@Edge function to inspect the authorized token inside the GET/POST request payload
- F. Use the Lambda@Edge function also to insert a customized header to inform the web application of an authenticated customer request.
- G. Set up an EC2 instance that has a third-party packet inspection tool to inspect the authorized token inside the GET/POST request payload
- H. Configure the tool to insert a customized header to inform the web application of an authenticated customer request.

Answer: C

NEW QUESTION 62

A company is planning to deploy many software-defined WAN (SD-WAN) sites. The company is using AWS Transit Gateway and has deployed a transit gateway in the required AWS Region. A network engineer needs to deploy the SD-WAN hub virtual appliance into a VPC that is connected to the transit gateway. The solution must support at least 5 Gbps of throughput from the SD-WAN hub virtual appliance to other VPCs that are attached to the transit gateway. Which solution will meet these requirements?

- A. Create a new VPC for the SD-WAN hub virtual appliance
- B. Create two IPsec VPN connections between the SD-WAN hub virtual appliance and the transit gateway
- C. Configure BGP over the IPsec VPN connections
- D. Assign a new CIDR block to the transit gateway
- E. Create a new VPC for the SD-WAN hub virtual appliance
- F. Attach the new VPC to the transit gateway with a VPC attachment
- G. Add a transit gateway Connect attachment
- H. Create a Connect peer and specify the GRE and BGP parameter
- I. Create a route in the appropriate VPC for the SD-WAN hub virtual appliance to route to the transit gateway.
- J. Create a new VPC for the SD-WAN hub virtual appliance
- K. Attach the new VPC to the transit gateway with a VPC attachment
- L. Create two IPsec VPN connections between the SD-WAN hub virtual appliance and the transit gateway
- M. Configure BGP over the IPsec VPN connections.
- N. Assign a new CIDR block to the transit gateway
- O. Create a new VPC for the SD-WAN hub virtual appliance
- P. Attach the new VPC to the transit gateway with a VPC attachment
- Q. Add a transit gateway Connect attachment
- R. Create a Connect peer and specify the VXLAN and BGP parameter
- S. Create a route in the appropriate VPC for the SD-WAN hub virtual appliance to route to the transit gateway.

Answer: D

NEW QUESTION 63

A company wants to improve visibility into its AWS environment. The AWS environment consists of multiple VPCs that are connected to a transit gateway. The transit gateway connects to an on-premises data center through an AWS Direct Connect gateway and a pair of redundant Direct Connect connections that use transit VIFs. The company must receive notification each time a new route is advertised to AWS from on premises over Direct Connect. What should a network engineer do to meet these requirements?

- A. Enable Amazon CloudWatch metrics on Direct Connect to track the received route
- B. Configure a CloudWatch alarm to send notifications when routes change.
- C. Onboard Transit Gateway Network Manager to Amazon CloudWatch Logs Insight
- D. Use Amazon EventBridge (Amazon CloudWatch Events) to send notifications when routes change.
- E. Configure an AWS Lambda function to periodically check the routes on the Direct Connect gateway and to send notifications when routes change.
- F. Enable Amazon CloudWatch Logs on the transit VIFs to track the received route
- G. Create a metric filter Set an alarm on the filter to send notifications when routes change.

Answer: B

Explanation:

<https://docs.aws.amazon.com/network-manager/latest/cloudwan/cloudwan-cloudwatch-events.html>

To receive notification each time a new route is advertised to AWS from on premises over Direct Connect, a network engineer should onboard Transit Gateway Network Manager to Amazon CloudWatch Logs Insights and use Amazon EventBridge (Amazon CloudWatch Events) to send notifications when routes change (Option B). This solution allows for real-time monitoring of route changes and automatic notification when new routes are advertised.

NEW QUESTION 68

A company has created three VPCs: a production VPC, a nonproduction VPC, and a shared services VPC. The production VPC and the nonproduction VPC must each have communication with the shared services VPC. There must be no communication between the production VPC and the nonproduction VPC. A transit gateway is deployed to facilitate communication between VPCs.

Which route table configurations on the transit gateway will meet these requirements?

- A. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for only the shared services VP
- B. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- C. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for each VP
- D. Create an additional route table with only the shared services VPC attachment associated with propagated routes from each VPC.
- E. Configure a route table with all the VPC attachments associated with propagated routes for only the shared services VPC
- F. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- G. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes disable
- G. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.

Answer: A

NEW QUESTION 73

.....

Relate Links

100% Pass Your ANS-C01 Exam with ExamBible Prep Materials

<https://www.exambible.com/ANS-C01-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>