

DOP-C02 Dumps

AWS Certified DevOps Engineer - Professional

<https://www.certleader.com/DOP-C02-dumps.html>



NEW QUESTION 1

A DevOps engineer needs to apply a core set of security controls to an existing set of AWS accounts. The accounts are in an organization in AWS Organizations. Individual teams will administer individual accounts by using the AdministratorAccess AWS managed policy. For all accounts, AWS CloudTrail and AWS Config must be turned on in all available AWS Regions. Individual account administrators must not be able to edit or delete any of the baseline resources. However, individual account administrators must be able to edit or delete their own CloudTrail trails and AWS Config rules.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. Create an AWS CloudFormation template that defines the standard account resource
 - B. Deploy the template to all accounts from the organization's management account by using CloudFormation StackSet
 - C. Set the stack policy to deny Update:Delete actions.
 - D. Enable AWS Control Tower
 - E. Enroll the existing accounts in AWS Control Tower
 - F. Grant the individual account administrators access to CloudTrail and AWS Config.
 - G. Designate an AWS Config management account
 - H. Create AWS Config recorders in all accounts by using AWS CloudFormation StackSet
 - I. Deploy AWS Config rules to the organization by using the AWS Config management account
 - J. Create a CloudTrail organization trail in the organization's management account
 - K. Deny modification or deletion of the AWS Config recorders by using an SCP.
 - L. Create an AWS CloudFormation template that defines the standard account resource
 - M. Deploy the template to all accounts from the organization's management account by using CloudFormation StackSets
- Create an SCP that prevents updates or deletions to CloudTrail resources or AWS Config resources unless the principal is an administrator of the organization's management account.

Answer: D

NEW QUESTION 2

A DevOps engineer is designing an application that integrates with a legacy REST API. The application has an AWS Lambda function that reads records from an Amazon Kinesis data stream. The Lambda function sends the records to the legacy REST API.

Approximately 10% of the records that the Lambda function sends from the Kinesis data stream have data errors and must be processed manually. The Lambda function event source configuration has an Amazon Simple Queue Service (Amazon SQS) dead-letter queue as an on-failure destination. The DevOps engineer has configured the Lambda function to process records in batches and has implemented retries in case of failure.

During testing the DevOps engineer notices that the dead-letter queue contains many records that have no data errors and that already have been processed by the legacy REST API. The DevOps engineer needs to configure the Lambda function's event source options to reduce the number of errorless records that are sent to the dead-letter queue.

Which solution will meet these requirements?

- A. Increase the retry attempts
- B. Configure the setting to split the batch when an error occurs
- C. Increase the concurrent batches per shard
- D. Decrease the maximum age of record

Answer: B

Explanation:

This solution will meet the requirements because it will reduce the number of errorless records that are sent to the dead-letter queue. When you configure the setting to split the batch when an error occurs, Lambda will retry only the records that caused the error, instead of retrying the entire batch. This way, the records that have no data errors and have already been processed by the legacy REST API will not be retried and sent to the dead-letter queue unnecessarily.

<https://docs.aws.amazon.com/lambda/latest/dg/with-kinesis.html>

NEW QUESTION 3

A DevOps engineer is implementing governance controls for a company that requires its infrastructure to be housed within the United States. The engineer must restrict which AWS Regions can be used, and ensure an alert is sent as soon as possible if any activity outside the governance policy takes place. The controls should be automatically enabled on any new Region outside the United States (US).

Which combination of actions will meet these requirements? (Select TWO.)

- A. Create an AWS Organizations SCP that denies access to all non-global services in non-US Region
- B. Attach the policy to the root of the organization.
- C. Configure AWS CloudTrail to send logs to Amazon CloudWatch Logs and enable it for all Region
- D. Use a CloudWatch Logs metric filter to send an alert on any service activity in non-US Regions.
- E. Use an AWS Lambda function that checks for AWS service activity and deploy it to all Region
- F. Write an Amazon EventBridge rule that runs the Lambda function every hour, sending an alert if activity is found in a non-US Region.
- G. Use an AWS Lambda function to query Amazon Inspector to look for service activity in non-US Regions and send alerts if any activity is found.
- H. Write an SCP using the aws:RequestedRegion condition key limiting access to US Region
- I. Apply the policy to all users, groups, and roles

Answer: AB

Explanation:

To implement governance controls that restrict AWS service usage to within the United States and ensure alerts for any activity outside the governance policy, the following actions will meet the requirements:

? A. Create an AWS Organizations SCP that denies access to all non-global services in non-US Regions. Attach the policy to the root of the organization. This action will effectively prevent users and roles in all accounts within the organization from accessing services in non-US Regions¹².

? B. Configure AWS CloudTrail to send logs to Amazon CloudWatch Logs and enable it for all Regions. Use a CloudWatch Logs metric filter to send an alert on any service activity in non-US Regions. This action will allow monitoring of all AWS Regions and will trigger alerts if any activity is detected in non-US Regions, ensuring that the governance team is notified as soon as possible³.

References:

? AWS Documentation on Service Control Policies (SCPs) and how they can be used to manage permissions and restrict access based on Regions¹².

? AWS Documentation on monitoring CloudTrail log files with Amazon CloudWatch Logs to set up alerts for specific activities³.

NEW QUESTION 4

A company has an application that runs on AWS Lambda and sends logs to Amazon CloudWatch Logs. An Amazon Kinesis data stream is subscribed to the log groups in CloudWatch Logs. A single consumer Lambda function processes the logs from the data stream and stores the logs in an Amazon S3 bucket. The company's DevOps team has noticed high latency during the processing and ingestion of some logs. Which combination of steps will reduce the latency? (Select THREE.)

- A. Create a data stream consumer with enhanced fan-out
- B. Set the Lambda function that processes the logs as the consumer.
- C. Increase the ParallelizationFactor setting in the Lambda event source mapping.
- D. Configure reserved concurrency for the Lambda function that processes the logs.
- E. Increase the batch size in the Kinesis data stream.
- F. Turn off the ReportBatchItemFailures setting in the Lambda event source mapping.
- G. Increase the number of shards in the Kinesis data stream.

Answer: ABC

Explanation:

The latency in processing and ingesting logs can be caused by several factors, such as the throughput of the Kinesis data stream, the concurrency of the Lambda function, and the configuration of the event source mapping. To reduce the latency, the following steps can be taken:

? Create a data stream consumer with enhanced fan-out. Set the Lambda function that processes the logs as the consumer. This will allow the Lambda function to receive records from the data stream with dedicated throughput of up to 2 MB per second per shard, independent of other consumers¹. This will reduce the contention and delay in accessing the data stream.

? Increase the ParallelizationFactor setting in the Lambda event source mapping. This will allow the Lambda service to invoke more instances of the function concurrently to process the records from the data stream². This will increase the processing capacity and reduce the backlog of records in the data stream.

? Configure reserved concurrency for the Lambda function that processes the logs. This will ensure that the function has enough concurrency available to handle the increased load from the data stream³. This will prevent the function from being throttled by the account-level concurrency limit.

The other options are not effective or may have negative impacts on the latency. Option D is not suitable because increasing the batch size in the Kinesis data stream will increase the amount of data that the Lambda function has to process in each invocation, which may increase the execution time and latency⁴. Option E is not advisable because turning off the ReportBatchItemFailures setting in the Lambda event source mapping will prevent the Lambda service from retrying the failed records, which may result in data loss. Option F is not necessary because increasing the number of shards in the Kinesis data stream will increase the throughput of the data stream, but it will not affect the processing speed of the Lambda function, which is the bottleneck in this scenario.

References:

? 1: Using AWS Lambda with Amazon Kinesis Data Streams - AWS Lambda

? 2: AWS Lambda event source mappings - AWS Lambda

? 3: Managing concurrency for a Lambda function - AWS Lambda

? 4: AWS Lambda function scaling - AWS Lambda

? : AWS Lambda event source mappings - AWS Lambda

? : Scaling Amazon Kinesis Data Streams with AWS CloudFormation - Amazon Kinesis Data Streams

NEW QUESTION 5

A company uses AWS Key Management Service (AWS KMS) keys and manual key rotation to meet regulatory compliance requirements. The security team wants to be notified when any keys have not been rotated after 90 days.

Which solution will accomplish this?

- A. Configure AWS KMS to publish to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.
- B. Configure an Amazon EventBridge event to launch an AWS Lambda function to call the AWS Trusted Advisor API and publish to an Amazon Simple Notification Service (Amazon SNS) topic.
- C. Develop an AWS Config custom rule that publishes to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.
- D. Configure AWS Security Hub to publish to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/security/how-to-use-aws-config-to-determine-compliance-of-aws-kms-key-policies-to-your-specifications/>

NEW QUESTION 6

A development team is using AWS CodeCommit to version control application code and AWS CodePipeline to orchestrate software deployments. The team has decided to use a remote main branch as the trigger for the pipeline to integrate code changes. A developer has pushed code changes to the CodeCommit repository, but noticed that the pipeline had no reaction, even after 10 minutes.

Which of the following actions should be taken to troubleshoot this issue?

- A. Check that an Amazon EventBridge rule has been created for the main branch to trigger the pipeline.
- B. Check that the CodePipeline service role has permission to access the CodeCommit repository.
- C. Check that the developer's IAM role has permission to push to the CodeCommit repository.
- D. Check to see if the pipeline failed to start because of CodeCommit errors in Amazon CloudWatch Logs.

Answer: A

Explanation:

When you create a pipeline from CodePipeline during the step-by-step it creates a CloudWatch Event rule for a given branch and repo like this:

```
{
  "source": [ "aws.codecommit"
],
  "detail-type": [
    "CodeCommit Repository State Change"
  ],
  "resources": [
    "arn:aws:codecommit:us-east-1:xxxxx:repo-name"
  ],
  "detail": {
```

```
"event": [ "referenceCreated", "referenceUpdated"
],
"referenceType": [ "branch"
],
"referenceName": [ "master"
]
}
}
```

<https://docs.aws.amazon.com/codepipeline/latest/userguide/pipelines-trigger-source-repo-changes-console.html>

NEW QUESTION 7

A company is implementing a well-architected design for its globally accessible API stack. The design needs to ensure both high reliability and fast response times for users located in North America and Europe.

The API stack contains the following three tiers: Amazon API Gateway

AWS Lambda Amazon DynamoDB

Which solution will meet the requirements?

- A. Configure Amazon Route 53 to point to API Gateway APIs in North America and Europe using health check
- B. Configure the APIs to forward requests to a Lambda function in that Region
- C. Configure the Lambda functions to retrieve and update the data in a DynamoDB table in the same Region as the Lambda function.
- D. Configure Amazon Route 53 to point to API Gateway APIs in North America and Europe using latency-based routing and health check
- E. Configure the APIs to forward requests to a Lambda function in that Region
- F. Configure the Lambda functions to retrieve and update the data in a DynamoDB global table.
- G. Configure Amazon Route 53 to point to API Gateway in North America, create a disaster recovery API in Europe, and configure both APIs to forward requests to the Lambda functions in that Region
- H. Retrieve the data from a DynamoDB global table
- I. Deploy a Lambda function to check the North America API health every 5 minutes
- J. In the event of a failure, update Route 53 to point to the disaster recovery API.
- K. Configure Amazon Route 53 to point to API Gateway API in North America using latency-based routing
- L. Configure the API to forward requests to the Lambda function in the Region nearest to the user
- M. Configure the Lambda function to retrieve and update the data in a DynamoDB table.

Answer: B

NEW QUESTION 8

A company has a mobile application that makes HTTP API calls to an Application Load Balancer (ALB). The ALB routes requests to an AWS Lambda function. Many different versions of the application are in use at any given time, including versions that are in testing by a subset of users. The version of the application is defined in the user-agent header that is sent with all requests to the API.

After a series of recent changes to the API, the company has observed issues with the application. The company needs to gather a metric for each API operation by response code for each version of the application that is in use. A DevOps engineer has modified the Lambda function to extract the API operation name, version information from the user-agent header and response code.

Which additional set of actions should the DevOps engineer take to gather the required metrics?

- A. Modify the Lambda function to write the API operation name, response code, and version number as a log line to an Amazon CloudWatch Logs log group
- B. Configure a CloudWatch Logs metric filter that increments a metric for each API operation name
- C. Specify response code and application version as dimensions for the metric.
- D. Modify the Lambda function to write the API operation name, response code, and version number as a log line to an Amazon CloudWatch Logs log group
- E. Configure a CloudWatch Logs Insights query to populate CloudWatch metrics from the log line
- F. Specify response code and application version as dimensions for the metric.
- G. Configure the ALB access logs to write to an Amazon CloudWatch Logs log group
- H. Modify the Lambda function to respond to the ALB with the API operation name, response code, and version number as response metadata
- I. Configure a CloudWatch Logs metric filter that increments a metric for each API operation name
- J. Specify response code and application version as dimensions for the metric.
- K. Configure AWS X-Ray integration on the Lambda function
- L. Modify the Lambda function to create an X-Ray subsegment with the API operation name, response code, and version number
- M. Configure X-Ray insights to extract an aggregated metric for each API operation name and to publish the metric to Amazon CloudWatch
- N. Specify response code and application version as dimensions for the metric.

Answer: A

Explanation:

"Note that the metric filter is different from a log insights query, where the experience is interactive and provides immediate search results for the user to investigate.

No automatic action can be invoked from an insights query. Metric filters, on the other hand, will generate metric data in the form of a time series. This lets you create alarms that integrate into your ITSM processes, execute AWS Lambda functions, or even create anomaly detection models."

<https://aws.amazon.com/blogs/mt/quantify-custom-application-metrics-with-amazon-cloudwatch-logs-and-metric-filters/>

NEW QUESTION 9

A growing company manages more than 50 accounts in an organization in AWS Organizations. The company has configured its applications to send logs to Amazon CloudWatch Logs.

A DevOps engineer needs to aggregate logs so that the company can quickly search the logs to respond to future security incidents. The DevOps engineer has created a new AWS account for centralized monitoring.

Which combination of steps should the DevOps engineer take to make the application logs searchable from the monitoring account? (Select THREE.)

- A. In the monitoring account, download an AWS CloudFormation template from CloudWatch to use in Organization
- B. Use CloudFormation StackSets in the organization's management account to deploy the CloudFormation template to the entire organization.
- C. Create an AWS CloudFormation template that defines an IAM role
- D. Configure the role to allow logs-amazonaws.com to perform the logs:Link action if the aws:ResourceAccount property is equal to the monitoring account ID
- E. Use CloudFormation StackSets in the organization's management account to deploy the CloudFormation template to the entire organization.
- F. Create an IAM role in the monitoring account

- G. Attach a trust policy that allows logs.amazonaws.com to perform the iam:CreateSink action if the aws:PrincipalOrgId property is equal to the organization ID.
- H. In the organization's management account, enable the logging policies for the organization.
- I. use CloudWatch Observability Access Manager in the monitoring account to create a sink
- J. Allow logs to be shared with the monitoring account
- K. Configure the monitoring account data selection to view the Observability data from the organization ID.
- L. In the monitoring account, attach the CloudWatchLogsReadOnlyAccess AWS managed policy to an IAM role that can be assumed to search the logs.

Answer: BCF

Explanation:

? To aggregate logs from multiple accounts in an organization, the DevOps engineer needs to create a cross-account subscription¹ that allows the monitoring account to receive log events from the sharing accounts.

? To enable cross-account subscription, the DevOps engineer needs to create an IAM role in each sharing account that grants permission to CloudWatch Logs to link the log groups to the destination in the monitoring account². This can be done using a CloudFormation template and StackSets³ to deploy the role to all accounts in the organization.

? The DevOps engineer also needs to create an IAM role in the monitoring account that allows CloudWatch Logs to create a sink for receiving log events from other accounts⁴. The role must have a trust policy that specifies the organization ID as a condition.

? Finally, the DevOps engineer needs to attach the CloudWatchLogsReadOnlyAccess policy⁵ to an IAM role in the monitoring account that can be used to search the logs from the cross-account subscription.

References: 1: Cross-account log data sharing with subscriptions 2: Create an IAM role for CloudWatch Logs in each sharing account 3: AWS CloudFormation StackSets 4: Create an IAM role for CloudWatch Logs in your monitoring account 5: CloudWatchLogsReadOnlyAccess policy

NEW QUESTION 10

A large enterprise is deploying a web application on AWS. The application runs on Amazon EC2 instances behind an Application Load Balancer. The instances run in an Auto Scaling group across multiple Availability Zones. The application stores data in an Amazon RDS for Oracle DB instance and Amazon DynamoDB. There are separate environments for development testing and production. What is the MOST secure and flexible way to obtain password credentials during deployment?

- A. Retrieve an access key from an AWS Systems Manager securestring parameter to access AWS service
- B. Retrieve the database credentials from a Systems Manager SecureString parameter.
- C. Launch the EC2 instances with an EC2 IAM role to access AWS services Retrieve the database credentials from AWS Secrets Manager.
- D. Retrieve an access key from an AWS Systems Manager plaintext parameter to access AWS service
- E. Retrieve the database credentials from a Systems Manager SecureString parameter.
- F. Launch the EC2 instances with an EC2 IAM role to access AWS services Store the database passwords in an encrypted config file with the application artifacts.

Answer: B

Explanation:

AWS Secrets Manager is a secrets management service that helps you protect access to your applications, services, and IT resources. This service enables you to easily rotate, manage, and retrieve database credentials, API keys, and other secrets throughout their lifecycle. Using Secrets Manager, you can secure and manage secrets used to access resources in the AWS Cloud, on third-party services, and on-premises. SSM parameter store and AWS Secret manager are both a secure option. However, Secrets manager is more flexible and has more options like password generation. Reference:

<https://www.1strategy.com/blog/2019/02/28/aws-parameter-store-vs-aws-secrets-manager/>

NEW QUESTION 10

A company recently launched multiple applications that use Application Load Balancers. Application response time often slows down when the applications experience problems A DevOps engineer needs to Implement a monitoring solution that alerts the company when the applications begin to perform slowly The DevOps engineer creates an Amazon Simple Notification Service (Amazon SNS) topic and subscribe the company's email address to the topic What should the DevOps engineer do next to meet the requirements?

- A. Create an Amazon EventBridge rule that invokes an AWS Lambda function to query the applications on a 5-minute interval Configure the Lambda function to publish a notification to the SNS topic when the applications return errors.
- B. Create an Amazon CloudWatch Synthetics canary that runs a custom script to query the applications on a 5-minute interval
- C. Configure the canary to use the SNS topic when the applications return errors.
- D. Create an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric Configure the CloudWatch alarm to send a notification when the number of connections becomes greater than the configured number of threads that the application supports Configure the CloudWatch alarm to use the SNS topic.
- E. Create an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric Configure the CloudWatch alarm to send a notification when the average response time becomes greater than the longest response time that the application supports Configure the CloudWatch alarm to use the SNS topic

Answer: B

Explanation:

? Option A is incorrect because creating an Amazon EventBridge rule that invokes an AWS Lambda function to query the applications on a 5-minute interval is not a valid solution. EventBridge rules can only trigger Lambda functions based on events, not on time intervals. Moreover, querying the applications on a 5-minute interval might incur unnecessary costs and network overhead, and might not detect performance issues in real time.

? Option B is correct because creating an Amazon CloudWatch Synthetics canary that runs a custom script to query the applications on a 5-minute interval is a valid solution. CloudWatch Synthetics canaries are configurable scripts that monitor endpoints and APIs by simulating customer behavior. Canaries can run as often as once per minute, and can measure the latency and availability of the applications. Canaries can also send notifications to an Amazon SNS topic when they detect errors or performance issues¹.

? Option C is incorrect because creating an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric is not a valid solution. The RequestCountPerTarget metric measures the number of requests completed or connections made per target in a target group². This metric does not reflect the application response time, which is the requirement. Moreover, configuring the CloudWatch alarm to send a notification when the number of connections becomes greater than the configured number of threads that the application supports is not a valid way to measure the application performance, as it depends on the application design and implementation.

? Option D is incorrect because creating an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric is not a valid solution, for the same reason as option C. The RequestCountPerTarget metric does not reflect the application response time, which is the requirement. Moreover, configuring the CloudWatch alarm to send a notification when the average response time becomes greater than the longest response time that the application supports is not a valid way to measure the application performance, as it does not account for variability or outliers in the response time distribution.

References:

- ? 1: Using synthetic monitoring
? 2: Application Load Balancer metrics

NEW QUESTION 14

A company manages multiple AWS accounts by using AWS Organizations with OUS for the different business divisions. The company is updating their corporate network to use new IP address ranges. The company has 10 Amazon S3 buckets in different AWS accounts. The S3 buckets store reports for the different divisions. The S3 bucket configurations allow only private corporate network IP addresses to access the S3 buckets.

A DevOps engineer needs to change the range of IP addresses that have permission to access the contents of the S3 buckets. The DevOps engineer also needs to revoke the permissions of two OUS in the company.

Which solution will meet these requirements?

- A. Create a new SCP that has two statements, one that allows access to the new range of IP addresses for all the S3 buckets and one that denies access to the old range of IP addresses for all the S3 bucket.
- B. Set a permissions boundary for the OrganizationAccountAccessRole role in the two OUS to deny access to the S3 buckets.
- C. Create a new SCP that has a statement that allows only the new range of IP addresses to access the S3 bucket.
- D. Create another SCP that denies access to the S3 bucket.
- E. Attach the second SCP to the two OUS.
- F. On all the S3 buckets, configure resource-based policies that allow only the new range of IP addresses to access the S3 bucket.
- G. Create a new SCP that denies access to the S3 bucket.
- H. Attach the SCP to the two OUs.
- I. On all the S3 buckets, configure resource-based policies that allow only the new range of IP addresses to access the S3 bucket.
- J. Set a permissions boundary for the OrganizationAccountAccessRole role in the two OUS to deny access to the S3 buckets.

Answer: C

Explanation:

The correct answer is C.

A comprehensive and detailed explanation is:

? Option A is incorrect because creating a new SCP that has two statements, one that allows access to the new range of IP addresses for all the S3 buckets and one that denies access to the old range of IP addresses for all the S3 buckets, is not a valid solution. SCPs are not resource-based policies, and they cannot specify the S3 buckets or the IP addresses as resources or conditions. SCPs can only control the actions that can be performed by the principals in the organization, not the access to specific resources. Moreover, setting a permissions boundary for the OrganizationAccountAccessRole role in the two OUs to deny access to the S3 buckets is not sufficient to revoke the permissions of the two OUs, as there might be other roles or users in those OUs that can still access the S3 buckets.

? Option B is incorrect because creating a new SCP that has a statement that allows only the new range of IP addresses to access the S3 buckets is not a valid solution, for the same reason as option A. SCPs are not resource-based policies, and they cannot specify the S3 buckets or the IP addresses as resources or conditions. Creating another SCP that denies access to the S3 buckets and attaching it to the two OUs is also not a valid solution, as SCPs cannot specify the S3 buckets as resources either.

? Option C is correct because it meets both requirements of changing the range of IP addresses that have permission to access the contents of the S3 buckets and revoking the permissions of two OUs in the company. On all the S3 buckets, configuring resource-based policies that allow only the new range of IP addresses to access the S3 buckets is a valid way to update the IP address ranges, as resource-based policies can specify both resources and conditions. Creating a new SCP that denies access to the S3 buckets and attaching it to the two OUs is also a valid way to revoke the permissions of those OUs, as SCPs can deny actions such as s3:PutObject or s3:GetObject on any resource.

? Option D is incorrect because setting a permissions boundary for the OrganizationAccountAccessRole role in the two OUs to deny access to the S3 buckets is not sufficient to revoke the permissions of the two OUs, as there might be other roles or users in those OUs that can still access the S3 buckets. A permissions boundary is a policy that defines the maximum permissions that an IAM entity can have. However, it does not revoke any existing permissions that are granted by other policies.

References:

- ? AWS Organizations
- ? S3 Bucket Policies
- ? Service Control Policies
- ? Permissions Boundaries

NEW QUESTION 15

A company has an organization in AWS Organizations. The organization includes workload accounts that contain enterprise applications. The company centrally manages users from an operations account. No users can be created in the workload accounts. The company recently added an operations team and must provide the operations team members with administrator access to each workload account.

Which combination of actions will provide this access? (Choose three.)

- A. Create a SysAdmin role in the operations account.
- B. Attach the AdministratorAccess policy to the role.
- C. Modify the trust relationship to allow the sts:AssumeRole action from the workload accounts.
- D. Create a SysAdmin role in each workload account.
- E. Attach the AdministratorAccess policy to the role.
- F. Modify the trust relationship to allow the sts:AssumeRole action from the operations account.
- G. Create an Amazon Cognito identity pool in the operations account.
- H. Attach the SysAdmin role as an authenticated role.
- I. In the operations account, create an IAM user for each operations team member.
- J. In the operations account, create an IAM user group that is named SysAdmin.
- K. Add an IAM policy that allows the sts:AssumeRole action for the SysAdmin role in each workload account.
- L. Add all operations team members to the group.
- M. Create an Amazon Cognito user pool in the operations account.
- N. Create an Amazon Cognito user for each operations team member.

Answer: BDE

Explanation:

https://docs.aws.amazon.com/IAM/latest/UserGuide/tutorial_cross-account-with-roles.html

NEW QUESTION 16

A company runs a workload on Amazon EC2 instances. The company needs a control that requires the use of Instance Metadata Service Version 2 (IMDSv2) on all EC2 instances in the AWS account. If an EC2 instance does not prevent the use of Instance Metadata Service Version 1 (IMDSv1), the EC2 instance must be terminated.

Which solution will meet these requirements?

- A. Set up AWS Config in the account
- B. Use a managed rule to check EC2 instance
- C. Configure the rule to remediate the findings by using AWS Systems Manager Automation to terminate the instance.
- D. Create a permissions boundary that prevents the `ec2:RunInstance` action if the `ec2:MetadataHttpTokens` condition key is not set to a value of `required`
- E. Attach the permissions boundary to the IAM role that was used to launch the instance.
- F. Set up Amazon Inspector in the account
- G. Configure Amazon Inspector to activate deep inspection for EC2 instance
- H. Create an Amazon EventBridge rule for an Inspector2 finding
- I. Set an AWS Lambda function as the target to terminate the instance.
- J. Create an Amazon EventBridge rule for the EC2 instance launch successful event
- K. Send the event to an AWS Lambda function to inspect the EC2 metadata and to terminate the instance.

Answer: B

Explanation:

To implement a control that requires the use of IMDSv2 on all EC2 instances in the account, the DevOps engineer can use a permissions boundary. A permissions boundary is a policy that defines the maximum permissions that an IAM entity can have. The DevOps engineer can create a permissions boundary that prevents the `ec2:RunInstance` action if the `ec2:MetadataHttpTokens` condition key is not set to a value of `required`. This condition key enforces the use of IMDSv2 on EC2 instances. The DevOps engineer can attach the permissions boundary to the IAM role that was used to launch the instance. This way, any attempt to launch an EC2 instance without using IMDSv2 will be denied by the permissions boundary.

NEW QUESTION 21

A company has enabled all features for its organization in AWS Organizations. The organization contains 10 AWS accounts. The company has turned on AWS CloudTrail in all the accounts. The company expects the number of AWS accounts in the organization to increase to 500 during the next year. The company plans to use multiple OUs for these accounts.

The company has enabled AWS Config in each existing AWS account in the organization.

A DevOps engineer must implement a solution that enables AWS Config automatically for all future AWS accounts that are created in the organization.

Which solution will meet this requirement?

- A. In the organization's management account, create an Amazon EventBridge rule that reacts to a `CreateAccount` API call
- B. Configure the rule to invoke an AWS Lambda function that enables trusted access to AWS Config for the organization.
- C. In the organization's management account, create an AWS CloudFormation stack set to enable AWS Config
- D. Configure the stack set to deploy automatically when an account is created through Organizations.
- E. In the organization's management account, create an SCP that allows the appropriate AWS Config API calls to enable AWS Config
- F. Apply the SCP to the root-level OU.
- G. In the organization's management account, create an Amazon EventBridge rule that reacts to a `CreateAccount` API call
- H. Configure the rule to invoke an AWS Systems Manager Automation runbook to enable AWS Config for the account.

Answer: B

Explanation:

<https://aws.amazon.com/about-aws/whats-new/2020/02/aws-cloudformation-stacksets-introduces-automatic-deployments-across-accounts-and-regions-through-aws-organizations/>

NEW QUESTION 23

A company uses an Amazon API Gateway regional REST API to host its application API. The REST API has a custom domain. The REST API's default endpoint is deactivated.

The company's internal teams consume the API. The company wants to use mutual TLS between the API and the internal teams as an additional layer of authentication.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Use AWS Certificate Manager (ACM) to create a private certificate authority (CA). Provision a client certificate that is signed by the private CA.
- B. Provision a client certificate that is signed by a public certificate authority (CA). Import the certificate into AWS Certificate Manager (ACM).
- C. Upload the provisioned client certificate to an Amazon S3 bucket
- D. Configure the API Gateway mutual TLS to use the client certificate that is stored in the S3 bucket as the trust store.
- E. Upload the provisioned client certificate private key to an Amazon S3 bucket
- F. Configure the API Gateway mutual TLS to use the private key that is stored in the S3 bucket as the trust store.
- G. Upload the root private certificate authority (CA) certificate to an Amazon S3 bucket
- H. Configure the API Gateway mutual TLS to use the private CA certificate that is stored in the S3 bucket as the trust store.

Answer: AE

Explanation:

Mutual TLS (mTLS) authentication requires two-way authentication between the client and the server. For Amazon API Gateway, you can enable mTLS for a custom domain name, which requires clients to present X.509 certificates to verify their identity to access your API. To set up mTLS, you would typically use AWS Certificate Manager (ACM) to create a private certificate authority (CA) and provision a client certificate signed by this private CA. The root CA certificate is then uploaded to an Amazon S3 bucket and configured in API Gateway as the trust store¹².

References:

- ? Introducing mutual TLS authentication for Amazon API Gateway¹.
- ? Configuring mutual TLS authentication for a REST API².
- ? AWS Private Certificate Authority details³.
- ? AWS Certificate Manager Private Certificate Authority updates⁴.

NEW QUESTION 28

A company sells products through an ecommerce web application. The company wants a dashboard that shows a pie chart of product transaction details. The

company wants to integrate the dashboard With the company's existing Amazon CloudWatch dashboards Which solution Will meet these requirements With the MOST operational efficiency?

- A. Update the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transactio
- B. Use CloudWatch Logs Insights to query the log group and to visualize the results in a pie chart format Attach the results to the desired CloudWatch dashboard.
- C. Update the ecommerce application to emit a JSON object to an Amazon S3 bucket for each processed transactio
- D. Use Amazon Athena to query the S3 bucket and to visualize the results In a Pie chart forma
- E. Export the results from Athena Attach the results to the desired CloudWatch dashboard
- F. Update the ecommerce application to use AWS X-Ray for instrumentatio
- G. Create a new X-Ray subsegment Add an annotation for each processed transactio
- H. Use X-Ray traces to query the data and to visualize the results in a pie chart format Attach the results to the desired CloudWatch dashboard
- I. Update the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction_ Create an AWS Lambda function to aggregate and write the results to Amazon DynamoD
- J. Create a Lambda subscription filter for the log fil
- K. Attach the results to the desired CloudWatch dashboard.

Answer: A

Explanation:

The correct answer is A.

A comprehensive and detailed explanation is:

? Option A is correct because it meets the requirements with the most operational efficiency. Updating the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction is a simple and cost- effective way to collect the data needed for the dashboard. Using CloudWatch Logs Insights to query the log group and to visualize the results in a pie chart format is also a convenient and integrated solution that leverages the existing CloudWatch dashboards. Attaching the results to the desired CloudWatch dashboard is straightforward and does not require any additional steps or services.

? Option B is incorrect because it introduces unnecessary complexity and cost.

Updating the ecommerce application to emit a JSON object to an Amazon S3 bucket for each processed transaction is a valid way to store the data, but it requires creating and managing an S3 bucket and its permissions. Using Amazon Athena to query the S3 bucket and to visualize the results in a pie chart format is also a valid way to analyze the data, but it incurs charges based on the amount of data scanned by each query. Exporting the results from Athena and attaching them to the desired CloudWatch dashboard is also an extra step that adds more overhead and latency.

? Option C is incorrect because it uses AWS X-Ray for an inappropriate purpose.

Updating the ecommerce application to use AWS X-Ray for instrumentation is a good practice for monitoring and tracing distributed applications, but it is not designed for aggregating product transaction details. Creating a new X-Ray subsegment and adding an annotation for each processed transaction is possible, but it would clutter the X-Ray service map and make it harder to debug performance issues. Using X-Ray traces to query the data and to visualize the results in a pie chart format is also possible, but it would require custom code and logic that are not supported by X-Ray natively. Attaching the results to the desired CloudWatch dashboard is also not supported by X-Ray directly, and would require additional steps or services.

? Option D is incorrect because it introduces unnecessary complexity and cost.

Updating the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction is a simple and cost-effective way to collect the data needed for the dashboard, as in option A. However, creating an AWS Lambda function to aggregate and write the results to Amazon DynamoDB is redundant, as CloudWatch Logs Insights can already perform aggregation queries on log data. Creating a Lambda subscription filter for the log file is also redundant, as CloudWatch Logs Insights can already access log data directly. Attaching the results to the desired CloudWatch dashboard would also require additional steps or services, as DynamoDB does not support native integration with CloudWatch dashboards.

References:

? CloudWatch Logs Insights

? Amazon Athena

? AWS X-Ray

? AWS Lambda

? Amazon DynamoDB

NEW QUESTION 33

A company deploys its corporate infrastructure on AWS across multiple AWS Regions and Availability Zones. The infrastructure is deployed on Amazon EC2 instances and connects with AWS IoT Greengrass devices. The company deploys additional resources on on- premises servers that are located in the corporate headquarters.

The company wants to reduce the overhead involved in maintaining and updating its resources. The company's DevOps team plans to use AWS Systems Manager to implement automated management and application of patches. The DevOps team confirms that Systems Manager is available in the Regions that the resources are deployed m Systems Manager also is available in a Region near the corporate headquarters.

Which combination of steps must the DevOps team take to implement automated patch and configuration management across the company's EC2 instances IoT devices and on- premises infrastructure? (Select THREE.)

- A. Apply tags lo all the EC2 instance
- B. AWS IoT Greengrass devices, and on-premises server
- C. Use Systems Manager Session Manager to push patches to all the tagged devices.
- D. Use Systems Manager Run Command to schedule patching for the EC2 instances AWS IoT Greengrass devices and on-premises servers.
- E. Use Systems Manager Patch Manager to schedule patching IoT the EC2 instances AWS IoT Greengrass devices and on-premises servers as a Systems Manager maintenance window task.
- F. Configure Amazon EventBridge to monitor Systems Manager Patch Manager for updates to patch baseline
- G. Associate Systems Manager Run Command with the event lo initiate a patch action for all EC2 instances AWS IoT Greengrass devices and on-premises servers.
- H. Create an IAM instance profile for Systems Manager Attach the instance profile to all the EC2 instances in the AWS accoun
- I. For the AWS IoT Greengrass devices and on-premises servers create an IAM service role for Systems Manager.
- J. Generate a managed-instance activation Use the Activation Code and Activation ID to install Systems Manager Agent (SSM Agent) on each server in the on-premises environment Update the AWS IoT Greengrass IAM token exchange role Use the role to deploy SSM Agent on all the IoT devices.

Answer: CEF

Explanation:

https://aws.amazon.com/blogs/mt/how-to-centrally-manage-aws-iot-greengrass-devices-using-aws-systems-manager/?force_isolation=true

NEW QUESTION 34

An Amazon EC2 instance is running in a VPC and needs to download an object from a restricted Amazon S3 bucket. When the DevOps engineer tries to

download the object, an AccessDenied error is received,
What are the possible causes for this error? (Select TWO,)

- A. The S3 bucket default encryption is enabled.
- B. There is an error in the S3 bucket policy.
- C. The object has been moved to S3 Glacier.
- D. There is an error in the IAM role configuration.
- E. S3 Versioning is enabled.

Answer: BD

Explanation:

These are the possible causes for the AccessDenied error because they affect the permissions to access the S3 object from the EC2 instance. An S3 bucket policy is a resource-based policy that defines who can access the bucket and its objects, and what actions they can perform. An IAM role is an identity that can be assumed by an EC2 instance to grant it permissions to access AWS services and resources. If there is an error in the S3 bucket policy or the IAM role configuration, such as a missing or incorrect statement, condition, or principal, then the EC2 instance may not have the necessary permissions to download the object from the S3 bucket . <https://docs.aws.amazon.com/AmazonS3/latest/userguide/example-bucket-policies.html>
<https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/iam-roles-for-amazon-ec2.html>

NEW QUESTION 35

A company recently migrated its legacy application from on-premises to AWS. The application is hosted on Amazon EC2 instances behind an Application Load Balancer which is behind Amazon API Gateway. The company wants to ensure users experience minimal disruptions during any deployment of a new version of the application. The company also wants to ensure it can quickly roll back updates if there is an issue.
Which solution will meet these requirements with MINIMAL changes to the application?

- A. Introduce changes as a separate environment parallel to the existing one Configure API Gateway to use a canary release deployment to send a small subset of user traffic to the new environment.
- B. Introduce changes as a separate environment parallel to the existing one Update the application's DNS alias records to point to the new environment.
- C. Introduce changes as a separate target group behind the existing Application Load Balancer Configure API Gateway to route user traffic to the new target group in steps.
- D. Introduce changes as a separate target group behind the existing Application Load Balancer Configure API Gateway to route all traffic to the Application Load Balancer which then sends the traffic to the new target group.

Answer: A

Explanation:

API Gateway supports canary deployment on a deployment stage before you direct all traffic to that stage. A parallel environment means we will create a new ALB and a target group that will target a new set of EC2 instances on which the newer version of the app will be deployed. So the canary setting associated to the new version of the API will connect with the new ALB instance which in turn will direct the traffic to the new EC2 instances on which the newer version of the application is deployed.

NEW QUESTION 40

A company's development team uses AWS CloudFormation to deploy its application resources The team must use for any changes to the environment The team cannot use AWS Management Console or the AWS CLI to make manual changes directly.
The team uses a developer IAM role to access the environment The role is configured with the AdministratorAccess managed policy. The company has created a new CloudFormationDeployment IAM role that has the following policy.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "elasticloadbalancing:*",
        "lambda:*",
        "dynamodb:*"
      ],
      "Resource": "*"
    }
  ]
}
```

The company wants ensure that only CloudFormation can use the new role. The development team cannot make any manual changes to the deployed resources.
Which combination of steps meet these requirements? (Select THREE.)

- A. Remove the AdministratorAccess policy
- B. Assign the ReadOnlyAccess managed IAM policy to the developer role
- C. Instruct the developers to use the CloudFormationDeployment role as a CloudFormation service role when the developers deploy new stacks.
- D. Update the trust of CloudFormationDeployment role to allow the developer IAM role to assume the CloudFormationDeployment role.
- E. Configure the IAM to be to get and pass the CloudFormationDeployment role if cloudformation actions for resources,
- F. Update the trust Of the CloudFormationDeployment role to allow the cloudformation.amazonaws.com AWS principal to perform the iam:AssumeRole action
- G. Remove the AdministratorAccess policy
- H. Assign the ReadOnly/Access managed IAM policy to the developer role Instruct the developers to assume the CloudFormationDeployment role when the

developers new stacks

I. Add an IAM policy to CloudFormationDeployment to allow cloudformation * on an Add a policy that allows the iam:PassRole action for ARN of if iam PassedToService equal cloudformation.amazonaws.com

Answer: ADF

Explanation:

A comprehensive and detailed explanation is:

? Option A is correct because removing the AdministratorAccess policy and assigning the ReadOnlyAccess managed IAM policy to the developer role is a valid way to prevent the developers from making any manual changes to the deployed resources. The AdministratorAccess policy grants full access to all AWS resources and actions, which is not necessary for the developers. The ReadOnlyAccess policy grants read-only access to most AWS resources and actions, which is sufficient for the developers to view the status of their stacks. Instructing the developers to use the CloudFormationDeployment role as a CloudFormation service role when they deploy new stacks is also a valid way to ensure that only CloudFormation can use the new role. A CloudFormation service role is an IAM role that allows CloudFormation to make calls to resources in a stack on behalf of the user1. The user can specify a service role when they create or update a stack, and CloudFormation will use that role's credentials for all operations that are performed on that stack1.

? Option B is incorrect because updating the trust of CloudFormationDeployment role to allow the developer IAM role to assume the CloudFormationDeployment role is not a valid solution. This would allow the developers to manually assume the CloudFormationDeployment role and perform actions on the deployed resources, which is not what the company wants. The trust of CloudFormationDeployment role should only allow the cloudformation.amazonaws.com AWS principal to assume the role, as in option D.

? Option C is incorrect because configuring the IAM user to be able to get and pass the CloudFormationDeployment role if cloudformation actions for resources is not a valid solution. This would allow the developers to manually pass the CloudFormationDeployment role to other services or resources, which is not what the company wants. The IAM user should only be able to pass the CloudFormationDeployment role as a service role when they create or update a stack with CloudFormation, as in option A.

? Option D is correct because updating the trust of CloudFormationDeployment role to allow the cloudformation.amazonaws.com AWS principal to perform the iam:AssumeRole action is a valid solution. This allows CloudFormation to assume the CloudFormationDeployment role and access resources in other services on behalf of the user2. The trust policy of an IAM role defines which entities can assume the role2. By specifying cloudformation.amazonaws.com as the principal, you grant permission only to CloudFormation to assume this role.

? Option E is incorrect because instructing the developers to assume the CloudFormationDeployment role when they deploy new stacks is not a valid solution. This would allow the developers to manually assume the CloudFormationDeployment role and perform actions on the deployed resources, which is not what the company wants. The developers should only use the CloudFormationDeployment role as a service role when they deploy new stacks with CloudFormation, as in option A.

? Option F is correct because adding an IAM policy to CloudFormationDeployment that allows cloudformation:* on all resources and adding a policy that allows the iam:PassRole action for ARN of CloudFormationDeployment if iam:PassedToService equals cloudformation.amazonaws.com are valid solutions. The first policy grants permission for CloudFormationDeployment to perform any action with any resource using cloudformation.amazonaws.com as a service principal3. The second policy grants permission for passing this role only if it is passed by cloudformation.amazonaws.com as a service principal4. This ensures that only CloudFormation can use this role.

References:

? 1: AWS CloudFormation service roles

? 2: How to use trust policies with IAM roles

? 3: AWS::IAM::Policy

? 4: IAM: Pass an IAM role to a specific AWS service

NEW QUESTION 41

A company requires its developers to tag all Amazon Elastic Block Store (Amazon EBS) volumes in an account to indicate a desired backup frequency. This requirement Includes EBS volumes that do not require backups. The company uses custom tags named Backup_Frequency that have values of none, daily, or weekly that correspond to the desired backup frequency. An audit finds that developers are occasionally not tagging the EBS volumes.

A DevOps engineer needs to ensure that all EBS volumes always have the Backup_Frequency tag so that the company can perform backups at least weekly unless a different value is specified.

Which solution will meet these requirements?

- A. Set up AWS Config in the account
- B. Create a custom rule that returns a compliance failure for all Amazon EC2 resources that do not have a Backup Frequency tag applied. Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly.
- C. Set up AWS Config in the account
- D. Use a managed rule that returns a compliance failure for EC2::Volume resources that do not have a Backup Frequency tag applied
- E. Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly.
- F. Turn on AWS CloudTrail in the account
- G. Create an Amazon EventBridge rule that reacts to EBS CreateVolume event
- H. Configure a custom AWS Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly
- I. Specify the runbook as the target of the rule.
- J. Turn on AWS CloudTrail in the account
- K. Create an Amazon EventBridge rule that reacts to EBS CreateVolume events or EBS ModifyVolume event
- L. Configure a custom AWS Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly
- M. Specify the runbook as the target of the rule.

Answer: B

Explanation:

The following are the steps that the DevOps engineer should take to ensure that all EBS volumes always have the Backup_Frequency tag so that the company can perform backups at least weekly unless a different value is specified:

? Set up AWS Config in the account.

? Use a managed rule that returns a compliance failure for EC2::Volume resources that do not have a Backup Frequency tag applied.

? Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly.

The managed rule AWS::Config::EBSVolumesWithoutBackupTag will return a compliance failure for any EBS volume that does not have the Backup_Frequency tag applied. The remediation action will then use the Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly to the EBS volume.

NEW QUESTION 42

An IT team has built an AWS CloudFormation template so others in the company can quickly and reliably deploy and terminate an application. The template creates an Amazon EC2 instance with a user data script to install the application and an Amazon S3 bucket that the application uses to serve static webpages while it is running.

All resources should be removed when the CloudFormation stack is deleted. However, the team observes that CloudFormation reports an error during stack deletion, and the S3 bucket created by the stack is not deleted.

How can the team resolve the error in the MOST efficient manner to ensure that all resources are deleted without errors?

- A. Add a DeletionPolicy attribute to the S3 bucket resource, with the value Delete forcing the bucket to be removed when the stack is deleted.
- B. Add a custom resource with an AWS Lambda function with the DependsOn attribute specifying the S3 bucket, and an IAM role
- C. Write the Lambda function to delete all objects from the bucket when RequestType is Delete.
- D. Identify the resource that was not deleted
- E. Manually empty the S3 bucket and then delete it.
- F. Replace the EC2 and S3 bucket resources with a single AWS OpsWorks Stacks resource
- G. Define a custom recipe for the stack to create and delete the EC2 instance and the S3 bucket.

Answer: B

Explanation:

<https://aws.amazon.com/premiumsupport/knowledge-center/cloudformation-s3-custom-resources/>

NEW QUESTION 44

A company's security policies require the use of security hardened AMIs in production environments. A DevOps engineer has used EC2 Image Builder to create a pipeline that builds the AMIs on a recurring schedule.

The DevOps engineer needs to update the launch templates of the company's Auto Scaling groups. The Auto Scaling groups must use the newest AMI during the launch of Amazon EC2 instances.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Configure an Amazon EventBridge rule to receive new AMI events from Image Builder
- B. Target an AWS Systems Manager Run Command document that updates the launch templates of the Auto Scaling groups with the newest AMI ID.
- C. Configure an Amazon EventBridge rule to receive new AMI events from Image Builder
- D. Target an AWS Lambda function that updates the launch templates of the Auto Scaling groups with the newest AMI ID.
- E. Configure the launch template to use a value from AWS Systems Manager Parameter Store for the AMI ID
- F. Configure the Image Builder pipeline to update the Parameter Store value with the newest AMI ID.
- G. Configure the Image Builder distribution settings to update the launch templates with the newest AMI ID
- H. Configure the Auto Scaling groups to use the newest version of the launch template.

Answer: C

Explanation:

? The most operationally efficient solution is to use AWS Systems Manager Parameter Store¹ to store the AMI ID and reference it in the launch template². This way, the launch template does not need to be updated every time a new AMI is created by Image Builder. Instead, the Image Builder pipeline can update the Parameter Store value with the newest AMI ID³, and the Auto Scaling group can launch instances using the latest value from Parameter Store.

? The other solutions require updating the launch template or creating a new version of it every time a new AMI is created, which adds complexity and overhead. Additionally, using EventBridge rules and Lambda functions or Run Command documents introduces additional dependencies and potential points of failure.

References: 1: AWS Systems Manager Parameter Store 2: Using AWS Systems Manager parameters instead of AMI IDs in launch templates 3: Update an SSM parameter with Image Builder

NEW QUESTION 45

A DevOps engineer is working on a project that is hosted on Amazon Linux and has failed a security review. The DevOps manager has been asked to review the company buildspec.yaml file for an AWS CodeBuild project and provide recommendations. The buildspec.yaml file is configured as follows:

```
env:
  variables:
    AWS_ACCESS_KEY_ID: AKIAJF7BRFWJBA4GHXNA
    AWS_SECRET_ACCESS_KEY: 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
    AWS_DEFAULT_REGION: us-east-1
    DB_PASSWORD: cuj5RptFa3va
  phases:
    build:
      commands:
        - aws s3 cp s3://db-deploy-bucket/my.cnf.template /tmp/my.cnf
        - sed -i '' s/DB_PW/${DB_PASSWORD}/ /tmp/my.cnf
        - aws s3 cp s3://db-deploy-bucket/instance.key /tmp/instance.key
        - chmod 600 /tmp/instance.key
        - scp -i /tmp/instance.key /tmp/my.cnf root@10.25.15.23:/etc/my.cnf
        - ssh -i /tmp/instance.key root@10.25.15.23 /etc/init.d/mysqld restart
```

What changes should be recommended to comply with AWS security best practices? (Select THREE.)

- A. Add a post-build command to remove the temporary files from the container before termination to ensure they cannot be seen by other CodeBuild users.
- B. Update the CodeBuild project role with the necessary permissions and then remove the AWS credentials from the environment variable.
- C. Store the db_password as a SecureString value in AWS Systems Manager Parameter Store and then remove the db_password from the environment variables.
- D. Move the environment variables to the 'db-deploy-bucket' Amazon S3 bucket, add a prebuild stage to download then export the variables.
- E. Use AWS Systems Manager run command versus scp and ssh commands directly to the instance.

Answer: BCE

Explanation:

B. Update the CodeBuild project role with the necessary permissions and then remove the AWS credentials from the environment variable. C. Store the DB_PASSWORD as a SecureString value in AWS Systems Manager Parameter Store and then remove the DB_PASSWORD from the environment variables. E. Use AWS Systems Manager run command versus scp and ssh commands directly to the instance.

NEW QUESTION 47

A company runs its container workloads in AWS App Runner. A DevOps engineer manages the company's container repository in Amazon Elastic Container Registry (Amazon ECR).

The DevOps engineer must implement a solution that continuously monitors the container repository. The solution must create a new container image when the solution detects an operating system vulnerability or language package vulnerability.

Which solution will meet these requirements?

- A. Use EC2 Image Builder to create a container image pipelin
- B. Use Amazon ECR as the target repositor
- C. Turn on enhanced scanning on the ECR repositor
- D. Create an Amazon EventBridge rule to capture an Inspector2 finding even
- E. Use the event to invoke the image pipelin
- F. Re-upload the container to the repository.
- G. Use EC2 Image Builder to create a container image pipelin
- H. Use Amazon ECR as the target repositor
- I. Enable Amazon GuardDuty Malware Protection on the container workloa
- J. Create an Amazon EventBridge rule to capture a GuardDuty finding even
- K. Use the event to invoke the image pipeline.
- L. Create an AWS CodeBuild project to create a container imag
- M. Use Amazon ECR as the target repositor
- N. Turn on basic scanning on the repositor
- O. Create an Amazon EventBridge rule to capture an ECR image action even
- P. Use the event to invoke the CodeBuild projec
- Q. Re-upload the container to the repository.
- R. Create an AWS CodeBuild project to create a container imag
- S. Use Amazon ECR as the target repositor
- T. Configure AWS Systems Manager Compliance to scan all managed node
- . Create an Amazon EventBridge rule to capture a configuration compliance state change even
- . Use the event to invoke the CodeBuild project.

Answer: A

Explanation:

The solution that meets the requirements is to use EC2 Image Builder to create a container image pipeline, use Amazon ECR as the target repository, turn on enhanced scanning on the ECR repository, create an Amazon EventBridge rule to capture an Inspector2 finding event, and use the event to invoke the image pipeline. Re-upload the container to the repository.

This solution will continuously monitor the container repository for vulnerabilities using enhanced scanning, which is a feature of Amazon ECR that provides detailed information and guidance on how to fix security issues found in your container images. Enhanced scanning uses Inspector2, a security assessment service that integrates with Amazon ECR and generates findings for any vulnerabilities detected in your images. You can use Amazon EventBridge to create a rule that triggers an action when an Inspector2 finding event occurs. The action can be to invoke an EC2 Image Builder pipeline, which is a service that automates the creation of container images. The pipeline can use the latest patches and updates to build a new container image and upload it to the same ECR repository, replacing the vulnerable image.

The other options are not correct because they do not meet all the requirements or use services that are not relevant for the scenario.

Option B is not correct because it uses Amazon GuardDuty Malware Protection, which is a feature of GuardDuty that detects malicious activity and unauthorized behavior on your AWS accounts and resources. GuardDuty does not scan container images for vulnerabilities, nor does it integrate with Amazon ECR or EC2 Image Builder.

Option C is not correct because it uses basic scanning on the ECR repository, which only provides a summary of the vulnerabilities found in your container images. Basic scanning does not use Inspector2 or generate findings that can be captured by Amazon EventBridge. Moreover, basic scanning does not provide guidance on how to fix the vulnerabilities.

Option D is not correct because it uses AWS Systems Manager Compliance, which is a feature of Systems Manager that helps you monitor and manage the compliance status of your AWS resources based on AWS Config rules and AWS Security Hub standards. Systems Manager Compliance does not scan container images for vulnerabilities, nor does it integrate with Amazon ECR or EC2 Image Builder.

NEW QUESTION 51

A company that runs many workloads on AWS has an Amazon EBS spend that has increased over time. The DevOps team notices there are many unattached EBS volumes. Although there are workloads where volumes are detached, volumes over 14 days old are stale and no longer needed. A DevOps engineer has been tasked with creating automation that deletes unattached EBS volumes that have been unattached for 14 days.

Which solution will accomplish this?

- A. Configure the AWS Config ec2-volume-inuse-check managed rule with a configuration changes trigger type and an Amazon EC2 volume resource target
- B. Create a new Amazon CloudWatch Events rule scheduled to execute an AWS Lambda function in 14 days to delete the specified EBS volume.
- C. Use Amazon EC2 and Amazon Data Lifecycle Manager to configure a volume lifecycle polic
- D. Set the interval period for unattached EBS volumes to 14 days and set the retention rule to delet
- E. Set the policy target volumes as *.
- F. Create an Amazon CloudWatch Events rule to execute an AWS Lambda function dail
- G. The Lambda function should find unattached EBS volumes and tag them with the current date, and delete unattached volumes that have tags with dates that are more than 14 days old.
- H. Use AWS Trusted Advisor to detect EBS volumes that have been detached for more than 14 day
- I. Execute an AWS Lambda function that creates a snapshot and then deletes the EBS volume.

Answer: C

Explanation:

The requirement is to create automation that deletes unattached EBS volumes that have been unattached for 14 days. To do this, the DevOps engineer needs to use the following steps:

? Create an Amazon CloudWatch Events rule to execute an AWS Lambda function

daily. CloudWatch Events is a service that enables event-driven architectures by delivering events from various sources to targets. Lambda is a service that lets you

run code without provisioning or managing servers. By creating a CloudWatch Events rule that executes a Lambda function daily, the DevOps engineer can schedule a recurring task to check and delete unattached EBS volumes.

? The Lambda function should find unattached EBS volumes and tag them with the

current date, and delete unattached volumes that have tags with dates that are more than 14 days old. The Lambda function can use the EC2 API to list and filter

unattached EBS volumes based on their state and tags. The function can then tag each unattached volume with the current date using the create-tags command. The function can also compare the tag value with the current date and delete any unattached volume that has been tagged more than 14 days ago using the delete-volume command.

NEW QUESTION 55

A company has its AWS accounts in an organization in AWS Organizations. AWS Config is manually configured in each AWS account. The company needs to implement a solution to centrally configure AWS Config for all accounts in the organization. The solution also must record resource changes to a central account. Which combination of actions should a DevOps engineer perform to meet these requirements? (Choose two.)

- A. Configure a delegated administrator account for AWS Config
- B. Enable trusted access for AWS Config in the organization.
- C. Configure a delegated administrator account for AWS Config
- D. Create a service-linked role for AWS Config in the organization's management account.
- E. Create an AWS CloudFormation template to create an AWS Config aggregator
- F. Configure a CloudFormation stack set to deploy the template to all accounts in the organization.
- G. Create an AWS Config organization aggregator in the organization's management account
- H. Configure data collection from all AWS accounts in the organization and from all AWS Regions.
- I. Create an AWS Config organization aggregator in the delegated administrator account
- J. Configure data collection from all AWS accounts in the organization and from all AWS Regions.

Answer: AE

Explanation:

<https://aws.amazon.com/blogs/mt/org-aggregator-delegated-admin/> <https://docs.aws.amazon.com/organizations/latest/userguide/services-that-can-integrate-config.html>

NEW QUESTION 58

A DevOps engineer is building a continuous deployment pipeline for a serverless application that uses AWS Lambda functions. The company wants to reduce the customer impact of an unsuccessful deployment. The company also wants to monitor for issues. Which deploy stage configuration will meet these requirements?

- A. Use an AWS Serverless Application Model (AWS SAM) template to define the serverless application
- B. Use AWS CodeDeploy to deploy the Lambda functions with the Canary10Percent15Minutes Deployment Preference Type
- C. Use Amazon CloudWatch alarms to monitor the health of the functions.
- D. Use AWS CloudFormation to publish a new stack update, and include Amazon CloudWatch alarms on all resources
- E. Set up an AWS CodePipeline approval action for a developer to verify and approve the AWS CloudFormation change set.
- F. Use AWS CloudFormation to publish a new version on every stack update, and include Amazon CloudWatch alarms on all resources
- G. Use the RoutingConfig property of the AWS::Lambda::Alias resource to update the traffic routing during the stack update.
- H. Use AWS CodeBuild to add sample event payloads for testing to the Lambda function
- I. Publish a new version of the functions, and include Amazon CloudWatch alarm
- J. Update the production alias to point to the new version
- K. Configure rollbacks to occur when an alarm is in the ALARM state.

Answer: D

Explanation:

Use routing configuration on an alias to send a portion of traffic to a second function version. For example, you can reduce the risk of deploying a new version by configuring the alias to send most of the traffic to the existing version, and only a small percentage of traffic to the new version.

<https://docs.aws.amazon.com/lambda/latest/dg/configuration-aliases.html>

The following are the steps involved in the deploy stage configuration that will meet the requirements:

? Use AWS CodeBuild to add sample event payloads for testing to the Lambda functions.

? Publish a new version of the functions, and include Amazon CloudWatch alarms.

? Update the production alias to point to the new version.

? Configure rollbacks to occur when an alarm is in the ALARM state.

This configuration will help to reduce the customer impact of an unsuccessful deployment

by deploying the new version of the functions to a staging environment first. This will allow the DevOps engineer to test the new version of the functions before deploying it to production.

The configuration will also help to monitor for issues by including Amazon CloudWatch alarms. These alarms will alert the DevOps engineer if there are any problems with the new version of the functions.

NEW QUESTION 62

A company is deploying a new application that uses Amazon EC2 instances. The company needs a solution to query application logs and AWS account API activity. Which solution will meet these requirements?

- A. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon CloudWatch Logs. Configure AWS CloudTrail to deliver the API logs to Amazon S3. Use CloudWatch to query both sets of logs.
- B. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon CloudWatch Logs. Configure AWS CloudTrail to deliver the API logs to CloudWatch Logs. Use CloudWatch Logs Insights to query both sets of logs.
- C. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon Kinesis. Configure AWS CloudTrail to deliver the API logs to Kinesis. Use Kinesis to load the data into Amazon Redshift. Use Amazon Redshift to query both sets of logs.
- D. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon S3. Use AWS CloudTrail to deliver the API logs to Amazon S3. Use Amazon Athena to query both sets of logs in Amazon S3.

Answer: D

Explanation:

This solution will meet the requirements because it will use Amazon S3 as a common data lake for both the application logs and the API logs. Amazon S3 is a service that provides scalable, durable, and secure object storage for any type of data. You can use the Amazon CloudWatch agent to send logs from your EC2 instances to S3 buckets, and use AWS CloudTrail to deliver the API logs to S3 buckets as well. You can also use Amazon Athena to query both sets of logs in S3.

using standard SQL, without loading or transforming them. Athena is a serverless interactive query service that allows you to analyze data in S3 using a variety of data formats, such as JSON, CSV, Parquet, and ORC.

NEW QUESTION 67

A company hosts a security auditing application in an AWS account. The auditing application uses an IAM role to access other AWS accounts. All the accounts are in the same organization in AWS Organizations.

A recent security audit revealed that users in the audited AWS accounts could modify or delete the auditing application's IAM role. The company needs to prevent any modification to the auditing application's IAM role by any entity other than a trusted administrator IAM role.

Which solution will meet these requirements?

- A. Create an SCP that includes a Deny statement for changes to the auditing application's IAM rol
- B. Include a condition that allows the trusted administrator IAM role to make change
- C. Attach the SCP to the root of the organization.
- D. Create an SCP that includes an Allow statement for changes to the auditing application's IAM role by the trusted administrator IAM rol
- E. Include a Deny statement for changes by all other IAM principal
- F. Attach the SCP to the IAM service in each AWS account where the auditing application has an IAM role.
- G. Create an IAM permissions boundary that includes a Deny statement for changes to the auditing application's IAM rol
- H. Include a condition that allows the trusted administrator IAM role to make change
- I. Attach the permissions boundary to the audited AWS accounts.
- J. Create an IAM permissions boundary that includes a Deny statement for changes to the auditing application's IAM rol
- K. Include a condition that allows the trusted administrator IAM role to make change
- L. Attach the permissions boundary to the auditing application's IAM role in the AWS accounts.

Answer: A

Explanation:

https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_policies_scps.html?icmpid=docs_orgs_console

SCPs (Service Control Policies) are the best way to restrict permissions at the organizational level, which in this case would be used to restrict modifications to the IAM role used by the auditing application, while still allowing trusted administrators to make changes to it. Options C and D are not as effective because IAM permission boundaries are applied to IAM entities (users, groups, and roles), not the account itself, and must be applied to all IAM entities in the account.

NEW QUESTION 72

A rapidly growing company wants to scale for developer demand for AWS development environments. Development environments are created manually in the AWS Management Console. The networking team uses AWS CloudFormation to manage the networking infrastructure, exporting stack output values for the Amazon VPC and all subnets. The development environments have common standards, such as Application Load Balancers, Amazon EC2 Auto Scaling groups, security groups, and Amazon DynamoDB tables.

To keep up with demand, the DevOps engineer wants to automate the creation of development environments. Because the infrastructure required to support the application is expected to grow, there must be a way to easily update the deployed infrastructure. CloudFormation will be used to create a template for the development environments.

Which approach will meet these requirements and quickly provide consistent AWS environments for developers?

- A. Use Fn::ImportValue intrinsic functions in the Resources section of the template to retrieve Virtual Private Cloud (VPC) and subnet value
- B. Use CloudFormation StackSets for the development environments, using the Count input parameter to indicate the number of environments neede
- C. Use the UpdateStackSet command to update existing development environments.
- D. Use nested stacks to define common infrastructure component
- E. To access the exported values, use TemplateURL to reference the networking team's templat
- F. To retrieve Virtual Private Cloud (VPC) and subnet values, use Fn::ImportValue intrinsic functions in the Parameters section of the root templat
- G. Use the CreateChangeSet and ExecuteChangeSet commands to update existing development environments.
- H. Use nested stacks to define common infrastructure component
- I. Use Fn::ImportValue intrinsic functions with the resources of the nested stack to retrieve Virtual Private Cloud (VPC) and subnet value
- J. Use the CreateChangeSet and ExecuteChangeSet commands to update existing development environments.
- K. Use Fn::ImportValue intrinsic functions in the Parameters section of the root template to retrieve Virtual Private Cloud (VPC) and subnet value
- L. Define the development resources in the order they need to be created in the CloudFormation nested stack
- M. Use the CreateChangeSe
- N. and ExecuteChangeSet commands to update existing development environments.

Answer: C

Explanation:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/intrinsic-function-reference-importvalue.html>

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/intrinsic-function-reference-importvalue.html> CF of network exports the VPC, subnet or needed information CF of application imports the above information to its stack and UpdateChangeSet/ ExecuteChangeSet

NEW QUESTION 74

A company uses an organization in AWS Organizations that has all features enabled. The company uses AWS Backup in a primary account and uses an AWS Key Management Service (AWS KMS) key to encrypt the backups.

The company needs to automate a cross-account backup of the resources that AWS Backup backs up in the primary account. The company configures cross-account backup in the Organizations management account. The company creates a new AWS account in the organization and configures an AWS Backup backup vault in the new account. The company creates a KMS key in the new account to encrypt the backups. Finally, the company configures a new backup plan in the primary account. The destination for the new backup plan is the backup vault in the new account.

When the AWS Backup job in the primary account is invoked, the job creates backups in the primary account. However, the backups are not copied to the new account's backup vault.

Which combination of steps must the company take so that backups can be copied to the new account's backup vault? (Select TWO.)

- A. Edit the backup vault access policy in the new account to allow access to the primary account.
- B. Edit the backup vault access policy in the primary account to allow access to the new account.
- C. Edit the backup vault access policy in the primary account to allow access to the KMS key in the new account.
- D. Edit the key policy of the KMS key in the primary account to share the key with the new account.
- E. Edit the key policy of the KMS key in the new account to share the key with the primary account.

Answer: AE

Explanation:

To enable cross-account backup, the company needs to grant permissions to both the backup vault and the KMS key in the destination account. The backup vault access policy in the destination account must allow the primary account to copy backups into the vault. The key policy of the KMS key in the destination account must allow the primary account to use the key to encrypt and decrypt the backups. These steps are described in the AWS documentation¹². Therefore, the correct answer is A and E.

References:

? 1: Creating backup copies across AWS accounts - AWS Backup

? 2: Using AWS Backup with AWS Organizations - AWS Backup

NEW QUESTION 79

A DevOps engineer has implemented a CI/CO pipeline to deploy an AWS Cloud Formation template that provisions a web application. The web application consists of an Application Load Balancer (ALB) a target group, a launch template that uses an Amazon Linux 2 AMI an Auto Scaling group of Amazon EC2 instances, a security group and an Amazon RDS for MySQL database The launch template includes user data that specifies a script to install and start the application.

The initial deployment of the application was successful. The DevOps engineer made changes to update the version of the application with the user data. The CI/CD pipeline has deployed a new version of the template However, the health checks on the ALB are now failing The health checks have marked all targets as unhealthy.

During investigation the DevOps engineer notices that the Cloud Formation stack has a status of UPDATE_COMPLETE. However, when the DevOps engineer connects to one of the EC2 instances and checks /var/log messages, the DevOps engineer notices that the Apache web server failed to start successfully because of a configuration error

How can the DevOps engineer ensure that the CloudFormation deployment will fail if the user data fails to successfully finish running?

- A. Use the cfn-signal helper script to signal success or failure to CloudFormation Use the WaitOnResourceSignals update policy within the CloudFormation template Set an appropriate timeout for the update policy.
- B. Create an Amazon CloudWatch alarm for the UnhealthyHostCount metri
- C. Include an appropriate alarm threshold for the target group Create an Amazon Simple Notification Service (Amazon SNS) topic as the target to signal success or failure to CloudFormation
- D. Create a lifecycle hook on the Auto Scaling group by using the AWS AutoScaling LifecycleHook resource Create an Amazon Simple Notification Service (Amazon SNS) topic as the target to signal success or failure to CloudFormation Set an appropriate timeout on the lifecycle hook.
- E. Use the Amazon CloudWatch agent to stream the cloud-init logs Create a subscription filter that includes an AWS Lambda function with an appropriate invocation timeout Configure the Lambda function to use the SignalResource API operation to signal success or failure to CloudFormation.

Answer: A

Explanation:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/aws-attribute-updatepolicy.html>

NEW QUESTION 81

An application running on a set of Amazon EC2 instances in an Auto Scaling group requires a configuration file to operate. The instances are created and maintained with AWS CloudFormation. A DevOps engineer wants the instances to have the latest configuration file when launched and wants changes to the configuration file to be reflected on all the instances with a minimal delay when the CloudFormation template is updated. Company policy requires that application configuration files be maintained along with AWS infrastructure configuration files m source control.

Which solution will accomplish this?

- A. In the CloudFormaion template add an AWS Config rul
- B. Place the configuration file content in the rule's InputParameters property and set the Scope property to the EC2 Auto Scaling grou
- C. Add an AWS Systems Manager Resource Data Sync resource to the template to poll for updates to the configuration.
- D. In the CloudFormation template add an EC2 launch template resourc
- E. Place the configuration file content in the launch templat
- F. Configure the cfn-mit script to run when the instance is launched and configure the cfn-hup script to poll for updates to the configuration.
- G. In the CloudFormation template add an EC2 launch template resourc
- H. Place the configuration file content in the launch templat
- I. Add an AWS Systems Manager Resource Data Sync resource to the template to poll for updates to the configuration.
- J. In the CloudFormation template add CloudFormation imt metadat
- K. Place the configuration file content m the metadat
- L. Configure the cfn-init script to run when the instance is launched and configure the cfn-hup script to poll for updates to the configuration.

Answer: D

Explanation:

Use the AWS::CloudFormation::Init type to include metadata on an Amazon EC2 instance for the cfn-init helper script. If your template calls the cfn-init script, the script looks for resource metadata rooted in the AWS::CloudFormation::Init metadata key. Reference:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/aws-resource-init.html>

NEW QUESTION 86

A company has a single AWS account that runs hundreds of Amazon EC2 instances in a single AWS Region. New EC2 instances are launched and terminated each hour in the account. The account also includes existing EC2 instances that have been running for longer than a week.

The company's security policy requires all running EC2 instances to use an EC2 instance profile. If an EC2 instance does not have an instance profile attached, the EC2 instance must use a default instance profile that has no IAM permissions assigned.

A DevOps engineer reviews the account and discovers EC2 instances that are running without an instance profile. During the review, the DevOps engineer also observes that new EC2 instances are being launched without an instance profile.

Which solution will ensure that an instance profile is attached to all existing and future EC2 instances in the Region?

- A. Configure an Amazon EventBridge rule that reacts to EC2 RunInstances API call
- B. Configure the rule to invoke an AWS Lambda function to attach the default instance profile to the EC2 instances.
- C. Configure the ec2-instance-profile-attached AWS Config managed rule with a trigger type of configuration change
- D. Configure an automatic remediation action that invokes an AWS Systems Manager Automation runbook to attach the default instance profile to the EC2 instances.

- E. Configure an Amazon EventBridge rule that reacts to EC2 StartInstances API call
- F. Configure the rule to invoke an AWS Systems Manager Automation runbook to attach the default instance profile to the EC2 instances.
- G. Configure the iam-role-managed-policy-check AWS Config managed rule with a trigger type of configuration change
- H. Configure an automatic remediation action that invokes an AWS Lambda function to attach the default instance profile to the EC2 instances.

Answer: B

Explanation:

<https://docs.aws.amazon.com/config/latest/developerguide/ec2-instance-profile-attached.html>

NEW QUESTION 91

A developer is maintaining a fleet of 50 Amazon EC2 Linux servers. The servers are part of an Amazon EC2 Auto Scaling group, and also use Elastic Load Balancing for load balancing.

Occasionally, some application servers are being terminated after failing ELB HTTP health checks. The developer would like to perform a root cause analysis on the issue, but before being able to access application logs, the server is terminated.

How can log collection be automated?

- A. Use Auto Scaling lifecycle hooks to put instances in a Pending:Wait stat
- B. Create an Amazon CloudWatch alarm for EC2 Instance Terminate Successful and trigger an AWS Lambda function that invokes an SSM Run Command script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- C. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait stat
- D. Create an AWS Config rule for EC2 Instance-terminate Lifecycle Action and trigger a step function that invokes a script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- E. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait stat
- F. Create an Amazon CloudWatch subscription filter for EC2 Instance Terminate Successful and trigger a CloudWatch agent that invokes a script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- G. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait stat
- H. Create an Amazon EventBridge rule for EC2 Instance-terminate Lifecycle Action and trigger an AWS Lambda function that invokes an SSM Run Command script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.

Answer: D

Explanation:

<https://blog.fourninecloud.com/auto-scaling-lifecycle-hooks-to-export-server-logs-when-instance-terminating-58e06d7c0d6a>

NEW QUESTION 93

A global company manages multiple AWS accounts by using AWS Control Tower. The company hosts internal applications and public applications.

Each application team in the company has its own AWS account for application hosting. The accounts are consolidated in an organization in AWS Organizations.

One of the AWS Control Tower member accounts serves as a centralized DevOps account with CI/CD pipelines that application teams use to deploy applications to their respective target AWS accounts. An 1AM role for deployment exists in the centralized DevOps account.

An application team is attempting to deploy its application to an Amazon Elastic Kubernetes Service (Amazon EKS) cluster in an application AWS account. An 1AM role for deployment exists in the application AWS account. The deployment is through an AWS CodeBuild project that is set up in the centralized DevOps account. The CodeBuild project uses an 1AM service role for CodeBuild. The deployment is failing with an Unauthorized error during attempts to connect to the cross-account EKS cluster from CodeBuild.

Which solution will resolve this error?

- A. Configure the application account's deployment 1AM role to have a trust relationship with the centralized DevOps account
- B. Configure the trust relationship to allow the sts:AssumeRole action
- C. Configure the application account's deployment 1AM role to have the required access to the EKS cluster
- D. Configure the EKS cluster aws-auth ConfigMap to map the role to the appropriate system permissions.
- E. Configure the centralized DevOps account's deployment 1AM role to have a trust relationship with the application account
- F. Configure the trust relationship to allow the sts:AssumeRole action
- G. Configure the centralized DevOps account's deployment 1AM role to allow the required access to CodeBuild.
- H. Configure the centralized DevOps account's deployment 1AM role to have a trust relationship with the application account
- I. Configure the trust relationship to allow the sts:AssumeRoleWithSAML action
- J. Configure the centralized DevOps account's deployment 1AM role to allow the required access to CodeBuild.
- K. Configure the application account's deployment 1AM role to have a trust relationship with the AWS Control Tower management account
- L. Configure the trust relationship to allow the sts:AssumeRole action
- M. Configure the application account's deployment 1AM role to have the required access to the EKS cluster
- N. Configure the EKS cluster aws-auth ConfigMap to map the role to the appropriate system permissions.

Answer: A

Explanation:

In the source AWS account, the IAM role used by the CI/CD pipeline should have permissions to access the source code repository, build artifacts, and any other resources required for the build process. In the destination AWS accounts, the IAM role used for deployment should have permissions to access the AWS resources required for deploying the application, such as EC2 instances, RDS databases, S3 buckets, etc. The exact permissions required will depend on the specific resources being used by the application. The IAM role used for deployment in the destination accounts should also have permissions to assume the IAM role for deployment in the centralized DevOps account. This is typically done using an IAM role trust policy that allows the destination account to assume the DevOps account role.

NEW QUESTION 97

A company updated the AWS CloudFormation template for a critical business application. The stack update process failed due to an error in the updated template and AWS CloudFormation automatically began the stack rollback process. Later a DevOps engineer discovered that the application was still unavailable and that the stack was in the UPDATE_ROLLBACK_FAILED state.

Which combination of actions should the DevOps engineer perform so that the stack rollback can complete successfully? (Select TWO.)

- A. Attach the AWS CloudFormation FullAccess IAM policy to the AWS CloudFormation role.
- B. Automatically recover the stack resources by using AWS CloudFormation drift detection.
- C. Issue a ContinueUpdateRollback command from the AWS CloudFormation console or the AWS CLI.

- D. Manually adjust the resources to match the expectations of the stack.
- E. Update the existing AWS CloudFormation stack by using the original template.

Answer: CD

Explanation:

<https://docs.aws.amazon.com/cli/latest/reference/cloudformation/continue-update-rollback.html> For a specified stack that is in the UPDATE_ROLLBACK_FAILED state, continues rolling it back to the UPDATE_ROLLBACK_COMPLETE state. Depending on the cause of the failure, you can manually fix the error and continue the rollback. By continuing the rollback, you can return your stack to a working state (the UPDATE_ROLLBACK_COMPLETE state), and then try to update the stack again.

NEW QUESTION 100

A business has an application that consists of five independent AWS Lambda functions.

The DevOps engineer has built a CI/CD pipeline using AWS CodePipeline and AWS CodeBuild that builds tests packages and deploys each Lambda function in sequence. The pipeline uses an Amazon EventBridge rule to ensure the pipeline starts as quickly as possible after a change is made to the application source code.

After working with the pipeline for a few months the DevOps engineer has noticed the pipeline takes too long to complete.

What should the DevOps engineer implement to BEST improve the speed of the pipeline?

- A. Modify the CodeBuild projects within the pipeline to use a compute type with more available network throughput.
- B. Create a custom CodeBuild execution environment that includes a symmetric multiprocessing configuration to run the builds in parallel.
- C. Modify the CodePipeline configuration to run actions for each Lambda function in parallel by specifying the same runorder.
- D. Modify each CodeBuild project to run within a VPC and use dedicated instances to increase throughput.

Answer: C

Explanation:

<https://docs.aws.amazon.com/codepipeline/latest/userguide/reference-pipeline-structure.html>

AWS doc: "To specify parallel actions, use the same integer for each action you want to run in parallel. For example, if you want three actions to run in sequence in a stage, you would give the first action the runOrder value of 1, the second action the runOrder value of 2, and the third the runOrder value of 3. However, if you want the second and third actions to run in parallel, you would give the first action the runOrder value of 1 and both the second and third actions the runOrder value of 2."

NEW QUESTION 102

A company uses AWS Storage Gateway in file gateway mode in front of an Amazon S3 bucket that is used by multiple resources. In the morning when business begins, users do not see the objects processed by a third party the previous evening. When a DevOps engineer looks directly at the S3 bucket, the data is there, but it is missing in Storage Gateway.

Which solution ensures that all the updated third-party files are available in the morning?

- A. Configure a nightly Amazon EventBridge event to invoke an AWS Lambda function to run the RefreshCache command for Storage Gateway.
- B. Instruct the third party to put data into the S3 bucket using AWS Transfer for SFTP.
- C. Modify Storage Gateway to run in volume gateway mode.
- D. Use S3 Same-Region Replication to replicate any changes made directly in the S3 bucket to Storage Gateway.

Answer: A

Explanation:

https://docs.aws.amazon.com/storagegateway/latest/APIReference/API_RefreshCache.html "It only updates the cached inventory to reflect changes in the inventory of the objects in the S3 bucket. This operation is only supported in the S3 File Gateway types."

NEW QUESTION 103

A company uses AWS Directory Service for Microsoft Active Directory as its identity provider (IdP). The company requires all infrastructure to be defined and deployed by AWS CloudFormation.

A DevOps engineer needs to create a fleet of Windows-based Amazon EC2 instances to host an application. The DevOps engineer has created a CloudFormation template that contains an EC2 launch template, IAM role, EC2 security group, and EC2 Auto Scaling group. The DevOps engineer must implement a solution that joins all EC2 instances to the domain of the AWS Managed Microsoft AD directory.

Which solution will meet these requirements with the MOST operational efficiency?

- A. In the CloudFormation template, create an AWS::SSM::Document resource that joins the EC2 instance to the AWS Managed Microsoft AD domain by using the parameters for the existing director
- B. Update the launch template to include the SSMAssociation property to use the new SSM document
- C. Attach the AmazonSSMManagedInstanceCore and AmazonSSMDirectoryServiceAccess AWS managed policies to the IAM role that the EC2 instances use.
- D. In the CloudFormation template, update the launch template to include specific tags that propagate on launch
- E. Create an AWS::SSM::Association resource to associate the AWS-JoinDirectoryServiceDomain Automation runbook with the EC2 instances that have the specified tag
- F. Define the required parameters to join the AWS Managed Microsoft AD director
- G. Attach the AmazonSSMManagedInstanceCore and AmazonSSMDirectoryServiceAccess AWS managed policies to the IAM role that the EC2 instances use.
- H. Store the existing AWS Managed Microsoft AD domain connection details in AWS Secrets Manager
- I. In the CloudFormation template, create an AWS::SSM::Association resource to associate the AWS-CreateManagedWindowsInstanceWithApproval Automation runbook with the EC2 Auto Scaling group
- J. Pass the ARNs for the parameters from Secrets Manager to join the domain
- K. Attach the AmazonSSMDirectoryServiceAccess and SecretsManagerReadWrite AWS managed policies to the IAM role that the EC2 instances use.
- L. Store the existing AWS Managed Microsoft AD domain administrator credentials in AWS Secrets Manager
- M. In the CloudFormation template, update the EC2 launch template to include user data
- N. Configure the user data to pull the administrator credentials from Secrets Manager and to join the AWS Managed Microsoft AD domain
- O. Attach the AmazonSSMManagedInstanceCore and SecretsManagerReadWrite AWS managed policies to the IAM role that the EC2 instances use.

Answer: B

Explanation:

To meet the requirements, the DevOps engineer needs to create a solution that joins all EC2 instances to the domain of the AWS Managed Microsoft AD directory with the most operational efficiency. The DevOps engineer can use AWS Systems Manager Automation to automate the domain join process using an existing runbook called AWS- JoinDirectoryServiceDomain. This runbook can join Windows instances to an AWS Managed Microsoft AD or Simple AD directory by using PowerShell commands. The DevOps engineer can create an AWS::SSM::Association resource in the CloudFormation template to associate the runbook with the EC2 instances that have specific tags. The tags can be defined in the launch template and propagated on launch to the EC2 instances. The DevOps engineer can also define the required parameters for the runbook, such as the directory ID, directory name, and organizational unit. The DevOps engineer can attach the AmazonSSMManagedInstanceCore and AmazonSSMDirectoryServiceAccess AWS managed policies to the IAM role that the EC2 instances use. These policies grant the necessary permissions for Systems Manager and Directory Service operations.

NEW QUESTION 104

A company is implementing an Amazon Elastic Container Service (Amazon ECS) cluster to run its workload. The company architecture will run multiple ECS services on the cluster. The architecture includes an Application Load Balancer on the front end and uses multiple target groups to route traffic.

A DevOps engineer must collect application and access logs. The DevOps engineer then needs to send the logs to an Amazon S3 bucket for near-real-time analysis.

Which combination of steps must the DevOps engineer take to meet these requirements? (Choose three.)

- A. Download the Amazon CloudWatch Logs container instance from AW
- B. Configure this instance as a tas
- C. Update the application service definitions to include the logging task.
- D. Install the Amazon CloudWatch Logs agent on the ECS instance
- E. Change the logging driver in the ECS task definition to awslogs.
- F. Use Amazon EventBridge to schedule an AWS Lambda function that will run every 60 seconds and will run the Amazon CloudWatch Logs create-export-task command
- G. Then point the output to the logging S3 bucket.
- H. Activate access logging on the AL
- I. Then point the ALB directly to the logging S3 bucket.
- J. Activate access logging on the target groups that the ECS services use
- K. Then send the logs directly to the logging S3 bucket.
- L. Create an Amazon Kinesis Data Firehose delivery stream that has a destination of the logging S3 bucket
- M. Then create an Amazon CloudWatch Logs subscription filter for Kinesis Data Firehose.

Answer: BDF

Explanation:

<https://docs.aws.amazon.com/AmazonECS/latest/developerguide/ecs-logging-monitoring.html>

NEW QUESTION 105

A company's security team requires that all external Application Load Balancers (ALBs) and Amazon API Gateway APIs are associated with AWS WAF web ACLs. The company

has hundreds of AWS accounts, all of which are included in a single organization in AWS Organizations. The company has configured AWS Config for the organization. During an audit, the company finds some externally facing ALBs that are not associated with AWS WAF web ACLs.

Which combination of steps should a DevOps engineer take to prevent future violations? (Choose two.)

- A. Delegate AWS Firewall Manager to a security account.
- B. Delegate Amazon GuardDuty to a security account.
- C. Create an AWS Firewall Manager policy to attach AWS WAF web ACLs to any newly created ALBs and API Gateway APIs.
- D. Create an Amazon GuardDuty policy to attach AWS WAF web ACLs to any newly created ALBs and API Gateway APIs.
- E. Configure an AWS Config managed rule to attach AWS WAF web ACLs to any newly created ALBs and API Gateway APIs.

Answer: AC

Explanation:

If instead you want to automatically apply the policy to existing in-scope resources, choose Auto remediate any noncompliant resources. This option creates a web ACL in each applicable account within the AWS organization and associates the web ACL with the resources in the accounts. When you choose Auto remediate any noncompliant resources, you can also choose to remove existing web ACL associations from in-scope resources, for the web ACLs that aren't managed by another active Firewall Manager policy. If you choose this option, Firewall Manager first associates the policy's web ACL with the resources, and then removes the prior associations. If a resource has an association with another web ACL that's managed by a different active Firewall Manager policy, this choice doesn't affect that association.

NEW QUESTION 108

A company is using AWS to run digital workloads. Each application team in the company has its own AWS account for application hosting. The accounts are consolidated in an organization in AWS Organizations.

The company wants to enforce security standards across the entire organization. To avoid noncompliance because of security misconfiguration, the company has enforced the use of AWS CloudFormation. A production support team can modify resources in the production environment by using the AWS Management Console to troubleshoot and resolve application-related issues.

A DevOps engineer must implement a solution to identify in near real time any AWS

service misconfiguration that results in noncompliance. The solution must automatically remediate the issue within 15 minutes of identification. The solution also must track noncompliant resources and events in a centralized dashboard with accurate timestamps.

Which solution will meet these requirements with the LEAST development overhead?

- A. Use CloudFormation drift detection to identify noncompliant resource
- B. Use drift detection events from CloudFormation to invoke an AWS Lambda function for remediation
- C. Configure the Lambda function to publish logs to an Amazon CloudWatch Logs log group
- D. Configure an Amazon CloudWatch dashboard to use the log group for tracking.
- E. Turn on AWS CloudTrail in the AWS account
- F. Analyze CloudTrail logs by using Amazon Athena to identify noncompliant resource
- G. Use AWS Step Functions to track query results on Athena for drift detection and to invoke an AWS Lambda function for remediation
- H. For tracking, set up an Amazon QuickSight dashboard that uses Athena as the data source.
- I. Turn on the configuration recorder in AWS Config in all the AWS accounts to identify noncompliant resource
- J. Enable AWS Security Hub with the ~no-enable-default-standards option in all the AWS account

- K. Set up AWS Config managed rules and custom rule
- L. Set up automatic remediation by using AWS Config conformance pack
- M. For tracking, set up a dashboard on Security Hub in a designated Security Hub administrator account.
- N. Turn on AWS CloudTrail in the AWS account
- O. Analyze CloudTrail logs by using Amazon CloudWatch Logs to identify noncompliant resource
- P. Use CloudWatch Logs filters for drift detectio
- Q. Use Amazon EventBridge to invoke the Lambda function for remediation
- R. Stream filtered CloudWatch logs to Amazon OpenSearch Service
- S. Set up a dashboard on OpenSearch Service for tracking.

Answer: C

Explanation:

The best solution is to use AWS Config and AWS Security Hub to identify and remediate noncompliant resources across multiple AWS accounts. AWS Config enables continuous monitoring of the configuration of AWS resources and evaluates them against desired configurations. AWS Config can also automatically remediate noncompliant resources by using conformance packs, which are a collection of AWS Config rules and remediation actions that can be deployed as a single entity. AWS Security Hub provides a comprehensive view of the security posture of AWS accounts and resources. AWS Security Hub can aggregate and normalize the findings from AWS Config and other AWS services, as well as from partner solutions. AWS Security Hub can also be used to create a dashboard for tracking noncompliant resources and events in a centralized location.

The other options are not optimal because they either require more development overhead, do not provide near real time detection and remediation, or do not provide a centralized dashboard for tracking.

Option A is not optimal because CloudFormation drift detection is not a near real time solution. Drift detection has to be manually initiated on each stack or resource, or scheduled using a cron expression. Drift detection also does not provide remediation

actions, so a custom Lambda function has to be developed and invoked. CloudWatch Logs and dashboard can be used for tracking, but they do not provide a comprehensive view of the security posture of the AWS accounts and resources.

Option B is not optimal because CloudTrail logs analysis using Athena is not a near real time solution. Athena queries have to be manually run or scheduled using a cron expression. Athena also does not provide remediation actions, so a custom Lambda function has to be developed and invoked. Step Functions can be used to orchestrate the query and remediation workflow, but it adds more complexity and cost. QuickSight dashboard can be used for tracking, but it does not provide a comprehensive view of the security posture of the AWS accounts and resources.

Option D is not optimal because CloudTrail logs analysis using CloudWatch Logs is not a near real time solution. CloudWatch Logs filters have to be manually created or updated for each resource type and configuration change. CloudWatch Logs also does not provide remediation actions, so a custom Lambda function has to be developed and invoked. EventBridge can be used to trigger the Lambda function, but it adds more complexity and cost. OpenSearch Service dashboard can be used for tracking, but it does not provide a comprehensive view of the security posture of the AWS accounts and resources. References:

? AWS Config conformance packs

? Introducing AWS Config conformance packs

? Managing conformance packs across all accounts in your organization

NEW QUESTION 112

A company plans to use Amazon CloudWatch to monitor its Amazon EC2 instances. The company needs to stop EC2 instances when the average of the NetworkPacketsIn metric is less than 5 for at least 3 hours in a 12-hour time window. The company must evaluate the metric every hour. The EC2 instances must continue to run if there is missing data for the NetworkPacketsIn metric during the evaluation period.

A DevOps engineer creates a CloudWatch alarm for the NetworkPacketsIn metric. The DevOps engineer configures a threshold value of 5 and an evaluation period of 1 hour.

Which set of additional actions should the DevOps engineer take to meet these requirements?

- A. Configure the Datapoints to Alarm value to be 3 out of 12. Configure the alarm to treat missing data as breaching the threshold
- B. Add an AWS Systems Manager action to stop the instance when the alarm enters the ALARM state.
- C. Configure the Datapoints to Alarm value to be 3 out of 12. Configure the alarm to treat missing data as not breaching the threshold
- D. Add an EC2 action to stop the instance when the alarm enters the ALARM state.
- E. Configure the Datapoints to Alarm value to be 9 out of 12. Configure the alarm to treat missing data as breaching the threshold
- F. Add an EC2 action to stop the instance when the alarm enters the ALARM state.
- G. Configure the Datapoints to Alarm value to be 9 out of 12. Configure the alarm to treat missing data as not breaching the threshold
- H. Add an AWS Systems Manager action to stop the instance when the alarm enters the ALARM state.

Answer: B

Explanation:

To meet the requirements, the DevOps engineer needs to configure the CloudWatch alarm to stop the EC2 instances when the average of the NetworkPacketsIn metric is less than 5 for at least 3 hours in a 12-hour time window. This means that the alarm should trigger when 3 out of 12 datapoints are below the threshold of 5. The alarm should also treat missing data as not breaching the threshold, so that the EC2 instances continue to run if there is no data for the metric during the evaluation period. The DevOps engineer can add an EC2 action to stop the instance when the alarm enters the ALARM state, which is a built-in action type for CloudWatch alarms.

NEW QUESTION 115

A DevOps engineer is setting up a container-based architecture. The engineer has decided to use AWS CloudFormation to automatically provision an Amazon ECS cluster and an Amazon EC2 Auto Scaling group to launch the EC2 container instances. After successfully creating the CloudFormation stack, the engineer noticed that, even though the ECS cluster and the EC2 instances were created successfully and the stack finished the creation, the EC2 instances were associating with a different cluster.

How should the DevOps engineer update the CloudFormation template to resolve this issue?

- A. Reference the EC2 instances in the AWS: ECS: Cluster resource and reference the ECS cluster in the AWS: ECS: Service resource.
- B. Reference the ECS cluster in the AWS: AutoScaling: LaunchConfiguration resource of the UserData property.
- C. Reference the ECS cluster in the AWS:EC2: Instance resource of the UserData property.
- D. Reference the ECS cluster in the AWS: CloudFormation: CustomResource resource to trigger an AWS Lambda function that registers the EC2 instances with the appropriate ECS cluster.

Answer: B

Explanation:

The UserData property of the AWS: AutoScaling: LaunchConfiguration resource can be used to specify a script that runs when the EC2 instances are launched. This script can include the ECS cluster name as an environment variable for the ECS agent running on the EC2 instances. This way, the EC2 instances will

register with the correct ECS cluster. Option A is incorrect because the AWS: ECS: Cluster resource does not have a property to reference the EC2 instances. Option C is incorrect because the EC2 instances are launched by the Auto Scaling group, not by the AWS: EC2: Instance resource. Option D is incorrect because using a custom resource and a Lambda function is unnecessary and overly complex for this scenario. References: AWS::AutoScaling::LaunchConfiguration, Amazon ECS Container Agent Configuration

NEW QUESTION 118

A company has an application that runs on Amazon EC2 instances that are in an Auto Scaling group. When the application starts up, the application needs to process data from an Amazon S3 bucket before the application can start to serve requests.

The size of the data that is stored in the S3 bucket is growing. When the Auto Scaling group adds new instances, the application now takes several minutes to download and process the data before the application can serve requests. The company must reduce the time that elapses before new EC2 instances are ready to serve requests.

Which solution is the MOST cost-effective way to reduce the application startup time?

- A. Configure a warm pool for the Auto Scaling group with warmed EC2 instances in the Stopped state
- B. Configure an autoscaling:EC2_INSTANCE_LAUNCHING lifecycle hook on the Auto Scaling group
- C. Modify the application to complete the lifecycle hook when the application is ready to serve requests.
- D. Increase the maximum instance count of the Auto Scaling group
- E. Configure an autoscaling:EC2_INSTANCE_LAUNCHING lifecycle hook on the Auto Scaling group
- F. Modify the application to complete the lifecycle hook when the application is ready to serve requests.
- G. Configure a warm pool for the Auto Scaling group with warmed EC2 instances in the Running state
- H. Configure an autoscaling:EC2_INSTANCE_LAUNCHING lifecycle hook on the Auto Scaling group
- I. Modify the application to complete the lifecycle hook when the application is ready to serve requests.
- J. Increase the maximum instance count of the Auto Scaling group
- K. Configure an autoscaling:EC2_INSTANCE_LAUNCHING lifecycle hook on the Auto Scaling group
- L. Modify the application to complete the lifecycle hook and to place the new instance in the Standby state when the application is ready to serve requests.

Answer: A

Explanation:

Option A is the most cost-effective solution. By configuring a warm pool of EC2 instances in the Stopped state, the company can reduce the time it takes for new instances to be ready to serve requests. When the Auto Scaling group launches a new instance, it can attach the stopped EC2 instance from the warm pool. The instance can then be started up immediately, rather than having to wait for the data to be downloaded and processed. This reduces the overall startup time for the application.

NEW QUESTION 122

An AWS CodePipeline pipeline has implemented a code release process. The pipeline is integrated with AWS CodeDeploy to deploy versions of an application to multiple Amazon EC2 instances for each CodePipeline stage.

During a recent deployment the pipeline failed due to a CodeDeploy issue. The DevOps team wants to improve monitoring and notifications during deployment to decrease resolution times.

What should the DevOps engineer do to create notifications. When issues are discovered?

- A. Implement Amazon CloudWatch Logs for CodePipeline and CodeDeploy create an AWS Config rule to evaluate code deployment issues, and create an Amazon Simple Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.
- B. Implement Amazon EventBridge for CodePipeline and CodeDeploy create an AWS Lambda function to evaluate code deployment issues, and create an Amazon Simple Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.
- C. Implement AWS CloudTrail to record CodePipeline and CodeDeploy API call information create an AWS Lambda function to evaluate code deployment issues and create an Amazon Simple Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.
- D. Implement Amazon EventBridge for CodePipeline and CodeDeploy create an Amazon
- E. Inspector assessment target to evaluate code deployment issues and create an Amazon Simple
- F. Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.

Answer: B

Explanation:

AWS CloudWatch Events can be used to monitor events across different AWS resources, and a CloudWatch Event Rule can be created to trigger an AWS Lambda function when a deployment issue is detected in the pipeline. The Lambda function can then evaluate the issue and send a notification to the appropriate stakeholders through an Amazon SNS topic. This approach allows for real-time notifications and faster resolution times.

NEW QUESTION 127

A company has configured an Amazon S3 event source on an AWS Lambda function. The company needs the Lambda function to run when a new object is created or an existing object is modified in a particular S3 bucket. The Lambda function will use the S3 bucket name and the S3 object key of the incoming event to read the contents of the created or modified S3 object. The Lambda function will parse the contents and save the parsed contents to an Amazon DynamoDB table.

The Lambda function's execution role has permissions to read from the S3 bucket and to write to the DynamoDB table. During testing, a DevOps engineer discovers that the Lambda

function does not run when objects are added to the S3 bucket or when existing objects are modified.

Which solution will resolve this problem?

- A. Increase the memory of the Lambda function to give the function the ability to process large files from the S3 bucket.
- B. Create a resource policy on the Lambda function to grant Amazon S3 the permission to invoke the Lambda function for the S3 bucket
- C. Configure an Amazon Simple Queue Service (Amazon SQS) queue as an OnFailure destination for the Lambda function
- D. Provision space in the /tmp folder of the Lambda function to give the function the ability to process large files from the S3 bucket

Answer: B

Explanation:

? Option A is incorrect because increasing the memory of the Lambda function does not address the root cause of the problem, which is that the Lambda function is not triggered by the S3 event source. Increasing the memory of the Lambda function might improve its performance or reduce its execution time, but it does not affect its invocation. Moreover, increasing the memory of the Lambda function might incur higher costs, as Lambda charges based on the amount of memory allocated to the function.

? Option B is correct because creating a resource policy on the Lambda function to grant Amazon S3 the permission to invoke the Lambda function for the S3

bucket is a necessary step to configure an S3 event source. A resource policy is a JSON document that defines who can access a Lambda resource and under what conditions. By granting Amazon S3 permission to invoke the Lambda function, the company ensures that the Lambda function runs when a new object is created or an existing object is modified in the S3 bucket1.

? Option C is incorrect because configuring an Amazon Simple Queue Service (Amazon SQS) queue as an On-Failure destination for the Lambda function does not help with triggering the Lambda function. An On-Failure destination is a feature that allows Lambda to send events to another service, such as SQS or Amazon Simple Notification Service (Amazon SNS), when a function invocation fails. However, this feature only applies to asynchronous invocations, and S3 event sources use synchronous invocations. Therefore, configuring an SQS queue as an On-Failure destination would have no effect on the problem.

? Option D is incorrect because provisioning space in the /tmp folder of the Lambda function does not address the root cause of the problem, which is that the Lambda function is not triggered by the S3 event source. Provisioning space in the /tmp folder of the Lambda function might help with processing large files from the S3 bucket, as it provides temporary storage for up to 512 MB of data. However, it does not affect the invocation of the Lambda function.

References:

? Using AWS Lambda with Amazon S3

? Lambda resource access permissions

? AWS Lambda destinations

? [AWS Lambda file system]

NEW QUESTION 129

A space exploration company receives telemetry data from multiple satellites. Small packets of data are received through Amazon API Gateway and are placed directly into an Amazon Simple Queue Service (Amazon SQS) standard queue. A custom application is subscribed to the queue and transforms the data into a standard format.

Because of inconsistencies in the data that the satellites produce, the application is occasionally unable to transform the data. In these cases, the messages remain in the SQS queue. A DevOps engineer must develop a solution that retains the failed messages and makes them available to scientists for review and future processing.

Which solution will meet these requirements?

- A. Configure AWS Lambda to poll the SQS queue and invoke a Lambda function to check whether the queue messages are valid
- B. If validation fails, send a copy of the data that is not valid to an Amazon S3 bucket so that the scientists can review and correct the data
- C. When the data is corrected, amend the message in the SQS queue by using a replay Lambda function with the corrected data.
- D. Convert the SQS standard queue to an SQS FIFO queue
- E. Configure AWS Lambda to poll the SQS queue every 10 minutes by using an Amazon EventBridge schedule
- F. Invoke the Lambda function to identify any messages with a SentTimestamp value that is older than 5 minutes, push the data to the same location as the application's output location, and remove the messages from the queue.
- G. Create an SQS dead-letter queue
- H. Modify the existing queue by including a redrive policy that sets the Maximum Receives setting to 1 and sets the dead-letter queue ARN to the ARN of the newly created queue
- I. Instruct the scientists to use the dead-letter queue to review the data that is not valid
- J. Reprocess this data at a later time.
- K. Configure API Gateway to send messages to different SQS virtual queues that are named for each of the satellite
- L. Update the application to use a new virtual queue for any data that it cannot transform, and send the message to the new virtual queue
- M. Instruct the scientists to use the virtual queue to review the data that is not valid
- N. Reprocess this data at a later time.

Answer: C

Explanation:

Create an SQS dead-letter queue. Modify the existing queue by including a redrive policy that sets the Maximum Receives setting to 1 and sets the dead-letter queue ARN to the ARN of the newly created queue. Instruct the scientists to use the dead-letter queue to review the data that is not valid. Reprocess this data at a later time.

NEW QUESTION 134

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your DOP-C02 Exam with Our Prep Materials Via below:

<https://www.certleader.com/DOP-C02-dumps.html>