

Exam Questions 350-801

Implementing and Operating Cisco Collaboration Core Technologies

<https://www.2passeasy.com/dumps/350-801/>



NEW QUESTION 1

Which action prevents toll fraud in Cisco Unified Communications Manager?

- A. Implement toll fraud restriction in the Cisco IOS router.
- B. Implement route patterns in Cisco Unified CM.
- C. Allow off-net to off-net transfers.
- D. Configure ad hoc conference restriction.

Answer: B

Explanation:

Reference: <https://www.cisco.com/c/en/us/support/docs/voice-unified-communications/unified-communications-manager-express/107626-cme-toll-fraud.html>

NEW QUESTION 2

Refer to the exhibit.

When a UC Administrator is troubleshooting DTMF negotiated by this SIP INVITE, which two messages should be examined next to further troubleshoot the issue? (Choose two.)

- A. REGISTER
- B. UPDATE
- C. PRACK
- D. NOTIFY
- E. SUBSCRIBE

Answer: DE

NEW QUESTION 3

An engineer configures Cisco Unified Communications Manager to prevent toll fraud. At which two points does the engineer block the pattern in Cisco Unified CM to complete this task? (Choose two.)

- A. route pattern
- B. route group
- C. translation pattern
- D. partition
- E. CSS

Answer: CE

NEW QUESTION 4

How can an engineer determine location-based CAC bandwidth requirements for Cisco Unified Communications Manager?

- A. Set the requirements in the service parameters.
- B. Add the requirements for each audio and video codec and how many calls must be supported.
- C. Execute the Resource Reservation Protocol to return location-based requirements.
- D. Calculate the number of calls against the license for Cisco Unified Border Element to determine calls per location.

Answer: A

NEW QUESTION 5

When a user dials a number with a phone that is registered to the Cisco Unified Communications Manager, what is the default timeout before the number is sent?

- A. 15 seconds
- B. 5 seconds

- C. 10 seconds
- D. 3 seconds

Answer: C

Explanation:

Reference: <https://www.cisco.com/c/en/us/support/docs/voice-unified-communications/unified-communications-manager-callmanager/13920-call-routing.html>

NEW QUESTION 6

Which two conditions must a user meet to provision a new device using the Self-Provisioning feature? (Choose two.)

- A. The user must have a primary extension.
- B. At least two DNs must be assigned to the user device.
- C. The user must be part of "Standard CCM Super User".
- D. The user must have the appropriate universal device template linked to the user profile.
- E. The user must have at least user device profile assigned.

Answer: AD

NEW QUESTION 7

A user reports transfer failure from an IP phone for calls received from a PSTN to another PSTN number. What is a reason for these failures?

- A. The IP phone is configured with the wrong region.
- B. The incoming calling search space of the SIP trunk does not include the partition of the line in the IP phone.
- C. The service parameter related to Offnet to Offnet Call Transfer is set to TRUE.
- D. The gateway is configured with the wrong device pool.

Answer: D

NEW QUESTION 8

Refer to the exhibit

The SDP offer/answer has been completed successfully but there is no DTMF when users press keys. What is the cause of the issue?

- A. DTMF was negotiated properly in these messages.
- B. G.729 rather than G.711ulaw was negotiated.
- C. Payload type 110 was negotiated rather than type 101.
- D. DTMF was not negotiated on the call.

Answer: D

NEW QUESTION 9

Which configuration tells a switch port to send Cisco Discovery Protocol packets that configure an attached Cisco IP phone to trust tagged traffic that is received from a device that is connected to the access port on the Cisco IP phone?

- A. Router# configure terminalRouter(config)# interface gigabitethernet 5/1 Router(config-if)# platform qos trust extend
- B. Router# configure terminalRouter(config)# interface gigabitethernet 5/1 Router(config-if)# platform qos trust extend cos 3
- C. Router# configure terminalRouter(config)# interface gigabitethernet 5/1 Router(config-if)# platform qos trust extend cos 5
- D. Router# configure terminalRouter(config)# interface gigabitethernet 5/1 Router(config-if)# platform qos extend trust

Answer: A

NEW QUESTION 10

A customer wants a video conference with five Cisco TelePresence IX5000 Series systems. Which media resource is necessary in the design to fully utilize the immersive functions?

- A. Cisco PVDM4-128
- B. software conference bridge on Cisco Unified Communications Manager
- C. Cisco Webex Meetings Server
- D. Cisco Meeting Server

Answer: C

NEW QUESTION 10

Which statement about Cisco Unified Communications Manager and Cisco IM and Presence backups is true?

- A. Backups should be scheduled during off-peak hours to avoid system performance issues.
- B. Backups are saved as .tar files and encrypted using the web administrator account.
- C. Backups are saved as unencrypted .tar files.
- D. Backups are not needed for subscriber Cisco Unified Communications Manager and Cisco IM and Presence servers.

Answer: A

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/admin/11_5_1_SU1/Administration/cucm_b_administration-guide-1151su1/cucm_b_administration-guide-1151su1_chapter_01010.html#CUCM_TK_S7FC26D5_00

NEW QUESTION 14

An engineer is designing a high availability and failover solution for two Cisco Unified Border Element routers. The first router (cube1.ab?.com) takes 60% of the calls and the second router (cube2.abc.com) takes 40% of the calls. Assume all DNS A records have been created. Which two SRV records are needed for a load balanced solution? (Choose two.)

- A. _sip._udp.abc.com 60 IN SRV 2 60 cube1.abc.com
- B. _sip._udp.abc.com 60 IN SRV 60 1 cube1.abc.com
- C. _sip._udp.abc.com 60 IN SRV 1 40 cube2.abc.com
- D. _sip._udp.abc.com 60 IN SRV 3 60 cube2.abc.com
- E. _sip._udp.abc.com 60 IN SRV 1 60 cube1.abc.com

Answer: CE

NEW QUESTION 17

Which statement describes the outcome when the trust boundary is defined at the Cisco IP phone?

- A. Packets or Ethernet frames are remarked at the access layer switch.
- B. Packets or Ethernet frames are not remarked by the IP phone.
- C. Packets or Ethernet frames are not remarked at the layer switch.
- D. Packets or Ethernet frames are remarked at the distribution layer switch.

Answer: C

Explanation:

Reference: <https://networklessons.com/quality-of-service/how-to-configure-qos-trust-boundary-on-cisco-switches>

NEW QUESTION 18

An administrator is trying to change the default LINECODE for a voice ISDN T1 PRI. Which command makes this change?

- A. linecode esf
- B. linecode ami
- C. linecode hdb3
- D. linecode b8zs

Answer: D

Explanation:

Reference: https://www.cisco.com/en/US/docs/ios/dial/configuration/guide/dia_cfg_isdn_pri_external_docbase_0900e4b1806c752c_4container_external_docbase_0900e4b18216dd1b.html

NEW QUESTION 19

How can an administrator stop Cisco Unified Communications Manager from advertising the OPUS codec for recording enabled devices?

- A. Route recorded calls through Cisco Unified Border Element because it does not support OPUS.
- B. Go to the phone's configuration page and set "Advertise OPUS Codec" to be "false".
- C. Integrate the Cisco Unified CM with 3 recording solution that does not support OPUS.
- D. In CUCM Service Parameters set "Opus Codec Enabled" to "Enabled for all Devices Except Recording-Enabled Devices."

Answer: D

Explanation:

Reference: <https://www.cisco.com/c/en/us/support/docs/unified-communications/unified-communications-manager-callmanager/211297-Configure-Opus-Support-on-Cisco-Unified.pdf>

NEW QUESTION 23

A DTMF mismatch is occurring between an MGCP gateway registered FXS port and a Cisco Unified Communications Manager SIP trunk. Which media resource can be leveraged to interwork this mismatch?

- A. Conference Bridge
- B. Trusted Relay Point
- C. Media Termination Point
- D. Annunciator

Answer: C

NEW QUESTION 24

DRAG DROP

According to the QoS Baseline Model, drag and drop the applications from the left onto the correct Per-Hop Behavior values on the right.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

NEW QUESTION 29

After an engineer runs the `utils ntp status` command on the Cisco Unified Communications Manager publisher, the stratum value is 16. Which issue can the Cisco Unified CM cluster experience?

- A. Unified CM sends an NTPV4 packet.
- B. Database replication is not synchronized on the Unified CM nodes.
- C. The cluster loses access to port 124 at the firewall.
- D. The date/time group on all phones defaults to the time zone of the engineer.

Answer: B

NEW QUESTION 33

When a new SIP phone is registered to Cisco Unified Communications Manager, it keeps failing and showing an “unprovisioned” error message in the phone display. Which problem is a possible cause of this issue?

- A. Auto-registration is disabled on the Cisco Unified Communications Manager nodes and the phone device does not have a DN configured.
- B. The DN assigned to the phone is already in use by another SIP phone.
- C. The phone cannot download and install the latest firmware.
- D. The DHCP settings are set incorrectly and the phone does not have an alternate TFTP defined.
- E. The DN configuration for this phone is shared with an SCCP phone.
- F. which is not supported.

Answer: C

NEW QUESTION 35

An engineer must configure an MGCP gateway and register it to Cisco Unified Communications Manager. Which prerequisite must be met before applying the gateway commands to enable MGCP?

- A. The MGCP gateway and the Cisco Unified CM must be able to communicate over ports 5060 and 5061.
- B. Cisco Unified CM and the MGCP gateway must utilize the SIP OPTIONS ping feature to monitor status.
- C. The MGCP gateway must have voice service VoIP configured.
- D. The MGCP gateway and the Cisco Unified CM must be able to communicate over ports 2427, 2428, and 2727.

Answer: D

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/ios/voice/cminterop/configuration/guide/12_4t/vc_12_4t_book/vc_ucm_mgcp_gw.html

NEW QUESTION 40

Which wildcard must an engineer configure to match a whole domain in SIP route patterns?

- A. .
- B. !
- C. @
- D. *

Answer: D

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/admin/10_0_1/ccmcfg/CUCM_BK_C95ABA82_00_admin-guide-100/CUCM_BK_C95ABA82_00_admin-guide-100_chapter_0100111.html

NEW QUESTION 42

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 350-801 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 350-801 Product From:

<https://www.2passeasy.com/dumps/350-801/>

Money Back Guarantee

350-801 Practice Exam Features:

- * 350-801 Questions and Answers Updated Frequently
- * 350-801 Practice Questions Verified by Expert Senior Certified Staff
- * 350-801 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 350-801 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year