



Amazon-Web-Services

Exam Questions ANS-C01

AWS Certified Advanced Networking Specialty Exam

About ExamBible

Your Partner of IT Exam

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

A company is using custom DNS servers that run BIND for name resolution in its VPCs. The VPCs are deployed across multiple AWS accounts that are part of the same organization in AWS Organizations. All the VPCs are connected to a transit gateway. The BIND servers are running in a central VPC and are configured to forward all queries for an on-premises DNS domain to DNS servers that are hosted in an on-premises data center. To ensure that all the VPCs use the custom DNS servers, a network engineer has configured a VPC DHCP options set in all the VPCs that specifies the custom DNS servers to be used as domain name servers.

Multiple development teams in the company want to use Amazon Elastic File System (Amazon EFS). A development team has created a new EFS file system but cannot mount the file system to one of its Amazon EC2 instances. The network engineer discovers that the EC2 instance cannot resolve the IP address for the EFS mount point fs-33444567d.efs.us-east-1.amazonaws.com. The network engineer needs to implement a solution so that development teams throughout the organization can mount EFS file systems.

Which combination of steps will meet these requirements? (Choose two.)

- A. Configure the BIND DNS servers in the central VPC to forward queries for fs-33444567d.efs.us-east-1.amazonaws.com to the Amazon provided DNS server (169.254.169.253).
- B. Create an Amazon Route 53 Resolver outbound endpoint in the central VPC.
- C. Update all the VPC DHCP options sets to use AmazonProvidedDNS for name resolution.
- D. Create an Amazon Route 53 Resolver inbound endpoint in the central VPC. Update all the VPC DHCP options sets to use the Route 53 Resolver inbound endpoint in the central VPC for name resolution.
- E. Create an Amazon Route 53 Resolver rule to forward queries for the on-premises domain to the on-premises DNS server.
- F. Share the rule with the organization by using AWS Resource Access Manager (AWS RAM). Associate the rule with all the VPCs.
- G. Create an Amazon Route 53 private hosted zone for the fs-33444567d.efs.us-east-1.amazonaws.com domain. Associate the private hosted zone with the VPC where the EC2 instance is deployed.
- H. Create an A record for fs-33444567d.efs.us-east-1.amazonaws.com in the private hosted zone.
- I. Configure the A record to return the mount target of the EFS mount point.

Answer: BD

Explanation:

Option B suggests using Amazon Route 53 Resolver outbound endpoint, which would replace the existing BIND DNS servers with the AmazonProvidedDNS for name resolution. However, the scenario specifically mentions that the company is using custom DNS servers that run BIND for name resolution in its VPCs, so this solution would not work. Option D suggests creating a Route 53 Resolver rule to forward queries for the on-premises domain to the on-premises DNS servers, which would not address the issue of resolving the EFS mount point. The problem is not with resolving queries for the on-premises domain, but rather with resolving the IP address for the EFS mount point.

NEW QUESTION 2

An IoT company sells hardware sensor modules that periodically send out temperature, humidity, pressure, and location data through the MQTT messaging protocol. The hardware sensor modules send this data to the company's on-premises MQTT brokers that run on Linux servers behind a load balancer. The hardware sensor modules have been hardcoded with public IP addresses to reach the brokers.

The company is growing and is acquiring customers across the world. The existing solution can no longer scale and is introducing additional latency because of the company's global presence. As a result, the company decides to migrate its entire infrastructure from on-premises to the AWS Cloud. The company needs to migrate without reconfiguring the hardware sensor modules that are already deployed across the world. The solution also must minimize latency.

The company migrates the MQTT brokers to run on Amazon EC2 instances. What should the company do next to meet these requirements?

- A. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener.
- B. Use Bring Your Own IP (BYOIP) from the on-premises network with the NLB.
- C. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener.
- D. Create an AWS Global Accelerator accelerator in front of the NLB. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator.
- E. Place the EC2 instances behind an Application Load Balancer (ALB). Configure TCP listener.
- F. Create an AWS Global Accelerator accelerator in front of the ALB.
- G. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator.
- H. Place the EC2 instances behind an Amazon CloudFront distribution.
- I. Use Bring Your Own IP (BYOIP) from the on-premises network with CloudFront.

Answer: B

NEW QUESTION 3

A company has hundreds of VPCs on AWS. All the VPCs access the public endpoints of Amazon S3 and AWS Systems Manager through NAT gateways. All the traffic from the VPCs to Amazon S3 and Systems Manager travels through the NAT gateways. The company's network engineer must centralize access to these services and must eliminate the need to use public endpoints.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a central egress VPC that has private NAT gateway.
- B. Connect all the VPCs to the central egress VPC by using AWS Transit Gateway.
- C. Use the private NAT gateways to connect to Amazon S3 and Systems Manager by using private IP addresses.
- D. Create a central shared services VPC.
- E. In the central shared services VPC, create interface VPC endpoints for Amazon S3 and Systems Manager to access.
- F. Ensure that private DNS is turned off.
- G. Connect all the VPCs to the central shared services VPC by using AWS Transit Gateway.
- H. Create an Amazon Route 53 forwarding rule for each interface VPC endpoint.
- I. Associate the forwarding rules with all the VPCs.
- J. Forward DNS queries to the interface VPC endpoints in the shared services VPC.
- K. Create a central shared services VPC. In the central shared services VPC, create interface VPC endpoints for Amazon S3 and Systems Manager to access.
- L. Ensure that private DNS is turned off.
- M. Connect all the VPCs to the central shared services VPC by using AWS Transit Gateway.
- N. Create an Amazon Route 53 private hosted zone with a full service endpoint name for Amazon S3 and Systems Manager.
- O. Associate the private hosted zones with all the VPCs.
- P. Create an alias record in each private hosted zone with the full AWS service endpoint pointing to the interface VPC endpoint in the shared services VPC.
- Q. Create a central shared services VPC.
- R. In the central shared services VPC, create interface VPC endpoints for Amazon S3 and Systems Manager to access.

- S. Connect all the VPCs to the central shared services VPC by using AWS Transit Gateway
- T. Ensure that private DNS is turned on for the interface VPC endpoints and that the transit gateway is created with DNS support turned on.

Answer: B

Explanation:

Interface VPC endpoints enable private connectivity between VPCs and supported AWS services without requiring an internet gateway, NAT device, VPN connection, or AWS Direct Connect connection. Interface VPC endpoints are powered by AWS PrivateLink, a technology that enables private access to AWS services. Amazon S3 and AWS Systems Manager support interface VPC endpoints. By turning off private DNS, the interface VPC endpoints can be accessed by using their private IP addresses. By using Amazon Route 53 forwarding rules, DNS queries can be resolved to the interface VPC endpoints in the shared services VPC.

NEW QUESTION 4

A company is deploying third-party firewall appliances for traffic inspection and NAT capabilities in its VPC. The VPC is configured with private subnets and public subnets. The company needs to deploy the firewall appliances behind a load balancer.

Which architecture will meet these requirements MOST cost-effectively?

- A. Deploy a Gateway Load Balancer with the firewall appliances as target
- B. Configure the firewall appliances with a single network interface in a private subnet
- C. Use a NAT gateway to send the traffic to the internet after inspection.
- D. Deploy a Gateway Load Balancer with the firewall appliances as target
- E. Configure the firewall appliances with two network interfaces: one network interface in a private subnet and another network interface in a public subnet
- F. Use the NAT functionality on the firewall appliances to send the traffic to the internet after inspection.
- G. Deploy a Network Load Balancer with the firewall appliances as target
- H. Configure the firewall appliances with a single network interface in a private subnet
- I. Use a NAT gateway to send the traffic to the internet after inspection.
- J. Deploy a Network Load Balancer with the firewall appliances as target
- K. Configure the firewall appliances with two network interfaces: one network interface in a private subnet and another network interface in a public subnet
- L. Use the NAT functionality on the firewall appliances to send the traffic to the internet after inspection.

Answer: B

NEW QUESTION 5

A company's network engineer is designing a hybrid DNS solution for an AWS Cloud workload. Individual teams want to manage their own DNS hostnames for their applications in their development environment. The solution must integrate the application-specific hostnames with the centrally managed DNS hostnames from the on-premises network and must provide bidirectional name resolution. The solution also must minimize management overhead.

Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Use an Amazon Route 53 Resolver inbound endpoint.
- B. Modify the DHCP options set by setting a custom DNS server value.
- C. Use an Amazon Route 53 Resolver outbound endpoint.
- D. Create DNS proxy servers.
- E. Create Amazon Route 53 private hosted zones.
- F. Set up a zone transfer between Amazon Route 53 and the on-premises DNS.

Answer: ABE

NEW QUESTION 6

A software-as-a-service (SaaS) provider hosts its solution on Amazon EC2 instances within a VPC in the AWS Cloud. All of the provider's customers also have their environments in the AWS Cloud.

A recent design meeting revealed that the customers have IP address overlap with the provider's AWS deployment. The customers have stated that they will not share their internal IP addresses and that they do not want to connect to the provider's SaaS service over the internet.

Which combination of steps is part of a solution that meets these requirements? (Choose two.)

- A. Deploy the SaaS service endpoint behind a Network Load Balancer.
- B. Configure an endpoint service, and grant the customers permission to create a connection to the endpoint service.
- C. Deploy the SaaS service endpoint behind an Application Load Balancer.
- D. Configure a VPC peering connection to the customer VPC
- E. Route traffic through NAT gateways.
- F. Deploy an AWS Transit Gateway, and connect the SaaS VPC to it
- G. Share the transit gateway with the customer
- H. Configure routing on the transit gateway.

Answer: AB

Explanation:

NLB for creating the private link which solves the overlapping IP address issue and the SaaS service endpoint behind it. (the SaaS endpoint could be an ALB)
<https://aws.amazon.com/about-aws/whats-new/2021/09/application-load-balancer-aws-privatelink-static-ip>

NEW QUESTION 7

A company has two AWS accounts one for Production and one for Connectivity. A network engineer needs to connect the Production account VPC to a transit gateway in the Connectivity account. The feature to auto accept shared attachments is not enabled on the transit gateway.

Which set of steps should the network engineer follow in each AWS account to meet these requirements?

- A. * 1. In the Production account: Create a resource share in AWS Resource Access Manager for the transit gateway
- B. Provide the Connectivity account ID
- C. Enable the feature to allow external accounts* 2. In the Connectivity account: Accept the resource.* 3. In the Connectivity account: Create an attachment to the VPC subnets.* 4. In the Production account: Accept the attachment
- D. Associate a route table with the attachment.

- E. * 1. In the Production account: Create a resource share in AWS Resource Access Manager for the VPC subnet
F. Provide the Connectivity account ID
G. Enable the feature to allow external accounts.* 2. In the Connectivity account: Accept the resource.* 3. In the Production account: Create an attachment on the transit gateway to the VPC subnets.* 4. In the Connectivity account: Accept the attachment
H. Associate a route table with the attachment.
I. * 1. In the Connectivity account: Create a resource share in AWS Resource Access Manager for the VPC subnet
J. Provide the Production account ID
K. Enable the feature to allow external accounts.* 2. In the Production account: Accept the resource.* 3. In the Connectivity account: Create an attachment on the transit gateway to the VPC subnets.* 4. In the Production account: Accept the attachment
L. Associate a route table with the attachment.
M. * 1. In the Connectivity account: Create a resource share in AWS Resource Access Manager for the transit gateway
N. Provide the Production account ID Enable the feature to allow external accounts.* 2. In the Production account: Accept the resource.* 3. In the Production account: Create an attachment to the VPC subnets.* 4. In the Connectivity account: Accept the attachment
O. Associate a route table with the attachment.

Answer: A

Explanation:

step 1: In the Production account, create a resource share in AWS Resource Access Manager for the transit gateway and provide the Connectivity account ID. Enabling the feature to allow external accounts is also required to share resources between accounts. Step 2: In the Connectivity account, accept the shared resource. This action will allow the Production account to use the transit gateway in the Connectivity account. Step 3: In the Connectivity account, create an attachment to the VPC subnets. This attachment will enable communication between the VPC in the Production account and the transit gateway in the Connectivity account. Step 4: In the Production account, accept the attachment and associate a route table with the attachment. This will enable the VPC to route traffic through the transit gateway to other resources in the Connectivity account.

NEW QUESTION 8

A network engineer needs to update a company's hybrid network to support IPv6 for the upcoming release of a new application. The application is hosted in a VPC in the AWS Cloud. The company's current AWS infrastructure includes VPCs that are connected by a transit gateway. The transit gateway is connected to the on-premises network by AWS Direct Connect and AWS Site-to-Site VPN. The company's on-premises devices have been updated to support the new IPv6 requirements.

The company has enabled IPv6 for the existing VPC by assigning a new IPv6 CIDR block to the VPC and by assigning IPv6 to the subnets for dual-stack support. The company has launched new Amazon EC2 instances for the new application in the updated subnets.

When updating the hybrid network to support IPv6 the network engineer must avoid making any changes to the current infrastructure. The network engineer also must block direct access to the instances' new IPv6 addresses from the internet. However, the network engineer must allow outbound internet access from the instances.

What is the MOST operationally efficient solution that meets these requirements?

- A. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- B. Create a new VPN connection that supports IPv6 connectivity
- C. Add an egress-only internet gateway
- D. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices
- E. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- F. Update the existing VPN connection to support IPv6 connectivity
- G. Add an egress-only internet gateway
- H. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- I. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- J. Create a new VPN connection that supports IPv6 connectivity
- K. Add an egress-only internet gateway
- L. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- M. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- N. Create a new VPN connection that supports IPv6 connectivity
- O. Add a NAT gateway
- P. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.

Answer: B

NEW QUESTION 9

A company is planning a migration of its critical workloads from an on-premises data center to Amazon EC2 instances. The plan includes a new 10 Gbps AWS Direct Connect dedicated connection from the on-premises data center to a VPC that is attached to a transit gateway. The migration must occur over encrypted paths between the on-premises data center and the AWS Cloud.

Which solution will meet these requirements while providing the HIGHEST throughput?

- A. Configure a public VIF on the Direct Connect connection
- B. Configure an AWS Site-to-Site VPN connection to the transit gateway as a VPN attachment.
- C. Configure a transit VIF on the Direct Connect connection
- D. Configure an IPsec VPN connection to an EC2 instance that is running third-party VPN software.
- E. Configure MACsec for the Direct Connect connection
- F. Configure a transit VIF to a Direct Connect gateway that is associated with the transit gateway.
- G. Configure a public VIF on the Direct Connect connection
- H. Configure two AWS Site-to-Site VPN connections to the transit gateway
- I. Enable equal-cost multi-path (ECMP) routing.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/networking-and-content-delivery/adding-macsec-security-to-aws-direct-connect-c>

NEW QUESTION 10

A company uses a 1 Gbps AWS Direct Connect connection to connect its AWS environment to its on-premises data center. The connection provides employees with access to an application VPC that is hosted on AWS. Many remote employees use a company-

provided VPN to connect to the data center. These employees are reporting slowness when they access the application during business hours. On-premises users have started to report similar slowness while they are in the office.

The company plans to build an additional application on AWS. On-site and remote employees will use the additional application. After the deployment of this additional application, the company will need 20% more bandwidth than the company currently uses. With the increased usage, the company wants to add resiliency to the AWS connectivity. A network engineer must review the current implementation and must make improvements within a limited budget. What should the network engineer do to meet these requirements MOST cost-effectively?

- A. Set up a new 1 Gbps Direct Connect dedicated connection to accommodate the additional traffic load from remote employees and the additional application
- B. Create a link aggregation group (LAG).
- C. Deploy an AWS Site-to-Site VPN connection to the application VPC
- D. Configure the on-premises routing for the remote employees to connect to the Site-to-Site VPN connection.
- E. Deploy Amazon Workspaces into the application VPC and instruct the remote employees to connect to Workspaces.
- F. Replace the existing 1 Gbps Direct Connect connection with two new 2 Gbps Direct Connect hosted connections
- G. Create an AWS Client VPN endpoint in the application VPC
- H. Instruct the remote employees to connect to the Client VPN endpoint.

Answer: A

Explanation:

Setting up a new 1 Gbps Direct Connect dedicated connection to accommodate the additional traffic load from remote employees and the additional application would provide more bandwidth and lower latency than a VPN connection over the public internet¹. Creating a link aggregation group (LAG) with the existing and new Direct Connect connections would provide resiliency and redundancy for the AWS connectivity².

NEW QUESTION 10

A company is building its website on AWS in a single VPC. The VPC has public subnets and private subnets in two Availability Zones. The website has static content such as images. The company is using Amazon S3 to store the content.

The company has deployed a fleet of Amazon EC2 instances as web servers in a private subnet. The EC2 instances are in an Auto Scaling group behind an Application Load Balancer. The EC2 instances will serve traffic, and they must pull content from an S3 bucket to render the webpages. The company is using AWS Direct Connect with a public VIF for on-premises connectivity to the S3 bucket.

A network engineer notices that traffic between the EC2 instances and Amazon S3 is routing through a NAT gateway. As traffic increases, the company's costs are increasing. The network engineer needs to change the connectivity to reduce the NAT gateway costs that result from the traffic between the EC2 instances and Amazon S3.

Which solution will meet these requirements?

- A. Create a Direct Connect private VIF
- B. Migrate the traffic from the public VIF to the private VIF.
- C. Create an AWS Site-to-Site VPN tunnel over the existing public VIF.
- D. Implement interface VPC endpoints for Amazon S3. Update the VPC route table.
- E. Implement gateway VPC endpoints for Amazon S3. Update the VPC route table.

Answer: D

NEW QUESTION 15

A global delivery company is modernizing its fleet management system. The company has several business units. Each business unit designs and maintains applications that are hosted in its own AWS account in separate application VPCs in the same AWS Region. Each business unit's applications are designed to get data from a central shared services VPC.

The company wants the network connectivity architecture to provide granular security controls. The architecture also must be able to scale as more business units consume data from the central shared services VPC in the future.

Which solution will meet these requirements in the MOST secure manner?

- A. Create a central transit gateway
- B. Create a VPC attachment to each application VPC
- C. Provide full mesh connectivity between all the VPCs by using the transit gateway.
- D. Create VPC peering connections between the central shared services VPC and each application VPC in each business unit's AWS account.
- E. Create VPC endpoint services powered by AWS PrivateLink in the central shared services VPC and create VPC endpoints in each application VPC.
- F. Create a central transit VPC with a VPN appliance from AWS Marketplace
- G. Create a VPN attachment from each VPC to the transit VPC
- H. Provide full mesh connectivity among all the VPCs.

Answer: C

Explanation:

Option C provides a secure and scalable solution using VPC endpoint services powered by AWS PrivateLink. AWS PrivateLink enables private connectivity between VPCs and services without exposing the data to the public internet or using a VPN connection. By creating VPC endpoints in each application VPC, the company can securely access the central shared services VPC without the need for complex network configurations. Furthermore, PrivateLink supports cross-account connectivity, which makes it a scalable solution as more business units consume data from the central shared services VPC in the future.

NEW QUESTION 20

A company is using Amazon Route 53 Resolver DNS Firewall in a VPC to block all domains except domains that are on an approved list. The company is concerned that if DNS Firewall is unresponsive, resources in the VPC might be affected if the network cannot resolve any DNS queries. To maintain application service level agreements, the company needs DNS queries to continue to resolve even if Route 53 Resolver does not receive a response from DNS Firewall. Which change should a network engineer implement to meet these requirements?

- A. Update the DNS Firewall VPC configuration to disable fail open for the VPC.
- B. Update the DNS Firewall VPC configuration to enable fail open for the VPC.
- C. Create a new DHCP options set with parameter `dns_firewall_fail_open=false`
- D. Associate the new DHCP options set with the VPC.
- E. Create a new DHCP options set with parameter `dns_firewall_fail_open=true`
- F. Associate the new DHCP options set with the VPC.

Answer: B

NEW QUESTION 25

A company has created three VPCs: a production VPC, a nonproduction VPC, and a shared services VPC. The production VPC and the nonproduction VPC must each have communication with the shared services VPC. There must be no communication between the production VPC and the nonproduction VPC. A transit gateway is deployed to facilitate communication between VPCs.

Which route table configurations on the transit gateway will meet these requirements?

- A. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for only the shared services VPC
- B. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- C. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for each VPC
- D. Create an additional route table with only the shared services VPC attachment associated with propagated routes from each VPC.
- E. Configure a route table with all the VPC attachments associated with propagated routes for only the shared services VPC
- F. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- G. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes disabled
- H. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.

Answer: A

NEW QUESTION 28

A company is using a NAT gateway to allow internet connectivity for private subnets in a VPC in the us-west-2 Region. After a security audit, the company needs to remove the NAT gateway.

In the private subnets, the company has resources that use the unified Amazon CloudWatch agent. A network engineer must create a solution to ensure that the unified CloudWatch agent continues to work after the removal of the NAT gateway.

Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Validate that private DNS is enabled on the VPC by setting the enableDnsHostnames VPC attribute and the enableDnsSupport VPC attribute to true.
- B. Create a new security group with an entry to allow outbound traffic that uses the TCP protocol on port 443 to destination 0.0.0.0/0
- C. Create a new security group with entries to allow inbound traffic that uses the TCP protocol on port 443 from the IP prefixes of the private subnets.
- D. Create the following interface VPC endpoints in the VPC: com.amazonaws.us-west-2.logs and com.amazonaws.us-west-2.monitoring
- E. Associate the new security group with the endpoint network interfaces.
- F. Create the following interface VPC endpoint in the VPC: com.amazonaws.us-west-2.cloudwatch. Associate the new security group with the endpoint network interfaces.
- G. Associate the VPC endpoint or endpoints with route tables that the private subnets use.

Answer: BDF

NEW QUESTION 29

A company is hosting an application on Amazon EC2 instances behind an Application Load Balancer. The instances are in an Amazon EC2 Auto Scaling group. Because of a recent change to a security group, external users cannot access the application.

A network engineer needs to prevent this downtime from happening again. The network engineer must implement a solution that remediates noncompliant changes to security groups.

Which solution will meet these requirements?

- A. Configure Amazon GuardDuty to detect inconsistencies between the desired security group configuration and the current security group configuration
- B. Create an AWS Systems Manager Automation runbook to remediate noncompliant security groups.
- C. Configure an AWS Config rule to detect inconsistencies between the desired security group configuration and the current security group configuration
- D. Configure AWS OpsWorks for Chef to remediate noncompliant security groups.
- E. Configure Amazon GuardDuty to detect inconsistencies between the desired security group configuration and the current security group configuration
- F. Configure AWS OpsWorks for Chef to remediate noncompliant security groups.
- G. Configure an AWS Config rule to detect inconsistencies between the desired security group configuration and the current security group configuration
- H. Create an AWS Systems Manager Automation runbook to remediate noncompliant security groups.

Answer: D

Explanation:

Configuring an AWS Config rule to detect inconsistencies between the desired security group configuration and the current security group configuration would enable evaluation of the compliance status of the security groups based on predefined or custom rules³. Creating an AWS Systems Manager Automation runbook to remediate noncompliant security groups would enable automation of the remediation process². Additionally, configuring AWS Config to trigger the runbook when a noncompliant change is detected would enable timely and consistent remediation of security group changes.

NEW QUESTION 33

A company's development team has created a new product recommendation web service. The web service is hosted in a VPC with a CIDR block of 192.168.224.0/19. The company has deployed the web service on Amazon EC2 instances and has configured an Auto Scaling group as the target of a Network Load Balancer (NLB).

The company wants to perform testing to determine whether users who receive product recommendations spend more money than users who do not receive product recommendations. The company has a big sales event in 5 days and needs to integrate its existing production environment with the recommendation engine by then. The existing production environment is hosted in a VPC with a CIDR block of 192.168.128.0/17.

A network engineer must integrate the systems by designing a solution that results in the least possible disruption to the existing environments.

Which solution will meet these requirements?

- A. Create a VPC peering connection between the web service VPC and the existing production VPC
- B. Add a routing rule to the appropriate route table to allow data to flow to 192.168.224.0/19 from the existing production environment and to flow to 192.168.128.0/17 from the web service environment
- C. Configure the relevant security groups and ACLs to allow the systems to communicate.
- D. Ask the development team of the web service to redeploy the web service into the production VPC and integrate the systems there.
- E. Create a VPC endpoint service
- F. Associate the VPC endpoint service with the NLB for the web service. Create an interface VPC endpoint for the web service in the existing production VPC.
- G. Create a transit gateway in the existing production environment

- H. Create attachments to the production VPC and the web service VP
- I. Configure appropriate routing rules in the transit gateway and VPC route tables for 192.168.224.0/19 and 192.168.128.0/17. Configure the relevant security groups and ACLs to allow the systems to communicate.

Answer: C

NEW QUESTION 35

A company has deployed its AWS environment in a single AWS Region. The environment consists of a few hundred application VPCs, a shared services VPC, and a VPN connection to the company's on-premises environment. A network engineer needs to implement a transit gateway with the following requirements:

- Application VPCs must be isolated from each other.
- Bidirectional communication must be allowed between the application VPCs and the on-premises network.
- Bidirectional communication must be allowed between the application VPCs and the shared services VPC. The network engineer creates the transit gateway with options disabled for default route table association and default route table propagation. The network engineer also creates the VPN attachment for the on-premises network and creates the VPC attachments for the application VPCs and the shared services VPC. The network engineer must meet all the requirements for the transit gateway by designing a solution that needs the least number of transit gateway route tables. Which combination of actions should the network engineer perform to accomplish this goal?(Choose two.)

- A. Configure a separate transit gateway route table for on premise
- B. Associate the VPN attachment with this transit gateway route tabl
- C. Propagate all application VPC attachments to this transit gateway route table.
- D. Configure a separate transit gateway route table for each application VP
- E. Associate each application VPC attachment with its respective transit gateway route tabl
- F. Propagate the shared services VPC attachment and the VPN attachment to this transit gateway route table.
- G. Configure a separate transit gateway route table for all application VPC
- H. Associate all application VPCs with this transit gateway route tabl
- I. Propagate the shared services VPC attachment and the VPN attachment to this transit gateway route table.
- J. Configure a separate transit gateway route table for the shared services VP
- K. Associate the shared services VPC attachment with this transit gateway route tabl
- L. Propagate all application VPC attachments to this transit gateway route table.
- M. Configure a separate transit gateway route table for on premises and the shared services VP
- N. Associate the VPN attachment and the shared services VPC attachment with this transit gateway route tabl
- O. Propagate all application VPC attachments to this transit gateway route table.

Answer: BD

NEW QUESTION 38

An organization is using a VPC endpoint for Amazon S3. When the security group rules for a set of instances were initially configured, access was restricted to allow traffic only to the IP addresses of the Amazon S3 API endpoints in the region from the published JSON file. The application was working properly, but now is logging a growing number of timeouts when connecting with Amazon S3. No internet gateway is configured for the VPC. Which solution will fix the connectivity failures with the LEAST amount of effort?

- A. Create a Lambda function to update the security group based on AmazonIPSpaceChanged notifications.
- B. Update the VPC routing to direct Amazon S3 prefix-list traffic to the VPC endpoint using the route table APIs.
- C. Update the application server's outbound security group to use the prefix-list for Amazon S3 in the same region.
- D. Create an additional VPC endpoint for Amazon S3 in the same route table to scale the concurrent connections to Amazon.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/aws/subscribe-to-aws-public-ip-address-changes-via-amazon-sns/>

NEW QUESTION 43

A company is planning to deploy many software-defined WAN (SD-WAN) sites. The company is using AWS Transit Gateway and has deployed a transit gateway in the required AWS Region. A network engineer needs to deploy the SD-WAN hub virtual appliance into a VPC that is connected to the transit gateway. The solution must support at least 5 Gbps of throughput from the SD-WAN hub virtual appliance to other VPCs that are attached to the transit gateway. Which solution will meet these requirements?

- A. Create a new VPC for the SD-WAN hub virtual applianc
- B. Create two IPsec VPN connections between the SD-WAN hub virtual appliance and the transit gatewa
- C. Configure BGP over the IPsec VPN connections
- D. Assign a new CIDR block to the transit gatewa
- E. Create a new VPC for the SD-WAN hub virtual applianc
- F. Attach the new VPC to the transit gateway with a VPC attachmen
- G. Add a transit gateway Connect attachmen
- H. Create a Connect peer and specify the GRE and BGP parameter
- I. Create a route in the appropriate VPC for the SD-WAN hub virtual appliance to route to the transit gateway.
- J. Create a new VPC for the SD-WAN hub virtual applianc
- K. Attach the new VPC to the transit gateway with a VPC attachmen
- L. Create two IPsec VPN connections between the SD-WAN hub virtual appliance and the transit gatewa
- M. Configure BGP over the IPsec VPN connections.
- N. Assign a new CIDR block to the transit gatewa
- O. Create a new VPC for the SD-WAN hub virtual applianc
- P. Attach the new VPC to the transit gateway with a VPC attachmen
- Q. Add a transit gateway Connect attachmen
- R. Create a Connect peer and specify the VXLAN and BGP parameter
- S. Create a route in the appropriate VPC for the SD-WAN hub virtual appliance to route to the transit gateway.

Answer: D

NEW QUESTION 48

A company is deploying a new application in the AWS Cloud. The company wants a highly available web server that will sit behind an Elastic Load Balancer. The load balancer will route requests to multiple target groups based on the URL in the request. All traffic must use HTTPS. TLS processing must be offloaded to the load balancer. The web server must know the user's IP address so that the company can keep accurate logs for security purposes.

Which solution will meet these requirements?

- A. Deploy an Application Load Balancer with an HTTPS listener
- B. Use path-based routing rules to forward the traffic to the correct target group
- C. Include the X-Forwarded-For request header with traffic to the targets.
- D. Deploy an Application Load Balancer with an HTTPS listener for each domain
- E. Use host-based routing rules to forward the traffic to the correct target group for each domain
- F. Include the X-Forwarded-For request header with traffic to the targets.
- G. Deploy a Network Load Balancer with a TLS listener
- H. Use path-based routing rules to forward the traffic to the correct target group
- I. Configure client IP address preservation for traffic to the targets.
- J. Deploy a Network Load Balancer with a TLS listener for each domain
- K. Use host-based routing rules to forward the traffic to the correct target group for each domain
- L. Configure client IP address preservation for traffic to the targets.

Answer: A

Explanation:

An Application Load Balancer (ALB) can be used to route traffic to multiple target groups based on the URL in the request. The ALB can be configured with an HTTPS listener to ensure all traffic uses HTTPS. TLS processing can be offloaded to the ALB, which reduces the load on the web server. Path-based routing rules can be used to route traffic to the correct target group based on the URL in the request. The X-Forwarded-For request header can be included with traffic to the targets, which will allow the web server to know the user's IP address and keep accurate logs for security purposes.

NEW QUESTION 50

A company deploys a new web application on Amazon EC2 instances. The application runs in private subnets in three Availability Zones behind an Application Load Balancer (ALB). Security auditors require encryption of all connections. The company uses Amazon Route 53 for DNS and uses AWS Certificate Manager (ACM) to automate SSL/TLS certificate provisioning. SSL/TLS connections are terminated on the ALB.

The company tests the application with a single EC2 instance and does not observe any problems. However, after production deployment, users report that they can log in but that they cannot use the application. Every new web request restarts the login process.

What should a network engineer do to resolve this issue?

- A. Modify the ALB listener configuration
- B. Edit the rule that forwards traffic to the target group
- C. Change the rule to enable group-level stickiness
- D. Set the duration to the maximum application session length.
- E. Replace the ALB with a Network Load Balance
- F. Create a TLS listener
- G. Create a new target group with the protocol type set to TLS Register the EC2 instance
- H. Modify the target group configuration by enabling the stickiness attribute.
- I. Modify the ALB target group configuration by enabling the stickiness attribute
- J. Use an application-based cookie
- K. Set the duration to the maximum application session length.
- L. Remove the AL
- M. Create an Amazon Route 53 rule with a failover routing policy for the application name
- N. Configure ACM to issue certificates for each EC2 instance.

Answer: C

NEW QUESTION 54

A Network Engineer is provisioning a subnet for a load balancer that will sit in front of a fleet of application servers in a private subnet. There is limited IP space left in the VPC CIDR. The application has few users now but is expected to grow quickly to millions of users.

What design will use the LEAST amount of IP space, while allowing for this growth?

- A. Use two /29 subnets for an Application Load Balancer in different Availability Zones.
- B. Use one /29 subnet for the Network Load Balance
- C. Add another VPC CIDR to the VPC to allow for future growth.
- D. Use two /28 subnets for a Network Load Balancer in different Availability Zones.
- E. Use one /28 subnet for an Application Load Balance
- F. Add another VPC CIDR to the VPC to allow for future growth.

Answer: C

NEW QUESTION 56

A company uses a 4 Gbps AWS Direct Connect dedicated connection with a link aggregation group (LAG) bundle to connect to five VPCs that are deployed in the us-east-1 Region. Each VPC serves a different business unit and uses its own private VIF for connectivity to the on-premises environment. Users are reporting slowness when they access resources that are hosted on AWS.

A network engineer finds that there are sudden increases in throughput and that the Direct Connect connection becomes saturated at the same time for about an hour each business day. The company wants to know which business unit is causing the sudden increase in throughput. The network engineer must find out this information and implement a solution to resolve the problem.

Which solution will meet these requirements?

- A. Review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observed
- B. Create a new 10 Gbps dedicated connection
- C. Shift traffic from the existing dedicated connection to the new dedicated connection.
- D. Review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest

throughput during the period in which slowness is observe

E. Upgrade the bandwidth of the existing dedicated connection to 10 Gbps.

F. Review the Amazon CloudWatch metrics for ConnectionBpsIngress and ConnectionPpsEgress to determine which VIF is sending the highest throughput during the period in which slowness is observe

G. Upgrade the existing dedicated connection to a 5 Gbps hosted connection.

H. Review the Amazon CloudWatch metrics for ConnectionBpsIngress and ConnectionPpsEgress to determine which VIF is sending the highest throughput during the period in which slowness is observed. Create a new 10 Gbps dedicated connectio

I. Shift traffic from the existing dedicated connection to the new dedicated connection.

Answer: A

Explanation:

To meet the requirements of finding out which business unit is causing the sudden increase in throughput and resolving the problem, the network engineer should review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observed (Option B). After identifying the VIF that is causing the issue, they can upgrade the bandwidth of the existing dedicated connection to 10 Gbps to resolve the problem (Option B).

NEW QUESTION 61

A company is developing an application in which IoT devices will report measurements to the AWS Cloud. The application will have millions of end users. The company observes that the IoT devices cannot support DNS resolution. The company needs to implement an Amazon EC2 Auto Scaling solution so that the IoT devices can connect to an application endpoint without using DNS.

Which solution will meet these requirements MOST cost-effectively?

A. Use an Application Load Balancer (ALB)-type target group for a Network Load Balancer (NLB). Create an EC2 Auto Scaling grou

B. Attach the Auto Scaling group to the AL

C. Set up the IoT devices to connect to the IP addresses of the NLB.

D. Use an AWS Global Accelerator accelerator with an Application Load Balancer (ALB) endpoint

E. Create an EC2 Auto Scaling grou

F. Attach the Auto Scaling group to the ALSet up the IoT devices to connect to the IP addresses of the accelerator.

G. Use a Network Load Balancer (NLB). Create an EC2 Auto Scaling grou

H. Attach the Auto Scaling group to the NL

I. Set up the IoT devices to connect to the IP addresses of the NLB.

J. Use an AWS Global Accelerator accelerator with a Network Load Balancer (NLB) endpoint

K. Create anEC2 Auto Scaling grou

L. Attach the Auto Scaling group to the NL

M. Set up the IoT devices to connect to the IP addresses of the accelerator.

Answer: D

Explanation:

AWS Global Accelerator can provide static IP addresses that the IoT devices can connect to without using DNS². It can also route traffic over the AWS global network and improve performance and availability for the IoT devices². An NLB can provide end-to-end encryption for HTTPS traffic by using TLS as a target group protocol and terminating SSL connections at the load balancer level¹. An NLB can also support session affinity (sticky sessions) with TCP connections¹.

NEW QUESTION 64

A bank built a new version of its banking application in AWS using containers that content to an on-premises database over VPN connection. This application version requires users to also update their client application. The bank plans to deprecate the earlier client version. However, the company wants to keep supporting earlier clients through their on-premises version of the application to serve a small portion of the customers who haven't yet upgraded.

What design will allow the company to serve both newer and earlier clients in the MOST efficient way?

A. Use an Amazon Route 53 multivalue answer routing policy to route older client traffic to the on-premises application version and the rest of the traffic to the new AWS based version.

B. Use a Classic Load Balancer for the new applicatio

C. Route all traffic to the new application by using an Elastic Load Balancing (ELB) load balancer DN

D. Define a user-agent-based rule on the backend servers to redirect earlier clients to the on-premises application.

E. Use an Application Load Balancer for the new applicatio

F. Register both the new and earlier applications as separate target groups and use path-based routing to route traffic based on the application version.

G. Use an Application Load Balancer for the new applicatio

H. Register both the new and earlier application backends as separate target group

I. Use header-based routing to route traffic based on the application version.

Answer: D

NEW QUESTION 65

A security team is performing an audit of a company's AWS deployment. The security team is concerned that two applications might be accessing resources that should be blocked by network ACLs and security groups. The applications are deployed across two Amazon Elastic Kubernetes Service (Amazon EKS) clusters that use the Amazon VPC Container Network Interface (CNI) plugin for Kubernetes. The clusters are in separate subnets within the same VPC and have a Cluster Autoscaler configured.

The security team needs to determine which POD IP addresses are communicating with which services throughout the VPC. The security team wants to limit the number of flow logs and wants to examine the traffic from only the two applications.

Which solution will meet these requirements with the LEAST operational overhead?

A. Create VPC flow logs in the default forma

B. Create a filter to gather flow logs only from the EKS nodes. Include the srcaddr field and the dstaddr field in the flow logs.

C. Create VPC flow logs in a custom forma

D. Set the EKS nodes as the resource Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.

E. Create VPC flow logs in a custom forma

F. Set the application subnets as resource

G. Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.

H. Create VPC flow logs in a custom forma

I. Create a filter to gather flow logs only from the EKS nodes. Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.

Answer: D

NEW QUESTION 66

A retail company is running its service on AWS. The company's architecture includes Application Load Balancers (ALBs) in public subnets. The ALB target groups are configured to send traffic to backend Amazon EC2 instances in private subnets. These backend EC2 instances can call externally hosted services over the internet by using a NAT gateway.

The company has noticed in its billing that NAT gateway usage has increased significantly. A network engineer needs to find out the source of this increased usage.

Which options can the network engineer use to investigate the traffic through the NAT gateway? (Choose two.)

- A. Enable VPC flow logs on the NAT gateway's elastic network interface
- B. Publish the logs to a log group in Amazon CloudWatch Log
- C. Use CloudWatch Logs Insights to query and analyze the logs.
- D. Enable NAT gateway access log
- E. Publish the logs to a log group in Amazon CloudWatch Log
- F. Use CloudWatch Logs Insights to query and analyze the logs.
- G. Configure Traffic Mirroring on the NAT gateway's elastic network interface
- H. Send the traffic to an additional EC2 instance
- I. Use tools such as tcpdump and Wireshark to query and analyze the mirrored traffic.
- J. Enable VPC flow logs on the NAT gateway's elastic network interface
- K. Publish the logs to an Amazon S3 bucket
- L. Create a custom table for the S3 bucket in Amazon Athena to describe the log structure
- M. Use Athena to query and analyze the logs.
- N. Enable NAT gateway access log
- O. Publish the logs to an Amazon S3 bucket
- P. Create a custom table for the S3 bucket in Amazon Athena to describe the log structure
- Q. Use Athena to query and analyze the logs.

Answer: AD

Explanation:

To investigate the increased usage of a NAT gateway in a VPC architecture with ALBs and backend EC2 instances, a network engineer can use the following options:

➤ Enable VPC flow logs on the NAT gateway's elastic network interface and publish the logs to a log group in Amazon CloudWatch Logs. Use CloudWatch Logs Insights to query and analyze the logs.

(Option A)

➤ Enable VPC flow logs on the NAT gateway's elastic network interface and publish the logs to an Amazon S3 bucket. Create a custom table for the S3 bucket in Amazon Athena to describe the log structure and use Athena to query and analyze the logs. (Option D)

These options allow for detailed analysis of traffic through the NAT gateway to identify the source of increased usage.

NEW QUESTION 67

An ecommerce company is hosting a web application on Amazon EC2 instances to handle continuously changing customer demand. The EC2 instances are part of an Auto Scaling group. The company wants to implement a solution to distribute traffic from customers to the EC2 instances. The company must encrypt all traffic at all stages between the customers and the application servers. No decryption at intermediate points is allowed.

Which solution will meet these requirements?

- A. Create an Application Load Balancer (ALB). Add an HTTPS listener to the ALB
- B. Configure the Auto Scaling group to register instances with the ALB's target group.
- C. Create an Amazon CloudFront distribution
- D. Configure the distribution with a custom SSL/TLS certificate
- E. Set the Auto Scaling group as the distribution's origin.
- F. Create a Network Load Balancer (NLB). Add a TCP listener to the NLB
- G. Configure the Auto Scaling group to register instances with the NLB's target group.
- H. Create a Gateway Load Balancer (GLB). Configure the Auto Scaling group to register instances with the GLB's target group.

Answer: C

Explanation:

To distribute traffic from customers to EC2 instances in an Auto Scaling group and encrypt all traffic at all stages between the customers and the application servers without decryption at intermediate points, the company should create a Network Load Balancer (NLB) with a TCP listener and configure the Auto Scaling group to register instances with the NLB's target group (Option C). This solution allows for end-to-end encryption of traffic without decryption at intermediate points.

NEW QUESTION 70

.....

Relate Links

100% Pass Your ANS-C01 Exam with ExamBible Prep Materials

<https://www.exambible.com/ANS-C01-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>