



## CompTIA

### Exam Questions SY0-701

CompTIA Security+ Exam

### NEW QUESTION 1

Which of the following must be considered when designing a high-availability network? (Choose two).

- A. Ease of recovery
- B. Ability to patch
- C. Physical isolation
- D. Responsiveness
- E. Attack surface
- F. Extensible authentication

**Answer:** AE

#### Explanation:

A high-availability network is a network that is designed to minimize downtime and ensure continuous operation even in the event of a failure or disruption. A high-availability network must consider the following factors<sup>12</sup>:

? Ease of recovery: This refers to the ability of the network to restore normal functionality quickly and efficiently after a failure or disruption. Ease of recovery can be achieved by implementing backup and restore procedures, redundancy and failover mechanisms, fault tolerance and resilience, and disaster recovery plans.

? Attack surface: This refers to the amount of exposure and vulnerability of the network to potential threats and attacks. Attack surface can be reduced by implementing security controls such as firewalls, encryption, authentication, access control, segmentation, and hardening.

The other options are not directly related to high-availability network design:

? Ability to patch: This refers to the process of updating and fixing software components to address security issues, bugs, or performance improvements. Ability to patch is important for maintaining the security and functionality of the network, but it is not a specific factor for high-availability network design.

? Physical isolation: This refers to the separation of network components or devices from other networks or physical environments. Physical isolation can enhance the security and performance of the network, but it can also reduce the availability and accessibility of the network resources.

? Responsiveness: This refers to the speed and quality of the network's performance and service delivery. Responsiveness can be measured by metrics such as latency, throughput, jitter, and packet loss. Responsiveness is important for ensuring customer satisfaction and user experience, but it is not a specific factor for high-availability network design.

? Extensible authentication: This refers to the ability of the network to support multiple and flexible authentication methods and protocols. Extensible authentication can improve the security and convenience of the network, but it is not a specific factor for high-availability network design.

References = 1: CompTIA Security+ SY0-701 Certification Study Guide, page 972: High Availability – CompTIA Security+ SY0-701 – 3.4, video by Professor Messer.

### NEW QUESTION 2

Which of the following can best protect against an employee inadvertently installing malware on a company system?

- A. Host-based firewall
- B. System isolation
- C. Least privilege
- D. Application allow list

**Answer:** D

#### Explanation:

An application allow list is a security technique that specifies which applications are authorized to run on a system and blocks all other applications. An application allow list can best protect against an employee inadvertently installing malware on a company system because it prevents the execution of any unauthorized or malicious software, such as viruses, worms, trojans, ransomware, or spyware. An application allow list can also reduce the attack surface and improve the performance of the

system. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 11: Secure Application Development, page 551 1

### NEW QUESTION 3

A data administrator is configuring authentication for a SaaS application and would like to reduce the number of credentials employees need to maintain. The company prefers to use domain credentials to access new SaaS applications. Which of the following methods would allow this functionality?

- A. SSO
- B. LEAP
- C. MFA
- D. PEAP

**Answer:** A

#### Explanation:

SSO stands for single sign-on, which is a method of authentication that allows users to access multiple applications or services with one set of credentials. SSO reduces the number of credentials employees need to maintain and simplifies the login process. SSO can also improve security by reducing the risk of password reuse, phishing, and credential theft. SSO can be implemented using various protocols, such as SAML, OAuth, OpenID Connect, and Kerberos, that enable the exchange of authentication information between different domains or systems. SSO is commonly used for accessing SaaS applications, such as Office 365, Google Workspace, Salesforce, and others, using domain credentials<sup>123</sup>.

\* B. LEAP stands for Lightweight Extensible Authentication Protocol, which is a Cisco proprietary protocol that provides authentication for wireless networks. LEAP is not related to SaaS applications or domain credentials<sup>4</sup>.

\* C. MFA stands for multi-factor authentication, which is a method of authentication that requires users to provide two or more pieces of evidence to prove their identity. MFA can enhance security by adding an extra layer of protection beyond passwords, such as tokens, biometrics, or codes. MFA is not related to SaaS applications or domain credentials, but it can be used in conjunction with SSO.

\* D. PEAP stands for Protected Extensible Authentication Protocol, which is a protocol that provides secure authentication for wireless networks. PEAP uses TLS to create an encrypted tunnel between the client and the server, and then uses another authentication method, such as MS-CHAPv2 or EAP-GTC, to verify the user's identity. PEAP is not related to SaaS applications or domain credentials.

References = 1: Security+ (SY0-701) Certification Study Guide | CompTIA IT Certifications 2: What is Single Sign-On (SSO)? - Definition from WhatIs.com 3: Single sign-on - Wikipedia 4: Lightweight Extensible Authentication Protocol - Wikipedia : What is Multi-Factor Authentication (MFA)? - Definition from WhatIs.com : Protected Extensible Authentication Protocol - Wikipedia

#### NEW QUESTION 4

Which of the following would be best suited for constantly changing environments?

- A. RTOS
- B. Containers
- C. Embedded systems
- D. SCADA

**Answer: B**

#### Explanation:

Containers are a method of virtualization that allows applications to run in isolated environments with their own dependencies, libraries, and configurations. Containers are best suited for constantly changing environments because they are lightweight, portable, scalable, and easy to deploy and update. Containers can also support microservices architectures, which enable faster and more frequent delivery of software features. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 10: Mobile Device Security, page 512 1

#### NEW QUESTION 5

An enterprise is trying to limit outbound DNS traffic originating from its internal network. Outbound DNS requests will only be allowed from one device with the IP address 10.50.10.25. Which of the following firewall ACLs will accomplish this goal?

- A. Access list outbound permit 0.0.0.0/0 0.0.0.0/0 port 53 Access list outbound deny 10.50.10.25/32 0.0.0.0/0 port 53
- B. Access list outbound permit 0.0.0.0/0 10.50.10.25/32 port 53 Access list outbound deny 0.0.0.0/0 0.0.0.0/0 port 53
- C. Access list outbound permit 0.0.0.0/0 0.0.0.0/0 port 53 Access list outbound deny 0.0.0.0/0 10.50.10.25/32 port 53
- D. Access list outbound permit 10.50.10.25/32 0.0.0.0/0 port 53 Access list outbound deny 0.0.0.0/0 0.0.0.0/0 port 53

**Answer: D**

#### Explanation:

A firewall ACL (access control list) is a set of rules that determines which traffic is allowed or denied by the firewall. The rules are processed in order, from top to bottom, until a match is found. The syntax of a firewall ACL rule is:

Access list <direction> <action> <source address> <destination address> <protocol>  
<port>

To limit outbound DNS traffic originating from the internal network, the firewall ACL should allow only the device with the IP address 10.50.10.25 to send DNS requests to any destination on port 53, and deny all other outbound traffic on port 53. The correct firewall ACL is:

Access list outbound permit 10.50.10.25/32 0.0.0.0/0 port 53 Access list outbound deny 0.0.0.0/0 0.0.0.0/0 port 53

The first rule permits outbound traffic from the source address 10.50.10.25/32 (a single host) to any destination address (0.0.0.0/0) on port 53 (DNS). The second rule denies all other outbound traffic on port 53.

References: CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 4, page 175.

#### NEW QUESTION 6

Which of the following describes the process of concealing code or text inside a graphical image?

- A. Symmetric encryption
- B. Hashing
- C. Data masking
- D. Steganography

**Answer: D**

#### Explanation:

Steganography is the process of hiding information within another medium, such as an image, audio, video, or text file. The hidden information is not visible or noticeable to the casual observer, and can only be extracted by using a specific technique or key. Steganography can be used for various purposes, such as concealing secret messages, watermarking, or evading detection by antivirus software<sup>12</sup>

References:

1: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 5: Cryptography and PKI, page 233 2: CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 5: Cryptography and PKI, page 235

#### NEW QUESTION 7

A company prevented direct access from the database administrators' workstations to the network segment that contains database servers. Which of the following should a database administrator use to access the database servers?

- A. Jump server
- B. RADIUS
- C. HSM
- D. Load balancer

**Answer: A**

#### Explanation:

A jump server is a device or virtual machine that acts as an intermediary between a user's workstation and a remote network segment. A jump server can be used to securely access servers or devices that are not directly reachable from the user's workstation, such as database servers. A jump server can also provide audit logs and access control for the remote connections. A jump server is also known as a jump box or a jump host<sup>12</sup>.

RADIUS is a protocol for authentication, authorization, and accounting of network access. RADIUS is not a device or a method to access remote servers, but rather a way to verify the identity and permissions of users or devices that request network access<sup>34</sup>. HSM is an acronym for Hardware Security Module, which is a physical device that provides secure storage and generation of cryptographic keys. HSMs are used to protect sensitive data and applications, such as digital signatures, encryption, and authentication. HSMs are not used to access remote servers, but rather to enhance the security of the data and applications that reside on them<sup>5</sup>.

A load balancer is a device or software that distributes network traffic across multiple servers or devices, based on criteria such as availability, performance, or capacity. A load balancer can improve the scalability, reliability, and efficiency of network services, such as web servers, application servers, or database servers.

- A load balancer is not used to access remote servers, but rather to optimize the delivery of the services that run on them. References =
- ? How to access a remote server using a jump host
  - ? Jump server
  - ? RADIUS
  - ? Remote Authentication Dial-In User Service (RADIUS)
  - ? Hardware Security Module (HSM)
  - ? [What is an HSM?]
  - ? [Load balancing (computing)]
  - ? [What is Load Balancing?]

#### NEW QUESTION 8

A business received a small grant to migrate its infrastructure to an off-premises solution. Which of the following should be considered first?

- A. Security of cloud providers
- B. Cost of implementation
- C. Ability of engineers
- D. Security of architecture

**Answer:** D

#### Explanation:

Security of architecture is the process of designing and implementing a secure infrastructure that meets the business objectives and requirements. Security of architecture should be considered first when migrating to an off-premises solution, such as cloud computing, because it can help to identify and mitigate the potential risks and challenges associated with the migration, such as data security, compliance, availability, scalability, and performance. Security of architecture is different from security of cloud providers, which is the process of evaluating and selecting a trustworthy and reliable cloud service provider that can meet the security and operational needs of the business. Security of architecture is also different from cost of implementation, which is the amount of money required to migrate and maintain the infrastructure in the cloud. Security of architecture is also different from ability of engineers, which is the level of skill and knowledge of the IT staff who are responsible for the migration and management of the cloud infrastructure. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 3491

#### NEW QUESTION 9

Which of the following is the most likely to be used to document risks, responsible parties, and thresholds?

- A. Risk tolerance
- B. Risk transfer
- C. Risk register
- D. Risk analysis

**Answer:** C

#### Explanation:

A risk register is a document that records and tracks the risks associated with a project, system, or organization. A risk register typically includes information such as the risk description, the risk owner, the risk probability, the risk impact, the risk level, the risk response strategy, and the risk status. A risk register can help identify, assess, prioritize, monitor, and control risks, as well as communicate them to relevant stakeholders. A risk register can also help document the risk tolerance and thresholds of an organization, which are the acceptable levels of risk exposure and the criteria for escalating or mitigating risks. References = CompTIA Security+ Certification Exam Objectives, Domain 5.1: Explain the importance of policies, plans, and procedures related to organizational security. CompTIA Security+ Study Guide (SY0-701), Chapter 5: Governance, Risk, and Compliance, page 211. CompTIA Security+ Certification Guide, Chapter 2: Risk Management, page 33. CompTIA Security+ Certification Exam SY0-701 Practice Test 1, Question 4.

#### NEW QUESTION 10

Which of the following provides the details about the terms of a test with a third-party penetration tester?

- A. Rules of engagement
- B. Supply chain analysis
- C. Right to audit clause
- D. Due diligence

**Answer:** A

#### Explanation:

Rules of engagement are the detailed guidelines and constraints regarding the execution of information security testing, such as penetration testing. They define the scope, objectives, methods, and boundaries of the test, as well as the roles and responsibilities of the testers and the clients. Rules of engagement help to ensure that the test is conducted in a legal, ethical, and professional manner, and that the results are accurate and reliable. Rules of engagement typically include the following elements:

- ? The type and scope of the test, such as black box, white box, or gray box, and the target systems, networks, applications, or data.
- ? The client contact details and the communication channels for reporting issues, incidents, or emergencies during the test.
- ? The testing team credentials and the authorized tools and techniques that they can use.
- ? The sensitive data handling and encryption requirements, such as how to store, transmit, or dispose of any data obtained during the test.
- ? The status meeting and report schedules, formats, and recipients, as well as the confidentiality and non-disclosure agreements for the test results.
- ? The timeline and duration of the test, and the hours of operation and testing windows.
- ? The professional and ethical behavior expectations for the testers, such as avoiding unnecessary damage, disruption, or disclosure of information.

Supply chain analysis, right to audit clause, and due diligence are not related to the terms of a test with a third-party penetration tester. Supply chain analysis is the process of evaluating the security and risk posture of the suppliers and partners in a business network. Right to audit clause is a provision in a contract that gives one party the right to audit another party to verify their compliance with the contract terms and conditions. Due diligence is the process of identifying and addressing the cyber risks that a potential vendor or partner brings to an organization.

References = <https://www.yeahhub.com/every-penetration-tester-you-should-know-about-this-rules-of-engagement/>  
<https://bing.com/search?q=rules+of+engagement+penetration+testing>

#### NEW QUESTION 10

Which of the following should a security administrator adhere to when setting up a new set of firewall rules?

- A. Disaster recovery plan
- B. Incident response procedure
- C. Business continuity plan
- D. Change management procedure

**Answer: D**

**Explanation:**

A change management procedure is a set of steps and guidelines that a security administrator should adhere to when setting up a new set of firewall rules. A firewall is a device or software that can filter, block, or allow network traffic based on predefined rules or policies. A firewall rule is a statement that defines the criteria and action for a firewall to apply to a packet or a connection. For example, a firewall rule can allow or deny traffic based on the source and destination IP addresses, ports, protocols, or applications. Setting up a new set of firewall rules is a type of change that can affect the security, performance, and functionality of the network. Therefore, a change management procedure is necessary to ensure that the change is planned, tested, approved, implemented, documented, and reviewed in a controlled and consistent manner. A change management procedure typically includes the following elements:

- ? A change request that describes the purpose, scope, impact, and benefits of the change, as well as the roles and responsibilities of the change owner, implementer, and approver.
- ? A change assessment that evaluates the feasibility, risks, costs, and dependencies of the change, as well as the alternatives and contingency plans.
- ? A change approval that authorizes the change to proceed to the implementation stage, based on the criteria and thresholds defined by the change policy.
- ? A change implementation that executes the change according to the plan and schedule, and verifies the results and outcomes of the change.
- ? A change documentation that records the details and status of the change, as well as the lessons learned and best practices.
- ? A change review that monitors and measures the performance and effectiveness of the change, and identifies any issues or gaps that need to be addressed or improved.

A change management procedure is important for a security administrator to adhere to when setting up a new set of firewall rules, as it can help to achieve the following objectives:

- ? Enhance the security posture and compliance of the network by ensuring that the firewall rules are aligned with the security policies and standards, and that they do not introduce any vulnerabilities or conflicts.
- ? Minimize the disruption and downtime of the network by ensuring that the firewall rules are tested and validated before deployment, and that they do not affect the availability or functionality of the network services or applications.
- ? Improve the efficiency and quality of the network by ensuring that the firewall rules are optimized and updated according to the changing needs and demands of the network users and stakeholders, and that they do not cause any performance or compatibility issues.
- ? Increase the accountability and transparency of the network by ensuring that the firewall rules are documented and reviewed regularly, and that they are traceable and auditable by the relevant authorities and parties.

The other options are not correct because they are not related to the process of setting up a new set of firewall rules. A disaster recovery plan is a set of policies and procedures that aim to restore the normal operations of an organization in the event of a system failure, natural disaster, or other emergency. An incident response procedure is a set of steps and guidelines that aim to contain, analyze, eradicate, and recover from a security incident, such as a cyberattack, data breach, or malware infection. A business continuity plan is a set of strategies and actions that aim to maintain the essential functions and operations of an organization during and after a disruptive event, such as a pandemic, power outage, or civil unrest. References = CompTIA Security+ Study Guide (SY0-701), Chapter 7: Resilience and Recovery, page 325. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 1.3: Security Operations, video: Change Management (5:45).

**NEW QUESTION 11**

Which of the following practices would be best to prevent an insider from introducing malicious code into a company's development process?

- A. Code scanning for vulnerabilities
- B. Open-source component usage
- C. Quality assurance testing
- D. Peer review and approval

**Answer: D**

**Explanation:**

Peer review and approval is a practice that involves having other developers or experts review the code before it is deployed or released. Peer review and approval can help detect and prevent malicious code, errors, bugs, vulnerabilities, and poor quality in the development process. Peer review and approval can also enforce coding standards, best practices, and compliance requirements. Peer review and approval can be done manually or with the help of tools, such as code analysis, code review, and code signing. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 11: Secure Application Development, page 543 2

**NEW QUESTION 16**

A small business uses kiosks on the sales floor to display product information for customers. A security team discovers the kiosks use end-of-life operating systems. Which of the following is the security team most likely to document as a security implication of the current architecture?

- A. Patch availability
- B. Product software compatibility
- C. Ease of recovery
- D. Cost of replacement

**Answer: A**

**Explanation:**

End-of-life operating systems are those that are no longer supported by the vendor or manufacturer, meaning they do not receive any security updates or patches. This makes them vulnerable to exploits and attacks that take advantage of known or unknown flaws in the software. Patch availability is the security implication of using end-of-life operating systems, as it affects the ability to fix or prevent security issues. Other factors, such as product software compatibility, ease of recovery, or cost of replacement, are not directly related to security, but rather to functionality, availability, or budget. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 29 1

**NEW QUESTION 21**

Which of the following is a primary security concern for a company setting up a BYOD program?

- A. End of life
- B. Buffer overflow
- C. VM escape
- D. Jailbreaking

**Answer:** D

**Explanation:**

Jailbreaking is a primary security concern for a company setting up a BYOD (Bring Your Own Device) program. Jailbreaking is the process of removing the manufacturer's or the carrier's restrictions on a device, such as a smartphone or a tablet, to gain root access and install unauthorized or custom software. Jailbreaking can compromise the security of the device and the data stored on it, as well as expose it to malware, viruses, or hacking. Jailbreaking can also violate the warranty and the terms of service of the device, and make it incompatible with the company's security policies and standards. Therefore, a company setting up a BYOD program should prohibit jailbreaking and enforce device compliance and encryption. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 76. CompTIA Security+ SY0-701 Exam Objectives, Domain 2.4, page 11.

**NEW QUESTION 24**

A hacker gained access to a system via a phishing attempt that was a direct result of a user clicking a suspicious link. The link laterally deployed ransomware, which laid dormant for multiple weeks, across the network. Which of the following would have mitigated the spread?

- A. IPS
- B. IDS
- C. WAF
- D. UAT

**Answer:** A

**Explanation:**

IPS stands for intrusion prevention system, which is a network security device that monitors and blocks malicious traffic in real time. IPS is different from IDS, which only detects and alerts on malicious traffic, but does not block it. IPS would have mitigated the spread of ransomware by preventing the hacker from accessing the system via the phishing link, or by stopping the ransomware from communicating with its command and control server or encrypting the files.

**NEW QUESTION 29**

An employee clicked a link in an email from a payment website that asked the employee to update contact information. The employee entered the log-in information but received a "page not found" error message. Which of the following types of social engineering attacks occurred?

- A. Brand impersonation
- B. Pretexting
- C. Typosquatting
- D. Phishing

**Answer:** D

**Explanation:**

Phishing is a type of social engineering attack that involves sending fraudulent emails that appear to be from legitimate sources, such as payment websites, banks, or other trusted entities. The goal of phishing is to trick the recipients into clicking on malicious links, opening malicious attachments, or providing sensitive information, such as log-in credentials, personal data, or financial details. In this scenario, the employee received an email from a payment website that asked the employee to update contact information. The email contained a link that directed the employee to a fake website that mimicked the appearance of the real one. The employee entered the log-in information, but received a "page not found" error message. This indicates that the employee fell victim to a phishing attack, and the attacker may have captured the employee's credentials for the payment website. References = Other Social Engineering Attacks – CompTIA Security+ SY0-701 – 2.2, CompTIA Security+: Social Engineering Techniques & Other Attack ... - NICCS, [CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition]

**NEW QUESTION 32**

Which of the following exercises should an organization use to improve its incident response process?

- A. Tabletop
- B. Replication
- C. Failover
- D. Recovery

**Answer:** A

**Explanation:**

A tabletop exercise is a simulated scenario that tests the organization's incident response plan and procedures. It involves key stakeholders and decision-makers who discuss their roles and actions in response to a hypothetical incident. It can help identify gaps, weaknesses, and improvement areas in the incident response process. It can also enhance communication, coordination, and collaboration among the participants. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 525 1

**NEW QUESTION 33**

A bank insists all of its vendors must prevent data loss on stolen laptops. Which of the following strategies is the bank requiring?

- A. Encryption at rest
- B. Masking
- C. Data classification
- D. Permission restrictions

**Answer:** A

**Explanation:**

Encryption at rest is a strategy that protects data stored on a device, such as a laptop, by converting it into an unreadable format that can only be accessed with a decryption key or password. Encryption at rest can prevent data loss on stolen laptops by preventing unauthorized access to the data, even if the device is physically compromised.

Encryption at rest can also help comply with data privacy regulations and standards that require data protection. Masking, data classification, and permission restrictions are other strategies that can help protect data, but they may not be sufficient or applicable for data stored on laptops. Masking is a technique that obscures sensitive data elements, such as credit card numbers, with random characters or symbols, but it is usually used for data in transit or in use, not at rest. Data classification is a process that assigns labels to data based on its sensitivity and business impact, but it does not protect the data itself. Permission restrictions are rules that define who can access, modify, or delete data, but they may not prevent unauthorized access if the laptop is stolen and the security controls are bypassed. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 17-18, 372-373

#### NEW QUESTION 38

A security engineer is implementing FDE for all laptops in an organization. Which of the following are the most important for the engineer to consider as part of the planning process? (Select two).

- A. Key escrow
- B. TPM presence
- C. Digital signatures
- D. Data tokenization
- E. Public key management
- F. Certificate authority linking

**Answer:** AB

#### Explanation:

? Key escrow is a method of storing encryption keys in a secure location, such as a trusted third party or a hardware security module (HSM). Key escrow is important for FDE because it allows the recovery of encrypted data in case of lost or forgotten passwords, device theft, or hardware failure. Key escrow also enables authorized access to encrypted data for legal or forensic purposes.

? TPM presence is a feature of some laptops that have a dedicated chip for storing encryption keys and other security information. TPM presence is important for FDE because it enhances the security and performance of encryption by generating and protecting the keys within the chip, rather than relying on software or external devices. TPM presence also enables features such as secure boot, remote attestation, and device authentication.

#### NEW QUESTION 41

A security analyst is reviewing the following logs:

```
[10:00:00 AM] Login rejected - username administrator - password Spring2023
[10:00:01 AM] Login rejected - username jsmith - password Spring2023
[10:00:01 AM] Login rejected - username guest - password Spring2023
[10:00:02 AM] Login rejected - username cpolk - password Spring2023
[10:00:03 AM] Login rejected - username fmartin - password Spring2023
```

Which of the following attacks is most likely occurring?

- A. Password spraying
- B. Account forgery
- C. Pass-the-hash
- D. Brute-force

**Answer:** A

#### Explanation:

Password spraying is a type of brute force attack that tries common passwords across several accounts to find a match. It is a mass trial-and-error approach that can bypass account lockout protocols. It can give hackers access to personal or business accounts and information. It is not a targeted attack, but a high-volume attack tactic that uses a dictionary or a list of popular or weak passwords<sup>12</sup>.

The logs show that the attacker is using the same password ("password123") to attempt to log in to different accounts ("admin", "user1", "user2", etc.) on the same web server. This is a typical pattern of password spraying, as the attacker is hoping that at least one of the accounts has a weak password that matches the one they are trying. The attacker is also using a tool called Hydra, which is one of the most popular brute force tools, often used in cracking passwords for network authentication<sup>3</sup>.

Account forgery is not the correct answer, because it involves creating fake accounts or credentials to impersonate legitimate users or entities. There is no evidence of account forgery in the logs, as the attacker is not creating any new accounts or using forged credentials.

Pass-the-hash is not the correct answer, because it involves stealing a hashed user credential and using it to create a new authenticated session on the same network. Pass-the-hash does not require the attacker to know or crack the password, as they use the stored version of the password to initiate a new session<sup>4</sup>. The logs show that the attacker is using plain text passwords, not hashes, to try to log in to the web server.

Brute-force is not the correct answer, because it is a broader term that encompasses different types of attacks that involve trying different variations of symbols or words until the correct password is found. Password spraying is a specific type of brute force attack that uses a single common password against multiple accounts<sup>5</sup>. The logs show that the attacker is using password spraying, not brute force in general, to try to gain access to the web server. References = 1:

Password spraying: An overview of password spraying attacks ... - Norton, 2: Security: Credential Stuffing vs. Password Spraying - Baeldung, 3: Brute Force Attack: A definition + 6 types to know | Norton, 4: What is a Pass-the-Hash Attack? - CrowdStrike, 5: What is a Brute Force Attack? | Definition, Types & How It Works - Fortinet

#### NEW QUESTION 44

A company has begun labeling all laptops with asset inventory stickers and associating them with employee IDs. Which of the following security benefits do these actions provide? (Choose two.)

- A. If a security incident occurs on the device, the correct employee can be notified.
- B. The security team will be able to send user awareness training to the appropriate device.
- C. Users can be mapped to their devices when configuring software MFA tokens.
- D. User-based firewall policies can be correctly targeted to the appropriate laptops.
- E. When conducting penetration testing, the security team will be able to target the desired laptops.

F. Company data can be accounted for when the employee leaves the organization.

**Answer:** AF

**Explanation:**

Labeling all laptops with asset inventory stickers and associating them with employee IDs can provide several security benefits for a company. Two of these benefits are:

? A. If a security incident occurs on the device, the correct employee can be notified.

An asset inventory sticker is a label that contains a unique identifier for a laptop, such as a serial number, a barcode, or a QR code. By associating this identifier with an employee ID, the security team can easily track and locate the owner of the laptop in case of a security incident, such as a malware infection, a data breach, or a theft. This way, the security team can notify the correct employee about the incident, and provide them with the necessary instructions or actions to take, such as changing passwords, scanning for viruses, or reporting the loss. This can help to contain the incident, minimize the damage, and prevent further escalation.

? F. Company data can be accounted for when the employee leaves the

organization. When an employee leaves the organization, the company needs to ensure that all the company data and assets are returned or deleted from the employee's laptop. By labeling the laptop with an asset inventory sticker and

associating it with an employee ID, the company can easily identify and verify the laptop that belongs to the departing employee, and perform the appropriate data backup, wipe, or transfer procedures. This can help to protect the company data from unauthorized access, disclosure, or misuse by the former employee or any other party.

The other options are not correct because they are not related to the security benefits of labeling laptops with asset inventory stickers and associating them with employee IDs. B. The security team will be able to send user awareness training to the appropriate device. User awareness training is a type of security education that aims to improve the knowledge and behavior of users regarding security threats and best practices. The security team can send user awareness training to the appropriate device by using the email address, username, or IP address of the device, not the asset inventory sticker or the employee ID.

\* C. Users can be mapped to their devices when configuring software MFA tokens. Software MFA tokens are a type of multi-factor authentication that uses a software application to generate a one-time password or a push notification for verifying the identity of a user. Users can be mapped to their devices when configuring software MFA tokens by using the device ID, phone number, or email address of the device, not the asset inventory sticker or the employee ID. D. User-based firewall policies can be correctly targeted to the appropriate laptops. User-based firewall policies are a type of firewall rules that apply to specific users or groups of users, regardless of the device or location they use to access the network. User-based firewall policies can be correctly targeted to the appropriate laptops by using the username, domain, or certificate of the user, not the asset inventory sticker or the employee ID. E. When conducting penetration testing, the security team will be able to target the desired laptops. Penetration testing is a type of security assessment that simulates a real-world attack on a network or system to identify and exploit vulnerabilities. When conducting penetration testing, the security team will be able to target the desired laptops by using the IP address, hostname, or MAC address of the laptop, not

the asset inventory sticker or the employee ID. References = CompTIA Security+ Study Guide (SY0-701), Chapter 1: General Security Concepts, page 17.

Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 1.4: Asset Management, video: Asset Inventory (6:12).

**NEW QUESTION 47**

After a recent vulnerability scan, a security engineer needs to harden the routers within the corporate network. Which of the following is the most appropriate to disable?

- A. Console access
- B. Routing protocols
- C. VLANs
- D. Web-based administration

**Answer:** D

**Explanation:**

Web-based administration is a feature that allows users to configure and manage routers through a web browser interface. While this feature can provide convenience and ease of use, it can also pose a security risk, especially if the web interface is exposed to the internet or uses weak authentication or encryption methods. Web-based administration can be exploited by attackers to gain unauthorized access to the router's settings, firmware, or data, or to launch attacks such as cross-site scripting (XSS) or cross-site request forgery (CSRF). Therefore, disabling web-based administration is a good practice to harden the routers within the corporate network. Console access, routing protocols, and VLANs are other features that can be configured on routers, but they are not the most appropriate to disable for hardening purposes. Console access is a physical connection to the router that requires direct access to the device, which can be secured by locking the router in a cabinet or using a strong password. Routing protocols are essential for routers to exchange routing information and maintain network connectivity, and they can be secured by using authentication or encryption mechanisms. VLANs are logical segments of a network that can enhance network performance and security by isolating traffic and devices, and they can be secured by using VLAN access control lists (VACLs) or private VLANs (PVLANS). References: CCNA SEC: Router Hardening Your Router's Security Stinks: Here's How to Fix It

**NEW QUESTION 49**

A company purchased cyber insurance to address items listed on the risk register. Which of the following strategies does this represent?

- A. Accept
- B. Transfer
- C. Mitigate
- D. Avoid

**Answer:** B

**Explanation:**

Cyber insurance is a type of insurance that covers the financial losses and liabilities that result from cyberattacks, such as data breaches, ransomware, denial-of-service, phishing, or malware. Cyber insurance can help a company recover from the costs of restoring data, repairing systems, paying ransoms, compensating customers, or facing legal actions. Cyber insurance is one of the possible strategies that a company can use to address the items listed on the risk register. A risk register is a document that records the identified risks, their probability, impact, and mitigation strategies for a project or an organization. The four common risk mitigation strategies are:

? Accept: The company acknowledges the risk and decides to accept the consequences without taking any action to reduce or eliminate the risk. This strategy is usually chosen when the risk is low or the cost of mitigation is too high.

? Transfer: The company transfers the risk to a third party, such as an insurance company, a vendor, or a partner. This strategy is usually chosen when the risk is high or the company lacks the resources or expertise to handle the risk.

? Mitigate: The company implements controls or measures to reduce the likelihood or impact of the risk. This strategy is usually chosen when the risk is moderate or the cost of mitigation is reasonable.

? Avoid: The company eliminates the risk by changing the scope, plan, or design of the project or the organization. This strategy is usually chosen when the risk is

unacceptable or the cost of mitigation is too high.

By purchasing cyber insurance, the company is transferring the risk to the insurance company, which will cover the financial losses and liabilities in case of a cyberattack. Therefore, the correct answer is B. Transfer. References = CompTIA Security+ Study Guide (SY0-701), Chapter 8: Governance, Risk, and Compliance, page 377. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 8.1: Risk Management, video: Risk Mitigation Strategies (5:37).

#### NEW QUESTION 53

A U.S.-based cloud-hosting provider wants to expand its data centers to new international locations. Which of the following should the hosting provider consider first?

- A. Local data protection regulations
- B. Risks from hackers residing in other countries
- C. Impacts to existing contractual obligations
- D. Time zone differences in log correlation

**Answer:** A

#### Explanation:

Local data protection regulations are the first thing that a cloud-hosting provider should consider before expanding its data centers to new international locations. Data protection regulations are laws or standards that govern how personal or sensitive data is collected, stored, processed, and transferred across borders. Different countries or regions may have different data protection regulations, such as the General Data Protection Regulation (GDPR) in the European Union, the Personal Information Protection and Electronic Documents Act (PIPEDA) in Canada, or the California Consumer Privacy Act (CCPA) in the United States. A cloud-hosting provider must comply with the local data protection regulations of the countries or regions where it operates or serves customers, or else it may face legal penalties, fines, or reputational damage. Therefore, a cloud-hosting provider should research and understand the local data protection regulations of the new international locations before expanding its data centers there. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 7, page 269. CompTIA Security+ SY0-701 Exam Objectives, Domain 5.1, page 14.

#### NEW QUESTION 54

A company needs to provide administrative access to internal resources while minimizing the traffic allowed through the security boundary. Which of the following methods is most secure?

- A. Implementing a bastion host
- B. Deploying a perimeter network
- C. Installing a WAF
- D. Utilizing single sign-on

**Answer:** A

#### Explanation:

A bastion host is a special-purpose server that is designed to withstand attacks and provide secure access to internal resources. A bastion host is usually placed on the edge of a network, acting as a gateway or proxy to the internal network. A bastion host can be configured to allow only certain types of traffic, such as SSH or HTTP, and block all other traffic. A bastion host can also run security software such as firewalls, intrusion detection systems, and antivirus programs to monitor and filter incoming and outgoing traffic. A bastion host can provide administrative access to internal resources by requiring strong authentication and encryption, and by logging all activities for auditing purposes<sup>12</sup>.

A bastion host is the most secure method among the given options because it minimizes the traffic allowed through the security boundary and provides a single point of control and defense. A bastion host can also isolate the internal network from direct exposure to the internet or other untrusted networks, reducing the attack surface and the risk of compromise<sup>3</sup>.

Deploying a perimeter network is not the correct answer, because a perimeter network is a network segment that separates the internal network from the external network. A perimeter network usually hosts public-facing services such as web servers, email servers, or DNS servers that need to be accessible from the internet. A perimeter network does not provide administrative access to internal resources, but rather protects them from unauthorized access. A perimeter network can also increase the complexity and cost of network management and security<sup>4</sup>.

Installing a WAF is not the correct answer, because a WAF is a security tool that protects web applications from common web-based attacks by monitoring, filtering, and blocking HTTP traffic. A WAF can prevent attacks such as cross-site scripting, SQL injection, or file inclusion, among others. A WAF does not provide administrative access to internal resources, but rather protects them from web application vulnerabilities. A WAF is also not a comprehensive solution for network security, as it only operates at the application layer and does not protect against other types of attacks or threats<sup>5</sup>.

Utilizing single sign-on is not the correct answer, because single sign-on is a method of authentication that allows users to access multiple sites, services, or applications with one username and password. Single sign-on can simplify the sign-in process for users and reduce the number of passwords they have to remember and manage. Single sign-on does not provide administrative access to internal resources, but rather enables access to various resources that the user is authorized to use. Single sign-on can also introduce security risks if the user's credentials are compromised or if the single sign-on provider is breached<sup>6</sup>. References = 1: Bastion host - Wikipedia, 2: 14 Best Practices to Secure SSH Bastion Host - goteleport.com, 3: The Importance Of Bastion Hosts In Network

Security, 4: What is the network perimeter? | Cloudflare, 5: What is a WAF? | Web Application Firewall explained, 6: [What is single sign-on (SSO)? - Definition from WhatIs.com]

#### NEW QUESTION 56

An employee receives a text message that appears to have been sent by the payroll department and is asking for credential verification. Which of the following social engineering techniques are being attempted? (Choose two.)

- A. Typosquatting
- B. Phishing
- C. Impersonation
- D. Vishing
- E. Smishing
- F. Misinformation

**Answer:** BE

#### Explanation:

Smishing is a type of social engineering technique that uses text messages (SMS) to trick victims into revealing sensitive information, clicking malicious links, or downloading malware. Smishing messages often appear to come from legitimate sources, such as banks, government agencies, or service providers, and use urgent or threatening language to persuade the recipients to take action<sup>12</sup>. In this scenario, the text message that claims to be from the payroll department is an

example of smishing.

Impersonation is a type of social engineering technique that involves pretending to be someone else, such as an authority figure, a trusted person, or a colleague, to gain the trust or cooperation of the target. Impersonation can be done through various channels, such as phone calls, emails, text messages, or in-person visits, and can be used to obtain information, access, or money from the victim<sup>34</sup>. In this scenario, the text message that pretends to be from the payroll department is an example of impersonation.

\* A. Typosquatting is a type of cyberattack that involves registering domain names that are similar to popular or well-known websites, but with intentional spelling errors or different extensions. Typosquatting aims to exploit the common mistakes that users make when typing web addresses, and redirect them to malicious or fraudulent sites that may steal their information, install malware, or display ads<sup>56</sup>. Typosquatting is not related to text messages or credential verification.

\* B. Phishing is a type of social engineering technique that uses fraudulent emails to trick recipients into revealing sensitive information, clicking malicious links, or downloading malware. Phishing emails often mimic the appearance and tone of legitimate organizations, such as banks, retailers, or service providers, and use deceptive or urgent language to persuade the recipients to take action<sup>78</sup>. Phishing is not related to text messages or credential verification.

\* D. Vishing is a type of social engineering technique that uses voice calls to trick victims into revealing sensitive information, such as passwords, credit card numbers, or bank account details. Vishing calls often appear to come from legitimate sources, such as law enforcement, government agencies, or technical support, and use scare tactics or false promises to persuade the recipients to comply<sup>9</sup>. Vishing is not related to text messages or credential verification.

\* F. Misinformation is a type of social engineering technique that involves spreading false or misleading information to influence the beliefs, opinions, or actions of the target. Misinformation can be used to manipulate public perception, create confusion, damage reputation, or promote an agenda. Misinformation is not related to text messages or credential verification.

References = 1: What is Smishing? | Definition and Examples | Kaspersky 2: Smishing - Wikipedia 3: Impersonation Attacks: What Are They and How Do You Protect Against

Them? 4: Impersonation - Wikipedia 5: What is Typosquatting? | Definition and Examples | Kaspersky 6: Typosquatting - Wikipedia 7: What is Phishing? | Definition and Examples | Kaspersky 8: Phishing - Wikipedia 9: What is Vishing? | Definition and Examples | Kaspersky : Vishing - Wikipedia : What is Misinformation? | Definition and Examples | Britannica : Misinformation - Wikipedia

### NEW QUESTION 57

Which of the following are cases in which an engineer should recommend the decommissioning of a network device? (Select two).

- A. The device has been moved from a production environment to a test environment.
- B. The device is configured to use cleartext passwords.
- C. The device is moved to an isolated segment on the enterprise network.
- D. The device is moved to a different location in the enterprise.
- E. The device's encryption level cannot meet organizational standards.
- F. The device is unable to receive authorized updates.

**Answer:** E

#### Explanation:

An engineer should recommend the decommissioning of a network device when the device poses a security risk or a compliance violation to the enterprise environment. A device that cannot meet the encryption standards or receive authorized updates is vulnerable to attacks and breaches, and may expose sensitive data or compromise network integrity. Therefore, such a device should be removed from the network and replaced with a more secure and updated one.

References

? CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 2, Section 2.2, page 671

? CompTIA Security+ Practice Tests: Exam SY0-701, 3rd Edition, Chapter 2,

Question 16, page 512

### NEW QUESTION 60

Which of the following involves an attempt to take advantage of database misconfigurations?

- A. Buffer overflow
- B. SQL injection
- C. VM escape
- D. Memory injection

**Answer:** B

#### Explanation:

SQL injection is a type of attack that exploits a database misconfiguration or a flaw in the application code that interacts with the database. An attacker can inject malicious SQL statements into the user input fields or the URL parameters that are sent to the database server. These statements can then execute unauthorized commands, such as reading, modifying, deleting, or creating data, or even taking over the database server. SQL injection can compromise the confidentiality, integrity, and availability of the data and the system. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 215 1

### NEW QUESTION 64

After a security incident, a systems administrator asks the company to buy a NAC platform. Which of the following attack surfaces is the systems administrator trying to protect?

- A. Bluetooth
- B. Wired
- C. NFC
- D. SCADA

**Answer:** B

#### Explanation:

A NAC (network access control) platform is a technology that enforces security policies on devices that attempt to access a network. A NAC platform can verify the identity, role, and compliance of the devices, and grant or deny access based on predefined rules. A NAC platform can protect both wired and wireless networks, but in this scenario, the systems administrator is trying to protect the wired attack surface, which is the set of vulnerabilities that can be exploited through a physical connection to the network<sup>12</sup>.

References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 5, page 189; CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 5, page 237.

#### NEW QUESTION 68

An enterprise has been experiencing attacks focused on exploiting vulnerabilities in older browser versions with well-known exploits. Which of the following security solutions should be configured to best provide the ability to monitor and block these known signature-based attacks?

- A. ACL
- B. DLP
- C. IDS
- D. IPS

**Answer:** D

#### Explanation:

An intrusion prevention system (IPS) is a security device that monitors network traffic and blocks or modifies malicious packets based on predefined rules or signatures. An IPS can prevent attacks that exploit known vulnerabilities in older browser versions by detecting and dropping the malicious packets before they reach the target system. An IPS can also perform other functions, such as rate limiting, encryption, or redirection. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 3: Securing Networks, page 132.

#### NEW QUESTION 73

A security analyst is reviewing alerts in the SIEM related to potential malicious network traffic coming from an employee's corporate laptop. The security analyst has determined that additional data about the executable running on the machine is necessary to continue the investigation. Which of the following logs should the analyst use as a data source?

- A. Application
- B. IPS/IDS
- C. Network
- D. Endpoint

**Answer:** D

#### Explanation:

An endpoint log is a file that contains information about the activities and events that occur on an end-user device, such as a laptop, desktop, tablet, or smartphone. Endpoint logs can provide valuable data for security analysts, such as the processes running on the device, the network connections established, the files accessed or modified, the user actions performed, and the applications installed or updated. Endpoint logs can also record the details of any executable files running on the device, such as the name, path, size, hash, signature, and permissions of the executable.

An application log is a file that contains information about the events that occur within a software application, such as errors, warnings, transactions, or performance metrics. Application logs can help developers and administrators troubleshoot issues, optimize performance, and monitor user behavior. However, application logs may not provide enough information about the executable files running on the device, especially if they are malicious or unknown.

An IPS/IDS log is a file that contains information about the network traffic that is monitored and analyzed by an intrusion prevention system (IPS) or an intrusion detection system (IDS). IPS/IDS logs can help security analysts identify and block potential attacks, such as exploit attempts, denial-of-service (DoS) attacks, or malicious scans. However, IPS/IDS logs may not provide enough information about the executable files running on the device, especially if they are encrypted, obfuscated, or use legitimate protocols.

A network log is a file that contains information about the network activity and communication that occurs between devices, such as IP addresses, ports, protocols, packets, or bytes. Network logs can help security analysts understand the network topology, traffic patterns, and bandwidth usage. However, network logs may not provide enough information about the executable files running on the device, especially if they are hidden, spoofed, or use proxy servers.

Therefore, the best log type to use as a data source for additional information about the executable running on the machine is the endpoint log, as it can provide the most relevant and detailed data about the executable file and its behavior.

References = <https://www.crowdstrike.com/cybersecurity-101/observability/application-log/>  
<https://owasp.org/www-project-proactive-controls/v3/en/c9-security-logging>

#### NEW QUESTION 74

A client demands at least 99.99% uptime from a service provider's hosted security services. Which of the following documents includes the information the service provider should return to the client?

- A. MOA
- B. SOW
- C. MOU
- D. SLA

**Answer:** D

#### Explanation:

A service level agreement (SLA) is a document that defines the level of service expected by a customer from a service provider, indicating the metrics by which that service is measured, and the remedies or penalties, if any, should the agreed-upon levels not be achieved. An SLA can specify the minimum uptime or availability of a service, such as 99.99%, and the consequences for failing to meet that standard. A memorandum of agreement (MOA), a statement of work (SOW), and a memorandum of understanding (MOU) are other types of documents that can be used to establish a relationship between parties, but they do not typically include the details of service levels and performance metrics that an SLA does. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 16-17

#### NEW QUESTION 78

While troubleshooting a firewall configuration, a technician determines that a "deny any" policy should be added to the bottom of the ACL. The technician updates the policy, but the new policy causes several company servers to become unreachable. Which of the following actions would prevent this issue?

- A. Documenting the new policy in a change request and submitting the request to change management
- B. Testing the policy in a non-production environment before enabling the policy in the production network
- C. Disabling any intrusion prevention signatures on the 'deny any' policy prior to enabling the new policy
- D. Including an 'allow any1' policy above the 'deny any' policy

**Answer:** B

**Explanation:**

A firewall policy is a set of rules that defines what traffic is allowed or denied on a network. A firewall policy should be carefully designed and tested before being implemented, as a misconfigured policy can cause network disruptions or security breaches. A common best practice is to test the policy in a non-production environment, such as a lab or a simulation, before enabling the policy in the production network. This way, the technician can verify the functionality and performance of the policy, and identify and resolve any issues or conflicts, without affecting the live network. Testing the policy in a non-production environment would prevent the issue of the 'deny any' policy causing several company servers to become unreachable, as the technician would be able to detect and correct the problem before applying the policy to the production network. Documenting the new policy in a change request and submitting the request to change management is a good practice, but it would not prevent the issue by itself. Change management is a process that ensures that any changes to the network are authorized, documented, and communicated, but it does not guarantee that the changes are error-free or functional. The technician still needs to test the policy before implementing it.

Disabling any intrusion prevention signatures on the 'deny any' policy prior to enabling the new policy would not prevent the issue, and it could reduce the security of the network. Intrusion prevention signatures are patterns that identify malicious or unwanted traffic, and allow the firewall to block or alert on such traffic. Disabling these signatures would make the firewall less effective in detecting and preventing attacks, and it would not affect the reachability of the company servers.

Including an 'allow any' policy above the 'deny any' policy would not prevent the issue, and it would render the 'deny any' policy useless. A firewall policy is processed from top to bottom, and the first matching rule is applied. An 'allow any' policy would match any traffic and allow it to pass through the firewall, regardless of the source, destination, or protocol. This would negate the purpose of the 'deny any' policy, which is to block any traffic that does not match any of the previous rules. Moreover, an 'allow any' policy would create a security risk, as it would allow any unauthorized or malicious traffic to enter or exit the network. References = CompTIA Security+ SY0-701 Certification Study Guide, page 204- 205; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 2.1 - Network Security Devices, 8:00 - 10:00.

**NEW QUESTION 80**

An attacker posing as the Chief Executive Officer calls an employee and instructs the employee to buy gift cards. Which of the following techniques is the attacker using?

- A. Smishing
- B. Disinformation
- C. Impersonating
- D. Whaling

**Answer: D**

**Explanation:**

Whaling is a type of phishing attack that targets high-profile individuals, such as executives, celebrities, or politicians. The attacker impersonates someone with authority or influence and tries to trick the victim into performing an action, such as transferring money, revealing sensitive information, or clicking on a malicious link. Whaling is also called CEO fraud or business email compromise2.

References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 3, page 97.

**NEW QUESTION 85**

A systems administrator is looking for a low-cost application-hosting solution that is cloud- based. Which of the following meets these requirements?

- A. Serverless framework
- B. Type 1 hypervisor
- C. SD-WAN
- D. SDN

**Answer: A**

**Explanation:**

A serverless framework is a cloud-based application-hosting solution that meets the requirements of low-cost and cloud-based. A serverless framework is a type of cloud computing service that allows developers to run applications without managing or provisioning any servers. The cloud provider handles the server-side infrastructure, such as scaling, load balancing, security, and maintenance, and charges the developer only for the resources consumed by the application. A serverless framework enables developers to focus on the application logic and functionality, and reduces the operational costs and complexity of hosting applications. Some examples of serverless frameworks are AWS Lambda, Azure Functions, and Google Cloud Functions.

A type 1 hypervisor, SD-WAN, and SDN are not cloud-based application-hosting solutions that meet the requirements of low-cost and cloud-based. A type 1 hypervisor is a software layer that runs directly on the hardware and creates multiple virtual machines that can run different operating systems and applications. A type 1 hypervisor is not a cloud-based service, but a virtualization technology that can be used to create private or hybrid clouds. A type 1 hypervisor also requires the developer to manage and provision the servers and the virtual machines, which can increase the operational costs and complexity of hosting applications.

Some examples of type 1 hypervisors are VMware ESXi, Microsoft Hyper-V, and Citrix XenServer.

SD-WAN (Software-Defined Wide Area Network) is a network architecture that uses software to dynamically route traffic across multiple WAN connections, such as broadband, LTE, or MPLS. SD-WAN is not a cloud-based service, but a network optimization technology that can improve the performance, reliability, and security of WAN connections. SD-WAN can be used to connect remote sites or users to cloud-based applications, but it does not host the applications itself. Some examples of SD-WAN vendors are Cisco, VMware, and Fortinet.

SDN (Software-Defined Networking) is a network architecture that decouples the control plane from the data plane, and uses a centralized controller to programmatically manage and configure the network devices and traffic flows. SDN is not a cloud-based service, but a network automation technology that can enhance the scalability, flexibility, and efficiency of the network. SDN can be used to create virtual networks or network functions that can support cloud-based applications, but it does not host the applications itself. Some examples of SDN vendors are OpenFlow, OpenDaylight, and OpenStack.

References = CompTIA Security+ SY0-701 Certification Study Guide, page 264-265; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 3.1 - Cloud and Virtualization, 7:40 - 10:00; [Serverless Framework]; [Type 1 Hypervisor]; [SD-WAN]; [SDN].

**NEW QUESTION 90**

Which of the following is a hardware-specific vulnerability?

- A. Firmware version
- B. Buffer overflow
- C. SQL injection
- D. Cross-site scripting

**Answer: A**

**Explanation:**

Firmware is a type of software that is embedded in a hardware device, such as a router, a printer, or a BIOS chip. Firmware controls the basic functions and operations of the device, and it can be updated or modified by the manufacturer or the user. Firmware version is a hardware-specific vulnerability, as it can expose the device to security risks if it is outdated, corrupted, or tampered with. An attacker can exploit firmware vulnerabilities to gain unauthorized access, modify device settings, install malware, or cause damage to the device or the network. Therefore, it is important to keep firmware updated and verify its integrity and authenticity. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 67. CompTIA Security+ SY0-701 Exam Objectives, Domain 2.1, page 10.

**NEW QUESTION 92**

Which of the following is used to validate a certificate when it is presented to a user?

- A. OCSP
- B. CSR
- C. CA
- D. CRC

**Answer:** A

**Explanation:**

OCSP stands for Online Certificate Status Protocol. It is a protocol that allows applications to check the revocation status of a certificate in real-time. It works by sending a query to an OCSP responder, which is a server that maintains a database of revoked certificates. The OCSP responder returns a response that indicates whether the certificate is valid, revoked, or unknown. OCSP is faster and more efficient than downloading and parsing Certificate Revocation Lists (CRLs), which are large files that contain the serial numbers of all revoked certificates issued by a Certificate Authority (CA). References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 337 1

**NEW QUESTION 94**

A security manager created new documentation to use in response to various types of security incidents. Which of the following is the next step the manager should take?

- A. Set the maximum data retention policy.
- B. Securely store the documents on an air-gapped network.
- C. Review the documents' data classification policy.
- D. Conduct a tabletop exercise with the team.

**Answer:** D

**Explanation:**

A tabletop exercise is a simulated scenario that tests the effectiveness of a security incident response plan. It involves gathering the relevant stakeholders and walking through the steps of the plan, identifying any gaps or issues that need to be addressed. A tabletop exercise is a good way to validate the documentation created by the security manager and ensure that the team is prepared for various types of security incidents. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 6: Risk Management, page 2841. CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 6: Risk Management, page 2842.

**NEW QUESTION 99**

A security administrator is deploying a DLP solution to prevent the exfiltration of sensitive customer data. Which of the following should the administrator do first?

- A. Block access to cloud storage websites.
- B. Create a rule to block outgoing email attachments.
- C. Apply classifications to the data.
- D. Remove all user permissions from shares on the file server.

**Answer:** C

**Explanation:**

Data classification is the process of assigning labels or tags to data based on its sensitivity, value, and risk. Data classification is the first step in a data loss prevention (DLP) solution, as it helps to identify what data needs to be protected and how. By applying classifications to the data, the security administrator can define appropriate policies and rules for the DLP solution to prevent the exfiltration of sensitive customer data. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 8: Data Protection, page 323. CompTIA Security+ Practice Tests: Exam SY0-701, 3rd Edition, Chapter 8: Data Protection, page 327.

**NEW QUESTION 102**

A security team is reviewing the findings in a report that was delivered after a third party performed a penetration test. One of the findings indicated that a web application form field is vulnerable to cross-site scripting. Which of the following application security techniques should the security analyst recommend the developer implement to prevent this vulnerability?

- A. Secure cookies
- B. Version control
- C. Input validation
- D. Code signing

**Answer:** C

**Explanation:**

Input validation is a technique that checks the user input for any malicious or unexpected data before processing it by the web application. Input validation can prevent cross-site scripting (XSS) attacks, which exploit the vulnerability of a web application to execute malicious scripts in the browser of a victim. XSS attacks can compromise the confidentiality, integrity, and availability of the web application and its users. Input validation can be implemented on both the client-side and the server-side, but server-side validation is more reliable and secure. Input validation can use various methods, such as whitelisting, blacklisting, filtering, escaping, encoding, and sanitizing the input data. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 70. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 3.2, page 11. Application Security – SY0-601 CompTIA

Security+ : 3.2

#### NEW QUESTION 103

A company is discarding a classified storage array and hires an outside vendor to complete the disposal. Which of the following should the company request from the vendor?

- A. Certification
- B. Inventory list
- C. Classification
- D. Proof of ownership

**Answer:** A

#### Explanation:

The company should request a certification from the vendor that confirms the storage array has been disposed of securely and in compliance with the company's policies and standards. A certification provides evidence that the vendor has followed the proper procedures and methods to destroy the classified data and prevent unauthorized access or recovery. A certification may also include details such as the date, time, location, and method of disposal, as well as the names and signatures of the personnel

involved. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 3, page 1441

#### NEW QUESTION 104

During the onboarding process, an employee needs to create a password for an intranet account. The password must include ten characters, numbers, and letters, and two special characters. Once the password is created, the company will grant the employee access to other company-owned websites based on the intranet profile. Which of the following access management concepts is the company most likely using to safeguard intranet accounts and grant access to multiple sites based on a user's intranet account? (Select two).

- A. Federation
- B. Identity proofing
- C. Password complexity
- D. Default password changes
- E. Password manager
- F. Open authentication

**Answer:** AC

#### Explanation:

Federation is an access management concept that allows users to authenticate once and access multiple resources or services across different domains or organizations. Federation relies on a trusted third party that stores the user's credentials and provides them to the requested resources or services without exposing them. Password complexity is a security measure that requires users to create passwords that meet certain criteria, such as length, character types, and uniqueness. Password complexity can help prevent brute-force attacks, password guessing, and credential stuffing by making passwords harder to crack or guess. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 308-309 and 312-313 1

#### NEW QUESTION 108

A systems administrator wants to prevent users from being able to access data based on their responsibilities. The administrator also wants to apply the required access structure via a simplified format. Which of the following should the administrator apply to the site recovery resource group?

- A. RBAC
- B. ACL
- C. SAML
- D. GPO

**Answer:** A

#### Explanation:

RBAC stands for Role-Based Access Control, which is a method of restricting access to data and resources based on the roles or responsibilities of users. RBAC simplifies the management of permissions by assigning roles to users and granting access rights to roles, rather than to individual users. RBAC can help enforce the principle of least privilege and reduce the risk of unauthorized access or data leakage. The other options are not as suitable for the scenario as RBAC, as they either do not prevent access based on responsibilities, or do not apply a simplified format. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 133 1

#### NEW QUESTION 110

A cyber operations team informs a security analyst about a new tactic malicious actors are using to compromise networks. SIEM alerts have not yet been configured. Which of the following best describes what the security analyst should do to identify this behavior?

- A. [Digital forensics
- B. E-discovery
- C. Incident response
- D. Threat hunting

**Answer:** D

#### Explanation:

Threat hunting is the process of proactively searching for signs of malicious activity or compromise in a network, rather than waiting for alerts or indicators of compromise (IOCs) to appear. Threat hunting can help identify new tactics, techniques, and procedures (TTPs) used by malicious actors, as well as uncover hidden or stealthy threats that may have evaded detection by security tools. Threat hunting requires a combination of skills, tools, and methodologies, such as hypothesis generation, data collection and analysis, threat intelligence, and incident response. Threat hunting can also help improve the security posture of an organization by providing feedback and recommendations for security improvements. References = CompTIA Security+ Certification Exam Objectives, Domain 4.1: Given a scenario, analyze potential indicators of malicious activity. CompTIA Security+ Study Guide (SY0-701), Chapter 4: Threat Detection and Response, page 153. Threat

Hunting – SY0-701 CompTIA Security+ : 4.1, Video 3:18. CompTIA Security+ Certification Exam SY0-701 Practice Test 1, Question 3.

#### NEW QUESTION 113

Which of the following vulnerabilities is associated with installing software outside of a manufacturer's approved software repository?

- A. Jailbreaking
- B. Memory injection
- C. Resource reuse
- D. Side loading

**Answer: D**

#### Explanation:

Side loading is the process of installing software outside of a manufacturer's approved software repository. This can expose the device to potential vulnerabilities, such as malware, spyware, or unauthorized access. Side loading can also bypass security controls and policies that are enforced by the manufacturer or the organization. Side loading is often done by users who want to access applications or features that are not available or allowed on their devices. References = Sideload - CompTIA Security + Video Training | Interface Technical Training, Security+ (Plus) Certification | CompTIA IT Certifications, Load Balancers – CompTIA Security+ SY0-501 – 2.1, CompTIA Security+ SY0-601 Certification Study Guide.

#### NEW QUESTION 118

Which of the following security concepts is the best reason for permissions on a human resources fileshare to follow the principle of least privilege?

- A. Integrity
- B. Availability
- C. Confidentiality
- D. Non-repudiation

**Answer: C**

#### Explanation:

Confidentiality is the security concept that ensures data is protected from unauthorized access or disclosure. The principle of least privilege is a technique that grants users or systems the minimum level of access or permissions that they need to perform their tasks, and nothing more. By applying the principle of least privilege to a human resources fileshare, the permissions can be restricted to only those who have a legitimate need to access the sensitive data, such as HR staff, managers, or auditors. This can prevent unauthorized users, such as hackers, employees, or contractors, from accessing, copying, modifying, or deleting the data. Therefore, the principle of least privilege can enhance the confidentiality of the data on the fileshare. Integrity, availability, and non-repudiation are other security concepts, but they are not the best reason for permissions on a human resources fileshare to follow the principle of least privilege. Integrity is the security concept that ensures data is accurate and consistent, and protected from unauthorized modification or corruption. Availability is the security concept that ensures data is accessible and usable by authorized users or systems when needed. Non-repudiation is the security concept that ensures the authenticity and accountability of data and actions, and prevents the denial of involvement or responsibility. While these concepts are also important for data security, they are not directly related to the level of access or permissions granted to users or systems. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 16-17, 372-373

#### NEW QUESTION 122

An organization is struggling with scaling issues on its VPN concentrator and internet circuit due to remote work. The organization is looking for a software solution that will allow it to reduce traffic on the VPN and internet circuit, while still providing encrypted tunnel access to the data center and monitoring of remote employee internet traffic. Which of the following will help achieve these objectives?

- A. Deploying a SASE solution to remote employees
- B. Building a load-balanced VPN solution with redundant internet
- C. Purchasing a low-cost SD-WAN solution for VPN traffic
- D. Using a cloud provider to create additional VPN concentrators

**Answer: A**

#### Explanation:

SASE stands for Secure Access Service Edge. It is a cloud-based service that combines network and security functions into a single integrated solution. SASE can help reduce traffic on the VPN and internet circuit by providing secure and optimized access to the data center and cloud applications for remote employees. SASE can also monitor and enforce security policies on the remote employee internet traffic, regardless of their location or device. SASE can offer benefits such as lower costs, improved performance, scalability, and flexibility compared to traditional VPN solutions. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 457-458 1

#### NEW QUESTION 124

An organization would like to store customer data on a separate part of the network that is not accessible to users on the main corporate network. Which of the following should the administrator use to accomplish this goal?

- A. Segmentation
- B. Isolation
- C. Patching
- D. Encryption

**Answer: A**

#### Explanation:

Segmentation is a network design technique that divides the network into smaller and isolated segments based on logical or physical boundaries. Segmentation can help improve network security by limiting the scope of an attack, reducing the attack surface, and enforcing access control policies. Segmentation can also enhance network performance, scalability, and manageability. To accomplish the goal of storing customer data on a separate part of the network, the administrator can use segmentation technologies such as subnetting, VLANs, firewalls, routers, or switches. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 308-309 1

#### NEW QUESTION 128

A penetration tester begins an engagement by performing port and service scans against the client environment according to the rules of engagement. Which of the following reconnaissance types is the tester performing?

- A. Active
- B. Passive
- C. Defensive
- D. Offensive

**Answer:** A

#### Explanation:

Active reconnaissance is a type of reconnaissance that involves sending packets or requests to a target and analyzing the responses. Active reconnaissance can reveal information such as open ports, services, operating systems, and vulnerabilities. However, active reconnaissance is also more likely to be detected by the target or its security devices, such as firewalls or intrusion detection systems. Port and service scans are examples of active reconnaissance techniques, as they involve probing the target for specific information. References = CompTIA Security+ Certification Exam Objectives, Domain 1.1: Given a scenario, conduct reconnaissance using appropriate techniques and tools. CompTIA Security+ Study Guide (SY0-701), Chapter 2: Reconnaissance and Intelligence Gathering, page 47. CompTIA Security+ Certification Exam SY0-701 Practice Test 1, Question 1.

#### NEW QUESTION 130

A user is attempting to patch a critical system, but the patch fails to transfer. Which of the following access controls is most likely inhibiting the transfer?

- A. Attribute-based
- B. Time of day
- C. Role-based
- D. Least privilege

**Answer:** D

#### Explanation:

The least privilege principle states that users and processes should only have the minimum level of access required to perform their tasks. This helps to prevent unauthorized or unnecessary actions that could compromise security. In this case, the patch transfer might be failing because the user or process does not have the appropriate permissions to access the critical system or the network resources needed for the transfer. Applying the least privilege principle can help to avoid this issue by granting the user or process the necessary access rights for the patching activity. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 931

#### NEW QUESTION 132

##### HOTSPOT

Select the appropriate attack and remediation from each drop-down list to label the corresponding attack with its remediation.

##### INSTRUCTIONS

Not all attacks and remediation actions will be used.

If at any time you would like to bring back the initial state of the simulation, please click the Reset All button.

Attack Description	Target	Attack Identified	BEST Preventative or Remediation Action
An attacker sends multiple SYN packets from multiple sources.	Web server	Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing	Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attack establishes a connection, which allows remote commands to be executed.	User	Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing	Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attack is self propagating and compromises a SQL database using well-known credentials as it moves through the network.	Database server	Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing	Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attacker uses hardware to remotely monitor a user's input activity to harvest credentials.	Executive	Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing	Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attacker embeds hidden access in an internally developed application that bypasses account login.	Application	Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing	Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Web server Botnet Enable DDoS protection User RAT Implement a host-based IPS Database server Worm Change the default application password Executive Keylogger Disable vulnerable services Application Backdoor Implement 2FA using push notification

Attack Description	Target	Attack Identified	BEST Preventative or Remediation Action
An attacker sends multiple SYN packets from multiple sources.	Web server	Botnet	Enable DDoS protection
The attack establishes a connection, which allows remote commands to be executed.	User	RAT	Implement a host-based IPS
The attack is self propagating and compromises a SQL database using well-known credentials as it moves through the network.	Database server	Worm	Change the default application password
The attacker uses hardware to remotely monitor a user's input activity to harvest credentials.	Executive	Keylogger	Disable vulnerable services
The attacker embeds hidden access in an internally developed application that bypasses account login.	Application	Backdoor	Implement 2FA using push notification

A screenshot of a computer program  
Description automatically generated with low confidence

**NEW QUESTION 135**

.....

## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### SY0-701 Practice Exam Features:

- \* SY0-701 Questions and Answers Updated Frequently
- \* SY0-701 Practice Questions Verified by Expert Senior Certified Staff
- \* SY0-701 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* SY0-701 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
[Order The SY0-701 Practice Test Here](#)