

Exam Questions DVA-C02

DVA-C02

<https://www.2passeasy.com/dumps/DVA-C02/>



NEW QUESTION 1

A data visualization company wants to strengthen the security of its core applications. The applications are deployed on AWS across its development, staging, pre-production, and production environments. The company needs to encrypt all of its stored sensitive credentials. The sensitive credentials need to be automatically rotated. A version of the sensitive credentials need to be stored for each environment. Which solution will meet these requirements in the MOST operationally efficient way?

- A. Configure AWS Secrets Manager versions to store different copies of the same credentials across multiple environments.
- B. Create a new parameter version in AWS Systems Manager Parameter Store for each environment. Store the environment-specific credentials in the parameter version.
- C. Configure the environment variables in the application code. Use different names for each environment type. Store the environment-specific credentials in the secret.
- D. Configure AWS Secrets Manager to create a new secret for each environment type.

Answer: D

Explanation:

AWS Secrets Manager is the best option for managing sensitive credentials across multiple environments, as it provides automatic secret rotation, auditing, and monitoring features. It also allows storing environment-specific credentials in separate secrets, which can be accessed by the applications using the SDK or CLI. AWS Systems Manager Parameter Store does not have built-in secret rotation capability, and it requires creating individual parameters or storing the entire credential set as a JSON object. Configuring the environment variables in the application code is not a secure or scalable solution, as it exposes the credentials to anyone who can access the code. References

? AWS Secrets Manager vs. Systems Manager Parameter Store

? AWS System Manager Parameter Store vs Secrets Manager vs Environment Variation in Lambda, when to use which

? AWS Secrets Manager vs. Parameter Store: Features, Cost & More

NEW QUESTION 2

A developer is storing sensitive data generated by an application in Amazon S3. The developer wants to encrypt the data at rest. A company policy requires an audit trail of when the AWS Key Management Service (AWS KMS) key was used and by whom. Which encryption option will meet these requirements?

- A. Server-side encryption with Amazon S3 managed keys (SSE-S3)
- B. Server-side encryption with AWS KMS managed keys (SSE-KMS)
- C. Server-side encryption with customer-provided keys (SSE-C)
- D. Server-side encryption with self-managed keys

Answer: B

Explanation:

This solution meets the requirements because it encrypts data at rest using AWS KMS keys and provides an audit trail of when and by whom they were used. Server-side encryption with AWS KMS managed keys (SSE-KMS) is a feature of Amazon S3 that encrypts data using keys that are managed by AWS KMS. When SSE-KMS is enabled for an S3 bucket or object, S3 requests AWS KMS to generate data keys and encrypts data using these keys. AWS KMS logs every use of its keys in AWS CloudTrail, which records all API calls to AWS KMS as events. These events include information such as who made the request, when it was made, and which key was used. The company policy can use CloudTrail logs to audit critical events related to their data encryption and access. Server-side encryption with Amazon S3 managed keys (SSE-S3) also encrypts data at rest using keys that are managed by S3, but does not provide an audit trail of key usage. Server-side encryption with customer-provided keys (SSE-C) and server-side encryption with self-managed keys also encrypt data at rest using keys that are provided or managed by customers, but do not provide an audit trail of key usage and require additional overhead for key management.

Reference: [Protecting Data Using Server-Side Encryption with AWS KMS–Managed Encryption Keys (SSE-KMS)], [Logging AWS KMS API calls with AWS CloudTrail]

NEW QUESTION 3

A developer needs to perform geographic load testing of an API. The developer must deploy resources to multiple AWS Regions to support the load testing of the API.

How can the developer meet these requirements without additional application code?

- A. Create and deploy an AWS Lambda function in each desired Region.
- B. Configure the Lambda function to create a stack from an AWS CloudFormation template in that Region when the function is invoked. Create an AWS CloudFormation template that defines the load test resource.
- C. Use the AWS CLI create-stack-set command to create a stack set in the desired Regions.
- D. Create an AWS Systems Manager document that defines the resource.
- E. Use the document to create the resources in the desired Regions.
- F. Create an AWS CloudFormation template that defines the load test resource.
- G. Use the AWS CLI deploy command to create a stack from the template in each Region.

Answer: B

Explanation:

AWS CloudFormation is a service that allows developers to model and provision AWS resources using templates. A CloudFormation template can define the load test resources, such as EC2 instances, load balancers, and Auto Scaling groups. A CloudFormation stack set is a collection of stacks that can be created and managed from a single template in multiple Regions and accounts. The AWS CLI create-stack-set command can be used to create a stack set from a template and specify the Regions where the stacks should be created. Reference: Working with AWS CloudFormation stack sets

NEW QUESTION 4

A development team wants to build a continuous integration/continuous delivery (CI/CD) pipeline. The team is using AWS CodePipeline to automate the code build and deployment. The team wants to store the program code to prepare for the CI/CD pipeline.

Which AWS service should the team use to store the program code?

- A. AWS CodeDeploy
- B. AWS CodeArtifact

- C. AWS CodeCommit
Amazon CodeGuru
- D.

Answer: C

Explanation:

AWS CodeCommit is a service that provides fully managed source control for hosting secure and scalable private Git repositories. The development team can use CodeCommit to store the program code and prepare for the CI/CD pipeline. CodeCommit integrates with other AWS services such as CodePipeline, CodeBuild, and CodeDeploy to automate the code build and deployment process.

References:

- ? [What Is AWS CodeCommit? - AWS CodeCommit]
? [AWS CodePipeline - AWS CodeCommit]

NEW QUESTION 5

A developer is creating an application that includes an Amazon API Gateway REST API in the us-east-2 Region. The developer wants to use Amazon CloudFront and a custom domain name for the API. The developer has acquired an SSL/TLS certificate for the domain from a third-party provider. How should the developer configure the custom domain for the application?

- A. Import the SSL/TLS certificate into AWS Certificate Manager (ACM) in the same Region as the AP
B. Create a DNS A record for the custom domain.
C. Import the SSL/TLS certificate into CloudFront
D. Create a DNS CNAME record for the custom domain.
E. Import the SSL/TLS certificate into AWS Certificate Manager (ACM) in the same Region as the AP
F. Create a DNS CNAME record for the custom domain.
G. Import the SSL/TLS certificate into AWS Certificate Manager (ACM) in the us-east-1 Region
H. Create a DNS CNAME record for the custom domain.

Answer: D

Explanation:

Amazon API Gateway is a service that enables developers to create, publish, maintain, monitor, and secure APIs at any scale. Amazon CloudFront is a content delivery network (CDN) service that can improve the performance and security of web applications. The developer can use CloudFront and a custom domain name for the API Gateway REST API. To do so, the developer needs to import the SSL/TLS certificate into AWS Certificate Manager (ACM) in the us-east-1 Region. This is because CloudFront requires certificates from ACM to be in this Region. The developer also needs to create a DNS CNAME record for the custom domain that points to the CloudFront distribution.

References:

- ? [What Is Amazon API Gateway? - Amazon API Gateway]
? [What Is Amazon CloudFront? - Amazon CloudFront]
? [Custom Domain Names for APIs - Amazon API Gateway]

NEW QUESTION 6

A developer is designing a serverless application for a game in which users register and log in through a web browser. The application makes requests on behalf of users to a set of AWS Lambda functions that run behind an Amazon API Gateway HTTP API. The developer needs to implement a solution to register and log in users on the application's sign-in page. The solution must minimize operational overhead and must minimize ongoing management of user identities. Which solution will meet these requirements?

- A. Create Amazon Cognito user pools for external social identity providers. Configure IAM roles for the identity pools.
B. Program the sign-in page to create users' IAM groups with the IAM roles attached to the groups.
C. Create an Amazon RDS for SQL Server DB instance to store the users and manage the permissions to the backend resources in AWS.
D. Configure the sign-in page to register and store the users and their passwords in an Amazon DynamoDB table with an attached IAM policy.

Answer: A

Explanation:

<https://docs.aws.amazon.com/cognito/latest/developerguide/signing-up-users-in-your-app.html>

NEW QUESTION 7

An Amazon Simple Queue Service (Amazon SQS) queue serves as an event source for an AWS Lambda function. In the SQS queue, each item corresponds to a video file that the Lambda function must convert to a smaller resolution. The Lambda function is timing out on longer video files, but the Lambda function's timeout is already configured to its maximum value. What should a developer do to avoid the timeouts without additional code changes?

- A. Increase the memory configuration of the Lambda function.
B. Increase the visibility timeout on the SQS queue.
C. Increase the instance size of the host that runs the Lambda function.
D. Use multi-threading for the conversion.

Answer: A

Explanation:

Increasing the memory configuration of the Lambda function will also increase the CPU and network throughput available to the function. This can improve the performance of the video conversion process and reduce the execution time of the function. This solution does not require any code changes or additional resources. It is also recommended to follow the best practices for preventing Lambda function timeouts¹. References

- ? Troubleshoot Lambda function invocation timeout errors | AWS re:Post

NEW QUESTION 8

A company has a multi-node Windows legacy application that runs on premises. The application uses a network shared folder as a centralized configuration repository to store configuration files in .xml format. The company is migrating the application to Amazon EC2 instances. As part of the migration to AWS, a developer must identify a solution that provides high availability for the repository.

Which solution will meet this requirement MOST cost-effectively?

- A. Mount an Amazon Elastic Block Store (Amazon EBS) volume onto one of the EC2 instance
- B. Deploy a file system on the EBS volum
- C. Use the host operating system to share a folde
- D. Update the application code to read and write configuration files from the shared folder.
- E. Deploy a micro EC2 instance with an instance store volum
- F. Use the host operating system to share a folde
- G. Update the application code to read and write configuration files from the shared folder.
- H. Create an Amazon S3 bucket to host the repositor
- I. Migrate the existing .xml files to the S3 bucke
- J. Update the application code to use the AWS SDK to read and write configuration files from Amazon S3.
- K. Create an Amazon S3 bucket to host the repositor
- L. Migrate the existing .xml files to the S3 bucke
- M. Mount the S3 bucket to the EC2 instances as a local volum
- N. Update the application code to read and write configuration files from the disk.

Answer: C

Explanation:

Amazon S3 is a service that provides highly scalable, durable, and secure object storage. The developer can create an S3 bucket to host the repository and migrate the existing .xml files to the S3 bucket. The developer can update the application code to use the AWS SDK to read and write configuration files from S3. This solution will meet the requirement of high availability for the repository in a cost-effective way.

References:

- ? [Amazon Simple Storage Service (S3)]
- ? [Using AWS SDKs with Amazon S3]

NEW QUESTION 9

A developer is creating an AWS Lambda function that needs credentials to connect to an Amazon RDS for MySQL database. An Amazon S3 bucket currently stores the credentials. The developer needs to improve the existing solution by implementing credential rotation and secure storage. The developer also needs to provide integration with the Lambda function.

Which solution should the developer use to store and retrieve the credentials with the LEAST management overhead?

- A. Store the credentials in AWS Systems Manager Parameter Stor
- B. Select the database that the parameter will acces
- C. Use the default AWS Key Management Service (AWS KMS) key to encrypt the paramete
- D. Enable automatic rotation for the paramete
- E. Use the parameter from Parameter Store on the Lambda function to connect to the database.
- F. Encrypt the credentials with the default AWS Key Management Service (AWS KMS) ke
- G. Store the credentials as environment variables for the Lambda functio
- H. Create a second Lambda function to generate new credentials and to rotate the credentials by updating the environment variables of the first Lambda functio
- I. Invoke the second Lambda function by using an Amazon EventBridge rule that runs on a schedul
- J. Update the database to use the new credential
- K. On the first Lambda function, retrieve the credentials from the environment variable
- L. Decrypt the credentials by using AWS KMS, Connect to the database.
- M. Store the credentials in AWS Secrets Manage
- N. Set the secret type to Credentials for Amazon RDS databas
- O. Select the database that the secret will acces
- P. Use the default AWS Key Management Service (AWS KMS) key to encrypt the secre
- Q. Enable automatic rotation for the secre
- R. Use the secret from Secrets Manager on the Lambda function to connect to the database.
- S. Encrypt the credentials by using AWS Key Management Service (AWS KMS). Store the credentials in an Amazon DynamoDB tabl
- T. Create a second Lambda function to rotate the credential
- . Invoke the second Lambda function by using an Amazon EventBridge rule that runs on a schedul
- . Update the DynamoDB tabl
- . Update the database to use the generated credential
- . Retrieve the credentials from DynamoDB with the first Lambda functio
- . Connect to the database.

Answer: C

Explanation:

AWS Secrets Manager is a service that helps you protect secrets needed to access your applications, services, and IT resources. Secrets Manager enables you to store, retrieve, and rotate secrets such as database credentials, API keys, and passwords. Secrets Manager supports a secret type for RDS databases, which allows you to select an existing RDS database instance and generate credentials for it. Secrets Manager encrypts the secret using AWS Key Management Service (AWS KMS) keys and enables automatic rotation of the secret at a specified interval. A Lambda function can use the AWS SDK or CLI to retrieve the secret from Secrets Manager and use it to connect to the database. Reference: Rotating your AWS Secrets Manager secrets

NEW QUESTION 10

A developer is creating a simple proof-of-concept demo by using AWS CloudFormation and AWS Lambda functions The demo will use a CloudFormation template to deploy an existing Lambda function The Lambda function uses deployment packages and dependencies stored in Amazon S3 The developer defined anAWS Lambda Function resource in a CloudFormation template. The developer needs to add the S3 bucket to the CloudFormation template.

What should the developer do to meet these requirements with the LEAST development effort?

- A. Add the function code in the CloudFormation template inline as the code property
- B. Add the function code in the CloudFormation template as the ZipFile property.

- C. Find the S3 key for the Lambda function Add the S3 key as the ZipFile property in the CloudFormation template.
- D. Add the relevant key and bucket to the S3Bucket and S3Key properties in the CloudFormation template

Answer: D

Explanation:

The easiest way to add the S3 bucket to the CloudFormation template is to use the S3Bucket and S3Key properties of the AWS::Lambda::Function resource. These properties specify the name of the S3 bucket and the location of the .zip file that contains the function code and dependencies. This way, the developer does not need to modify the function code or upload it to a different location. The other options are either not feasible or not efficient. The code property can only be used for inline code, not for code stored in S3. The ZipFile property can only be used for code that is less than 4096 bytes, not for code that has dependencies. Finding the S3 key for the Lambda function and adding it as the ZipFile property would not work, as the ZipFile property expects a base64-encoded .zip file, not an S3 location. References

- ? AWS::Lambda::Function - AWS CloudFormation
- ? Deploying Lambda functions as .zip file archives
- ? AWS Lambda Function Code - AWS CloudFormation

NEW QUESTION 10

A company has a web application that is hosted on Amazon EC2 instances The EC2 instances are configured to stream logs to Amazon CloudWatch Logs The company needs to receive an Amazon Simple Notification Service (Amazon SNS) notification when the number of application error messages exceeds a defined threshold within a 5-minute period Which solution will meet these requirements?

- A. Rewrite the application code to stream application logs to Amazon SNS Configure an SNS topic to send a notification when the number of errors exceeds the defined threshold within a 5-minute period
- B. Configure a subscription filter on the CloudWatch Logs log grou
- C. Configure the filter to send an SNS notification when the number of errors exceeds the defined threshold within a 5-minute period.
- D. Install and configure the Amazon Inspector agent on the EC2 instances to monitor for errors Configure Amazon Inspector to send an SNS notification when the number of errors exceeds the defined threshold within a 5-minute period
- E. Create a CloudWatch metric filter to match the application error pattern in the log data. Set up a CloudWatch alarm based on the new custom metr
- F. Configure the alarm to send an SNS notification when the number of errors exceeds the defined threshold within a 5- minute period.

Answer: D

Explanation:

The best solution is to create a CloudWatch metric filter to match the application error pattern in the log data. This will allow you to create a custom metric that tracks the number of errors in your application. You can then set up a CloudWatch alarm based on this metric and configure it to send an SNS notification when the number of errors exceeds a defined threshold within a 5-minute period. This solution does not require any changes to your application code or installing any additional agents on your EC2 instances. It also leverages the existing integration between CloudWatch and SNS for sending notifications. References

- ? Create Metric Filters - Amazon CloudWatch Logs
- ? Creating Amazon CloudWatch Alarms - Amazon CloudWatch
- ? How to send alert based on log message on CloudWatch - Stack Overflow

NEW QUESTION 12

An online sales company is developing a serverless application that runs on AWS. The application uses an AWS Lambda function that calculates order success rates and stores the data in an Amazon DynamoDB table. A developer wants an efficient way to invoke the Lambda function every 15 minutes. Which solution will meet this requirement with the LEAST development effort?

- A. Create an Amazon EventBridge rule that has a rate expression that will run the rule every 15 minute
- B. Add the Lambda function as the target of the EventBridge rule.
- C. Create an AWS Systems Manager document that has a script that will invoke the Lambda function on Amazon EC2. Use a Systems Manager Run Command task to run the shell script every 15 minutes.
- D. Create an AWS Step Functions state machin
- E. Configure the state machine to invoke the Lambda function execution role at a specified interval by using a Wait stat
- F. Set the interval to 15 minutes.
- G. Provision a small Amazon EC2 instanc
- H. Set up a cron job that invokes the Lambda function every 15 minutes.

Answer: A

Explanation:

The best solution for this requirement is option A. Creating an Amazon EventBridge rule that has a rate expression that will run the rule every 15 minutes and adding the Lambda function as the target of the EventBridge rule is the most efficient way to invoke the Lambda function periodically. This solution does not require any additional resources or development effort, and it leverages the built-in scheduling capabilities of EventBridge1.

NEW QUESTION 17

A developer is creating an application that will store personal health information (PHI). The PHI needs to be encrypted at all times. An encrypted Amazon RDS for MySQL DB instance is storing the data. The developer wants to increase the performance of the application by caching frequently accessed data while adding the ability to sort or rank the cached datasets. Which solution will meet these requirements?

- A. Create an Amazon ElastiCache for Redis instanc
- B. Enable encryption of data in transit and at res
- C. Store frequently accessed data in the cache.
- D. Create an Amazon ElastiCache for Memcached instanc
- E. Enable encryption of data in transit and at res
- F. Store frequently accessed data in the cache.
- G. Create an Amazon RDS for MySQL read replic
- H. Connect to the read replica by using SS
- I. Configure the read replica to store frequently accessed data.

- J. Create an Amazon DynamoDB table and a DynamoDB Accelerator (DAX) cluster for the table.
 K. Store frequently accessed data in the DynamoDB table.

Answer: A

Explanation:

Amazon ElastiCache is a service that offers fully managed in-memory data stores that are compatible with Redis or Memcached. The developer can create an ElastiCache for Redis instance and enable encryption of data in transit and at rest. This will ensure that the PHI is encrypted at all times. The developer can store frequently accessed data in the cache and use Redis features such as sorting and ranking to enhance the performance of the application.

References:

- ? [What Is Amazon ElastiCache? - Amazon ElastiCache]
- ? [Encryption in Transit - Amazon ElastiCache for Redis]
- ? [Encryption at Rest - Amazon ElastiCache for Redis]

NEW QUESTION 22

A developer is working on a Python application that runs on Amazon EC2 instances. The developer wants to enable tracing of application requests to debug performance issues in the code.

Which combination of actions should the developer take to achieve this goal? (Select TWO)

- A. Install the Amazon CloudWatch agent on the EC2 instances.
- B. Install the AWS X-Ray daemon on the EC2 instances.
- C. Configure the application to write JSON-formatted logs to /var/log/cloudwatch.
- D. Configure the application to write trace data to /var/log/xray.
- E. Install and configure the AWS X-Ray SDK for Python in the application.

Answer: BE

Explanation:

This solution will meet the requirements by using AWS X-Ray to enable tracing of application requests to debug performance issues in the code. AWS X-Ray is a service that collects data about requests that the applications serve, and provides tools to view, filter, and gain insights into that data. The developer can install the AWS X-Ray daemon on the EC2 instances, which is a software that listens for traffic on UDP port 2000, gathers raw segment data, and relays it to the X-Ray API. The developer can also install and configure the AWS X-Ray SDK for Python in the application, which is a library that enables instrumenting Python code to generate and send trace data to the X-Ray daemon. Option A is not optimal because it will install the Amazon CloudWatch agent on the EC2 instances, which is a software that collects metrics and logs from EC2 instances and on-premises servers, not application performance data. Option C is not optimal because it will configure the application to write JSON-formatted logs to /var/log/cloudwatch, which is not a valid path or destination for CloudWatch logs. Option D is not optimal because it will configure the application to write trace data to /var/log/xray, which is also not a valid path or destination for X-Ray trace data.

References: [AWS X-Ray], [Running the X-Ray Daemon on Amazon EC2]

NEW QUESTION 27

A company has an application that runs as a series of AWS Lambda functions. Each Lambda function receives data from an Amazon Simple Notification Service (Amazon SNS) topic and writes the data to an Amazon Aurora DB instance.

To comply with an information security policy, the company must ensure that the Lambda functions all use a single securely encrypted database connection string to access Aurora.

Which solution will meet these requirements'?

- A. Use IAM database authentication for Aurora to enable secure database connections for all the Lambda functions.
- B. Store the credentials and read the credentials from an encrypted Amazon RDS DB instance.
- C. Store the credentials in AWS Systems Manager Parameter Store as a secure string parameter.
- D. Use Lambda environment variables with a shared AWS Key Management Service (AWS KMS) key for encryption.

Answer: A

Explanation:

This solution will meet the requirements by using IAM database authentication for Aurora, which enables using IAM roles or users to authenticate with Aurora databases instead of using passwords or other secrets. The developer can use IAM database authentication for Aurora to enable secure database connections for all the Lambda functions that access Aurora DB instance. The developer can create an IAM role with permission to connect to Aurora DB instance and attach it to each Lambda function. The developer can also configure Aurora DB instance to use IAM database authentication and enable encryption in transit using SSL certificates. This way, the Lambda functions can use a single securely encrypted database connection string to access Aurora without needing any secrets or passwords. Option B is not optimal because it will store the credentials and read them from an encrypted Amazon RDS DB instance, which may introduce additional costs and complexity for managing and accessing another RDS DB instance. Option C is not optimal because it will store the credentials in AWS Systems Manager Parameter Store as a secure string parameter, which may require additional steps or permissions to retrieve and decrypt the credentials from Parameter Store. Option D is not optimal because it will use Lambda environment variables with a shared AWS Key Management Service (AWS KMS) key for encryption, which may not be secure or scalable as environment variables are stored as plain text unless encrypted with AWS KMS. References: [IAM Database Authentication for MySQL and PostgreSQL], [Using SSL/TLS to Encrypt a Connection to a DB Instance]

NEW QUESTION 32

A financial company must store original customer records for 10 years for legal reasons. A complete record contains personally identifiable information (PII).

According to local regulations, PII is available to only certain people in the company and must not be shared with third parties. The company needs to make the records available to third-party organizations for statistical analysis without sharing the PII.

A developer wants to store the original immutable record in Amazon S3. Depending on who accesses the S3 document, the document should be returned as is or with all the PII removed. The developer has written an AWS Lambda function to remove the PII from the document. The function is named removePii.

What should the developer do so that the company can meet the PII requirements while maintaining only one copy of the document?

- A. Set up an S3 event notification that invokes the removePii function when an S3 GET request is made.
- B. Call Amazon S3 by using a GET request to access the object without PII.
- C. Set up an S3 event notification that invokes the removePii function when an S3 PUT request is made.
- D. Call Amazon S3 by using a PUT request to access the object without PII.
- E. Create an S3 Object Lambda access point from the S3 console.
- F. Select the removePii function.

- G. Use S3 Access Points to access the object without PII.
- H. Create an S3 access point from the S3 console
- I. Use the access point name to call the GetObjectLegalHold S3 API function
- J. Pass in the removePii function name to access the object without PII.

Answer: C

Explanation:

S3 Object Lambda allows you to add your own code to process data retrieved from S3 before returning it to an application. You can use an AWS Lambda function to modify the data, such as removing PII, redacting confidential information, or resizing images. You can create an S3 Object Lambda access point and associate it with your Lambda function. Then, you can use the access point to request objects from S3 and get the modified data back. This way, you can maintain only one copy of the original

document in S3 and apply different transformations depending on who accesses it. Reference: Using AWS Lambda with Amazon S3

NEW QUESTION 35

For a deployment using AWS Code Deploy, what is the run order of the hooks for in-place deployments?

- A. BeforeInstall -> ApplicationStop -> ApplicationStart -> AfterInstall
- B. ApplicationStop -> BeforeInstall -> AfterInstall -> ApplicationStart
- C. BeforeInstall -> ApplicationStop -> ValidateService -> ApplicationStart
- D. ApplicationStop -> BeforeInstall -> ValidateService -> ApplicationStart

Answer: B

Explanation:

For in-place deployments, AWS CodeDeploy uses a set of predefined hooks that run in a specific order during each deployment lifecycle event. The hooks are ApplicationStop, BeforeInstall, AfterInstall, ApplicationStart, and ValidateService. The run order of the hooks for in-place deployments is as follows:

? ApplicationStop: This hook runs first on all instances and stops the current application that is running on the instances.

? BeforeInstall: This hook runs after ApplicationStop on all instances and performs any tasks required before installing the new application revision.

? AfterInstall: This hook runs after BeforeInstall on all instances and performs any tasks required after installing the new application revision.

? ApplicationStart: This hook runs after AfterInstall on all instances and starts the new application that has been installed on the instances.

? ValidateService: This hook runs last on all instances and verifies that the new application is running properly on the instances.

Reference: [AWS CodeDeploy lifecycle event hooks reference]

NEW QUESTION 40

An application that runs on AWS Lambda requires access to specific highly confidential objects in an Amazon S3 bucket. In accordance with the principle of least privilege a company grants access to the S3 bucket by using only temporary credentials.

How can a developer configure access to the S3 bucket in the MOST secure way?

- A. Hardcode the credentials that are required to access the S3 objects in the application code
- B. Use the credentials to access the required S3 objects.
Create a secret access key and access key ID with permission to access the S3 bucket
- C. Store the key and key ID in AWS Secrets Manager
- E. Configure the application to retrieve the Secrets Manager secret and use the credentials to access the S3 objects.
- F. Create a Lambda function execution role. Attach a policy to the role that grants access to specific objects in the S3 bucket.
- G. Create a secret access key and access key ID with permission to access the S3 bucket. Store the key and key ID as environment variables in Lambda
- H. Use the environment variables to access the required S3 objects.

Answer: C

Explanation:

This solution will meet the requirements by creating a Lambda function execution role, which is an IAM role that grants permissions to a Lambda function to access AWS resources such as Amazon S3 objects. The developer can attach a policy to the role that grants access to specific objects in the S3 bucket that are required by the application, following the principle of least privilege. Option A is not optimal because it will hardcode the credentials that are required to access S3 objects in the application code, which is insecure and difficult to maintain. Option B is not optimal because it will create a secret access key and access key ID with permission to access the S3 bucket, which will introduce additional security risks and complexity for storing and managing credentials. Option D is not optimal because it will store the secret access key and access key ID as environment variables in Lambda, which is also insecure and difficult to maintain. References: [AWS Lambda Execution Role], [Using AWS Lambda with Amazon S3]

NEW QUESTION 45

An organization is using Amazon CloudFront to ensure that its users experience low-latency access to its web application. The organization has identified a need to encrypt all traffic between users and CloudFront, and all traffic between CloudFront and the web application.

How can these requirements be met? (Select TWO)

- A. Use AWS KMS to encrypt traffic between CloudFront and the web application.
- B. Set the Origin Protocol Policy to "HTTPS Only".
- C. Set the Origin's HTTP Port to 443.
- D. Set the Viewer Protocol Policy to "HTTPS Only" or Redirect HTTP to HTTPS"
- E. Enable the CloudFront option Restrict Viewer Access.

Answer: BD

Explanation:

This solution will meet the requirements by ensuring that all traffic between users and CloudFront, and all traffic between CloudFront and the web application, are encrypted using HTTPS protocol. The Origin Protocol Policy determines how CloudFront communicates with the origin server (the web application), and setting it to "HTTPS Only" will force CloudFront to use HTTPS for every request to the origin server. The Viewer Protocol Policy determines how CloudFront responds to HTTP or HTTPS requests from users, and setting it to "HTTPS Only" or "Redirect HTTP to HTTPS" will force CloudFront to use HTTPS for every response to

users. Option A is not optimal because it will use AWS KMS to encrypt traffic between CloudFront and the web application, which is not necessary or supported by CloudFront. Option C is not optimal because it will set the origin's HTTP port to 443, which is incorrect as port 443 is used for HTTPS protocol, not HTTP protocol. Option E is not optimal because it will enable the CloudFront option Restrict Viewer Access, which is used for controlling access to private content using signed URLs or signed cookies, not for encrypting traffic.

References: [Using HTTPS with CloudFront], [Restricting Access to Amazon S3 Content by Using an Origin Access Identity]

NEW QUESTION 48

A company is running Amazon EC2 instances in multiple AWS accounts. A developer needs to implement an application that collects all the lifecycle events of the EC2 instances. The application needs to store the lifecycle events in a single Amazon Simple Queue Service (Amazon SQS) queue in the company's main AWS account for further processing.

Which solution will meet these requirements?

- A. Configure Amazon EC2 to deliver the EC2 instance lifecycle events from all accounts to the Amazon EventBridge event bus of the main account
- B. Add an EventBridge rule to the event bus of the main account that matches all EC2 instance lifecycle event
- C. Add the SQS queue as a target of the rule.
- D. Use the resource policies of the SQS queue in the main account to give each account permissions to write to that SQS queue
- E. Add to the Amazon EventBridge event bus of each account an EventBridge rule that matches all EC2 instance lifecycle event
- F. Add the SQS queue in the main account as a target of the rule.
- G. Write an AWS Lambda function that scans through all EC2 instances in the company accounts to detect EC2 instance lifecycle change
- H. Configure the Lambda function to write a notification message to the SQS queue in the main account if the function detects an EC2 instance lifecycle change
- I. Add an Amazon EventBridge scheduled rule that invokes the Lambda function every minute.
- J. Configure the permissions on the main account event bus to receive events from all accounts
- K. Create an Amazon EventBridge rule in each account to send all the EC2 instance lifecycle events to the main account event bus
- L. Add an EventBridge rule to the main account event bus that matches all EC2 instance lifecycle event
- M. Set the SQS queue as a target for the rule.

Answer: D

Explanation:

Amazon EC2 instances can send the state-change notification events to Amazon EventBridge.

<https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/monitoring-instance-state-changes.html> Amazon EventBridge can send and receive events between event buses in AWS accounts. <https://docs.aws.amazon.com/eventbridge/latest/userguide/eb-cross-account.html>

NEW QUESTION 53

A developer is deploying an AWS Lambda function. The developer wants the ability to return to older versions of the function quickly and seamlessly.

How can the developer achieve this goal with the LEAST operational overhead?

- A. Use AWS OpsWorks to perform blue/green deployments.
- B. Use a function alias with different versions.
- C. Maintain deployment packages for older versions in Amazon S3.
- D. Use AWS CodePipeline for deployments and rollbacks.

Answer: B

Explanation:

A function alias is a pointer to a specific Lambda function version. You can use aliases to create different environments for your function, such as development, testing, and production. You can also use aliases to perform blue/green deployments by shifting traffic between two versions of your function gradually. This way, you can easily roll back to a previous version if something goes wrong, without having to redeploy your code or change your configuration. Reference: AWS Lambda function aliases

NEW QUESTION 55

A developer has created an AWS Lambda function that makes queries to an Amazon Aurora MySQL DB instance. When the developer performs a test the DB instance shows an error for too many connections.

Which solution will meet these requirements with the LEAST operational effort?

- A. Create a read replica for the DB instance. Query the replica DB instance instead of the primary DB instance.
- B. Migrate the data to an Amazon DynamoDB database.
- C. Configure the Amazon Aurora MySQL DB instance for Multi-AZ deployment.
- D. Create a proxy in Amazon RDS Proxy. Query the proxy instead of the DB instance.

Answer: D

Explanation:

This solution will meet the requirements by using Amazon RDS Proxy, which is a fully managed, highly available database proxy for Amazon RDS that makes applications more scalable, more resilient to database failures, and more secure. The developer can create a proxy in Amazon RDS Proxy, which sits between the application

and the DB instance and handles connection management, pooling, and routing. The developer can query the proxy instead of the DB instance, which reduces the number of open connections to the DB instance and avoids errors for too many connections. Option A is not optimal because it will create a read replica for the DB instance, which may not solve the problem of too many connections as read replicas also have connection limits and may incur additional costs. Option B is not optimal because it will migrate the data to an Amazon DynamoDB database, which may introduce additional complexity and overhead for migrating and accessing data from a different database service. Option C is not optimal because it will configure the Amazon Aurora MySQL DB instance for Multi-AZ deployment, which may improve availability and durability of the DB instance but not reduce the number of connections.

References: [Amazon RDS Proxy], [Working with Amazon RDS Proxy]

NEW QUESTION 57

A company has an analytics application that uses an AWS Lambda function to process transaction data asynchronously. A developer notices that asynchronous invocations of the Lambda function sometimes fail. When failed Lambda function invocations occur, the developer wants to invoke a second Lambda function to

handle errors and log details.
Which solution will meet these requirements?

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Configuring a Lambda function destination with a failure condition is the best solution for invoking a second Lambda function to handle errors and log details. A Lambda function destination is a resource that Lambda sends events to after a function is invoked. The developer can specify the destination type as Lambda function and the ARN of the error-handling Lambda function as the resource. The developer can also specify the failure condition, which means that the destination is invoked only when the initial Lambda function fails. The destination event will include the response from the initial function, the request ID, and the timestamp. The other solutions are either not feasible or not efficient. Enabling AWS X-Ray active tracing on the initial Lambda function will help to monitor and troubleshoot the function performance, but it will not automatically invoke the error-handling Lambda function. Configuring a Lambda function trigger with a failure condition is not a valid option, as triggers are used to invoke Lambda functions, not to send events from Lambda functions. Creating a status check alarm on the initial Lambda function will incur additional costs and complexity, and it will not capture the details of the failed invocations. References

- ? Using AWS Lambda destinations
- ? Asynchronous invocation - AWS Lambda
- ? AWS Lambda Destinations: What They Are and Why to Use Them
- ? AWS Lambda Destinations: A Complete Guide | Dashbird

NEW QUESTION 59

A company wants to deploy and maintain static websites on AWS. Each website's source code is hosted in one of several version control systems, including AWS CodeCommit, Bitbucket, and GitHub.

The company wants to implement phased releases by using development, staging, user acceptance testing, and production environments in the AWS Cloud. Deployments to each environment must be started by code merges on the relevant Git branch. The company wants to use HTTPS for all data exchange. The company needs a solution that does not require servers to run continuously.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Host each website by using AWS Amplify with a serverless backen
- B. Conned the repository branches that correspond to each of the desired environment
- C. Start deployments by merging code changes to a desired branch.
- D. Host each website in AWS Elastic Beanstalk with multiple environment
- E. Use the EB CLI to link each repository branc
- F. Integrate AWS CodePipeline to automate deployments from version control code merges.
- G. Host each website in different Amazon S3 buckets for each environmen
- H. Configure AWS CodePipeline to pull source code from version contro
- I. Add an AWS CodeBuild stage to copy source code to Amazon S3.
- J. Host each website on its own Amazon EC2 instanc
- K. Write a custom deployment script to bundle each website's static asset
- L. Copy the assets to Amazon EC2. Set up a workflow to run the script when code is merged.

Answer: A

Explanation:

AWS Amplify is a set of tools and services that enables developers to build and deploy full-stack web and mobile applications that are powered by AWS. AWS Amplify supports hosting static websites on Amazon S3 and Amazon CloudFront, with HTTPS enabled by default. AWS Amplify also integrates with various version control systems, such as AWS CodeCommit, Bitbucket, and GitHub, and allows developers to connect different branches to different environments. AWS Amplify automatically builds and deploys the website whenever code changes are merged to a connected branch, enabling phased releases with minimal operational overhead. Reference: AWS Amplify Console

NEW QUESTION 63

A company needs to set up secure database credentials for all its AWS Cloud resources. The company's resources include Amazon RDS DB instances Amazon DocumentDB clusters and Amazon Aurora DB instances. The company's security policy mandates that database credentials be encrypted at rest and rotated at a regular interval.

Which solution will meet these requirements MOST securely?

- A. Set up IAM database authentication for token-based acces
- B. Generate user tokens to provide centralized access to RDS DB instance
- C. Amazon DocumentDB clusters and Aurora DB instances.
- D. Create parameters for the database credentials in AWS Systems Manager Parameter Store Set the Type parameter to Secure Stin
- E. Set up automatic rotation on the parameters.
- F. Store the database access credentials as an encrypted Amazon S3 object in an S3 bucket Block all public access on the S3 bucke
automatic rotation on the encryption key.
- G. Use S3 server-side encryption to set up
- H. Create an AWS Lambda function by using the SecretsManagerRotationTemplate template in the AWS Secrets Manager consol
- I. Create secrets for the database credentials in Secrets Manager Set up secrets rotation on a schedule.

Answer: D

Explanation:

This solution will meet the requirements by using AWS Secrets Manager, which is a service that helps protect secrets such as database credentials by encrypting them with AWS Key Management Service (AWS KMS) and enabling automatic rotation of secrets. The developer can create an AWS Lambda function by using the SecretsManagerRotationTemplate template in the AWS Secrets Manager console, which provides a sample code for rotating secrets for RDS DB instances, Amazon DocumentDB clusters, and Amazon Aurora DB instances. The developer can also create secrets for the database credentials in Secrets Manager, which encrypts them at rest and provides secure access to them. The developer can set up secrets rotation on a schedule, which changes the database credentials periodically according to a specified interval or event. Option A is not optimal because it will set up IAM database authentication for token-based access, which may not be compatible with all database engines and may require additional configuration and management of IAM roles or users. Option B is not optimal because it will create parameters for the database credentials in AWS Systems Manager Parameter Store, which does not support automatic rotation of secrets. Option C is not optimal because it will store the database access credentials as an encrypted Amazon S3 object in an S3 bucket, which may introduce additional costs and

complexity for accessing and securing the data.

References: [AWS Secrets Manager], [Rotating Your AWS Secrets Manager Secrets]

NEW QUESTION 68

A company has an ecommerce application. To track product reviews, the company's development team uses an Amazon DynamoDB table.

Every record includes the following

- A Review ID a 16-digit universally unique identifier (UUID)
- A Product ID and User ID 16 digit UUIDs that reference other tables
- A Product Rating on a scale of 1-5
- An optional comment from the user

The table partition key is the Review ID. The most performed query against the table is to find the 10 reviews with the highest rating for a given product.

Which index will provide the FASTEST response for this query?"

- A. A global secondary index (GSI) with Product ID as the partition key and Product Rating as the sort key
- B. A global secondary index (GSI) with Product ID as the partition key and Review ID as the sort key
- C. A local secondary index (LSI) with Product ID as the partition key and Product Rating as the sort key
- D. A local secondary index (LSI) with Review ID as the partition key and Product ID as the sort key

Answer: A

Explanation:

This solution allows the fastest response for the query because it enables the query to use a single partition key value (the Product ID) and a range of sort key values (the Product Rating) to find the matching items. A global secondary index (GSI) is an index that has a partition key and an optional sort key that are different from those on the base table. A GSI can be created at any time and can be queried or scanned independently of the base table. A local secondary index (LSI) is an index that has the same partition key as the base table, but a different sort key. An LSI can only be created when the base table is created and must be queried together with the base table partition key. Using a GSI with Product ID as the partition key and Review ID as the sort key will not allow the query to use a range of sort key values to find the highest ratings. Using an LSI with Product ID as the partition key and Product Rating as the sort key will not work because Product ID is not the partition key of the base table. Using an LSI with Review ID as the partition key and Product ID as the sort key will not allow the query to use a single partition key value to find the matching items.

Reference: [Global Secondary Indexes], [Querying]

NEW QUESTION 73

A company has deployed infrastructure on AWS. A development team wants to create an AWS Lambda function that will retrieve data from an Amazon Aurora database. The Amazon Aurora database is in a private subnet in company's VPC. The VPC is named VPC1. The data is relational in nature. The Lambda function needs to access the data

securely.

Which solution will meet these requirements?

- A. Create the Lambda function
- B. Configure VPC1 access for the function
- C. Attach a security group named SG1 to both the Lambda function and the database
- D. Configure the security group inbound and outbound rules to allow TCP traffic on Port 3306.
- E. Create and launch a Lambda function in a new public subnet that is in a new VPC named VPC2. Create a peering connection between VPC1 and VPC2.
- F. Create the Lambda function
- G. Configure VPC1 access for the function
- H. Assign a security group named SG1 to the Lambda function
- I. Assign a second security group named SG2 to the database
- J. Add an inbound rule to SG1 to allow TCP traffic from Port 3306.
- K. Export the data from the Aurora database to Amazon S3. Create and launch a Lambda function in VPC1. Configure the Lambda function query the data from Amazon S3.

Answer: A

Explanation:

AWS Lambda is a service that lets you run code without provisioning or managing servers. Lambda functions can be configured to access resources in a VPC, such as an Aurora database, by specifying one or more subnets and security groups in the VPC settings of the function. A security group acts as a virtual firewall that controls inbound and outbound traffic for the resources in a VPC. To allow a Lambda function to communicate with an Aurora database, both resources need to be associated with the same security group, and the security group rules need to allow TCP traffic on Port 3306, which is the default port for MySQL databases.

Reference: [Configuring a Lambda function to access resources in a VPC]

NEW QUESTION 77

A company is expanding the compatibility of its photo-sharing mobile app to hundreds of additional devices with unique screen dimensions and resolutions. Photos are stored in Amazon S3 in their original format and resolution. The company uses an Amazon CloudFront distribution to serve the photos. The app includes the dimension and resolution of the display as GET parameters with every request.

A developer needs to implement a solution that optimizes the photos that are served to each device to reduce load time and increase photo quality.

Which solution will meet these requirements MOST cost-effectively?

- A. Use S3 Batch Operations to invoke an AWS Lambda function to create new variants of the photos with the required dimensions and resolution
- B. Create a dynamic CloudFront origin that automatically maps the request of each device to the corresponding photo variant.
- C. Use S3 Batch Operations to invoke an AWS Lambda function to create new variants of the photos with the required dimensions and resolution
- D. Create a Lambda@Edge function to route requests to the corresponding photo variant by using request headers.
- E. Create a Lambda@Edge function that optimizes the photos upon request and returns the photos as a response
- F. Change the CloudFront TTL cache policy to the maximum value possible.

Create a Lambda@Edge function that optimizes the photos upon request and returns the photos as a response

G. In the same function store a copy of the processed photos on Amazon S3 for subsequent requests.

Answer: D

Explanation:

This solution meets the requirements most cost-effectively because it optimizes the photos on demand and caches them for future requests. Lambda@Edge allows the developer to run Lambda functions at AWS locations closer to viewers, which can reduce latency and improve photo quality. The developer can create a Lambda@Edge function that uses the GET parameters from each request to optimize the photos with the required dimensions and resolutions and returns them as a response. The function can also store a copy of the processed photos on Amazon S3 for subsequent requests, which can reduce processing time and costs. Using S3 Batch Operations to create new variants of the photos will incur additional storage costs and may not cover all possible dimensions and resolutions. Creating a dynamic CloudFront origin or a Lambda@Edge function to route requests to corresponding photo variants will require maintaining a mapping of device types and photo variants, which can be complex and error-prone.

Reference: [Lambda@Edge Overview], [Resizing Images with Amazon CloudFront & Lambda@Edge]

NEW QUESTION 81

A company is using Amazon RDS as the Backend database for its application. After a recent marketing campaign, a surge of read requests to the database increased the latency of data retrieval from the database.

The company has decided to implement a caching layer in front of the database. The cached content must be encrypted and must be highly available. Which solution will meet these requirements?

- A. Amazon Cloudfront
- B. Amazon ElastiCache to Memcached
- C. Amazon ElastiCache for Redis in cluster mode
- D. Amazon DynamoDB Accelerate (DAX)

Answer: C

Explanation:

This solution meets the requirements because it provides a caching layer that can store and retrieve encrypted data from multiple nodes. Amazon ElastiCache for Redis supports encryption at rest and in transit, and can scale horizontally to increase the cache capacity and availability. Amazon ElastiCache for Memcached does not support encryption, Amazon CloudFront is a content delivery network that is not suitable for caching database queries, and Amazon DynamoDB Accelerator (DAX) is a caching service that only works with DynamoDB tables.

Reference: [Amazon ElastiCache for Redis Features], [Choosing a Cluster Engine]

NEW QUESTION 86

A company is planning to use AWS CodeDeploy to deploy an application to Amazon Elastic Container Service (Amazon ECS) During the deployment of a new version of the application, the company initially must expose only 10% of live traffic to the new version of the deployed application. Then, after 15 minutes elapse, the company must route all the remaining live traffic to the new version of the deployed application.

Which CodeDeploy predefined configuration will meet these requirements?

- A. CodeDeployDefault ECSCanary10Percent15Minutes
- B. CodeDeployDefault LambdaCanary10Percent5Minutes
- C. CodeDeployDefault LambdaCanary10Percent15Minutes
- D. CodeDeployDefault ECSLinear10PercentEvery1 Minutes

Answer: A

Explanation:

The predefined configuration "CodeDeployDefault.ECSCanary10Percent15Minutes" is designed for Amazon Elastic Container Service (Amazon ECS) deployments and meets the specified requirements. It will perform a canary deployment, which means it will initially route 10% of live traffic to the new version of the application, and then after 15 minutes elapse, it will automatically route all the remaining live traffic to the new version. This gradual deployment approach allows

the company to verify the health and performance of the new version with a small portion of traffic before fully deploying it to all users.

NEW QUESTION 90

A developer wants to store information about movies. Each movie has a title, release year, and genre. The movie information also can include additional properties about the cast and production crew. This additional information is inconsistent across movies. For example, one movie might have an assistant director, and another movie might have an animal trainer.

The developer needs to implement a solution to support the following use cases:

For a given title and release year, get all details about the movie that has that title and release year.

For a given title, get all details about all movies that have that title. For a given genre, get all details about all movies in that genre. Which data store configuration will meet these requirements?

- A. Create an Amazon DynamoDB table.
- B. Configure the table with a primary key that consists of the title as the partition key and the release year as the sort key.
- C. Create a global secondary index that uses the genre as the partition key and the title as the sort key.
- D. Create an Amazon DynamoDB table.
- E. Configure the table with a primary key that consists of the genre as the partition key and the release year as the sort key.
- F. Create a global secondary index that uses the title as the partition key.
- G. On an Amazon RDS DB instance, create a table that contains columns for title, release year, and genre.
- H. Configure the title as the primary key.
- I. On an Amazon RDS DB instance, create a table where the primary key is the title and all other data is encoded into JSON format as one additional column.

Answer: A

Explanation:

Amazon DynamoDB is a fully managed NoSQL database service that provides fast and consistent performance with seamless scalability. The developer can create a DynamoDB table and configure the table with a primary key that consists of the title as the partition key and the release year as the sort key. This will enable querying for a given title and release year efficiently. The developer can also create a global secondary index that uses the genre as the partition key and the title as the sort key. This will enable querying for a given genre efficiently. The developer can store additional properties about the cast and production crew as attributes in the DynamoDB table. These attributes can have different data types and structures, and they do not need to be consistent across items.

References:

? [Amazon DynamoDB]

? [Working with Queries - Amazon DynamoDB]

? [Working with Global Secondary Indexes - Amazon DynamoDB]

A developer is writing a serverless application that requires an AWS Lambda function to be invoked every 10 minutes. What is an automated and serverless way to invoke the function?

- A. Deploy an Amazon EC2 instance based on Linux, and edit its `/etc/crontab` file by adding a command to periodically invoke the lambda function
- B. Configure an environment variable named `PERIOD` for the Lambda function
- C. Set the value to 600.
- D. Create an Amazon EventBridge rule that runs on a regular schedule to invoke the Lambda function.
- E. Create an Amazon Simple Notification Service (Amazon SNS) topic that has a subscription to the Lambda function with a 600-second timer.

Answer: C

Explanation:

The solution that will meet the requirements is to create an Amazon EventBridge rule that runs on a regular schedule to invoke the Lambda function. This way, the developer can use an automated and serverless way to invoke the function every 10 minutes. The developer can also use a cron expression or a rate expression to specify the schedule for the rule. The other options either involve using an Amazon EC2 instance, which is not serverless, or using environment variables or query parameters, which do not trigger the function.

Reference: [Schedule AWS Lambda functions using EventBridge](#)

NEW QUESTION 98

A developer wants to insert a record into an Amazon DynamoDB table as soon as a new file is added to an Amazon S3 bucket. Which set of steps would be necessary to achieve this?

- A. Create an event with Amazon EventBridge that will monitor the S3 bucket and then insert the records into DynamoDB.
- B. Configure an S3 event to invoke an AWS Lambda function that inserts records into DynamoDB.
- C. Create an AWS Lambda function that will poll the S3 bucket and then insert the records into DynamoDB.
- D. Create a cron job that will run at a scheduled time and insert the records into DynamoDB.

Answer: B

Explanation:

Amazon S3 is a service that provides highly scalable, durable, and secure object storage. Amazon DynamoDB is a fully managed NoSQL database service that

provides fast and consistent performance with seamless scalability. AWS Lambda is a service that lets developers run code without

provisioning or managing servers. The developer can configure an S3 event to invoke a Lambda function that inserts records into DynamoDB whenever a new file is added to the S3 bucket. This solution will meet the requirement of inserting a record into DynamoDB as soon as a new file is added to S3. References:

? [Amazon Simple Storage Service (S3)]

? [Amazon DynamoDB]

? [What Is AWS Lambda? - AWS Lambda]

? [Using AWS Lambda with Amazon S3 - AWS Lambda]

NEW QUESTION 100

A company has a social media application that receives large amounts of traffic. User posts and interactions are continuously updated in an Amazon RDS database. The data changes frequently, and the data types can be complex. The application must serve read requests with minimal latency.

The application's current architecture struggles to deliver these rapid data updates efficiently. The company needs a solution to improve the application's performance.

Which solution will meet these requirements?

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Creating an Amazon ElastiCache for Redis cluster is the best solution for improving the application's performance. Redis is an in-memory data store that can serve read requests with minimal latency and handle complex data types, such as lists, sets, hashes, and streams. By using a write-through caching strategy, the application can ensure that the data in Redis is always consistent with the data in RDS. The application can read the data from Redis instead of RDS, reducing the load on the database and improving the response time. The other solutions are either not feasible or not effective. Amazon DynamoDB Accelerator (DAX) is a caching service that works only with DynamoDB, not RDS. Amazon S3 Transfer Acceleration is a feature that speeds up data transfers between S3 and clients across the internet, not between RDS and the application. Amazon CloudFront is a content delivery network that can cache static content, such as images, videos, or HTML files, but not dynamic content, such as user posts and interactions. References:

? Amazon ElastiCache for Redis

? Caching Strategies and Best Practices - Amazon ElastiCache for Redis

? Using Amazon ElastiCache for Redis with Amazon RDS

? Amazon DynamoDB Accelerator (DAX)

? Amazon S3 Transfer Acceleration

? Amazon CloudFront

NEW QUESTION 101

A company has an Amazon S3 bucket containing premier content that it intends to make available to only paid subscribers of its website. The S3 bucket currently has default permissions of all objects being private to prevent inadvertent exposure of the premier content to non-paying website visitors.

How can the company limit the ability to download a premier content file in the S3 Bucket to paid subscribers only?

- A. Apply a bucket policy that allows anonymous users to download the content from the S3 bucket.
- B. Generate a pre-signed object URL for the premier content file when a paid subscriber requests a download.
- C. Add a Docket policy that requires multi-factor authentication for request to access the S3 bucket objects.
- D. Enable server-side encryption on the S3 bucket for data protection against the non-paying website visitors.

Answer: B

Explanation:

This solution will limit the ability to download a premier content file in the S3 bucket to paid subscribers only because it uses a pre-signed object URL that grants temporary access to an S3 object for a specified duration. The pre-signed object URL can be generated by the company's website when a paid subscriber requests a download, and can be verified by Amazon S3 using the signature in the URL. Option A is not optimal because it will allow anyone to download the content from the S3 bucket without verifying their subscription status. Option C is not optimal because it will require additional steps and costs to configure multi-factor authentication for accessing the S3 bucket objects, which may not be feasible or user-friendly for paid subscribers. Option D is not optimal because it will not prevent non-paying website visitors from accessing the S3 bucket objects, but only encrypt them at rest.

References: Share an Object with Others, [Using Amazon S3 Pre-Signed URLs]

NEW QUESTION 103

A developer is modifying an existing AWS Lambda function. While checking the code, the developer notices hardcoded parameter values for an Amazon RDS for SQL Server user name, password, database, host, and port. There also are hardcoded parameter values for an Amazon DynamoDB table, an Amazon S3 bucket, and an Amazon Simple Notification Service (Amazon SNS) topic. The developer wants to securely store the parameter values outside the code in an encrypted format and wants to turn on rotation for the credentials. The developer also wants to be able to reuse the parameter values from other applications and to update the parameter values without modifying code. Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an RDS database secret in AWS Secrets Manager
- B. Set the user name, password, database, host, and port
- C. Turn on secret rotation
- D. Create encrypted Lambda environment variables for the DynamoDB table, S3 bucket, and SNS topic.
- E. Create an RDS database secret in AWS Secrets Manager
- F. Set the user name, password, database, host, and port
- G. Turn on secret rotation
- H. Create Secure String parameters in AWS Systems Manager Parameter Store for the DynamoDB table, S3 bucket, and SNS topic.
- I. Create RDS database parameters in AWS Systems Manager Parameter Store
- J. Store for the user name, password, database, host, and port
- K. Create encrypted Lambda environment variables for the DynamoDB table, S3 bucket, and SNS topic
- L. Create a Lambda function and set the logic for the credentials rotation task. Schedule the credentials rotation task in Amazon EventBridge.
- M. Create RDS database parameters in AWS Systems Manager Parameter Store
- N. Store for the user name, password, database, host, and port
- O. Store the DynamoDB table
- P. S3 bucket, and SNS topic in Amazon S3. Create a Lambda function and set the logic for the credentials rotation. Invoke the Lambda function on a schedule.

Answer: B

Explanation:

This solution will meet the requirements by using AWS Secrets Manager and AWS Systems Manager Parameter Store to securely store the parameter values outside the code in an encrypted format. AWS Secrets Manager is a service that helps protect secrets such as database credentials by encrypting them with AWS Key Management Service (AWS KMS) and enabling automatic rotation of secrets. The developer can create an RDS database secret in AWS Secrets Manager and set the user name, password, database, host, and port for accessing the RDS database. The developer can also turn on secret rotation, which will change the database credentials periodically according to a specified schedule or event. AWS Systems Manager Parameter Store is a service that provides secure and scalable storage for configuration data and secrets. The developer can create Secure String parameters in AWS Systems Manager Parameter Store for the DynamoDB table, S3 bucket, and SNS topic, which will encrypt them with AWS KMS. The developer can also reuse the parameter values from other applications and update them without modifying code. Option A is not optimal because it will create encrypted Lambda

DynamoDB table, S3 bucket, and SNS topic, which may not be reusable or updatable without modifying code. Option C is not optimal because it will create RDS database parameters in AWS Systems Manager Parameter Store, which does not support automatic rotation of secrets. Option D is not optimal because it will store the DynamoDB table, S3 bucket, and SNS topic in Amazon S3, which may introduce additional costs and complexity for accessing configuration data. References: AWS Secrets Manager, [AWS Systems Manager Parameter Store]

NEW QUESTION 107

An application uses Lambda functions to extract metadata from files uploaded to an S3 bucket; the metadata is stored in Amazon DynamoDB. The application starts behaving unexpectedly, and the developer wants to examine the logs of the Lambda function code for errors. Based on this system configuration, where would the developer find the logs?

- A. Amazon S3
- B. AWS CloudTrail
- C. Amazon CloudWatch
- D. Amazon DynamoDB

Answer: C

Explanation:

Amazon CloudWatch is the service that collects and stores logs from AWS Lambda functions. The developer can use CloudWatch Logs Insights to query and analyze the logs for errors and metrics. Option A is not correct because Amazon S3 is a storage service that does not store Lambda function logs. Option B is not correct because AWS CloudTrail is a service that records API calls and events for AWS services, not Lambda function logs. Option D is not correct because Amazon DynamoDB is a database service that does not store Lambda function logs. References: AWS Lambda Monitoring, [CloudWatch Logs Insights]

NEW QUESTION 109

A company is migrating its PostgreSQL database into the AWS Cloud. The company wants to use a database that will secure and regularly rotate database credentials. The company wants a solution that does not require additional programming overhead. Which solution will meet these requirements?

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

This solution meets the requirements because it uses a PostgreSQL-compatible database that can secure and regularly rotate database credentials without requiring additional programming overhead. Amazon Aurora PostgreSQL is a relational database service that is compatible with PostgreSQL and offers high performance, availability, and scalability. AWS Secrets Manager is a service that helps you protect secrets needed to access your applications, services, and IT resources. You can store database credentials in AWS Secrets Manager and use them to access your Aurora PostgreSQL database. You can also enable automatic rotation of your secrets according to a schedule or an event. AWS Secrets Manager handles the complexity of rotating secrets for you, such as generating new passwords and updating your database with the new credentials. Using Amazon DynamoDB for the database will not meet the requirements because it is a NoSQL database that is not compatible with PostgreSQL. Using AWS Systems Manager Parameter Store for storing and rotating database credentials will require additional programming overhead to integrate with your database. Reference: [What Is Amazon Aurora?], [What Is AWS Secrets Manager?]

NEW QUESTION 111

A company built a new application in the AWS Cloud. The company automated the bootstrapping of new resources with an Auto Scaling group by using AWS CloudFormation templates. The bootstrap scripts contain sensitive data. The company needs a solution that is integrated with CloudFormation to manage the sensitive data in the bootstrap scripts. Which solution will meet these requirements in the MOST secure way?

- A. Put the sensitive data into a CloudFormation parameter
- B. Encrypt the CloudFormation templates by using an AWS Key Management Service (AWS KMS) key.
- C. Put the sensitive data into an Amazon S3 bucket. Update the CloudFormation templates to download the object from Amazon S3 during bootstrap.
- D. Put the sensitive data into AWS Systems Manager Parameter Store as a secure string parameter
- E. Update the CloudFormation templates to use dynamic references to specify template values.
- F. Put the sensitive data into Amazon Elastic File System (Amazon EFS). Enforce EFS encryption after file system creation.
- G. Update the CloudFormation templates to retrieve data from Amazon EFS.

Answer: C

Explanation:

This solution meets the requirements in the most secure way because it uses a service that is integrated with CloudFormation to manage sensitive data in encrypted form. AWS Systems Manager Parameter Store provides secure, hierarchical storage for configuration data management and secrets management. You can store sensitive data as secure string parameters, which are encrypted using an AWS Key Management Service (AWS KMS) key of your choice. You can also use dynamic references in your CloudFormation templates to specify template values that are stored in Parameter Store or Secrets Manager without having to include them in your templates. Dynamic references are resolved only during stack creation or update operations, which reduces exposure risks for sensitive data. Putting sensitive data into a CloudFormation parameter will not encrypt them or protect them from unauthorized access. Putting sensitive data into an Amazon S3 bucket or Amazon Elastic File System (Amazon EFS) will require additional configuration and integration with CloudFormation and may not provide fine-grained access control or encryption for sensitive data. Reference: [What Is AWS Systems Manager Parameter Store?], [Using Dynamic References to Specify Template Values]

NEW QUESTION 112

A company is building a microservices application that consists of many AWS Lambda functions. The development team wants to use AWS Serverless Application Model (AWS SAM) templates to automatically test the Lambda functions. The development team plans to test a small percentage of traffic that is directed to new updates before the team commits to a full deployment of the application. Which combination of steps will meet these requirements in the MOST operationally efficient way? (Select TWO.)

- A. Use AWS SAM CLI commands in AWS CodeDeploy to invoke the Lambda functions to test the deployment
- B. Declare the EventInvokeConfig on the Lambda functions in the AWS SAM templates with OnSuccess and OnFailure configurations.
Enable gradual deployments through AWS SAM templates.
- D**. Set the deployment preference type to Canary10Percent30Minutes Use hooks to test the deployment.
- E. Set the deployment preference type to Linear10PercentEvery10Minutes Use hooks to test the deployment.

Answer: CD

Explanation:

This solution will meet the requirements by using AWS Serverless Application Model (AWS SAM) templates and gradual deployments to automatically test the Lambda functions. AWS SAM templates are configuration files that define serverless applications and resources such as Lambda functions. Gradual deployments are a feature of AWS SAM that enable deploying new versions of Lambda functions incrementally, shifting traffic gradually, and performing validation tests during deployment. The developer can enable gradual deployments through AWS SAM templates by adding a DeploymentPreference property to each Lambda function resource in the template. The developer can set the deployment preference type to Canary10Percent30Minutes, which means that 10 percent of traffic will be shifted to the new version of the Lambda function for 30 minutes before shifting 100 percent of traffic. The developer can also use hooks to test the deployment, which are custom Lambda functions that run before or after traffic shifting and perform validation tests or rollback actions.

References: [AWS Serverless Application Model (AWS SAM)], [Gradual Code Deployment]

NEW QUESTION 117

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual DVA-C02 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the DVA-C02 Product From:

<https://www.2passeasy.com/dumps/DVA-C02/>

Money Back Guarantee

DVA-C02 Practice Exam Features:

- * DVA-C02 Questions and Answers Updated Frequently
- * DVA-C02 Practice Questions Verified by Expert Senior Certified Staff
- * DVA-C02 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * DVA-C02 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year