



Amazon

Exam Questions AWS-Certified-Developer-Associate

Amazon AWS Certified Developer - Associate

NEW QUESTION 1

A user is running a MySQL RDS instance. The user will not use the DB for the next 3 months. How can the user save costs?

- A. Pause the RDS instance from CLI until it is required in the future
- B. Stop the RDS instance
- C. Create a snapshot of RDS to launch in the future and terminate the instance now
- D. Change the instance size to micro

Answer: C

Explanation:

The RDS instances unlike the AWS EBS backed instances cannot be stopped or paused. The user needs to take the final snapshot, terminate the instance and launch a new instance in the future from that snapshot

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 2

An organization has 500 employees. The organization wants to set up AWS access for each department. Which of the below mentioned options is a possible solution?

- A. Create IAM roles based on the permission and assign users to each role
- B. Create IAM users and provide individual permission to each
- C. Create IAM groups based on the permission and assign IAM users to the groups
- D. It is not possible to manage more than 100 IAM users with AWS

Answer: C

Explanation:

An IAM group is a collection of IAM users. Groups let the user specify permissions for a collection of users, which can make it easier to manage the permissions for those users.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_WorkingWithGroupsAndUsers.html

NEW QUESTION 3

How long can you keep your Amazon SQS messages in Amazon SQS queues?

- A. From 120 secs up to 4 weeks
- B. From 10 secs up to 7 days
- C. From 60 secs up to 2 weeks
- D. From 30 secs up to 1 week

Answer: C

Explanation:

The SQS message retention period is configurable and can be set anywhere from 1 minute to 2 weeks. The default is 4 days and once the message retention limit is reached your messages will be automatically deleted. The option for longer message retention provides greater flexibility to allow for longer intervals between message production and consumption.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 4

In regard to DynamoDB, which of the following statements is correct?

- A. An Item should have at least two value sets, a primary key and another attribute.
- B. An Item can have more than one attributes.
- C. A primary key should be single-valued.
- D. An attribute can have one or several other attribute

Answer: B

Explanation:

In Amazon DynamoDB, a database is a collection of tables. A table is a collection of items and each item is a collection of attributes.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 5

Regarding Amazon SNS, when you want to subscribe to a topic and receive notifications to your email, in the Protocol drop-down box, you should select .

- A. Email
- B. Message
- C. SMTP
- D. IMAP

Answer: A

Explanation:

In Amazon SNS, when you want to subscribe to a topic and receive notifications to your email, select Email in the Protocol drop-down box. Enter an email address you can use to receive the notification in the Endpoint field.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SubscribeTopic.html>

NEW QUESTION 6

In Amazon EC2, which of the following is the type of monitoring data for Amazon EBS volumes that is available automatically in 5-minute periods at no charge?

- A. Primary
- B. Basic
- C. Initial
- D. Detailed

Answer: B

Explanation:

Basic is the type of monitoring data (for Amazon EBS volumes) which is available automatically in 5-minute periods at no charge called.

Reference:

<http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/monitoring-volume-status.html>

NEW QUESTION 7

In DynamoDB, to get a detailed listing of secondary indexes on a table, you can use the action.

- A. DescribeTable
- B. BatchGetItem
- C. GetItem
- D. TableName

Answer: A

Explanation:

In DynamoDB, DescribeTable returns information about the table, including the current status of the table, when it was created, the primary key schema, and any indexes on the table.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

NEW QUESTION 8

is a task coordination and state management service for cloud applications.

- A. Amazon SES
- B. Amazon SWF
- C. Amazon FPS
- D. Amazon SNS

Answer: B

Explanation:

Amazon Simple Workflow (Amazon SWF) is a task coordination and state management service for cloud applications. With Amazon SWF, you can stop writing complex glue-code and state machinery and invest more in the business logic that makes your applications unique.

Reference: <http://aws.amazon.com/swf/>

NEW QUESTION 9

When you create a table with a hash-and-range key, you must define one or more secondary indexes on that table.

- A. False, hash-range key is another name for secondary index
- B. False, it is optional
- C. True
- D. False, when you have Hash-Range key you cannot define Secondary index

Answer: B

Explanation:

When you create a table with a hash-and-range key in DynamoDB, you can also define one or more secondary indexes on that table.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/LSI.html>

NEW QUESTION 10

A user has created a MySQL RDS instance with PIOPS. Which of the below mentioned statements will help user understand the advantage of PIOPS?

- A. The user can achieve additional dedicated capacity for the EBS I/O with an enhanced RDS option
- B. It uses optimized EBS volumes and optimized configuration stacks
- C. It provides a dedicated network bandwidth between EBS and RDS
- D. It uses a standard EBS volume with optimized configuration the stacks

Answer: B

Explanation:

RDS DB instance storage comes in two types: standard and provisioned IOPS. Standard storage is allocated on the Amazon EBS volumes and connected to the user's DB instance. Provisioned IOPS uses optimized EBS volumes and an optimized configuration stack. It provides additional, dedicated capacity for the EBS I/O.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 10

A user has not enabled versioning on an S3 bucket. What will be the version ID of the object inside that bucket?

- A. There will be no version attached
- B. Null
- C. Blank

Answer: C

Explanation:

S3 objects stored in the bucket before the user has set the versioning state have a version ID of null. When the user enables versioning, the objects in the bucket do not change and their ID remains null. Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/AddingObjectstoVersionSuspendedBuckets.html>

NEW QUESTION 14

What happens if your application performs more reads or writes than your provisioned capacity?

- A. Nothing
- B. requests above your provisioned capacity will be performed but you will receive 400 error codes.
- C. requests above your provisioned capacity will be performed but you will receive 200 error codes.
- D. requests above your provisioned capacity will be throttled and you will receive 400 error code

Answer: D

Explanation:

Speaking about DynamoDB, if your application performs more reads/second or writes/second than your table's provisioned throughput capacity allows, requests above your provisioned capacity will be throttled and you will receive 400 error codes.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ProvisionedThroughputIntro.html>

NEW QUESTION 16

In relation to Amazon SQS, how can you ensure that messages are delivered in order?

- A. Increase the size of your queue
- B. Send them with a timestamp
- C. Give each message a unique id.
- D. AWS cannot guarantee that you will receive messages in the exact order you sent them

Answer: D

Explanation:

Amazon SQS makes a best effort to preserve order in messages, but due to the distributed nature of the queue, AWS cannot guarantee that you will receive messages in the exact order you sent them. You typically place sequencing information or timestamps in your messages so that you can reorder them upon receipt.

Reference: <https://aws.amazon.com/items/1343?externalID=1343>

NEW QUESTION 17

An orgAMzation has launched two applications: one for blogging and one for ECM on the same AWS Linux EC2 instance running in the AWS VPC. The orgAMzation has attached two private IPs (primary and secondary) to the above mentioned instance. The orgAMzation wants the instance OS to recognize the secondary IP address. How can the orgAMzation configure this?

- A. Use the ec2-net-utility package which updates routing tables, uses DHCP to refresh the secondary IP and adds the network interface.
- B. Use the ec2-net-utils package which will configure an additional network interface and update the routing table
- C. Use the ec2-ip-update package which can configure the network interface as well as update the secondary IP with DHCP.
- D. Use the ec2-ip-utility package which can update the routing tables as well as refresh the secondary IP using DHCP.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. With VPC the user can specify multiple private IP addresses for his instances. The number of network interfaces and private IP addresses that a user can specify for an instance depends on the instance type. This scenario helps when the user wants to host multiple websites on a single EC2 instance. After the user has assigned a secondary private IP address to his instance, he needs to configure the operating system on that instance to recognize the secondary private IP address. For AWS Linux, the ec2-net-utils package can take care of this step. It configures additional network interfaces that the user can attach while the instance is running, refreshes secondary IP addresses during DHCP lease renewal, and updates the related routing rules.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/MultipleIP.html>

NEW QUESTION 20

In Amazon SNS, to send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following, except:

- A. Client secret
- B. Client ID
- C. Device token
- D. Registration ID

Answer: C

Explanation:

To send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following: Registration ID and Client secret.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePushPrereq.html>

NEW QUESTION 22

Regarding Amazon SNS, to begin using Amazon SNS mobile push notifications, you first need that uses one of the supported push notification services: APNS, GCM, or ADM.

- A. an access policy for the mobile endpoints
- B. to active push notification service of Amazon SNS
- C. to know the type of mobile device operating system
- D. an app for the mobile endpoints

Answer: D

Explanation:

In Amazon SNS, to begin using Amazon SNS mobile push notifications, you first need an app for the mobile endpoints that uses one of the supported push notification services: APNS, GCM, or ADM. After you've registered and configured the app to use one of these services, you configure Amazon SNS to send push notifications to the mobile endpoints.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePush.html>

NEW QUESTION 25

How many types of block devices does Amazon EC2 support?

- A. 5
- B. 1
- C. 2
- D. 4

Answer: C

Explanation:

Amazon EC2 supports 2 types of block devices. Reference:

<http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/block-device-mapping-concepts.html>

NEW QUESTION 28

Can you SSH to your private machines that reside in a VPC from outside without elastic IP?

- A. Yes, but only if you have direct connect or vpn
- B. Only if you are using a non-US region
- C. Only if you are using a US region
- D. No

Answer: A

Explanation:

The instances that reside in the private subnets of your VPC are not reachable from the Internet, meaning that it is not possible to ssh into them. To interact with them you can use a bastion server, located in a public subnet, that will act as a proxy for them.

You can also connect if you have direct connect or vpn.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Scenario2.html

NEW QUESTION 32

Does AWS CloudFormation support Amazon EC2 tagging?

- A. It depends if the Amazon EC2 tagging has been defined in the template.
- B. No, it doesn't support Amazon EC2 tagging.
- C. No, CloudFormation doesn't support any tagging
- D. Yes, AWS CloudFormation supports Amazon EC2 tagging

Answer: D

Explanation:

In AWS CloudFormation, Amazon EC2 resources that support the tagging feature can also be tagged in an AWS template. The tag values can refer to template parameters, other resource names, resource attribute values (e.g. addresses), or values computed by simple functions (e.g., a concatenated list of strings).

Reference: <http://aws.amazon.com/cloudformation/faqs/>

NEW QUESTION 34

A user has created a MySQL RDS instance. Which of the below mentioned options is mandatory to configure while creating an instance?

- A. Multi AZ deployment setup
- B. Automated backup window
- C. Availability Zone
- D. Maintenance window

Answer: A

Explanation:

When creating an RDS instance, the user needs to specify whether it is Multi AZ or not. If the user does not provide the value for the zone, the maintenance window or automated backup window, RDS will automatically select the value.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Concepts.MultiAZ.html>

NEW QUESTION 38

A user has enabled the automated backup, but not specified the backup window. What will RDS do in this case?

- A. Will throw an error on instance launch
- B. RDS will take 3 AM — 3:30 AM as the default window
- C. RDS assigns a random time period based on the region
- D. Will not allow to launch a DB instance

Answer: C

Explanation:

If the user does not specify a preferred backup window while enabling an automated backup, Amazon RDS assigns a default 30-minute backup window which is selected at random from an 8-hour block of time per region. Reference:

<http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 40

How long are the messages kept on an SQS queue by default?

- A. If a message is not read, it is never deleted
- B. 2 weeks
- C. 1 day
- D. 4 days

Answer: D

Explanation:

The SQS message retention period is configurable and can be set anywhere from 1 minute to 2 weeks. The default is 4 days and once the message retention limit is reached your messages will be automatically deleted. The option for longer message retention provides greater flexibility to allow for longer intervals between message production and consumption.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 44

A user has attached one RDS security group with 5 RDS instances. The user has changed the ingress rule for the security group. What will be the initial status of the ingress rule?

- A. Approving
- B. Implementing
- C. Authorizing
- D. It is not possible to assign a single group to multiple DB instances

Answer: C

Explanation:

When the user makes any changes to the RDS security group the rule status will be authorizing for some time until the changes are applied to all instances that the group is connected with. Once the changes are propagated the rule status will change to authorized.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_WorkingWithSecurityGroups.html

NEW QUESTION 46

A user has attached an EBS volume to a running Linux instance as a "/dev/sdf" device. The user is unable to see the attached device when he runs the command "df -h". What is the possible reason for this?

- A. The volume is not in the same AZ of the instance
- B. The volume is not formatted
- C. The volume is not attached as a root device
- D. The volume is not mounted

Answer: D

Explanation:

When a user creates an EBS volume and attaches it as a device, it is required to mount the device. If the device/volume is not mounted it will not be available in the listing.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/AmazonEBS.html>

NEW QUESTION 47

A user has setup an application on EC2 which uses the IAM user access key and secret access key to make secure calls to S3. The user wants to temporarily stop the access to S3 for that IAM user. What should the root owner do?

- A. Delete the IAM user
- B. Change the access key and secret access key for the users
- C. Disable the access keys for the IAM user
- D. Stop the instance

Answer: C

Explanation:

If the user wants to temporarily stop the access to S3 the best solution is to disable the keys. Deleting the user will result in a loss of all the credentials and the app will not be useful in the future. If the user stops the instance IAM users can still access S3. The change of the key does not help either as they are still active. The

best possible solution is to disable the keys.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/NlmanagingCredential\[s\].html](http://docs.aws.amazon.com/IAM/latest/UserGuide/NlmanagingCredential[s].html)

NEW QUESTION 52

When should a user try to Force Detach an EBS volume?

- A. If the volume is stuck in a detaching state
- B. If the volume is not accessible from the instance
- C. If the volume is not unmounted and the user still wants to detach
- D. If the volume is a root volume

Answer: A

Explanation:

If an EBS volume stays in the detaching state, the user can force the detachment by clicking Force Detach. Forcing the detachment can lead to either data loss or a corrupted file system. The user should use this option only as a last resort to detach a volume from a failed instance or if he is detaching a volume with the intention of deleting it.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 57

How can a user configure three termination policies for the AutoScaling group?

- A. Define multiple policies in random order
- B. Define multiple policies in the ordered list
- C. Keep updating the AutoScaling group with each policy
- D. The user cannot specify more than two policies for AutoScaling

Answer: B

Explanation:

To configure the Auto Scaling termination policy, the user can either specify any one of the policies as a standalone policy or list multiple policies in an ordered list. The policies are executed in the order that they are listed.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/us-termination-policy.html>

NEW QUESTION 58

A user wants to configure AutoScaling which scales up when the CPU utilization is above 70% and scales down when the CPU utilization is below 30%. How can the user configure AutoScaling for the above mentioned condition?

- A. Use AutoScaling with a schedule
- B. Configure ELB to notify AutoScaling on load increase or decrease
- C. Use dynamic AutoScaling with a policy
- D. Use AutoScaling by manually modifying the desired capacity during a condition

Answer: C

Explanation:

The user can configure the AutoScaling group to automatically scale up and then scale down based on the specified conditions. To configure this, the user must setup policies which will get triggered by the CloudWatch alarms.

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-scale-based-on-demand.html>

NEW QUESTION 60

You have a number of image files to encode. In an Amazon SQS worker queue, you create an Amazon SQS message for each file specifying the command (jpeg-encode) and the location of the file in Amazon S3. Which of the following statements best describes the functionality of Amazon SQS?

- A. Amazon SQS is for single-threaded sending or receiving speeds.
- B. Amazon SQS is a non-distributed queuing system.
- C. Amazon SQS is a distributed queuing system that is optimized for horizontal scalability, not for single-threaded sending or receiving speeds.
- D. Amazon SQS is a distributed queuing system that is optimized for vertical scalability and for single-threaded sending or receiving speeds.

Answer: C

Explanation:

Amazon SQS is a distributed queuing system that is optimized for horizontal scalability, not for single-threaded sending or receiving speeds. A single client can send or receive Amazon SQS messages at a rate of about 5 to 50 messages per second. Higher receive performance can be achieved by requesting multiple messages (up to 10) in a single call. It may take several seconds before a message that has been to a queue is available to be received.

Reference: http://media.amazonwebservices.com/AWS_Storage_Options.pdf

NEW QUESTION 63

Can you configure an RDS Read Replica using CloudFormation templates?

- A. Yes, provided that you have root access.
- B. Yes, when you create a new CloudFormation template
- C. Yes, but not for all Regions.
- D. No, you can add the ReadReplica only when the resource is made available by CloudFormation

Answer:

B

Explanation:

AWS CloudFormation gives developers and systems administrators an easy way to create and manage collections of AWS resources. You can now set Read Replicas for your databases with RDS when you create a new CloudFormation template. You can start using it with the sample template of CloudFormation.

Reference:

https://s3.amazonaws.com/cloudformation-templates-us-east-1/RDS_MySQL_With_Read_Replica.template

NEW QUESTION 66

A user is creating an ELB with VPC. Which of the following options is available as a part of the "Add EC2 instances" page?

- A. Select Subnet
- B. Select IAM
- C. Select ENI
- D. Select VPC

Answer: A

Explanation:

When a user is launching an ELB with VPC, he/she has to select the options, such as subnet and security group before selecting the instances part of that subnet.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/elb-getting-started.html>

NEW QUESTION 67

An account owner has created an IAM user with the name examkiller. The account owner wants to give EC2 access of only the US West region to that IAM user. How can the owner configure this?

- A. While creating a policy provide the region as a part of the resources
- B. Create an IAM user in the US West region and give access to EC2
- C. Create an IAM policy and define the region in the condition
- D. It is not possible to provide access based on the region

Answer: C

Explanation:

The IAM policy is never region specific. If the user wants to configure the region specific setting, he needs to provide conditions as part of the policy.

Reference: <http://awspolicygen.s3.amazonaws.com/policygen.html>

NEW QUESTION 69

In DynamoDB, the default table size is:

- A. 5 GB
- B. 1 GB
- C. 10 GB
- D. There is no table size

Answer: D

Explanation:

DynamoDB has seamless scalability with no table size limits and unlimited storage, so you shouldn't be worried about managing storage on the host or to provisioning more drive, as your data requirement changes.

Reference: <http://aws.amazon.com/dynamodb/>

NEW QUESTION 73

You want to have multiple versions of your application running at the same time, with all versions launched via AWS Elastic Beanstalk. Is this possible?

- A. N
- B. However if you have 2 AWS accounts this can be done
- C. N
- D. AWS Elastic Beanstalk is not designed to support multiple running environments
- E. Ye
- F. AWS Elastic Beanstalk is designed to support a number of multiple running environments
- G. Ye
- H. However AWS Elastic Beanstalk is designed to support only 2 multiple running environments

Answer: C

Explanation:

AWS Elastic Beanstalk is designed to support multiple running environments. As an example you could have one for integration testing, one for pre-production, and one for production, with each environment independently configured and running on its own separate AWS resources.

Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 76

In regard to DynamoDB, what is the Global secondary index?

- A. An index with a hash and range key that can be different from those on the table.
- B. An index that has the same range key as the table, but a different hash key

- C. An index that has the same hash key and range key as the table
- D. An index that has the same hash key as the table, but a different range key

Answer: A

Explanation:

Global secondary index - an index with a hash and range key that can be different from those on the table.
Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 77

A user has launched an EC2 instance and installed a website with the Apache webserver. The webserver is running but the user is not able to access the website from the internet. What can be the possible reason for this failure?

- A. The security group of the instance is not configured properly.
- B. The instance is not configured with the proper key-pairs.
- C. The Apache website cannot be accessed from the internet.
- D. Instance is not configured with an elastic IP

Answer: A

Explanation:

In Amazon Web Services, when a user has configured an instance with Apache, the user needs to ensure that the ports in the security group are opened as configured in Apache config. E.g. If Apache is running on port 80, the user should open port 80 in the security group.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-network-security.html>

NEW QUESTION 78

A user had defined an IAM policy similar to the one given below on a bucket:

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow",
    "Principal": {
      "AWS": "arn:aws:iam::12112112:user/test"
    }
  }],
  "Action": [ "s3:GetBucketLocation", "s3:ListBucket", "s3:GetObject" ],
  "Resource": [ "arn:aws:s3:::examkiller" ]
}
```

What will this do?

- A. It will result in an error saying invalid policy statement
- B. It will create an IAM policy for the user test
- C. Allows the user test of the AWS account ID 12112112 to perform GetBucketLocation, ListBucket and GetObject on the bucket examkiller
- D. It will allow all the IAM users of the account ID 12112112 to perform GetBucketLocation, ListBucket and GetObject on bucket examkiller

Answer: C

Explanation:

The IAM policy allows to test a user in the account 12112112 to perform: s3:GetBucketLocation s3:ListBucket s3:GetObject Amazon S3 permissions on the examkiller bucket.
Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/access-policy-language-overview.html>

NEW QUESTION 81

A user has configured a bucket S3 to host a static website. What difference will there be when static website hosting is enabled?

- A. It will help the user identify this bucket as the website root to map with the domain
- B. It will create a new version of the bucket
- C. It will not make any difference, but will help the user to configure the error page
- D. It will provide the region specific website endpoint

Answer: D

Explanation:

To host a static website, the user needs to configure an Amazon S3 bucket for website hosting and then upload the website contents to the bucket. The website is then available at the region-specific website endpoint of the bucket.
Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/WebsiteHosting.html>

NEW QUESTION 86

How does Amazon SQS allow multiple readers to access the same message queue without losing messages or processing them many times?

- A. By identifying a user by his unique id
- B. By using unique cryptography
- C. Amazon SQS queue has a configurable visibility timeout.
- D. Multiple readers can't access the same message queue

Answer: C

Explanation:

Every Amazon SQS queue has a configurable visibility timeout. For the designated amount of time after a message is read from a queue, it will not be visible to any other reader. As long as the amount of time that it takes to process the message is less than the visibility timeout, every message will be processed and deleted. In the event that the component processing the message fails or becomes unavailable, the message will again become visible to any component reading the queue once the visibility timeout ends. This allows you to have many components all reading messages from the same queue, with each working to process different messages.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 91

What does Amazon SQS provide?

- A. An asynchronous message queue service.
- B. A Simple Query Sewer, managed directly by Amazon Web Services.
- C. None of these.
- D. A synchronous message queue service.

Answer: A

Explanation:

Amazon SQS stands for Simple Queue Services, and provides a cost-effective way to decouple the components of your application through an asynchronous message queue service

Reference: <http://aws.amazon.com/sqs/>

NEW QUESTION 96

A user is trying to create a list of IAM users with the AWS console. When the IAM users are created which of the below mentioned credentials will be enabled by default for the user?

- A. IAM access key and secret access key
- B. IAM X.509 certificates
- C. Nothin
- D. Everything is disabled by default
- E. IAM passwords

Answer: C

Explanation:

Newly created IAM users have no password and no access key (access key ID and secret access key). If the user needs to administer your AWS resources using the AWS Management Console, you can create a password for the user. If the user needs to interact with AWS programmatically (using the command line interface (CLI), the AWS SDK, or service-specific APIs), you can create an access key for that user. The credentials you create for users are what they use to uniquely identify themselves to AWS.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_WorkingWithGroupsAndUsers.html

NEW QUESTION 100

Bob is an IAM user who has access to the EC2 services. Admin is an IAM user who has access to all the AWS services including IAM. Can Bob change his password?

- A. No, the IAM user can never change the password
- B. Yes, provided Admin has given Bob access to change his password
- C. Yes, only from AWS CLI
- D. Yes, only from the AWS console

Answer: B

Explanation:

The IAM users by default cannot change their password. The root owner or IAM administrator needs to set the policy in the password policy page, which should allow the user to change their password. Once it is enabled, the IAM user can always change their passwords from the AWS console or CLI.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_ManagingUserPwdSelf.htm

NEW QUESTION 101

A user has created photo editing software and hosted it on EC2. The software accepts requests from the user about the photo format and resolution and sends a message to S3 to enhance the picture accordingly. Which of the below mentioned AWS services will help make a scalable software with the AWS infrastructure in this scenario?

- A. AWS Elastic Transcoder
- B. AWS Simple Notification Service
- C. AWS Simple Queue Service
- D. AWS Glacier

Answer: C

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can configure SQS, which will decouple the call between the EC2 application and S3. Thus, the application does not keep waiting for S3 to provide the data.

Reference: <http://aws.amazon.com/sqs/faqs/>

NEW QUESTION 104

In DynamoDB, could you use IAM to grant access to Amazon DynamoDB resources and API actions?

- A. Yes
- B. Depended to the type of access
- C. In DynamoDB there is no need to grant access
- D. No

Answer: A

Explanation:

Amazon DynamoDB integrates with AWS Identity and Access Management (IAM). You can use AWS IAM to grant access to Amazon DynamoDB resources and API actions. To do this, you first write an AWS IAM policy, which is a document that explicitly lists the permissions you want to grant. You then attach that policy to an AWS IAM user or role.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/UsingIAMWithDDB.html>

NEW QUESTION 109

A user is planning to host a mobile game on EC2 which sends notifications to active users on either high score or the addition of new features. The user should get this notification when he is online on his mobile device. Which of the below mentioned AWS services can help achieve this functionality?

- A. AWS Simple Notification Service.
- B. AWS Simple Queue Service.
- C. AWS Mobile Communication Service.
- D. AWS Simple Email Service

Answer: A

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS makes it simple and cost-effective to push to mobile devices, such as iPhone, iPad, Android, Kindle Fire, and internet connected smart devices, as well as pushing to other distributed services.

Reference: <http://aws.amazon.com/sns>

NEW QUESTION 110

An organization is setting up their website on AWS. The organization is working on various security measures to be performed on the AWS EC2 instances. Which of the below mentioned security mechanisms will not help the organization to avoid future data leaks and identify security weaknesses?

- A. Perform SQL injection for application testing.
- B. Run penetration testing on AWS with prior approval from Amazon.
- C. Perform a hardening test on the AWS instance.
- D. Perform a Code Check for any memory leak

Answer: D

Explanation:

AWS security follows the shared security model where the user is as much responsible as Amazon. Since Amazon is a public cloud it is bound to be targeted by hackers. If an organization is planning to host their application on AWS EC2, they should perform the below mentioned security checks as a measure to find any security weakness/data leaks:

Perform penetration testing as performed by attackers to find any vulnerability. The organization must take an approval from AWS before performing penetration testing

Perform hardening testing to find if there are any unnecessary ports open Perform SQL injection to find any DB security issues

The code memory checks are generally useful when the organization wants to improve the application performance.

Reference: <http://aws.amazon.com/security/penetration-testing/>

NEW QUESTION 114

A root account owner is trying to setup an additional level of security for all his IAM users. Which of the below mentioned options is a recommended solution for the account owner?

- A. Enable access key and secret access key for all the IAM users
- B. Enable MFA for all IAM users
- C. Enable the password for all the IAM users
- D. Enable MFA for the root account

Answer: B

Explanation:

Multi-Factor Authentication adds an extra level of security for all the users. The user can enable MFA for all IAM users which ensures that each user has to provide an extra six digit code for authentication. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_ManagingMFA.html

NEW QUESTION 118

Which of the below mentioned options is a must to have an element as a part of the IAM policy?

- A. Condition
- B. ID
- C. Statement
- D. Version

Answer: C

Explanation:

The statement is the main element of the IAM policy and it is a must for a policy. Elements such as condition, version and ID are not required.
Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 123

Which of the below mentioned commands allows the user to share the AMI with his peers using the AWS EC2 CLI?

- A. ec2-share-image-public
- B. ec2-share-image-account
- C. ec2-share-image
- D. ec2-modify-image-attribute

Answer: D

Explanation:

A user can share an AMI with another user / peer using the command: ec2-modify-image-attribute
<AMI-ID> -| -a <AWS Account ID>
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/sharingamis-explicit.html>

NEW QUESTION 127

In regards to Amazon SQS how many times will you receive each message?

- A. At least twice
- B. Exactly once
- C. As many times as you want
- D. At least once

Answer: D

Explanation:

Amazon SQS is engineered to provide "at least once" delivery of all messages in its queues. Although most of the time, each message will be delivered to your application exactly once, you should design your system so that processing a message more than once does not create any errors or inconsistencies. Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 129

A user is running a webserver on EC2. The user wants to receive the SMS when the EC2 instance utilization is above the threshold limit. Which AWS services should the user configure in this case?

- A. AWS CloudWatch + AWS SES.
- B. AWS CloudWatch + AWS SNS.
- C. AWS CloudWatch + AWS SQS.
- D. AWS EC2 + AWS Cloudwatc

Answer: B

Explanation:

Amazon SNS makes it simple and cost-effective to push to mobile devices, such as iPhone, iPad, Android, Kindle Fire, and internet connected smart devices, as well as pushing to other distributed services. In this case, the user can configure that Cloudwatch sends an alarm on when the threshold is crossed to SNS which will trigger an SMS.
Reference: <http://aws.amazon.com/sns/>

NEW QUESTION 130

A user has setup Multi AZ with the MS SQL RDS instance. Which of the below mentioned functionalities can be achieved by the user?

- A. High availability
- B. Scalability
- C. MS SQL does not support Multi AZ
- D. Disaster recovery

Answer: C

Explanation:

The Multi AZ feature allows the user to achieve High Availability. MS SQL does not support Multi AZ. Reference: <https://aws.amazon.com/rds/faqs/#36>

NEW QUESTION 134

A user is part of a group which has a policy allowing him just read only access to EC2. The user is part of another group which has full access to EC2. What happens when the user tries to launch an instance?

- A. It will allow the user to launch the instance
- B. It will fail since the user has just read only access
- C. It will allow or deny based on the group under which the user has logged into EC2
- D. It will not allow the user to add to the conflicting groups

Answer: A

Explanation:

The IAM group policy is always aggregated. In this case, if the user does not have permission for one group, but has permission for another group, he will have full access to EC2. Unless there is specific deny policy, the user will be able to access EC2.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/PoliciesOverview.html>

NEW QUESTION 139

Can a user associate and use his own DNS with ELB instead of the DNS provided by AWS ELB?

- A. Yes, by creating a CNAME with the existing domain name provider
- B. Yes, by configuring DNS in the AWS Console
- C. No
- D. Yes, only through Route 53 by mapping ELB and DNS

Answer: A

Explanation:

The AWS ELB allows mapping a custom domain name with ELB. The user can map ELB with DNS in two ways: 1) By creating CNAME with the existing domain name service provider or 2) By creating a record with Route 53.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/using-domain-names-with-elb.html>

NEW QUESTION 142

In relation to Amazon Simple Workflow Service (Amazon SWF), what is an "ActMty Worker"?

- A. An individual task undertaken by a workflow
- B. The automation of a business process
- C. A piece of software that implements tasks
- D. All answers listed are correct

Answer: C

Explanation:

In relation to Amazon Simple Workflow Service (Amazon SWF), an actMty worker is a program that receives actMty tasks, performs them, and provides results back. Which translates to a piece of software that implements tasks.

Reference: <http://docs.aws.amazon.com/amazonswf/latest/developerguide/swf-dg-develop-actMty.html>

NEW QUESTION 145

An organization has 20 employees. The organization wants to give all the users access to the organization AWS account. Which of the below mentioned options is the right solution?

- A. Share the root credentials with all the users
- B. Create an IAM user for each employee and provide access to them
- C. It is not advisable to give AWS access to so many users
- D. Use the IAM role to allow access based on STS

Answer: B

Explanation:

AWS Identity and Access Management is a web service that enables the AWS customers to manage users and user permissions in AWS. The IAM is targeted at organizations with multiple users or systems that use AWS products such as Amazon EC2, Amazon RDS, and the AWS Management Console. With IAM, the organization can centrally manage users, security credentials such as access keys, and permissions that control which AWS resources users can access.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/IAM_Introduction.html

NEW QUESTION 148

When AutoScaling is launching a new instance based on condition, which of the below mentioned policies will it follow?

- A. Based on the criteria defined with cross zone Load balancing
- B. Launch an instance which has the highest load distribution
- C. Launch an instance in the AZ with the fewest instances
- D. Launch an instance in the AZ which has the highest instances

Answer: C

Explanation:

AutoScaling attempts to distribute instances evenly between the Availability Zones that are enabled for the user's AutoScaling group. Auto Scaling does this by attempting to launch new instances in the Availability Zone with the fewest instances.

Reference: http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AS_Concepts.html

NEW QUESTION 150

In regards to Amazon SQS how can you secure the messages in your queues?

- A. You can't
- B. Amazon SQS uses either your Access Key ID or an X.509 certificate to authenticate your identity
- C. Through your IAM access keys
- D. Don't use root access

Answer: B

Explanation:

Authentication mechanisms are provided to ensure that messages stored in Amazon SQS queues are secured against unauthorized access. Only the AWS

account owners can access the queues they create. Amazon SQS uses proven cryptographic methods to authenticate your identity, either through the use of your Access Key ID and request signature, or through the use of an X.509 certificate.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 152

Which of the below mentioned options can be a good use case for storing content in AWS RRS?

- A. Storing mission critical data Files
- B. Storing infrequently used log files
- C. Storing a video file which is not reproducible
- D. Storing image thumbnails

Answer: D

Explanation:

AWS RRS provides the same functionality as AWS S3, but at a cheaper rate. It is ideally suited for non-mission, critical applications, such as files which can be reproduced.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/UsingRRS.html>

NEW QUESTION 155

Which header received at the EC2 instance identifies the port used by the client while requesting ELB?

- A. X-Forwarded-Proto
- B. X-Requested-Proto
- C. X-Forwarded-Port
- D. X-Requested-Port

Answer: C

Explanation:

The X-Forwarded-Port request header helps the user identify the port used by the client while sending a request to ELB.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html>

NEW QUESTION 160

When you register an actMty in Amazon SWF, you provide the following information, except:

- A. a name
- B. timeout values
- C. a domain
- D. version

Answer: C

Explanation:

When designing an Amazon SWF workflow, you precisely define each of the required actMtys. You then register each actMty with Amazon SWF as an actMty type. When you register the actMty, you provide information such as a name and version, and some timeout values based on how long you expect the actMty to take.

Reference: <http://docs.aws.amazon.com/amazonswf/latest/developerguide/swf-dg-intro-to-swf.html>

NEW QUESTION 163

A user is using an EBS backed instance. Which of the below mentioned statements is true?

- A. The user will be charged for volume and instance only when the instance is running
- B. The user will be charged for the volume even if the instance is stopped
- C. The user will be charged only for the instance running cost
- D. The user will not be charged for the volume if the instance is stopped

Answer: B

Explanation:

If a user has launched an EBS backed instance, the user will be charged for the EBS volume even though the instance is in a stopped state. The instance will be charged for the EC2 hourly cost only when it is running.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 164

A user is trying to create a policy for an IAM user from the AWS console. Which of the below mentioned options is not available to the user while configuring policy?

- A. Use policy generator to create policy
- B. Use custom policy to create policy
- C. Use policy simulator to create policy
- D. Assign No permission

Answer: C

Explanation:

When a user is trying to create a policy from the AWS console, it will have options such as create policy from templates or use a policy generator. The user can

also define a custom policy or chose the option to have no permission. The policy simulator is not available in the console.
Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/IAMBestPractices.html>

NEW QUESTION 165

A user has an S3 object in the US Standard region with the content "color=red". The user updates the object with the content as "color=white". If the user tries to read the value 1 minute after it was uploaded, what will S3 return?

- A. It will return "color=white"
- B. It will return "color=red"
- C. It will return an error saying that the object was not found
- D. It may return either "color=red" or "color=white" i.
- E. any of the value

Answer: D

Explanation:

AWS S3 follows the eventual consistent model in the US Standard Region. Once the object is updated it may return the new value or the old value based on whether all the content is replicated across multiple servers until it becomes consistent (eventual).
Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/Introduction.html>

NEW QUESTION 167

AWS Elastic Beanstalk will change the health status of a web server environment tier to gray color when:

- A. AWS Elastic Beanstalk detects other problems with the environment that are known to make the application unavailable
- B. Your application hasn't responded to the application health check URL within the last one hour.
- C. Your application hasn't responded to the application health check URL within the last five minutes.
- D. Your application's health status is unknown because status is reported when the application is not in the ready state.

Answer: D

Explanation:

AWS Elastic Beanstalk will change the health status of a web server environment tier to gray color when your application's health status is unknown (because status is reported when the application is not in the ready state).
Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.healthstatus.html>

NEW QUESTION 172

A user is creating a snapshot of an EBS volume. Which of the below statements is incorrect in relation to the creation of an EBS snapshot?

- A. Its incremental
- B. It can be used to launch a new instance
- C. It is stored in the same AZ as the volume
- D. It is a point in time backup of the EBS volume

Answer: C

Explanation:

The EBS snapshots are a point in time backup of the EBS volume. It is an incremental snapshot, but is always specific to the region and never specific to a single AZ.
Hence the statement "It is stored in the same AZ as the volume" is incorrect.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSSnapshots.html>

NEW QUESTION 174

A user is planning to use EBS for his DB requirement. The user already has an EC2 instance running in the VPC private subnet. How can the user attach the EBS volume to a running instance?

- A. The user must create EBS within the same VPC and then attach it to a running instance.
- B. The user can create EBS in the same zone as the subnet of instance and attach that EBS to instance.
- C. It is not possible to attach an EBS to an instance running in VPC until the instance is stopped.
- D. The user can specify the same subnet while creating EBS and then attach it to a running instanc

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. The instance launched will always be in the same availability zone of the respective subnet. When creating an EBS the user cannot specify the subnet or VPC. However, the user must create the EBS in the same zone as the instance so that it can attach the EBS volume to the running instance.
Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.htm#VPCSubnet

NEW QUESTION 175

Which of the following groups is AWS Elastic Beanstalk best suited for?

- A. Those who want to deploy and manage their applications within minutes in the AWS cloud
- B. Those who want to privately store and manage Git repositories in the AWS cloud.
- C. Those who want to automate the deployment of applications to instances and to update the applications as required
- D. Those who want to model, visualize, and automate the steps required to release software

Answer:

A

Explanation:

AWS Elastic Beanstalk is best suited for those groups who want to deploy and manage their applications within minutes in the AWS cloud. As a bonus, you don't even need experience with cloud computing to get started.

Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 178

A user is trying to find the state of an S3 bucket with respect to versioning. Which of the below mentioned states AWS will not return when queried?

- A. versioning-enabled
- B. versioning-suspended
- C. unversioned
- D. versioned

Answer: D

Explanation:

S3 buckets can be in one of the three states: unversioned (the default), versioning-enabled or versioning-suspended. The bucket owner can configure the versioning state of a bucket. The versioning state applies to all (never some) of the objects in that bucket. The first time owner enables a bucket for versioning, objects in it are thereafter always versioned and given a unique version ID.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/Versioning.html>

NEW QUESTION 183

What is the maximum number of tags that a user can assign to an EC2 instance?

- A. 50
- B. 10
- C. 5
- D. 25

Answer: B

Explanation:

To help manage EC2 instances as well as their usage in a better way, the user can tag the instances. The tags are metadata assigned by the user which consists of a key and a value. One resource can have a maximum of 10 tags.

Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/Using_Tags.html

NEW QUESTION 188

A user has configured ELB with two instances running in separate AZs of the same region? Which of the below mentioned statements is true?

- A. NMulti AZ instances will provide HA with ELB
- B. IVMulti AZ instances are not possible with a single ELB
- C. NMulti AZ instances will provide scalability with ELB
- D. The user can achieve both HA and scalability with ELB

Answer: A

Explanation:

If a user is running two instances in separate AZs, it will provide HA with ELB since ELB will automatically stop routing the traffic to unhealthy instances and send it to healthy instances only.

NEW QUESTION 193

What is the data model of DynamoDB?

- A. "Items", with Keys and one or more Attribute; and "Attribute", with Name and Value.
- B. "Database", which is a set of "Tables", which is a set of "Items", which is a set of "Attributes".
- C. "Table", a collection of Items; "Items", with Keys and one or more Attribute; and "Attribute", with Name and Value.
- D. "Database", a collection of Tables; "Tables", with Keys and one or more Attribute; and "Attribute", with Name and Value.

Answer: C

Explanation:

The data model of DynamoDB is: "Table", a collection of Items;

"Items", with Keys and one or more Attribute; "Attribute", with Name and Value.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 194

A user is trying to configure access with S3. Which of the following options is not possible to provide access to the S3 bucket / object?

- A. Define the policy for the IAM user
- B. Define the ACL for the object
- C. Define the policy for the object
- D. Define the policy for the bucket

Answer: C

Explanation:

Amazon S3 offers access policy options broadly categorized as resource-based policies and user policies.

Access policies, such as ACL and resource policy can be attached to the bucket. With the object the user can only have ACL and not an object policy. The user can also attach access policies to the IAM users in the account. These are called user policies.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/s3-access-control.html>

NEW QUESTION 196

In regard to DynamoDB, can I modify the index once it is created?

- A. Yes, if it is a primary hash key index
- B. Yes, if it is a Global secondary index
- C. No
- D. Yes, if it is a local secondary index

Answer: C

Explanation:

Currently, in DynamoDB, an index cannot be modified once it is created. Reference: http://aws.amazon.com/dynamodb/faqs/#security_anchor

NEW QUESTION 201

ExamKiller (with AWS account ID 111122223333) has created 50 IAM users for its orgAMzation's employees. What will be the AWS console URL for these associates?

- A. [https:// 111122223333.signin.aws.amazon.com/console/](https://111122223333.signin.aws.amazon.com/console/)
- B. [https:// signin.aws.amazon.com/console/](https://signin.aws.amazon.com/console/)
- C. <https://signin.aws.amazon.com/111122223333/console/>
- D. <https://signin.aws.amazon.com/console/111122223333/>

Answer: A

Explanation:

When an orgAMzation is using AWS IAM for creating various users and manage their access rights, the IAM user cannot use the login URL

<http://aws.amazon.com/console> to access AWS management console. The console login URL for the IAM user will have AWS account ID of that orgAMzation to identify the IAM user belongs to particular account. The AWS console login URL for the IAM user will be https://<AWS_Account_ID>.signin.aws.amazon.com/console/. In this case it will be [https:// 111122223333.signin.aws.amazon.com/console/](https://111122223333.signin.aws.amazon.com/console/)

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/AccountAlias.html>

NEW QUESTION 203

A user is planning to host MS SQL on an EBS volume. It was recommended to use the AWS RDS. What advantages will the user have if he uses RDS in comparison to an EBS based DB?

- A. Better throughput with PIOPS
- B. Automated backup
- C. NIS SQL is not supported with RDS
- D. High availability with multi AZs

Answer: B

Explanation:

Comparing with on-premises or EC2 based NIS SQL, RDS provides an automated backup feature. PIOPS is available with both RDS and EBS. However, HA is not available with NIS SQL.

Reference: <https://aws.amazon.com/rds/faqs/>

NEW QUESTION 207

The user has configured AutoScaling based on the dynamic policy. Which of the following is not the right command to specify a change in capacity as a part of the policy?

- A. "adjustment=-50" (type is PercentChangeInCapacity)
- B. "adjustment=3" (type is ExactCapacity)
- C. "adjustment=-1" (type is ChangeInCapacity)
- D. "adjustment=-8" (type is ExactCapacity)

Answer: D

Explanation:

The user can configure the AutoScaling group to automatically scale up and then scale down based on the various specified CloudWatch monitoring conditions. The user needs to provide the adjustment value and the adjustment type. A positive adjustment value increases the current capacity and a negative adjustment value decreases the current capacity. The user can express the change to the current size as an absolute number, an increment or as a percentage of the current group size.

In this option specifying the exact capacity with the adjustment value = -8 will not work as when type is exact capacity the adjustment value cannot be negative.

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-scale-based-on-demand.html>

NEW QUESTION 212

A user has created a snapshot of an EBS volume. Which of the below mentioned usage cases is not possible with respect to a snapshot?

- A. Mirroring the volume from one AZ to another AZ

- B. Launch an instance
- C. Decrease the volume size
- D. Increase the size of the volume

Answer: C

Explanation:

The EBS snapshots are a point in time backup of the volume. It is helpful to move the volume from one AZ to another or launch a new instance. The user can increase the size of the volume but cannot decrease it less than the original snapshot size.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSSnapshots.html>

NEW QUESTION 214

True or False: AWS CloudFormation allows you to create Microsoft Windows stacks.

- A. False, AWS CloudFormation does not support Microsoft Windows.
- B. False, Amazon doesn't support Microsoft Windows.
- C. False, you cannot create Windows stacks.
- D. True

Answer: D

Explanation:

AWS CloudFormation allows you to create Microsoft Windows stacks based on Amazon EC2 Windows Amazon Machine Images (AMIs) and provides you with the ability to install software, to use remote desktop to access your stack, and to update and configure your stack.
Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/cfn-windows-stacks.html>

NEW QUESTION 215

Which of the following solutions is not supported by DynamoDB:

- A. Hash secondary index
- B. Local secondary index
- C. Hash Primary Key
- D. Global secondary index

Answer: A

Explanation:

In DynamoDB, a secondary index is a data structure that contains a subset of attributes from a table, along with an alternate key to support Query operations. DynamoDB supports the following two types of secondary indexes:
Local secondary index is an index that has the same hash key as the table, but a different range key. A local secondary index is "local" in the sense that every partition of a local secondary index is scoped to a table partition that has the same hash key.
Global secondary index is an index with a hash and range key that can be different from those on the table. A global secondary index is considered "global" because queries on the index can span all of the data in a table, across all partitions.
Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 219

An ELB is diverting traffic across 5 instances. One of the instances was unhealthy only for 20 minutes. What will happen after 20 minutes when the instance becomes healthy?

- A. ELB will never divert traffic back to the same instance
- B. ELB will not automatically send traffic to the same instance
- C. However, the user can configure to start sending traffic to the same instance
- D. ELB starts sending traffic to the instance once it is healthy
- E. ELB terminates the instance once it is unhealthy
- F. Thus, the instance cannot be healthy after 10 minutes

Answer: C

Explanation:

AWS Elastic Load Balancing continuously checks the health of an instance. If one of the instances is unhealthy it stops sending traffic to it and automatically reroutes the traffic to the remaining running EC2 instances. If the failed EC2 instance is restored, Elastic Load Balancing will again start sending traffic to that instance.
Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/SvcIntro.htm>

NEW QUESTION 222

Which OS does the current version of AWS Elastic Beanstalk use?

- A. Amazon Linux AMI, Windows Server 2003 R2 AMI or the Windows Server 2008 R2 AMI
- B. Amazon Linux AMI only
- C. Amazon Linux AMI or the Windows Server 2008 R2 AMI
- D. Windows Server 2008 R2 AMI only

Answer: C

Explanation:

The current version of AWS Elastic Beanstalk uses the Amazon Linux AMI or the Windows Server 2008 R2 AMI.
Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 226

AWS Elastic Beanstalk stores your application files and optionally server log files in .

- A. Amazon Storage Gateway
- B. Amazon Glacier
- C. Amazon EC2
- D. Amazon S3

Answer: D

Explanation:

AWS Elastic Beanstalk stores your application files and optionally server log files in Amazon S3. If you are using the AWS Management Console, Git, the AWS Toolkit for Visual Studio, or AWS Toolkit for Eclipse, an Amazon S3 bucket will be created in your account for you and the files you upload will be automatically copied from your local client to Amazon S3. Optionally, you may configure Elastic Beanstalk to copy your server log files every hour to Amazon S3. You do this by editing the environment configuration settings.

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/AWSHowTo.html>

NEW QUESTION 230

The AWS console for DynamoDB enables you to do all the following operations, except:

- A. Set up alarms to monitor your table's capacity usage.
- B. Create, update, and delete tables.
- C. Import Data from other databases or from files.
- D. View your table's top monitoring metrics on real-time graphs from CloudWatc

Answer: C

Explanation:

The AWS console for DynamoDB enables you to do all the above operation but not Importing Data from other databases or from files and it is not possible to do it.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ConsoleDynamoDB.html>

NEW QUESTION 232

An orgAMzation has created multiple components of a single application for compartmentalization. Currently all the components are hosted on a single EC2 instance. Due to security reasons the orgAMzation wants to implement two separate SSLs for the separate modules although it is already using VPC. How can the orgAMzation achieve this with a single instance?

- A. Create a VPC instance which will have both the ACL and the security group attached to it and have separate rules for each IP address.
- B. Create a VPC instance which will have multiple network interfaces with multiple elastic IP addresses.
- C. You have to launch two instances each in a separate subnet and allow VPC peering for a single IP.
- D. Create a VPC instance which will have multiple subnets attached to it and each will have a separate IP address.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. With VPC the user can specify multiple private IP addresses for his instances.

The number of network interfaces and private IP addresses that a user can specify for an instance depends on the instance type. With each network interface the orgAMzation can assign an EIP. This scenario helps when the user wants to host multiple websites on a single EC2 instance by using multiple SSL certificates on a single server and associating each certificate with a specific EIP address. It also helps in scenarios for operating network appliances, such as firewalls or load balancers that have multiple private IP addresses for each network interface.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/MultipleIP.html>

NEW QUESTION 233

In regards to VPC, select the correct statement:

- A. You can associate multiple subnets with the same Route Table.
- B. You can associate multiple subnets with the same Route Table, but you can't associate a subnet with only one Route Table.
- C. You can't associate multiple subnets with the same Route Table.
- D. None of thes

Answer: A

Explanation:

Every subnet in your VPC must be associated with exactly one Route Table. However, multiple subnets can be associated with the same Route Table.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Route_Tables.html

NEW QUESTION 236

Your supervisor has asked you to build a simple file synchronization service for your department. He doesn't want to spend too much money and he wants to be notified of any changes to files by email. What do you think would be the best Amazon service to use for the email solution?

- A. Amazon CloudSearch
- B. Amazon Elastic Transcoder
- C. Amazon SES
- D. Amazon AppStream

Answer: C

Explanation:

File change notifications can be sent via email to users following the resource with Amazon Simple Email Service (Amazon SES), an easy-to-use, cost-effective email solution.

Reference: http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_filesync_08.pdf

NEW QUESTION 241

A user has enabled automated backup for an RDS instance. What is the longest duration for which the user can retain the automated backup?

- A. 25 days
- B. 15 days
- C. 45 days
- D. 35 days

Answer: D

Explanation:

Amazon RDS provides two different methods for backing up and restoring the Amazon DB instances: automated backups and DB snapshots. Automated backups automatically back up the DB instance during a specific, user-definable backup window, and keep the backups for a limited, user-specified period of time. The maximum period can be 35 days.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 245

A user is enabling a static website hosting on an S3 bucket. Which of the below mentioned parameters cannot be configured by the user?

- A. Error document
- B. Conditional error on object name
- C. Index document
- D. Conditional redirection on object name

Answer: B

Explanation:

To host a static website, the user needs to configure an Amazon S3 bucket for website hosting and then upload the website contents to the bucket. The user can configure the index, error document as well as configure the conditional routing of on object name.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/HowDoIWebsiteConfiguration.html>

NEW QUESTION 247

A user is uploading archives to Glacier. The user is trying to understand key Glacier resources. Which of the below mentioned options is not a Glacier resource?

- A. Notification configuration
- B. Archive ID
- C. Job
- D. Archive

Answer: B

Explanation:

AWS Glacier has four resources. Vault and Archives are core data model concepts. Job is required to initiate download of archive. The notification configuration is required to send user notification when archive is available for download.

Reference: <http://docs.aws.amazon.com/amazonglacier/latest/dev/amazon-glacier-data-model.html>

NEW QUESTION 252

An organization has 10 departments. The organization wants to track the AWS usage of each department. Which of the below mentioned options meets the requirement?

- A. Setup IAM groups for each department and track their usage
- B. Create separate accounts for each department, but use consolidated billing for payment and tracking
- C. Create separate accounts for each department and track them separately
- D. Setup IAM users for each department and track their usage

Answer: B

Explanation:

The cost of an IAM user or groups can never be tracked separately for the purpose of billing. The best solution in this case is to create a separate account for each department and use consolidated billing. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/IAM_introduction.html

NEW QUESTION 257

Regarding Amazon SWF, at times you might want to record information in the workflow history of a workflow execution that is specific to your use case. enable you to record information in the workflow execution history that you can use for any custom or scenario-specific purpose.

- A. Markers B.Tags
- B. Hash keys
- C. Events

Answer: A

Explanation:

In Amazon SWF, at times you might want to record information in the workflow history of a workflow execution that is specific to your use case. Markers enable

you to record information in the workflow execution history that you can use for any custom or scenario-specific purpose.
Reference: <http://docs.aws.amazon.com/amazonswf/latest/developerguide/swf-dg-adv.html>

NEW QUESTION 262

In regard to DynamoDB, for which one of the following parameters does Amazon not charge you?

- A. Cost per provisioned write units
- B. Cost per provisioned read units
- C. Storage cost
- D. I/O usage within the same Region

Answer: D

Explanation:

In DynamoDB, you will be charged for the storage and the throughput you use rather than for the I/O which has been used.
Reference: <http://aws.amazon.com/dynamodb/pricing/>

NEW QUESTION 264

A user has configured an automated backup between 5 AM — 5:30 AM for the MySQL RDS DB. Will the performance of RDS get frozen momentarily during a backup?

- A. No
- B. Yes, only if the instance size is smaller than large size
- C. Yes, provided it is a single zone implementation
- D. Yes, always

Answer: C

Explanation:

Amazon RDS provides two different methods for backing up and restoring the Amazon DB instances. A brief I/O freeze, typically lasting a few seconds, occurs during both automated backups and DB snapshot operations on Single-AZ DB instances.
Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 265

Regarding Amazon SNS, to send messages to a queue through a topic, you must subscribe the queue to the Amazon SNS topic. You specify the queue by its .

- A. ARN
- B. Token
- C. Registration ID
- D. URL

Answer: A

Explanation:

In Amazon SNS, to send messages to a queue through a topic, you must subscribe the queue to the Amazon SNS topic. You specify the queue by its ARN.
Reference: <http://docs.aws.amazon.com/sns/latest/dg/SendMessageToSQS.html>

NEW QUESTION 266

A user wants to achieve High Availability with PostgreSQL DB. Which of the below mentioned functionalities helps achieve HA?

- A. Read Replica
- B. Multi AZ
- C. Multi region
- D. PostgreSQL does not support HA

Answer: B

Explanation:

The Multi AZ feature allows the user to achieve High Availability. For Multi AZ, Amazon RDS automatically provisions and maintains a synchronous "standby" replica in a different Availability Zone. Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 267

A user is launching an instance with EC2. Which of the below mentioned options does the user need to consider before launching an instance?

- A. Select the region where the instance is being launched.
- B. Select the instance type.
- C. All the options listed should be considered..
- D. Select the OS of the AM

Answer: C

Explanation:

Regarding Amazon EC2, when launching an instance, the user needs to select the region the instance would be launched from. While launching, the user needs to plan for the instance type and the OS of the instance.
Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-launch-instance_linux.html

NEW QUESTION 272

You have an environment that consists of a public subnet using Amazon VPC and 3 instances that are running in this subnet. These three instances can successfully communicate with other hosts on the Internet. You launch a fourth instance in the same subnet, using the same AMI and security group configuration you used for the others, but find that this instance cannot be accessed from the Internet. What should you do to enable internet access?

- A. Deploy a NAT instance into the public subnet.
- B. Modify the routing table for the public subnet
- C. Configure a publically routable IP Address In the host OS of the fourth instance.
- D. Assign an Elastic IP address to the fourth instanc

Answer: D

NEW QUESTION 275

Which of the following statements about SWF are true? Choose 3 answers

- A. SWF tasks are assigned once and never duplicated
- B. SWF requires an S3 bucket for workflow storage
- C. SWF workflow executions can last up to a year
- D. SWF triggers SNS notifications on task assignment
- E. SWF uses deciders and workers to complete tasks
- F. SWF requires atleast 1 EC2 instance per domain

Answer: ACE

NEW QUESTION 276

Company C has recently launched an online commerce site for bicycles on AWS. They have a "Product" DynamoDB table that stores details for each bicycle, such as, manufacturer, color, price, quantity and size to display in the online store. Due to customer demand, they want to include an image for each bicycle along with the existing details.

Which approach below provides the least impact to provisioned throughput on the "Product" table?

- A. Serialize the image and store it in multiple DynamoDB tables
- B. Create an "Images" DynamoDB table to store the Image with a foreign key constraint to the "Product" table
- C. Add an image data type to the "Product" table to store the images in binary format
- D. Store the images in Amazon S3 and add an S3 URL pointer to the "Product" table item for each image

Answer: D

NEW QUESTION 279

A startup s photo-sharing site is deployed in a VPC. An ELB distributes web traffic across two subnets. ELB session stickiness is configured to use the AWS-generated session cookie, with a session TTL of 5 minutes. The webserver Auto Scaling Group is configured as: min-size=4, max-size=4.

The startups preparing for a public launch, by running load-testing software installed on a single EC2 instance running in us-west-2a. After 60 minutes of load-testing, the webserver logs show:

WEBSERVER LOGS	# of HTTP requests from load-tester	# of HTTP requests from private beta users
webserver #1 (subnet in us-west-2a):	19,210	434
webserver #2 (subnet in us-west-2a):	21,790	490
webserver #3 (subnet in us-west-2b):	0	410
webserver #4 (subnet in us-west-2b):	0	428

Which recommendations can help ensure load-testing HTTP requests are evenly distributed across the four webserver? Choose 2 answers

- A. Launch and run the load-tester EC2 instance from us-east-1 instead.
- B. Re-configure the load-testing software to re-resolve DNS for each web request.
- C. Use a 3rd-party load-testing service which offers globally-distributed test clients.
- D. Configure ELB and Auto Scaling to distribute across us-west-2a and us-west-2c.
- E. Configure ELB session stickiness to use the app-specific session cooki

Answer: BE

NEW QUESTION 280

In DynamoDB, what type of HTTP response codes indicate that a problem was found with the client request sent to the service?

- A. 5xx HTTP response code
- B. 200 HTTP response code
- C. 306 HTTP response code
- D. 4xx HTTP response code

Answer: D

NEW QUESTION 282

Company C is currently hosting their corporate site in an Amazon S3 bucket with Static Website Hosting enabled. Currently, when visitors go to <http://www.companyc.com> the index.html page is returned. Company C now would like a new page welcome.html to be returned when a visitor enters <http://www.companyc.com> in the browser.

Which of the following steps will allow Company C to meet this requirement? Choose 2 answers

- A. Upload an html page named welcome.html to their S3 bucket

- B. Create a welcome subfolder in their S3 bucket
- C. Set the Index Document property to welcome.html
- D. Move the index.html page to a welcome subfolder
- E. Set the Error Document property to welcome.html

Answer: AC

NEW QUESTION 286

What item operation allows the retrieval of multiple items from a DynamoDB table in a single API call?

- A. GetItem
- B. BatchGetItem
- C. GetMultipleItems
- D. GetItemRange

Answer: B

NEW QUESTION 289

Which of the following platforms are supported by Elastic Beanstalk? Choose 2 answers

- A. Apache Tomcat
- B. .NET
- C. IBM Websphere
- D. Oracle JBoss
- E. Jetty

Answer: AB

NEW QUESTION 294

Which EC2 API call would you use to retrieve a list of Amazon Machine Images (AMIs)?

- A. DescribeInstances
- B. DescribeAMIs
- C. DescribeImages
- D. GetAMIs
- E. You cannot retrieve a list of AMIs as there are over 10,000 AMIs

Answer: E

NEW QUESTION 297

When a Simple Queue Service message triggers a task that takes 5 minutes to complete, which process below will result in successful processing of the message and remove it from the queue while minimizing the chances of duplicate processing?

- A. Retrieve the message with an increased visibility timeout, process the message, delete the message from the queue
- B. Retrieve the message with an increased visibility timeout, delete the message from the queue, process the message
- C. Retrieve the message with increased DelaySeconds, process the message, delete the message from the queue
- D. Retrieve the message with increased DelaySeconds, delete the message from the queue, process the message

Answer: A

NEW QUESTION 302

Which features can be used to restrict access to data in S3? Choose 2 answers

- A. Use S3 Virtual Hosting
- B. Set an S3 Bucket policy.
- C. Enable IAM Identity Federation.
- D. Set an S3 ACL on the bucket or the object.
- E. Create a CloudFront distribution for the bucket

Answer: CD

NEW QUESTION 306

Company B provides an online image recognition service and utilizes SQS to decouple system components for scalability. The SQS consumers poll the imaging queue as often as possible to keep end-to-end throughput as high as possible. However, Company B is realizing that polling in tight loops is burning CPU cycles and increasing costs with empty responses. How can Company B reduce the number of empty responses?

- A. Set the imaging queue visibility Timeout attribute to 20 seconds
- B. Set the Imaging queue ReceiveMessageWaitTimeSeconds attribute to 20 seconds
- C. Set the imaging queue MessageRetentionPeriod attribute to 20 seconds
- D. Set the DelaySeconds parameter of a message to 20 seconds

Answer: B

NEW QUESTION 309

What AWS products and features can be deployed by Elastic Beanstalk? Choose 3 answers

- A. Auto scaling groups
- B. Route 53 hosted zones
- C. Elastic Load Balancers
- D. RDS Instances
- E. Elastic IP addresses
- F. SQS Queues

Answer: ACD

NEW QUESTION 311

How can software determine the public and private IP addresses of the Amazon EC2 instance that it is running on?

- A. Query the appropriate Amazon CloudWatch metric.
- B. Use ipconfig or ifconfig command.
- C. Query the local instance userdata.
- D. Query the local instance metadata

Answer: D

NEW QUESTION 314

Which of the following services are key/value stores? Choose 3 answers

- A. Amazon ElastiCache
- B. Simple Notification Service
- C. DynamoDB
- D. Simple Workflow Service
- E. Simple Storage Service

Answer: ABC

NEW QUESTION 318

How is provisioned throughput affected by the chosen consistency model when reading data from a DynamoDB table?

- A. Strongly consistent reads use the same amount of throughput as eventually consistent reads
- B. Strongly consistent reads use more throughput than eventually consistent reads.
- C. Strongly consistent reads use less throughput than eventually consistent reads
- D. Strongly consistent reads use variable throughput depending on read actMty

Answer: B

NEW QUESTION 323

Which of the following services are included at no additional cost with the use of the AWS platform? Choose 2 answers

- A. Simple Storage Service
- B. Elastic Compute Cloud
- C. Auto Scaling
- D. Elastic Load Balancing
- E. CloudFormation
- F. Simple Workflow Service

Answer: CE

NEW QUESTION 326

If an application is storing hourly log files from thousands of instances from a high traffic web site, which naming scheme would give optimal performance on S3?

- A. Sequential
- B. instanceID_log-HH-DD-NIM-YYYY
- C. instanceID_log-YYYY-NIM-DD-HH
- D. HH-DD-NINI-YYYY-log_instanceID
- E. YYYY-MM-DD-HH-|og_instance|D

Answer: E

NEW QUESTION 330

You run an ad-supported photo sharing website using S3 to serve photos to visitors of your site. At some point you find out that other sites have been linking to the photos on your site, causing loss to your business.

What is an effective method to mitigate this?

- A. Store photos on an EBS volume of the web server
- B. Remove public read access and use signed URLs with expiry dates.
- C. Use CloudFront distributions for static content.
- D. Block the IPs of the offending websites in Security Group

Answer: B

NEW QUESTION 333

Which of the following is chosen as the default region when making an API call with an AWS SDK?

- A. ap-northeast-1
- B. us-west-2
- C. us-east-1
- D. eu-west-1
- E. us-central-1

Answer: C

NEW QUESTION 336

What happens, by default, when one of the resources in a CloudFormation stack cannot be created?

- A. Previously-created resources are kept but the stack creation terminates.
- B. Previously-created resources are deleted and the stack creation terminates.
- C. The stack creation continues, and the final results indicate which steps failed.
- D. CloudFormation templates are parsed in advance so stack creation is guaranteed to succeed.

Answer: B

NEW QUESTION 339

.....

About ExamBible

Your Partner of IT Exam

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

A user is running a MySQL RDS instance. The user will not use the DB for the next 3 months. How can the user save costs?

- A. Pause the RDS instance from CLI until it is required in the future
- B. Stop the RDS instance
- C. Create a snapshot of RDS to launch in the future and terminate the instance now
- D. Change the instance size to micro

Answer: C

Explanation:

The RDS instances unlike the AWS EBS backed instances cannot be stopped or paused. The user needs to take the final snapshot, terminate the instance and launch a new instance in the future from that snapshot

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 2

An organization has 500 employees. The organization wants to set up AWS access for each department. Which of the below mentioned options is a possible solution?

- A. Create IAM roles based on the permission and assign users to each role
- B. Create IAM users and provide individual permission to each
- C. Create IAM groups based on the permission and assign IAM users to the groups
- D. It is not possible to manage more than 100 IAM users with AWS

Answer: C

Explanation:

An IAM group is a collection of IAM users. Groups let the user specify permissions for a collection of users, which can make it easier to manage the permissions for those users.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_WorkingWithGroupsAndUsers.html

NEW QUESTION 3

How long can you keep your Amazon SQS messages in Amazon SQS queues?

- A. From 120 secs up to 4 weeks
- B. From 10 secs up to 7 days
- C. From 60 secs up to 2 weeks
- D. From 30 secs up to 1 week

Answer: C

Explanation:

The SQS message retention period is configurable and can be set anywhere from 1 minute to 2 weeks. The default is 4 days and once the message retention limit is reached your messages will be automatically deleted. The option for longer message retention provides greater flexibility to allow for longer intervals between message production and consumption.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 4

In regard to DynamoDB, which of the following statements is correct?

- A. An Item should have at least two value sets, a primary key and another attribute.
- B. An Item can have more than one attributes.
- C. A primary key should be single-valued.
- D. An attribute can have one or several other attribute

Answer: B

Explanation:

In Amazon DynamoDB, a database is a collection of tables. A table is a collection of items and each item is a collection of attributes.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 5

Regarding Amazon SNS, when you want to subscribe to a topic and receive notifications to your email, in the Protocol drop-down box, you should select .

- A. Email
- B. Message
- C. SMTP
- D. IMAP

Answer: A

Explanation:

In Amazon SNS, when you want to subscribe to a topic and receive notifications to your email, select Email in the Protocol drop-down box. Enter an email address you can use to receive the notification in the Endpoint field.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SubscribeTopic.html>

NEW QUESTION 6

In Amazon EC2, which of the following is the type of monitoring data for Amazon EBS volumes that is available automatically in 5-minute periods at no charge?

- A. Primary
- B. Basic
- C. Initial
- D. Detailed

Answer: B

Explanation:

Basic is the type of monitoring data (for Amazon EBS volumes) which is available automatically in 5-minute periods at no charge called.

Reference:

<http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/monitoring-volume-status.html>

NEW QUESTION 7

In DynamoDB, to get a detailed listing of secondary indexes on a table, you can use the action.

- A. DescribeTable
- B. BatchGetItem
- C. GetItem
- D. TableName

Answer: A

Explanation:

In DynamoDB, DescribeTable returns information about the table, including the current status of the table, when it was created, the primary key schema, and any indexes on the table.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

NEW QUESTION 8

is a task coordination and state management service for cloud applications.

- A. Amazon SES
- B. Amazon SWF
- C. Amazon FPS
- D. Amazon SNS

Answer: B

Explanation:

Amazon Simple Workflow (Amazon SWF) is a task coordination and state management service for cloud applications. With Amazon SWF, you can stop writing complex glue-code and state machinery and invest more in the business logic that makes your applications unique.

Reference: <http://aws.amazon.com/swf/>

NEW QUESTION 9

When you create a table with a hash-and-range key, you must define one or more secondary indexes on that table.

- A. False, hash-range key is another name for secondary index
- B. False, it is optional
- C. True
- D. False, when you have Hash-Range key you cannot define Secondary index

Answer: B

Explanation:

When you create a table with a hash-and-range key in DynamoDB, you can also define one or more secondary indexes on that table.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/LSI.html>

NEW QUESTION 10

A user has created a MySQL RDS instance with PIOPS. Which of the below mentioned statements will help user understand the advantage of PIOPS?

- A. The user can achieve additional dedicated capacity for the EBS I/O with an enhanced RDS option
- B. It uses optimized EBS volumes and optimized configuration stacks
- C. It provides a dedicated network bandwidth between EBS and RDS
- D. It uses a standard EBS volume with optimized configuration the stacks

Answer: B

Explanation:

RDS DB instance storage comes in two types: standard and provisioned IOPS. Standard storage is allocated on the Amazon EBS volumes and connected to the user's DB instance. Provisioned IOPS uses optimized EBS volumes and an optimized configuration stack. It provides additional, dedicated capacity for the EBS I/O.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 10

A user has not enabled versioning on an S3 bucket. What will be the version ID of the object inside that bucket?

- A. There will be no version attached
- B. Null
- C. Blank

Answer: C

Explanation:

S3 objects stored in the bucket before the user has set the versioning state have a version ID of null. When the user enables versioning, the objects in the bucket do not change and their ID remains null. Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/AddingObjectstoVersionSuspendedBuckets.html>

NEW QUESTION 14

What happens if your application performs more reads or writes than your provisioned capacity?

- A. Nothing
- B. requests above your provisioned capacity will be performed but you will receive 400 error codes.
- C. requests above your provisioned capacity will be performed but you will receive 200 error codes.
- D. requests above your provisioned capacity will be throttled and you will receive 400 error code

Answer: D

Explanation:

Speaking about DynamoDB, if your application performs more reads/second or writes/second than your table's provisioned throughput capacity allows, requests above your provisioned capacity will be throttled and you will receive 400 error codes.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ProvisionedThroughputIntro.html>

NEW QUESTION 16

In relation to Amazon SQS, how can you ensure that messages are delivered in order?

- A. Increase the size of your queue
- B. Send them with a timestamp
- C. Give each message a unique id.
- D. AWS cannot guarantee that you will receive messages in the exact order you sent them

Answer: D

Explanation:

Amazon SQS makes a best effort to preserve order in messages, but due to the distributed nature of the queue, AWS cannot guarantee that you will receive messages in the exact order you sent them. You typically place sequencing information or timestamps in your messages so that you can reorder them upon receipt.

Reference: <https://aws.amazon.com/items/1343?externalID=1343>

NEW QUESTION 17

An orgAMzation has launched two applications: one for blogging and one for ECM on the same AWS Linux EC2 instance running in the AWS VPC. The orgAMzation has attached two private IPs (primary and secondary) to the above mentioned instance. The orgAMzation wants the instance OS to recognize the secondary IP address. How can the orgAMzation configure this?

- A. Use the ec2-net-utility package which updates routing tables, uses DHCP to refresh the secondary IP and adds the network interface.
- B. Use the ec2-net-utils package which will configure an additional network interface and update the routing table
- C. Use the ec2-ip-update package which can configure the network interface as well as update the secondary IP with DHCP.
- D. Use the ec2-ip-utility package which can update the routing tables as well as refresh the secondary IP using DHCP.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. With VPC the user can specify multiple private IP addresses for his instances. The number of network interfaces and private IP addresses that a user can specify for an instance depends on the instance type. This scenario helps when the user wants to host multiple websites on a single EC2 instance. After the user has assigned a secondary private IP address to his instance, he needs to configure the operating system on that instance to recognize the secondary private IP address. For AWS Linux, the ec2-net-utils package can take care of this step. It configures additional network interfaces that the user can attach while the instance is running, refreshes secondary IP addresses during DHCP lease renewal, and updates the related routing rules.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/MultipleIP.html>

NEW QUESTION 20

In Amazon SNS, to send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following, except:

- A. Client secret
- B. Client ID
- C. Device token
- D. Registration ID

Answer: C

Explanation:

To send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following: Registration ID and Client secret.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePushPrereq.html>

NEW QUESTION 22

Regarding Amazon SNS, to begin using Amazon SNS mobile push notifications, you first need that uses one of the supported push notification services: APNS, GCM, or ADM.

- A. an access policy for the mobile endpoints
- B. to active push notification service of Amazon SNS
- C. to know the type of mobile device operating system
- D. an app for the mobile endpoints

Answer: D

Explanation:

In Amazon SNS, to begin using Amazon SNS mobile push notifications, you first need an app for the mobile endpoints that uses one of the supported push notification services: APNS, GCM, or ADM. After you've registered and configured the app to use one of these services, you configure Amazon SNS to send push notifications to the mobile endpoints.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePush.html>

NEW QUESTION 25

How many types of block devices does Amazon EC2 support?

- A. 5
- B. 1
- C. 2
- D. 4

Answer: C

Explanation:

Amazon EC2 supports 2 types of block devices. Reference:

<http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/block-device-mapping-concepts.html>

NEW QUESTION 28

Can you SSH to your private machines that reside in a VPC from outside without elastic IP?

- A. Yes, but only if you have direct connect or vpn
- B. Only if you are using a non-US region
- C. Only if you are using a US region
- D. No

Answer: A

Explanation:

The instances that reside in the private subnets of your VPC are not reachable from the Internet, meaning that it is not possible to ssh into them. To interact with them you can use a bastion server, located in a public subnet, that will act as a proxy for them.

You can also connect if you have direct connect or vpn.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Scenario2.html

NEW QUESTION 32

Does AWS CloudFormation support Amazon EC2 tagging?

- A. It depends if the Amazon EC2 tagging has been defined in the template.
- B. No, it doesn't support Amazon EC2 tagging.
- C. No, CloudFormation doesn't support any tagging
- D. Yes, AWS CloudFormation supports Amazon EC2 tagging

Answer: D

Explanation:

In AWS CloudFormation, Amazon EC2 resources that support the tagging feature can also be tagged in an AWS template. The tag values can refer to template parameters, other resource names, resource attribute values (e.g. addresses), or values computed by simple functions (e.g., a concatenated list of strings).

Reference: <http://aws.amazon.com/cloudformation/faqs/>

NEW QUESTION 34

A user has created a MySQL RDS instance. Which of the below mentioned options is mandatory to configure while creating an instance?

- A. Multi AZ deployment setup
- B. Automated backup window
- C. Availability Zone
- D. Maintenance window

Answer: A

Explanation:

When creating an RDS instance, the user needs to specify whether it is Multi AZ or not. If the user does not provide the value for the zone, the maintenance window or automated backup window, RDS will automatically select the value.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Concepts.MultiAZ.html>

NEW QUESTION 38

A user has enabled the automated backup, but not specified the backup window. What will RDS do in this case?

- A. Will throw an error on instance launch
- B. RDS will take 3 AM — 3:30 AM as the default window
- C. RDS assigns a random time period based on the region
- D. Will not allow to launch a DB instance

Answer: C

Explanation:

If the user does not specify a preferred backup window while enabling an automated backup, Amazon RDS assigns a default 30-minute backup window which is selected at random from an 8-hour block of time per region. Reference:

<http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 40

How long are the messages kept on an SQS queue by default?

- A. If a message is not read, it is never deleted
- B. 2 weeks
- C. 1 day
- D. 4 days

Answer: D

Explanation:

The SQS message retention period is configurable and can be set anywhere from 1 minute to 2 weeks. The default is 4 days and once the message retention limit is reached your messages will be automatically deleted. The option for longer message retention provides greater flexibility to allow for longer intervals between message production and consumption.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 44

A user has attached one RDS security group with 5 RDS instances. The user has changed the ingress rule for the security group. What will be the initial status of the ingress rule?

- A. Approving
- B. Implementing
- C. Authorizing
- D. It is not possible to assign a single group to multiple DB instances

Answer: C

Explanation:

When the user makes any changes to the RDS security group the rule status will be authorizing for some time until the changes are applied to all instances that the group is connected with. Once the changes are propagated the rule status will change to authorized.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_WorkingWithSecurityGroups.html

NEW QUESTION 46

A user has attached an EBS volume to a running Linux instance as a "/dev/sdf" device. The user is unable to see the attached device when he runs the command "df -h". What is the possible reason for this?

- A. The volume is not in the same AZ of the instance
- B. The volume is not formatted
- C. The volume is not attached as a root device
- D. The volume is not mounted

Answer: D

Explanation:

When a user creates an EBS volume and attaches it as a device, it is required to mount the device. If the device/volume is not mounted it will not be available in the listing.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/AmazonEBS.html>

NEW QUESTION 47

A user has setup an application on EC2 which uses the IAM user access key and secret access key to make secure calls to S3. The user wants to temporarily stop the access to S3 for that IAM user. What should the root owner do?

- A. Delete the IAM user
- B. Change the access key and secret access key for the users
- C. Disable the access keys for the IAM user
- D. Stop the instance

Answer: C

Explanation:

If the user wants to temporarily stop the access to S3 the best solution is to disable the keys. Deleting the user will result in a loss of all the credentials and the app will not be useful in the future. If the user stops the instance IAM users can still access S3. The change of the key does not help either as they are still active. The

best possible solution is to disable the keys.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/NlmanagingCredential\[s\].html](http://docs.aws.amazon.com/IAM/latest/UserGuide/NlmanagingCredential[s].html)

NEW QUESTION 52

When should a user try to Force Detach an EBS volume?

- A. If the volume is stuck in a detaching state
- B. If the volume is not accessible from the instance
- C. If the volume is not unmounted and the user still wants to detach
- D. If the volume is a root volume

Answer: A

Explanation:

If an EBS volume stays in the detaching state, the user can force the detachment by clicking Force Detach. Forcing the detachment can lead to either data loss or a corrupted file system. The user should use this option only as a last resort to detach a volume from a failed instance or if he is detaching a volume with the intention of deleting it.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 57

How can a user configure three termination policies for the AutoScaling group?

- A. Define multiple policies in random order
- B. Define multiple policies in the ordered list
- C. Keep updating the AutoScaling group with each policy
- D. The user cannot specify more than two policies for AutoScaling

Answer: B

Explanation:

To configure the Auto Scaling termination policy, the user can either specify any one of the policies as a standalone policy or list multiple policies in an ordered list. The policies are executed in the order that they are listed.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/us-termination-policy.html>

NEW QUESTION 58

A user wants to configure AutoScaling which scales up when the CPU utilization is above 70% and scales down when the CPU utilization is below 30%. How can the user configure AutoScaling for the above mentioned condition?

- A. Use AutoScaling with a schedule
- B. Configure ELB to notify AutoScaling on load increase or decrease
- C. Use dynamic AutoScaling with a policy
- D. Use AutoScaling by manually modifying the desired capacity during a condition

Answer: C

Explanation:

The user can configure the AutoScaling group to automatically scale up and then scale down based on the specified conditions. To configure this, the user must setup policies which will get triggered by the CloudWatch alarms.

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-scale-based-on-demand.html>

NEW QUESTION 60

You have a number of image files to encode. In an Amazon SQS worker queue, you create an Amazon SQS message for each file specifying the command (jpeg-encode) and the location of the file in Amazon S3. Which of the following statements best describes the functionality of Amazon SQS?

- A. Amazon SQS is for single-threaded sending or receiving speeds.
- B. Amazon SQS is a non-distributed queuing system.
- C. Amazon SQS is a distributed queuing system that is optimized for horizontal scalability, not for single-threaded sending or receiving speeds.
- D. Amazon SQS is a distributed queuing system that is optimized for vertical scalability and for single-threaded sending or receiving speeds.

Answer: C

Explanation:

Amazon SQS is a distributed queuing system that is optimized for horizontal scalability, not for single-threaded sending or receiving speeds. A single client can send or receive Amazon SQS messages at a rate of about 5 to 50 messages per second. Higher receive performance can be achieved by requesting multiple messages (up to 10) in a single call. It may take several seconds before a message that has been to a queue is available to be received.

Reference: http://media.amazonwebservices.com/AWS_Storage_Options.pdf

NEW QUESTION 63

Can you configure an RDS Read Replica using CloudFormation templates?

- A. Yes, provided that you have root access.
- B. Yes, when you create a new CloudFormation template
- C. Yes, but not for all Regions.
- D. No, you can add the ReadReplica only when the resource is made available by CloudFormation

Answer:

B

Explanation:

AWS CloudFormation gives developers and systems administrators an easy way to create and manage collections of AWS resources. You can now set Read Replicas for your databases with RDS when you create a new CloudFormation template. You can start using it with the sample template of CloudFormation.

Reference:

https://s3.amazonaws.com/cloudformation-templates-us-east-1/RDS_MySQL_With_Read_Replica.template

NEW QUESTION 66

A user is creating an ELB with VPC. Which of the following options is available as a part of the "Add EC2 instances" page?

- A. Select Subnet
- B. Select IAM
- C. Select ENI
- D. Select VPC

Answer: A

Explanation:

When a user is launching an ELB with VPC, he/she has to select the options, such as subnet and security group before selecting the instances part of that subnet.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/elb-getting-started.html>

NEW QUESTION 67

An account owner has created an IAM user with the name examkiller. The account owner wants to give EC2 access of only the US West region to that IAM user. How can the owner configure this?

- A. While creating a policy provide the region as a part of the resources
- B. Create an IAM user in the US West region and give access to EC2
- C. Create an IAM policy and define the region in the condition
- D. It is not possible to provide access based on the region

Answer: C

Explanation:

The IAM policy is never region specific. If the user wants to configure the region specific setting, he needs to provide conditions as part of the policy.

Reference: <http://awspolicygen.s3.amazonaws.com/policygen.html>

NEW QUESTION 69

In DynamoDB, the default table size is:

- A. 5 GB
- B. 1 GB
- C. 10 GB
- D. There is no table size

Answer: D

Explanation:

DynamoDB has seamless scalability with no table size limits and unlimited storage, so you shouldn't be worried about managing storage on the host or to provisioning more drive, as your data requirement changes.

Reference: <http://aws.amazon.com/dynamodb/>

NEW QUESTION 73

You want to have multiple versions of your application running at the same time, with all versions launched via AWS Elastic Beanstalk. Is this possible?

- A. N
- B. However if you have 2 AWS accounts this can be done
- C. N
- D. AWS Elastic Beanstalk is not designed to support multiple running environments
- E. Ye
- F. AWS Elastic Beanstalk is designed to support a number of multiple running environments
- G. Ye
- H. However AWS Elastic Beanstalk is designed to support only 2 multiple running environments

Answer: C

Explanation:

AWS Elastic Beanstalk is designed to support multiple running environments. As an example you could have one for integration testing, one for pre-production, and one for production, with each environment independently configured and running on its own separate AWS resources.

Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 76

In regard to DynamoDB, what is the Global secondary index?

- A. An index with a hash and range key that can be different from those on the table.
- B. An index that has the same range key as the table, but a different hash key

- C. An index that has the same hash key and range key as the table
- D. An index that has the same hash key as the table, but a different range key

Answer: A

Explanation:

Global secondary index - an index with a hash and range key that can be different from those on the table.
Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 77

A user has launched an EC2 instance and installed a website with the Apache webserver. The webserver is running but the user is not able to access the website from the internet. What can be the possible reason for this failure?

- A. The security group of the instance is not configured properly.
- B. The instance is not configured with the proper key-pairs.
- C. The Apache website cannot be accessed from the internet.
- D. Instance is not configured with an elastic IP

Answer: A

Explanation:

In Amazon Web Services, when a user has configured an instance with Apache, the user needs to ensure that the ports in the security group are opened as configured in Apache config. E.g. If Apache is running on port 80, the user should open port 80 in the security group.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-network-security.html>

NEW QUESTION 78

A user had defined an IAM policy similar to the one given below on a bucket:

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow",
    "Principal": {
      "AWS": "arn:aws:iam::12112112:user/test"
    }
  },
  {
    "Action": [ "s3:GetBucketLocation", "s3:ListBucket", "s3:GetObject" ],
    "Resource": [ "arn:aws:s3:::examkiller" ]
  }
]
```

What will this do?

- A. It will result in an error saying invalid policy statement
- B. It will create an IAM policy for the user test
- C. Allows the user test of the AWS account ID 12112112 to perform GetBucketLocation, ListBucket and GetObject on the bucket examkiller
- D. It will allow all the IAM users of the account ID 12112112 to perform GetBucketLocation, ListBucket and GetObject on bucket examkiller

Answer: C

Explanation:

The IAM policy allows to test a user in the account 12112112 to perform: s3:GetBucketLocation s3:ListBucket s3:GetObject Amazon S3 permissions on the examkiller bucket.
Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/access-policy-language-overview.html>

NEW QUESTION 81

A user has configured a bucket S3 to host a static website. What difference will there be when static website hosting is enabled?

- A. It will help the user identify this bucket as the website root to map with the domain
- B. It will create a new version of the bucket
- C. It will not make any difference, but will help the user to configure the error page
- D. It will provide the region specific website endpoint

Answer: D

Explanation:

To host a static website, the user needs to configure an Amazon S3 bucket for website hosting and then upload the website contents to the bucket. The website is then available at the region-specific website endpoint of the bucket.
Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/WebsiteHosting.html>

NEW QUESTION 86

How does Amazon SQS allow multiple readers to access the same message queue without losing messages or processing them many times?

- A. By identifying a user by his unique id
- B. By using unique cryptography
- C. Amazon SQS queue has a configurable visibility timeout.
- D. Multiple readers can't access the same message queue

Answer: C

Explanation:

Every Amazon SQS queue has a configurable visibility timeout. For the designated amount of time after a message is read from a queue, it will not be visible to any other reader. As long as the amount of time that it takes to process the message is less than the visibility timeout, every message will be processed and deleted. In the event that the component processing the message fails or becomes unavailable, the message will again become visible to any component reading the queue once the visibility timeout ends. This allows you to have many components all reading messages from the same queue, with each working to process different messages.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 91

What does Amazon SQS provide?

- A. An asynchronous message queue service.
- B. A Simple Query Sewer, managed directly by Amazon Web Services.
- C. None of these.
- D. A synchronous message queue service.

Answer: A

Explanation:

Amazon SQS stands for Simple Queue Services, and provides a cost-effective way to decouple the components of your application through an asynchronous message queue service

Reference: <http://aws.amazon.com/sqs/>

NEW QUESTION 96

A user is trying to create a list of IAM users with the AWS console. When the IAM users are created which of the below mentioned credentials will be enabled by default for the user?

- A. IAM access key and secret access key
- B. IAM X.509 certificates
- C. Nothin
- D. Everything is disabled by default
- E. IAM passwords

Answer: C

Explanation:

Newly created IAM users have no password and no access key (access key ID and secret access key). If the user needs to administer your AWS resources using the AWS Management Console, you can create a password for the user. If the user needs to interact with AWS programmatically (using the command line interface (CLI), the AWS SDK, or service-specific APIs), you can create an access key for that user. The credentials you create for users are what they use to uniquely identify themselves to AWS.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_WorkingWithGroupsAndUsers.html

NEW QUESTION 100

Bob is an IAM user who has access to the EC2 services. Admin is an IAM user who has access to all the AWS services including IAM. Can Bob change his password?

- A. No, the IAM user can never change the password
- B. Yes, provided Admin has given Bob access to change his password
- C. Yes, only from AWS CLI
- D. Yes, only from the AWS console

Answer: B

Explanation:

The IAM users by default cannot change their password. The root owner or IAM administrator needs to set the policy in the password policy page, which should allow the user to change their password. Once it is enabled, the IAM user can always change their passwords from the AWS console or CLI.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_ManagingUserPwdSelf.htm

NEW QUESTION 101

A user has created photo editing software and hosted it on EC2. The software accepts requests from the user about the photo format and resolution and sends a message to S3 to enhance the picture accordingly. Which of the below mentioned AWS services will help make a scalable software with the AWS infrastructure in this scenario?

- A. AWS Elastic Transcoder
- B. AWS Simple Notification Service
- C. AWS Simple Queue Service
- D. AWS Glacier

Answer: C

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can configure SQS, which will decouple the call between the EC2 application and S3. Thus, the application does not keep waiting for S3 to provide the data.

Reference: <http://aws.amazon.com/sqs/faqs/>

NEW QUESTION 104

In DynamoDB, could you use IAM to grant access to Amazon DynamoDB resources and API actions?

- A. Yes
- B. Depended to the type of access
- C. In DynamoDB there is no need to grant access
- D. No

Answer: A

Explanation:

Amazon DynamoDB integrates with AWS Identity and Access Management (IAM). You can use AWS IAM to grant access to Amazon DynamoDB resources and API actions. To do this, you first write an AWS IAM policy, which is a document that explicitly lists the permissions you want to grant. You then attach that policy to an AWS IAM user or role.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/UsingIAMWithDDB.html>

NEW QUESTION 109

A user is planning to host a mobile game on EC2 which sends notifications to active users on either high score or the addition of new features. The user should get this notification when he is online on his mobile device. Which of the below mentioned AWS services can help achieve this functionality?

- A. AWS Simple Notification Service.
- B. AWS Simple Queue Service.
- C. AWS Mobile Communication Service.
- D. AWS Simple Email Service

Answer: A

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS makes it simple and cost-effective to push to mobile devices, such as iPhone, iPad, Android, Kindle Fire, and internet connected smart devices, as well as pushing to other distributed services.

Reference: <http://aws.amazon.com/sns>

NEW QUESTION 110

An organization is setting up their website on AWS. The organization is working on various security measures to be performed on the AWS EC2 instances. Which of the below mentioned security mechanisms will not help the organization to avoid future data leaks and identify security weaknesses?

- A. Perform SQL injection for application testing.
- B. Run penetration testing on AWS with prior approval from Amazon.
- C. Perform a hardening test on the AWS instance.
- D. Perform a Code Check for any memory leak

Answer: D

Explanation:

AWS security follows the shared security model where the user is as much responsible as Amazon. Since Amazon is a public cloud it is bound to be targeted by hackers. If an organization is planning to host their application on AWS EC2, they should perform the below mentioned security checks as a measure to find any security weakness/data leaks:

Perform penetration testing as performed by attackers to find any vulnerability. The organization must take an approval from AWS before performing penetration testing

Perform hardening testing to find if there are any unnecessary ports open Perform SQL injection to find any DB security issues

The code memory checks are generally useful when the organization wants to improve the application performance.

Reference: <http://aws.amazon.com/security/penetration-testing/>

NEW QUESTION 114

A root account owner is trying to setup an additional level of security for all his IAM users. Which of the below mentioned options is a recommended solution for the account owner?

- A. Enable access key and secret access key for all the IAM users
- B. Enable MFA for all IAM users
- C. Enable the password for all the IAM users
- D. Enable MFA for the root account

Answer: B

Explanation:

Multi-Factor Authentication adds an extra level of security for all the users. The user can enable MFA for all IAM users which ensures that each user has to provide an extra six digit code for authentication. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_ManagingMFA.html

NEW QUESTION 118

Which of the below mentioned options is a must to have an element as a part of the IAM policy?

- A. Condition
- B. ID
- C. Statement
- D. Version

Answer: C

Explanation:

The statement is the main element of the IAM policy and it is a must for a policy. Elements such as condition, version and ID are not required.
Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 123

Which of the below mentioned commands allows the user to share the AMI with his peers using the AWS EC2 CLI?

- A. ec2-share-image-public
- B. ec2-share-image-account
- C. ec2-share-image
- D. ec2-modify-image-attribute

Answer: D

Explanation:

A user can share an AMI with another user / peer using the command: ec2-modify-image-attribute <AMI-ID> -| -a <AWS Account ID>
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/sharingamis-explicit.html>

NEW QUESTION 127

In regards to Amazon SQS how many times will you receive each message?

- A. At least twice
- B. Exactly once
- C. As many times as you want
- D. At least once

Answer: D

Explanation:

Amazon SQS is engineered to provide "at least once" delivery of all messages in its queues. Although most of the time, each message will be delivered to your application exactly once, you should design your system so that processing a message more than once does not create any errors or inconsistencies. Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 129

A user is running a webserver on EC2. The user wants to receive the SMS when the EC2 instance utilization is above the threshold limit. Which AWS services should the user configure in this case?

- A. AWS CloudWatch + AWS SES.
- B. AWS CloudWatch + AWS SNS.
- C. AWS CloudWatch + AWS SQS.
- D. AWS EC2 + AWS Cloudwatc

Answer: B

Explanation:

Amazon SNS makes it simple and cost-effective to push to mobile devices, such as iPhone, iPad, Android, Kindle Fire, and internet connected smart devices, as well as pushing to other distributed services. In this case, the user can configure that Cloudwatch sends an alarm on when the threshold is crossed to SNS which will trigger an SMS.
Reference: <http://aws.amazon.com/sns/>

NEW QUESTION 130

A user has setup Multi AZ with the MS SQL RDS instance. Which of the below mentioned functionalities can be achieved by the user?

- A. High availability
- B. Scalability
- C. MS SQL does not support Multi AZ
- D. Disaster recovery

Answer: C

Explanation:

The Multi AZ feature allows the user to achieve High Availability. MS SQL does not support Multi AZ. Reference: <https://aws.amazon.com/rds/faqs/#36>

NEW QUESTION 134

A user is part of a group which has a policy allowing him just read only access to EC2. The user is part of another group which has full access to EC2. What happens when the user tries to launch an instance?

- A. It will allow the user to launch the instance
- B. It will fail since the user has just read only access
- C. It will allow or deny based on the group under which the user has logged into EC2
- D. It will not allow the user to add to the conflicting groups

Answer: A

Explanation:

The IAM group policy is always aggregated. In this case, if the user does not have permission for one group, but has permission for another group, he will have full access to EC2. Unless there is specific deny policy, the user will be able to access EC2.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/PoliciesOverview.html>

NEW QUESTION 139

Can a user associate and use his own DNS with ELB instead of the DNS provided by AWS ELB?

- A. Yes, by creating a CNAME with the existing domain name provider
- B. Yes, by configuring DNS in the AWS Console
- C. No
- D. Yes, only through Route 53 by mapping ELB and DNS

Answer: A

Explanation:

The AWS ELB allows mapping a custom domain name with ELB. The user can map ELB with DNS in two ways: 1) By creating CNAME with the existing domain name service provider or 2) By creating a record with Route 53.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/using-domain-names-with-elb.html>

NEW QUESTION 142

In relation to Amazon Simple Workflow Service (Amazon SWF), what is an "ActMty Worker"?

- A. An individual task undertaken by a workflow
- B. The automation of a business process
- C. A piece of software that implements tasks
- D. All answers listed are correct

Answer: C

Explanation:

In relation to Amazon Simple Workflow Service (Amazon SWF), an actMty worker is a program that receives actMty tasks, performs them, and provides results back. Which translates to a piece of software that implements tasks.

Reference: <http://docs.aws.amazon.com/amazonswf/latest/developerguide/swf-dg-develop-actMty.html>

NEW QUESTION 145

An organization has 20 employees. The organization wants to give all the users access to the organization AWS account. Which of the below mentioned options is the right solution?

- A. Share the root credentials with all the users
- B. Create an IAM user for each employee and provide access to them
- C. It is not advisable to give AWS access to so many users
- D. Use the IAM role to allow access based on STS

Answer: B

Explanation:

AWS Identity and Access Management is a web service that enables the AWS customers to manage users and user permissions in AWS. The IAM is targeted at organizations with multiple users or systems that use AWS products such as Amazon EC2, Amazon RDS, and the AWS Management Console. With IAM, the organization can centrally manage users, security credentials such as access keys, and permissions that control which AWS resources users can access.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/IAM_Introduction.html

NEW QUESTION 148

When AutoScaling is launching a new instance based on condition, which of the below mentioned policies will it follow?

- A. Based on the criteria defined with cross zone Load balancing
- B. Launch an instance which has the highest load distribution
- C. Launch an instance in the AZ with the fewest instances
- D. Launch an instance in the AZ which has the highest instances

Answer: C

Explanation:

AutoScaling attempts to distribute instances evenly between the Availability Zones that are enabled for the user's AutoScaling group. Auto Scaling does this by attempting to launch new instances in the Availability Zone with the fewest instances.

Reference: http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AS_Concepts.html

NEW QUESTION 150

In regards to Amazon SQS how can you secure the messages in your queues?

- A. You can't
- B. Amazon SQS uses either your Access Key ID or an X.509 certificate to authenticate your identity
- C. Through your IAM access keys
- D. Don't use root access

Answer: B

Explanation:

Authentication mechanisms are provided to ensure that messages stored in Amazon SQS queues are secured against unauthorized access. Only the AWS

account owners can access the queues they create. Amazon SQS uses proven cryptographic methods to authenticate your identity, either through the use of your Access Key ID and request signature, or through the use of an X.509 certificate.
Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 152

Which of the below mentioned options can be a good use case for storing content in AWS RRS?

- A. Storing mission critical data Files
- B. Storing infrequently used log files
- C. Storing a video file which is not reproducible
- D. Storing image thumbnails

Answer: D

Explanation:

AWS RRS provides the same functionality as AWS S3, but at a cheaper rate. It is ideally suited for non-mission, critical applications, such as files which can be reproduced.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/UsingRRS.html>

NEW QUESTION 155

Which header received at the EC2 instance identifies the port used by the client while requesting ELB?

- A. X-Forwarded-Proto
- B. X-Requested-Proto
- C. X-Forwarded-Port
- D. X-Requested-Port

Answer: C

Explanation:

The X-Forwarded-Port request header helps the user identify the port used by the client while sending a request to ELB.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html>

NEW QUESTION 160

When you register an actMty in Amazon SWF, you provide the following information, except:

- A. a name
- B. timeout values
- C. a domain
- D. version

Answer: C

Explanation:

When designing an Amazon SWF workflow, you precisely define each of the required actMtys. You then register each actMty with Amazon SWF as an actMty type. When you register the actMty, you provide information such as a name and version, and some timeout values based on how long you expect the actMty to take.

Reference: <http://docs.aws.amazon.com/amazonswf/latest/developerguide/swf-dg-intro-to-swf.html>

NEW QUESTION 163

A user is using an EBS backed instance. Which of the below mentioned statements is true?

- A. The user will be charged for volume and instance only when the instance is running
- B. The user will be charged for the volume even if the instance is stopped
- C. The user will be charged only for the instance running cost
- D. The user will not be charged for the volume if the instance is stopped

Answer: B

Explanation:

If a user has launched an EBS backed instance, the user will be charged for the EBS volume even though the instance is in a stopped state. The instance will be charged for the EC2 hourly cost only when it is running.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 164

A user is trying to create a policy for an IAM user from the AWS console. Which of the below mentioned options is not available to the user while configuring policy?

- A. Use policy generator to create policy
- B. Use custom policy to create policy
- C. Use policy simulator to create policy
- D. Assign No permission

Answer: C

Explanation:

When a user is trying to create a policy from the AWS console, it will have options such as create policy from templates or use a policy generator. The user can

also define a custom policy or chose the option to have no permission. The policy simulator is not available in the console.
Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/IAMBestPractices.html>

NEW QUESTION 165

A user has an S3 object in the US Standard region with the content "color=red". The user updates the object with the content as "color="white". If the user tries to read the value 1 minute after it was uploaded, what will S3 return?

- A. It will return "color=white"
- B. It will return "color=red"
- C. It will return an error saying that the object was not found
- D. It may return either "color=red" or "color=white" i.
- E. any of the value

Answer: D

Explanation:

AWS S3 follows the eventual consistent model in the US Standard Region. Once the object is updated it may return the new value or the old value based on whether all the content is replicated across multiple servers until it becomes consistent (eventual).
Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/Introduction.html>

NEW QUESTION 167

AWS Elastic Beanstalk will change the health status of a web server environment tier to gray color when:

- A. AWS Elastic Beanstalk detects other problems with the environment that are known to make the application unavailable
- B. Your application hasn't responded to the application health check URL within the last one hour.
- C. Your application hasn't responded to the application health check URL within the last five minutes.
- D. Your application's health status is unknown because status is reported when the application is not in the ready state.

Answer: D

Explanation:

AWS Elastic Beanstalk will change the health status of a web server environment tier to gray color when your application's health status is unknown (because status is reported when the application is not in the ready state).
Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.healthstatus.html>

NEW QUESTION 172

A user is creating a snapshot of an EBS volume. Which of the below statements is incorrect in relation to the creation of an EBS snapshot?

- A. Its incremental
- B. It can be used to launch a new instance
- C. It is stored in the same AZ as the volume
- D. It is a point in time backup of the EBS volume

Answer: C

Explanation:

The EBS snapshots are a point in time backup of the EBS volume. It is an incremental snapshot, but is always specific to the region and never specific to a single AZ.
Hence the statement "It is stored in the same AZ as the volume" is incorrect.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSSnapshots.html>

NEW QUESTION 174

A user is planning to use EBS for his DB requirement. The user already has an EC2 instance running in the VPC private subnet. How can the user attach the EBS volume to a running instance?

- A. The user must create EBS within the same VPC and then attach it to a running instance.
- B. The user can create EBS in the same zone as the subnet of instance and attach that EBS to instance.
- C. It is not possible to attach an EBS to an instance running in VPC until the instance is stopped.
- D. The user can specify the same subnet while creating EBS and then attach it to a running instanc

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. The instance launched will always be in the same availability zone of the respective subnet. When creating an EBS the user cannot specify the subnet or VPC. However, the user must create the EBS in the same zone as the instance so that it can attach the EBS volume to the running instance.
Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.htm|#VPCSubnet

NEW QUESTION 175

Which of the following groups is AWS Elastic Beanstalk best suited for?

- A. Those who want to deploy and manage their applications within minutes in the AWS cloud
- B. Those who want to privately store and manage Git repositories in the AWS cloud.
- C. Those who want to automate the deployment of applications to instances and to update the applications as required
- D. Those who want to model, visualize, and automate the steps required to release software

Answer:

A

Explanation:

AWS Elastic Beanstalk is best suited for those groups who want to deploy and manage their applications within minutes in the AWS cloud. As a bonus, you don't even need experience with cloud computing to get started.

Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 178

A user is trying to find the state of an S3 bucket with respect to versioning. Which of the below mentioned states AWS will not return when queried?

- A. versioning-enabled
- B. versioning-suspended
- C. unversioned
- D. versioned

Answer: D

Explanation:

S3 buckets can be in one of the three states: unversioned (the default), versioning-enabled or versioning-suspended. The bucket owner can configure the versioning state of a bucket. The versioning state applies to all (never some) of the objects in that bucket. The first time owner enables a bucket for versioning, objects in it are thereafter always versioned and given a unique version ID.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/Versioning.html>

NEW QUESTION 183

What is the maximum number of tags that a user can assign to an EC2 instance?

- A. 50
- B. 10
- C. 5
- D. 25

Answer: B

Explanation:

To help manage EC2 instances as well as their usage in a better way, the user can tag the instances. The tags are metadata assigned by the user which consists of a key and a value. One resource can have a maximum of 10 tags.

Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/Using_Tags.html

NEW QUESTION 188

A user has configured ELB with two instances running in separate AZs of the same region? Which of the below mentioned statements is true?

- A. NMulti AZ instances will provide HA with ELB
- B. IMulti AZ instances are not possible with a single ELB
- C. NMulti AZ instances will provide scalability with ELB
- D. The user can achieve both HA and scalability with ELB

Answer: A

Explanation:

If a user is running two instances in separate AZs, it will provide HA with ELB since ELB will automatically stop routing the traffic to unhealthy instances and send it to healthy instances only.

NEW QUESTION 193

What is the data model of DynamoDB?

- A. "Items", with Keys and one or more Attribute; and "Attribute", with Name and Value.
- B. "Database", which is a set of "Tables", which is a set of "Items", which is a set of "Attributes".
- C. "Table", a collection of Items; "Items", with Keys and one or more Attribute; and "Attribute", with Name and Value.
- D. "Database", a collection of Tables; "Tables", with Keys and one or more Attribute; and "Attribute", with Name and Value.

Answer: C

Explanation:

The data model of DynamoDB is: "Table", a collection of Items;

"Items", with Keys and one or more Attribute; "Attribute", with Name and Value.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 194

A user is trying to configure access with S3. Which of the following options is not possible to provide access to the S3 bucket / object?

- A. Define the policy for the IAM user
- B. Define the ACL for the object
- C. Define the policy for the object
- D. Define the policy for the bucket

Answer: C

Explanation:

Amazon S3 offers access policy options broadly categorized as resource-based policies and user policies.

Access policies, such as ACL and resource policy can be attached to the bucket. With the object the user can only have ACL and not an object policy. The user can also attach access policies to the IAM users in the account. These are called user policies.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/s3-access-control.html>

NEW QUESTION 196

In regard to DynamoDB, can I modify the index once it is created?

- A. Yes, if it is a primary hash key index
- B. Yes, if it is a Global secondary index
- C. No
- D. Yes, if it is a local secondary index

Answer: C

Explanation:

Currently, in DynamoDB, an index cannot be modified once it is created. Reference: http://aws.amazon.com/dynamodb/faqs/#security_anchor

NEW QUESTION 201

ExamKiller (with AWS account ID 111122223333) has created 50 IAM users for its orgAMzation's employees. What will be the AWS console URL for these associates?

- A. <https://111122223333.signin.aws.amazon.com/console/>
- B. <https://signin.aws.amazon.com/console/>
- C. <https://signin.aws.amazon.com/111122223333/console/>
- D. <https://signin.aws.amazon.com/console/111122223333/>

Answer: A

Explanation:

When an orgAMzation is using AWS IAM for creating various users and manage their access rights, the IAM user cannot use the login URL

<http://aws.amazon.com/console> to access AWS management console. The console login URL for the IAM user will have AWS account ID of that orgAMzation to identify the IAM user belongs to particular account. The AWS console login URL for the IAM user will be https://<AWS_Account_ID>.signin.aws.amazon.com/console/. In this case it will be <https://111122223333.signin.aws.amazon.com/console/>

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/AccountAlias.html>

NEW QUESTION 203

A user is planning to host MS SQL on an EBS volume. It was recommended to use the AWS RDS. What advantages will the user have if he uses RDS in comparison to an EBS based DB?

- A. Better throughput with PIOPS
- B. Automated backup
- C. NIS SQL is not supported with RDS
- D. High availability with multi AZs

Answer: B

Explanation:

Comparing with on-premises or EC2 based NIS SQL, RDS provides an automated backup feature. PIOPS is available with both RDS and EBS. However, HA is not available with NIS SQL.

Reference: <https://aws.amazon.com/rds/faqs/>

NEW QUESTION 207

The user has configured AutoScaling based on the dynamic policy. Which of the following is not the right command to specify a change in capacity as a part of the policy?

- A. "adjustment=-50" (type is PercentChangeInCapacity)
- B. "adjustment=3" (type is ExactCapacity)
- C. "adjustment=-1" (type is ChangeInCapacity)
- D. "adjustment=-8" (type is ExactCapacity)

Answer: D

Explanation:

The user can configure the AutoScaling group to automatically scale up and then scale down based on the various specified CloudWatch monitoring conditions. The user needs to provide the adjustment value and the adjustment type. A positive adjustment value increases the current capacity and a negative adjustment value decreases the current capacity. The user can express the change to the current size as an absolute number, an increment or as a percentage of the current group size.

In this option specifying the exact capacity with the adjustment value = -8 will not work as when type is exact capacity the adjustment value cannot be negative.

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-scale-based-on-demand.html>

NEW QUESTION 212

A user has created a snapshot of an EBS volume. Which of the below mentioned usage cases is not possible with respect to a snapshot?

- A. Mirroring the volume from one AZ to another AZ

- B. Launch an instance
- C. Decrease the volume size
- D. Increase the size of the volume

Answer: C

Explanation:

The EBS snapshots are a point in time backup of the volume. It is helpful to move the volume from one AZ to another or launch a new instance. The user can increase the size of the volume but cannot decrease it less than the original snapshot size.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSSnapshots.html>

NEW QUESTION 214

True or False: AWS CloudFormation allows you to create Microsoft Windows stacks.

- A. False, AWS CloudFormation does not support Microsoft Windows.
- B. False, Amazon doesn't support Microsoft Windows.
- C. False, you cannot create Windows stacks.
- D. True

Answer: D

Explanation:

AWS CloudFormation allows you to create Microsoft Windows stacks based on Amazon EC2 Windows Amazon Machine Images (AMIs) and provides you with the ability to install software, to use remote desktop to access your stack, and to update and configure your stack.
Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/cfn-windows-stacks.html>

NEW QUESTION 215

Which of the following solutions is not supported by DynamoDB:

- A. Hash secondary index
- B. Local secondary index
- C. Hash Primary Key
- D. Global secondary index

Answer: A

Explanation:

In DynamoDB, a secondary index is a data structure that contains a subset of attributes from a table, along with an alternate key to support Query operations. DynamoDB supports the following two types of secondary indexes:
Local secondary index is an index that has the same hash key as the table, but a different range key. A local secondary index is "local" in the sense that every partition of a local secondary index is scoped to a table partition that has the same hash key.
Global secondary index is an index with a hash and range key that can be different from those on the table. A global secondary index is considered "global" because queries on the index can span all of the data in a table, across all partitions.
Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 219

An ELB is diverting traffic across 5 instances. One of the instances was unhealthy only for 20 minutes. What will happen after 20 minutes when the instance becomes healthy?

- A. ELB will never divert traffic back to the same instance
- B. ELB will not automatically send traffic to the same instance
- C. However, the user can configure to start sending traffic to the same instance
- D. ELB starts sending traffic to the instance once it is healthy
- E. ELB terminates the instance once it is unhealthy
- F. Thus, the instance cannot be healthy after 10 minutes

Answer: C

Explanation:

AWS Elastic Load Balancing continuously checks the health of an instance. If one of the instances is unhealthy it stops sending traffic to it and automatically reroutes the traffic to the remaining running EC2 instances. If the failed EC2 instance is restored, Elastic Load Balancing will again start sending traffic to that instance.
Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/SvcIntro.htm>

NEW QUESTION 222

Which OS does the current version of AWS Elastic Beanstalk use?

- A. Amazon Linux AMI, Windows Server 2003 R2 AMI or the Windows Server 2008 R2 AMI
- B. Amazon Linux AMI only
- C. Amazon Linux AMI or the Windows Server 2008 R2 AMI
- D. Windows Server 2008 R2 AMI only

Answer: C

Explanation:

The current version of AWS Elastic Beanstalk uses the Amazon Linux AMI or the Windows Server 2008 R2 AMI.
Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 226

AWS Elastic Beanstalk stores your application files and optionally server log files in .

- A. Amazon Storage Gateway
- B. Amazon Glacier
- C. Amazon EC2
- D. Amazon S3

Answer: D

Explanation:

AWS Elastic Beanstalk stores your application files and optionally server log files in Amazon S3. If you are using the AWS Management Console, Git, the AWS Toolkit for Visual Studio, or AWS Toolkit for Eclipse, an Amazon S3 bucket will be created in your account for you and the files you upload will be automatically copied from your local client to Amazon S3. Optionally, you may configure Elastic Beanstalk to copy your server log files every hour to Amazon S3. You do this by editing the environment configuration settings.

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/AWSHowTo.html>

NEW QUESTION 230

The AWS console for DynamoDB enables you to do all the following operations, except:

- A. Set up alarms to monitor your table's capacity usage.
- B. Create, update, and delete tables.
- C. Import Data from other databases or from files.
- D. View your table's top monitoring metrics on real-time graphs from CloudWatc

Answer: C

Explanation:

The AWS console for DynamoDB enables you to do all the above operation but not Importing Data from other databases or from files and it is not possible to do it.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ConsoleDynamoDB.html>

NEW QUESTION 232

An orgAMzation has created multiple components of a single application for compartmentalization. Currently all the components are hosted on a single EC2 instance. Due to security reasons the orgAMzation wants to implement two separate SSLs for the separate modules although it is already using VPC. How can the orgAMzation achieve this with a single instance?

- A. Create a VPC instance which will have both the ACL and the security group attached to it and have separate rules for each IP address.
- B. Create a VPC instance which will have multiple network interfaces with multiple elastic IP addresses.
- C. You have to launch two instances each in a separate subnet and allow VPC peering for a single IP.
- D. Create a VPC instance which will have multiple subnets attached to it and each will have a separate IP address.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. With VPC the user can specify multiple private IP addresses for his instances.

The number of network interfaces and private IP addresses that a user can specify for an instance depends on the instance type. With each network interface the orgAMzation can assign an EIP. This scenario helps when the user wants to host multiple websites on a single EC2 instance by using multiple SSL certificates on a single server and associating each certificate with a specific EIP address. It also helps in scenarios for operating network appliances, such as firewalls or load balancers that have multiple private IP addresses for each network interface.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/MultipleIP.html>

NEW QUESTION 233

In regards to VPC, select the correct statement:

- A. You can associate multiple subnets with the same Route Table.
- B. You can associate multiple subnets with the same Route Table, but you can't associate a subnet with only one Route Table.
- C. You can't associate multiple subnets with the same Route Table.
- D. None of thes

Answer: A

Explanation:

Every subnet in your VPC must be associated with exactly one Route Table. However, multiple subnets can be associated with the same Route Table.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Route_Tables.html

NEW QUESTION 236

Your supervisor has asked you to build a simple file synchronization service for your department. He doesn't want to spend too much money and he wants to be notified of any changes to files by email. What do you think would be the best Amazon service to use for the email solution?

- A. Amazon CloudSearch
- B. Amazon Elastic Transcoder
- C. Amazon SES
- D. Amazon AppStream

Answer: C

Explanation:

File change notifications can be sent via email to users following the resource with Amazon Simple Email Service (Amazon SES), an easy-to-use, cost-effective email solution.

Reference: http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_filesync_08.pdf

NEW QUESTION 241

A user has enabled automated backup for an RDS instance. What is the longest duration for which the user can retain the automated backup?

- A. 25 days
- B. 15 days
- C. 45 days
- D. 35 days

Answer: D

Explanation:

Amazon RDS provides two different methods for backing up and restoring the Amazon DB instances: automated backups and DB snapshots. Automated backups automatically back up the DB instance during a specific, user-definable backup window, and keep the backups for a limited, user-specified period of time. The maximum period can be 35 days.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 245

A user is enabling a static website hosting on an S3 bucket. Which of the below mentioned parameters cannot be configured by the user?

- A. Error document
- B. Conditional error on object name
- C. Index document
- D. Conditional redirection on object name

Answer: B

Explanation:

To host a static website, the user needs to configure an Amazon S3 bucket for website hosting and then upload the website contents to the bucket. The user can configure the index, error document as well as configure the conditional routing of on object name.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/HowDoIWebsiteConfiguration.html>

NEW QUESTION 247

A user is uploading archives to Glacier. The user is trying to understand key Glacier resources. Which of the below mentioned options is not a Glacier resource?

- A. Notification configuration
- B. Archive ID
- C. Job
- D. Archive

Answer: B

Explanation:

AWS Glacier has four resources. Vault and Archives are core data model concepts. Job is required to initiate download of archive. The notification configuration is required to send user notification when archive is available for download.

Reference: <http://docs.aws.amazon.com/amazonglacier/latest/dev/amazon-glacier-data-model.html>

NEW QUESTION 252

An organization has 10 departments. The organization wants to track the AWS usage of each department. Which of the below mentioned options meets the requirement?

- A. Setup IAM groups for each department and track their usage
- B. Create separate accounts for each department, but use consolidated billing for payment and tracking
- C. Create separate accounts for each department and track them separately
- D. Setup IAM users for each department and track their usage

Answer: B

Explanation:

The cost of an IAM user or groups can never be tracked separately for the purpose of billing. The best solution in this case is to create a separate account for each department and use consolidated billing. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/IAM_introduction.html

NEW QUESTION 257

Regarding Amazon SWF, at times you might want to record information in the workflow history of a workflow execution that is specific to your use case. enable you to record information in the workflow execution history that you can use for any custom or scenario-specific purpose.

- A. Markers B.Tags
- B. Hash keys
- C. Events

Answer: A

Explanation:

In Amazon SWF, at times you might want to record information in the workflow history of a workflow execution that is specific to your use case. Markers enable

you to record information in the workflow execution history that you can use for any custom or scenario-specific purpose.
Reference: <http://docs.aws.amazon.com/amazonswf/latest/developerguide/swf-dg-adv.html>

NEW QUESTION 262

In regard to DynamoDB, for which one of the following parameters does Amazon not charge you?

- A. Cost per provisioned write units
- B. Cost per provisioned read units
- C. Storage cost
- D. I/O usage within the same Region

Answer: D

Explanation:

In DynamoDB, you will be charged for the storage and the throughput you use rather than for the I/O which has been used.
Reference: <http://aws.amazon.com/dynamodb/pricing/>

NEW QUESTION 264

A user has configured an automated backup between 5 AM — 5:30 AM for the MySQL RDS DB. Will the performance of RDS get frozen momentarily during a backup?

- A. No
- B. Yes, only if the instance size is smaller than large size
- C. Yes, provided it is a single zone implementation
- D. Yes, always

Answer: C

Explanation:

Amazon RDS provides two different methods for backing up and restoring the Amazon DB instances. A brief I/O freeze, typically lasting a few seconds, occurs during both automated backups and DB snapshot operations on Single-AZ DB instances.
Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 265

Regarding Amazon SNS, to send messages to a queue through a topic, you must subscribe the queue to the Amazon SNS topic. You specify the queue by its .

- A. ARN
- B. Token
- C. Registration ID
- D. URL

Answer: A

Explanation:

In Amazon SNS, to send messages to a queue through a topic, you must subscribe the queue to the Amazon SNS topic. You specify the queue by its ARN.
Reference: <http://docs.aws.amazon.com/sns/latest/dg/SendMessageToSQS.html>

NEW QUESTION 266

A user wants to achieve High Availability with PostgreSQL DB. Which of the below mentioned functionalities helps achieve HA?

- A. Read Replica
- B. Multi AZ
- C. Multi region
- D. PostgreSQL does not support HA

Answer: B

Explanation:

The Multi AZ feature allows the user to achieve High Availability. For Multi AZ, Amazon RDS automatically provisions and maintains a synchronous "standby" replica in a different Availability Zone. Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 267

A user is launching an instance with EC2. Which of the below mentioned options does the user need to consider before launching an instance?

- A. Select the region where the instance is being launched.
- B. Select the instance type.
- C. All the options listed should be considered..
- D. Select the OS of the AM

Answer: C

Explanation:

Regarding Amazon EC2, when launching an instance, the user needs to select the region the instance would be launched from. While launching, the user needs to plan for the instance type and the OS of the instance.
Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-launch-instance_linux.html

NEW QUESTION 272

You have an environment that consists of a public subnet using Amazon VPC and 3 instances that are running in this subnet. These three instances can successfully communicate with other hosts on the Internet. You launch a fourth instance in the same subnet, using the same AMI and security group configuration you used for the others, but find that this instance cannot be accessed from the Internet. What should you do to enable internet access?

- A. Deploy a NAT instance into the public subnet.
- B. Modify the routing table for the public subnet
- C. Configure a publically routable IP Address In the host OS of the fourth instance.
- D. Assign an Elastic IP address to the fourth instanc

Answer: D

NEW QUESTION 275

Which of the following statements about SWF are true? Choose 3 answers

- A. SWF tasks are assigned once and never duplicated
- B. SWF requires an S3 bucket for workflow storage
- C. SWF workflow executions can last up to a year
- D. SWF triggers SNS notifications on task assignment
- E. SWF uses deciders and workers to complete tasks
- F. SWF requires atleast 1 EC2 instance per domain

Answer: ACE

NEW QUESTION 276

Company C has recently launched an online commerce site for bicycles on AWS. They have a "Product" DynamoDB table that stores details for each bicycle, such as, manufacturer, color, price, quantity and size to display in the online store. Due to customer demand, they want to include an image for each bicycle along with the existing details.

Which approach below provides the least impact to provisioned throughput on the "Product" table?

- A. Serialize the image and store it in multiple DynamoDB tables
- B. Create an "Images" DynamoDB table to store the Image with a foreign key constraint to the "Product" table
- C. Add an image data type to the "Product" table to store the images in binary format
- D. Store the images in Amazon S3 and add an S3 URL pointer to the "Product" table item for each image

Answer: D

NEW QUESTION 279

A startup s photo-sharing site is deployed in a VPC. An ELB distributes web traffic across two subnets. ELB session stickiness is configured to use the AWS-generated session cookie, with a session TTL of 5 minutes. The webserver Auto Scaling Group is configured as: min-size=4, max-size=4.

The startups preparing for a public launch, by running load-testing software installed on a single EC2 instance running in us-west-2a. After 60 minutes of load-testing, the webserver logs show:

WEBSERVER LOGS	# of HTTP requests from load-tester	# of HTTP requests from private beta users
webserver #1 (subnet in us-west-2a):	19,210	434
webserver #2 (subnet in us-west-2a):	21,790	490
webserver #3 (subnet in us-west-2b):	0	410
webserver #4 (subnet in us-west-2b):	0	428

Which recommendations can help ensure load-testing HTTP requests are evenly distributed across the four webserver? Choose 2 answers

- A. Launch and run the load-tester EC2 instance from us-east-1 instead.
- B. Re-configure the load-testing software to re-resolve DNS for each web request.
- C. Use a 3rd-party load-testing service which offers globally-distributed test clients.
- D. Configure ELB and Auto Scaling to distribute across us-west-2a and us-west-2c.
- E. Configure ELB session stickiness to use the app-specific session cooki

Answer: BE

NEW QUESTION 280

In DynamoDB, what type of HTTP response codes indicate that a problem was found with the client request sent to the service?

- A. 5xx HTTP response code
- B. 200 HTTP response code
- C. 306 HTTP response code
- D. 4xx HTTP response code

Answer: D

NEW QUESTION 282

Company C is currently hosting their corporate site in an Amazon S3 bucket with Static Website Hosting enabled. Currently, when visitors go to <http://www.companyc.com> the index.html page is returned. Company C now would like a new page welcome.html to be returned when a visitor enters <http://www.companyc.com> in the browser.

Which of the following steps will allow Company C to meet this requirement? Choose 2 answers

- A. Upload an html page named welcome.html to their S3 bucket

- B. Create a welcome subfolder in their S3 bucket
- C. Set the Index Document property to welcome.html
- D. Move the index.html page to a welcome subfolder
- E. Set the Error Document property to welcome.html

Answer: AC

NEW QUESTION 286

What item operation allows the retrieval of multiple items from a DynamoDB table in a single API call?

- A. GetItem
- B. BatchGetItem
- C. GetMultipleItems
- D. GetItemRange

Answer: B

NEW QUESTION 289

Which of the following platforms are supported by Elastic Beanstalk? Choose 2 answers

- A. Apache Tomcat
- B. .NET
- C. IBM Websphere
- D. Oracle JBoss
- E. Jetty

Answer: AB

NEW QUESTION 294

Which EC2 API call would you use to retrieve a list of Amazon Machine Images (AMIs)?

- A. DescribeInstances
- B. DescribeAMIs
- C. DescribeImages
- D. GetAMIs
- E. You cannot retrieve a list of AMIs as there are over 10,000 AMIs

Answer: E

NEW QUESTION 297

When a Simple Queue Service message triggers a task that takes 5 minutes to complete, which process below will result in successful processing of the message and remove it from the queue while minimizing the chances of duplicate processing?

- A. Retrieve the message with an increased visibility timeout, process the message, delete the message from the queue
- B. Retrieve the message with an increased visibility timeout, delete the message from the queue, process the message
- C. Retrieve the message with increased DelaySeconds, process the message, delete the message from the queue
- D. Retrieve the message with increased DelaySeconds, delete the message from the queue, process the message

Answer: A

NEW QUESTION 302

Which features can be used to restrict access to data in S3? Choose 2 answers

- A. Use S3 Virtual Hosting
- B. Set an S3 Bucket policy.
- C. Enable IAM Identity Federation.
- D. Set an S3 ACL on the bucket or the object.
- E. Create a CloudFront distribution for the bucket

Answer: CD

NEW QUESTION 306

Company B provides an online image recognition service and utilizes SQS to decouple system components for scalability. The SQS consumers poll the imaging queue as often as possible to keep end-to-end throughput as high as possible. However, Company B is realizing that polling in tight loops is burning CPU cycles and increasing costs with empty responses.

How can Company B reduce the number of empty responses?

- A. Set the imaging queue visibility Timeout attribute to 20 seconds
- B. Set the Imaging queue ReceiveMessageWaitTimeSeconds attribute to 20 seconds
- C. Set the imaging queue MessageRetentionPeriod attribute to 20 seconds
- D. Set the DelaySeconds parameter of a message to 20 seconds

Answer: B

NEW QUESTION 309

What AWS products and features can be deployed by Elastic Beanstalk? Choose 3 answers

- A. Auto scaling groups
- B. Route 53 hosted zones
- C. Elastic Load Balancers
- D. RDS Instances
- E. Elastic IP addresses
- F. SQS Queues

Answer: ACD

NEW QUESTION 311

How can software determine the public and private IP addresses of the Amazon EC2 instance that it is running on?

- A. Query the appropriate Amazon CloudWatch metric.
- B. Use ipconfig or ifconfig command.
- C. Query the local instance userdata.
- D. Query the local instance metadata

Answer: D

NEW QUESTION 314

Which of the following services are key/value stores? Choose 3 answers

- A. Amazon ElastiCache
- B. Simple Notification Service
- C. DynamoDB
- D. Simple Workflow Service
- E. Simple Storage Service

Answer: ABC

NEW QUESTION 318

How is provisioned throughput affected by the chosen consistency model when reading data from a DynamoDB table?

- A. Strongly consistent reads use the same amount of throughput as eventually consistent reads
- B. Strongly consistent reads use more throughput than eventually consistent reads.
- C. Strongly consistent reads use less throughput than eventually consistent reads
- D. Strongly consistent reads use variable throughput depending on read actMty

Answer: B

NEW QUESTION 323

Which of the following services are included at no additional cost with the use of the AWS platform? Choose 2 answers

- A. Simple Storage Service
- B. Elastic Compute Cloud
- C. Auto Scaling
- D. Elastic Load Balancing
- E. CloudFormation
- F. Simple Workflow Service

Answer: CE

NEW QUESTION 326

If an application is storing hourly log files from thousands of instances from a high traffic web site, which naming scheme would give optimal performance on S3?

- A. Sequential
- B. instanceID_log-HH-DD-NIM-YYYY
- C. instanceID_log-YYYY-NIM-DD-HH
- D. HH-DD-NINI-YYYY-log_instanceID
- E. YYYY-MM-DD-HH-|og_instance|D

Answer: E

NEW QUESTION 330

You run an ad-supported photo sharing website using S3 to serve photos to visitors of your site. At some point you find out that other sites have been linking to the photos on your site, causing loss to your business.

What is an effective method to mitigate this?

- A. Store photos on an EBS volume of the web server
- B. Remove public read access and use signed URLs with expiry dates.
- C. Use CloudFront distributions for static content.
- D. Block the IPs of the offending websites in Security Group

Answer: B

NEW QUESTION 333

Which of the following is chosen as the default region when making an API call with an AWS SDK?

- A. ap-northeast-1
- B. us-west-2
- C. us-east-1
- D. eu-west-1
- E. us-central-1

Answer: C

NEW QUESTION 336

What happens, by default, when one of the resources in a CloudFormation stack cannot be created?

- A. Previously-created resources are kept but the stack creation terminates.
- B. Previously-created resources are deleted and the stack creation terminates.
- C. The stack creation continues, and the final results indicate which steps failed.
- D. CloudFormation templates are parsed in advance so stack creation is guaranteed to succeed.

Answer: B

NEW QUESTION 339

.....

Relate Links

100% Pass Your AWS-Certified-Developer-Associate Exam with Exambible Prep Materials

<https://www.exambible.com/AWS-Certified-Developer-Associate-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>