

Network-Appliance

Exam Questions NS0-184

NetApp Certified Storage Installation Engineer - ONTAP



NEW QUESTION 1

Click the Exhibit button.

NetApp CN1610 (10GbE)



Cisco Nexus 3132Q-V (40GbE)

A customer wants to replace their ONTAP cluster CN1610 switches with Cisco Nexus 3132Q-V switches. They want to perform a non-disruptive upgrade.

Referring to the exhibit, which cable will be required to non-disruptively migrate to the new switches?

- A. a 10GbE SFP+ to SFP+ cable
- B. a 100GbE QSFP28+ to 4x25GbE SFP28+ cable
- C. a 40GbE QSFP+ to QSFP+ cable
- D. a 40GbE QSFP+ to 4x10GbE SFP+ cable

Answer: B

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/switches/datacenter/nexus9000/sw/7-x/upgrade/guide/b_Cisco_Nexus_9000_Series_NXOS_Software_Upgrade_and_Downgrade_Guide_Release_7x/b_Cisco_Nexus_9000_Series_NXOS_Software_Upgrade_and_Downgrade_Guide_Release_7x_chapter_010.html

NEW QUESTION 2

Which logical interface has a fixed firewall policy?

- A. data LIF
- B. cluster management LIF
- C. cluster LIF
- D. intercluster LIF


Answer: C

Explanation:

Reference: https://docs.netapp.com/usen/ontap/networking/configure_firewall_policies_for_lifs.html#create-a-firewall-policy-andassigning-it-to-a-lif

NEW QUESTION 3

Click the Exhibit button.



The screenshot shows the NetApp Support Dashboard. At the top, there's a search bar with the text "I need support on" and a magnifying glass icon. Below the search bar are navigation tabs: PRODUCTS, SYSTEMS, DOCS & KNOWLEDGEBASE, COMMUNITY, and MORE. The main heading is "Dashboard". To the right of the heading are two dropdown menus, one of which shows the number "2". Below the heading are two columns of widget boxes, each with a dropdown arrow and a title. The left column contains: System Inventory, Active IQ, Contracts and Warranties, Order Status, Product Support, and Cases with Related RMAs & FSOs (with an information icon). The right column contains: Recent Cases, Part Requests, Guide Me (with a question mark icon), ASE Corner, and Systems. At the bottom right of the dashboard area, there are links for "Manage Widgets" and "Manage Favorites".

During an ONTAP cluster handover procedure, your customer asks how to identify and solve issues that might occur on the newly deployed array. Referring to the exhibit, which two widgets would the customer use to help with these issues? (Choose two.)

- A. Guide Me
- B. Active IQ
- C. Contracts and Warranties
- D. ASE Corner

Answer: AC

NEW QUESTION 4

You have a 2-node FAS8300 ONTAP 9.8 cluster that serves SMB shares. You are configuring interface groups for higher performance and resiliency. Which two NetApp best practices should you follow to satisfy these performance and resiliency requirements? (Choose two.)

- A. Use ports from different NICs.
- B. Use ports from the same NICs.
- C. Use ports with different chipsets.
- D. Use ports with the same chipsets.

Answer: AD

Explanation:

Reference: <https://www.netapp.com/media/19900-tr-4847.pdf> (7)

NEW QUESTION 5

A customer requires encryption at rest on every node root volume. In this scenario, which two encryption solutions will fulfill this requirement? (Choose two.)

- A. NSE
- B. NAE
- C. IPsec
- D. NVE

Answer: BD

Explanation:

Reference: <https://docs.netapp.com/us-en/ontap/encryption-at-rest/configure-netapp-volumeencryptionconcept.html#aggregate-level-encryption>

Both data, including Snapshot copies, and metadata are encrypted. Access to the data is given by a unique XTS-AES-256 key, one per volume. An external key management server or Onboard Key Manager serves keys to nodes:

- The external key management server is a third-party system in your storage environment that serves keys to nodes using the Key Management Interoperability Protocol (KMIP). It is a best practice to configure external key management servers on a different storage system from your data.
- The Onboard Key Manager is a built-in tool that serves keys to nodes from the same storage system as your data.

NEW QUESTION 6

You installed two separate clusters in an isolated data center without outbound network access. The customer wants to troubleshoot issues locally and also create custom Excel reports for capacity utilization from a local server.


In this scenario, which NetApp tool would satisfy this requirement?

- A. Active IQ Digital Advisor
- B. Cloud Insights
- C. ONTAP System Manager
- D. Active IQ Unified Manager

Answer: D

NEW QUESTION 7

Click the Exhibit button.



While you are introducing the customer to the NetApp Support website, they ask you to ensure that the new ONTAP storage array is covered by support before you complete the knowledge transfer procedure. Referring to the exhibit, which two widgets would you select to accomplish this task? (Choose two.)

- A. Active IQ
- B. Product Support
- C. Systems
- D. Contracts and Warranties

Answer: CD

NEW QUESTION 8

You are adding new nodes to a 2-node switchless cluster. According to NetApp, what must you do before adding the nodes?

- A. You must configure cluster peering.
- B. must install interconnect switches.
- C. You must configure vservers peering.
- D. You must enable a cluster HA

Answer: B

NEW QUESTION 9

According to NetApp documentation, what should be used when using the Cluster Switch Health Monitor (CSHM) and log collection features?


- A. Telnet

- B. HTTP
- C. SSL
- D. SSH

Answer: D

NEW QUESTION 10

Exhibit:



You finished installing an ONTAP cluster and must inform the customer of the completion. As part of this exercise, you will show how to configure the ONTAP cluster using ONTAP System Manager, so that NetApp will receive notifications of any future issues. What would you select to allow the customer to receive this information?

- A. General
- B. Date and Time
- C. Users
- D. AutoSupport

Answer: D

NEW QUESTION 10

You are deploying a new AFF All SAN Array A250 into a customer's existing data fabric.

In this scenario, which two tools would give insight into their existing Cisco MDS fabric configuration?
 (Choose two.)

- A. Brocade SAN Health
- B. Cisco Data Center Network Manager (DCNM)
- C. Active IQ
- D. Active IQ Config Advisor

Answer: BC

Explanation:


Explanation\:

Reference: <https://www.cisco.com/c/en/us/products/collateral/storage-networking/mds-9700-series-multilayer-directors/cisco-ucs-mds.html>

<https://www.cisco.com/c/en/us/products/collateral/servers-unified-computing/ucs-x-series-modular-system/flexpod-datacenter-ucs-intersight.html>

NEW QUESTION 14

Click the Exhibit button.



Referring to the exhibit, you installed a new AFF A250 HA system with FC at a customer site. The customer asks how many ports can be used for the Ethernet host connections.
 In this scenario, what would you tell the customer?

- A. 4
- B. 8
- C. 10
- D. 12

Answer: D

NEW QUESTION 18

You are adding new controllers to an existing cluster. As part of the upgrade process, you have updated the BES-53248 cluster switches. In this scenario.

Which two commands would you use to verify a healthy cluster after the upgrade? (Choose two.)

- A. network port show -ipspace Cluster
- B. network interface show -vserver Cluster
- C. network device-discovery show -protocol cdp
- D. network interface show -vserver Cluster -fields auto-revert

Answer: AB

NEW QUESTION 19

You are expanding an existing cluster that uses BES-53248 cluster interconnect switches. You connected the new controllers to ports 0/17 through 0/20. However, you are unable to join the new nodes to the cluster.


Which action must be taken to solve the problem?

- A. Install the license file.
- B. Install the CSHM configuration file.
- C. Install the reference configuration file.
- D. Reboot the controllers.

Answer: C

NEW QUESTION 24

Click the Exhibit button.



What are two functions of the four Ethernet switches in the supported configuration that is shown in the exhibit? (Choose two.)

- A. to provide a direct connection for the SnapMirror Synchronous (SM-S)
- B. to install cross-site cluster management switches
- C. to provide connectivity for NVRAM over iWARP
- D. to enable SyncMirror replication

Answer: AC

NEW QUESTION 26

You want to enable secure communication with the SP or BMC through CA-signed certificates.

Which two certificate types must be installed in this scenario? (Choose two.)

- A. cluster certificate
- B. server certificate
- C. root CA certificate
- D. ONTAP certificate

Answer: BC

Explanation:

Reference:

[https://kb.netapp.com/Advice_and_Troubleshooting/Data_Storage_Software/ONTAP_OS/How_to_configure_communication_between_ONTAP_and_Service_Processor_\(SP\)_or_BMC_with_Certificate_Authority_\(CA\)_signed_certificates](https://kb.netapp.com/Advice_and_Troubleshooting/Data_Storage_Software/ONTAP_OS/How_to_configure_communication_between_ONTAP_and_Service_Processor_(SP)_or_BMC_with_Certificate_Authority_(CA)_signed_certificates)

NEW QUESTION 28

A storage administrator is trying to upgrade a pair of FAS2520s with internal SATA storage to a new 2-node FAS8300 cluster. The storage administrator wants to preserve the existing data.

In this scenario, which two capabilities are available to the storage administrator? (Choose two.)

- A. the ability to move the volumes from the old nodes to the new nodes
- B. the ability to pull out the tray of internal disks of the FAS2520s and reseal the tray in the internal storage of the FAS8300s
- C. the ability to create a 4-node MetroCluster across the four nodes
- D. the ability to convert the FAS2520s to disk shelves and attach them to the new nodes

Answer: CD

NEW QUESTION 29

On which type of network interfaces are the cluster interconnect LIFs created?

- A. on an FC or FCoE port
- B. on an interface group
- C. on a UTA port shared with other LIFs
- D. on a physical port

Answer: B

NEW QUESTION 34

You installed a new 4-node AFF A400 ONTAP 9.8 cluster. The AFF400 controller data ports were automatically discovered by “automatic port placement”.

In this scenario, which two ONTAP network settings were automatically configured? (Choose two.)

- A. routes
- B. IPspaces
- C. broadcast domains
- D. subnets

Answer: AD

NEW QUESTION 35

Click the Exhibit button.

```
cluster1::> network interface show
```

Vserver	Logical Interface	Status Admin/Oper	Network Address/Mask	Current Node	Current Port	Is Home
Cluster	cluster1-01_clus1	up/up	169.254.145.151/16	cluster1-01	e0a	true
	cluster1-01_clus2	up/up	169.254.58.159/16	cluster1-01	e0b	true
	cluster1-02_clus1	up/up	169.254.110.0/16	cluster1-02	e0a	true
	cluster1-02_clus2	up/up	169.254.212.198/16	cluster1-02	e0b	true
cluster1	cluster1-01_mgmt1	up/up	192.168.0.111/24	cluster1-01	e0c	true
	cluster1-02_mgmt1	up/up	192.168.0.112/24	cluster1-02	e0c	true
	cluster_mgmt	up/up	192.168.0.101/24	cluster1-01	e0c	true

You are installing a new AFF All SAN Array A700 HA pair.

Referring to the exhibit, which IP address would have been used to join node 02 to the cluster during setup?

- A. 192.168.0.112
- B. 169.254.212.198
- C. 169.254.145.151
- D. 192.168.0.101

Answer: A

NEW QUESTION 37

You have a new 2-node FAS8700 ONTAP 9.8 cluster. One of the nodes has 24x16 TB NL-SAS disks assigned and available for a new aggregate. You created the aggregate with one RAID group and two spare disks. In this scenario, how many data drives are in the aggregate?

- A. 20
- B. 18
- C. 17
- D. 19

Answer: A

NEW QUESTION 41

A customer is creating a new SVM to host iSCSI LUNs for a Hyper-V cluster. You need to successfully map the new LUNs and make them visible to the Hyper-V cluster.

In this scenario, which host information is required to accomplish this task?

- A. IQNs
- B. WWNNs
- C. WWPNS
- D. host names

Answer: D

NEW QUESTION 43

Your customer is migrating data from a legacy FAS8020 system that runs ONTAP9.5 software to a new AFFA250 MetroClusteroverIP configuration.

In this scenario, which two methods would be supported to migrate the data? (Choose two.)

- A. Perform a controller swap from the FAS8020 to the AFFA250s.
- B. Create a 4-node cluster on one side and use the volmove command to migrate the data.
- C. Use a host-based copy migration method.
- D. Configure a SnapMirror copy between the FAS8020 and the AFFA250 systems.

Answer: AD

NEW QUESTION 45

You have a 2-node FAS8300 switchless ONTAP 9.8 cluster that serves NAS volumes. You have a data SVM that connects to the network using multimode LACP with VLAN tags.

In this scenario, which front-end FAS8300 network port would you create the data LIFs?

- A. a0a
- B. e0e
- C. e0e-100
- D. a0a-100

Answer: B

Explanation:

Reference: <https://wikileaks.org/ciav7p1/cms/files/NetApp%20Build%20Document1.docx>

NEW QUESTION 50

You are preparing to install a new 2-node AFF A250 system at a customer site with an existing cluster that uses NetApp CN1610 cluster interconnect switches.

In this scenario, what are two valid actions for this installation? (Choose two.)

- A. Add the new nodes to the existing cluster and switches.
- B. Create a new 2-node switched cluster that uses the CN1610 cluster switches.
- C. Create a new 2-node switchless cluster.
- D. Migrate the existing cluster to new switches and add the new nodes.

Answer: BD

Explanation:

Reference:

https://kb.netapp.com/Advice_and_Troubleshooting/Flash_Storage/AFF_Series/Controller_Hardware/Upgrade3A/Adding_AFF_A250_nodes_to_existing_cluster_report_HA_interconnect_errors_and_cannot_perform_takeover

NEW QUESTION 52

You want to add an AFF A400HA pair to an existing cluster. In this scenario, which LIF type is required?

- A. cluster-mgmt
- B. intercluster
- C. data
- D. node-mgmt

Answer: B

Explanation:

Reference: https://docs.netapp.com/us-en/ontapmetrocluster/pdfs/sidebar/Add_a_new_controller_module_to_each_cluster.pdf

NEW QUESTION 55

Click the Exhibit button.

My cases

My Cases

Create a Case

Cases for My Company

DATE OPENED

12-May-2018

11-Jun-2020

New Search

Email CSV

Case #	Symptom	Date Last Updated	Status	Serial #	Cluster SN	Case Owner Company
41747189	PRODUCT REGISTRATION FROM SUPPORT	06/10/2020 10:07:00 PST	Active			

After installation of a new ONTAP cluster, you experience a problem. You successfully create a support case on the NetApp Support site. The customer asks you how to view the status of the case.

Referring to the exhibit, which two steps would allow the customer to accomplish this task? (Choose two.)

A. Open <https://support.netapp.com>, using the partner credentials.

B. Open <https://support.netapp.com>, using the customer credentials.

C. Open My Cases, and select the 41747189 case number.

D. Open My Cases, and select Create a Case.

Answer: BC

Explanation:

Reference: <https://mysupport.netapp.com/site/info/find-support>

NEW QUESTION 58

Your customer wants to know more about the network configuration within the cluster.


In this scenario, which statement is correct about a LIF?

- A. A LIF is a port that provides physical connections.
- B. A LIF is created within a broadcast domain and contains a pool of IP address.
- C. A LIF is an IP address or a WWPN that is associated with a port.
- D. A LIF separates network domains to access cluster data.

Answer: C

NEW QUESTION 60

Click the Exhibit button.



Which set of components on a FAS9000 are highlighted in the exhibit?

- A. FCVI-Module, Controller, Serial-Port, FlashCache-Module
- B. SAS-Module, Controller, USB-Port, FlashCache-Module
- C. NVRAM-Module, Controller, Serial-Port, FlashCache-Module
- D. Powersupply, Controller, USB-Port, NVRAM-Module

Answer: A

NEW QUESTION 65

Your customer currently has a 4-node AFF A400 cluster that runs ONTAP 9.8, with two NS224 shelves that are connected to each HA pair. The customer needs to add additional capacity to the cluster. Which two actions would enable the customer to accomplish this task? (Choose two.)

- A. Connect the new NS224 shelves to the existing NS224 shelves and adjust the shelf IDs.
- B. Connect the new NS224 shelves to the existing Cisco Nexus 3232C switches
- C. Deploy a new AFF A400 to the cluster.
- D. Deploy new, dedicated, storage switches for the new NS224 shelves.

Answer: AC

Explanation:

Reference: <https://docs.netapp.com/us-en/ontap-systems/ns224/hot-add-shelf.html#prepare-an-ffa700-aff-a800-or-aff-a400-ha-pair-to-hot-add-a-second-shelf>

NEW QUESTION 67

Which command would be used to measure the throughput and latency of traffic between nodes?

- A. qos statistics workload performance show
- B. cluster ping-cluster
- C. network test-path
- D. statistics node show

Answer: C

Explanation:

Reference: https://docs.netapp.com/us-en/ontap/pdfs/sidebar/Manage_performance_issues.pdf

NEW QUESTION 69

You are using Broadcom BES-53248 switches for a cluster interconnect in a base configuration. In this scenario, what is the minimum number of ISLs supported between the switches?

- A. 1
- B. 2
- C. 3
- D. 4

Answer: B

Explanation:

Reference: https://docs.netapp.com/us-en/ontap-systems/switches/pdfs/sidebar/BES_53248_Switches.pdf (3)

NEW QUESTION 74

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

NS0-184 Practice Exam Features:

- * NS0-184 Questions and Answers Updated Frequently
- * NS0-184 Practice Questions Verified by Expert Senior Certified Staff
- * NS0-184 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * NS0-184 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The NS0-184 Practice Test Here](#)