

1z0-083 Dumps

Oracle Database Administration II

<https://www.certleader.com/1z0-083-dumps.html>



NEW QUESTION 1

Which three are true about Database Point-in-Time Recovery? (Choose three.)

- A. The database must have FLASHBACK DATABASE ON to perform Database Point-in-Time Recovery.
- B. The database must be in MOUNT state when performing Database Point-in-Time Recovery.
- C. Database Point-in-Time Recovery is performed by the Managed Recovery Process (MRP)
- D. The Database must be in ARCHIVELOG mode.
- E. The target point for the recovery must be specified as a time or System Change Number (SCN).
- F. The database must be open RESETLOGS after Database Point-in-Time Recovery.

Answer: BDF

Explanation:

https://docs.oracle.com/cd/B19306_01/backup.102/b14192/flashptr006.htm#:~:text=Database%20point%2Din%2Dtime%2Drecovery,resetlogs

NEW QUESTION 2

Which two are true about RMAN backups when using a media manager to write backups to tape when there are only two tape drives? (Choose two.)

- A. SBT tape compression can be used even if no RMAN compression is configured.
- B. Any backup set written to the SBT device in this configuration can contain a maximum of two backup pieces.
- C. Any backup written to the SBT device in this configuration can contain a maximum of two backup sets.
- D. SBT tape compression and RMAN backup compression should be used in parallel.
- E. The SBT device should be configured to use PARALLELISM 2 to allow both tape drive to be used simultaneously.

Answer: DE

NEW QUESTION 3

Which two are true about data movement between a non-CDB and a PDB using Data Pump? (Choose two.)

- A. Tablespaces are automatically created as needed while importing full exports in either a non-CDB or a PDB.
- B. Oracle attempts to convert conventional database users to local users when moving schemas from a non-CDB to a PDB.
- C. A new PDB is automatically created when importing a non-CDB into a CDB.
- D. Oracle attempts to convert common users to conventional users when moving schemas from a PDB to a non-CDB.
- E. Moving data from a PDB to a non-CDB is only possible by using transportable tablespace export and import.
- F. Moving data from a non-CDB to a PDB is only possible by using conventional export and import.

Answer: DE

NEW QUESTION 4

A container database called CDB1 is OMF-enabled.

PDB_FILE_NAME_CONVERT is not configured in CDB1. PDB1 was unplugged from CDB1 earlier in the week. Examine this command, which will be executed in CDB1:

```
CREATE PLUGGABLE DATABASE pdb1
USING '/u01/app/oracle/oradata/pdb1.xml' SOURCE_FILE_NAME_CONVERT =
('/u01/app/oracle/oradata', '/u02/app/oracle/oradata');
```

Which two are true? (Choose two.)

- A. PDB1 data files already exist in the correct location.
- B. DBMS_PDB.CHECK_PLUG_COMPATIBILITY must be run in CDB1 before executing the command.
- C. PDB_FILE_NAME_CONVERT must be set before executing the command.
- D. /u01/app/oracle/oradata/pdb1.xml does not contain the current locations of data files for PDB1.
- E. PDB1 must be dropped from CDB1.

Answer: AE

NEW QUESTION 5

Examine this configuration:

- CDB1 is an Oracle Database 12c Release 2 database containing pluggable databases PDB\$SEED, PDB1, and PDB2.
- PDB\$SEED is open READ ONLY
- PDB1 is open READ WRITE
- PDB2 is MOUNTED.
- ORACLE_HOME is /u01/app/oracle/product/18.1.0/dbhome_1.

You execute these commands before upgrading the database to the current release:

```
$ . oraenv
ORACLE_SID = [cdb1] ? cdb1
The Oracle base remains unchanged with value /u01/app/oracle

$ $ORACLE_HOME/jdk/bin/java -jar preupgrade.jar TERMINAL TEXT
```

For which databases will fixup scripts be created?

- A. CDB1, PDB\$SEED, PDB1, and PDB2
- B. PDB\$SEED, PDB1, and PDB2 only
- C. CDB1 and PDB\$SEED only
- D. CDB1, PDB1, and PDB2 only

E. CDB1, PDB\$SEED, and PDB1 only

Answer: E

NEW QUESTION 6

A user complains about poor database performance.

You want to verify if the user's session has waited for certain types of I/O activity. Which view displays all waits waited on by a session at least once?

- A. V\$SESSION_EVENT
- B. V\$SESSTAT
- C. V\$SESSION_WAIT
- D. V\$SESSION_WAIT_CLASS
- E. V\$SESSION

Answer: A

NEW QUESTION 7

Which three are true about opatchauto? (Choose three.)

- A. It performs a shutdown and then a restart of all processes in both Oracle Grid Infrastructure and Oracle Database home during the patching process.
- B. It must be invoked by a user with root user privileges.
- C. Patches are applied via opatchauto.
- D. Users must always input patch plans to opatchauto.
- E. It requires the Oracle Grid Infrastructure and Oracle Database instances to be shut down before being invoked.
- F. It applies patches in nonrolling mode by default.
- G. It is used to apply interim patches to Oracle Grid Infrastructure and Oracle Database home combinations.

Answer: ABC

NEW QUESTION 8

On the 10th of August, you implement an incremental database backup strategy and configure a recovery window of five days.

Level 0 backups are taken on the 10th, 17th, and 24th of August.

Differential level 1 incremental backups are taken daily between the level 0 backups. Today is the 26th of August.

Which backups will be obsolete?

- A. all backups prior to 10th of August
- B. all backups prior to 22nd of August
- C. all backups prior to 24th of August
- D. all backups prior to 20th of August
- E. all backups prior to 17th of August

Answer: C

NEW QUESTION 9

Examine these queries and their output:

```
SQL> select pdb_name, name, pdb_restore_point, clean_pdb_restore_point
       2 from v$restore_point natural join dba_pdbs;
```

PDB_NAME	NAME	PDB_RESTORE_POINT	CLEAN_PDB_RESTORE_POINT
PDB1	R1	YES	NO

```
SQL> select property_name, property_value
       2 from database_properties where property_name like '%UNDO%';
```

PROPERTY_NAME	PROPERTY_VALUE
LOCAL_UNDO_ENABLED	FALSE

An online RMAN backup of the CDB was taken an hour before Restore Point R1 was created. You want to recover PDB1 to Restore Point R1. How do you achieve this?

- A. Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using RMAN while connected to PDB1.
- B. Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using SQL while connected to PDB1.
- C. Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using SQL while connected to CDB\$ROOT.
- D. Execute FLASHBACK PLUGGABLE DATABASE PDB1 TO RESTORE POINT R1 by using RMAN while connected to CDB\$ROOT.
- E. This cannot be done due to the lack of a clean restore point.

Answer: B

NEW QUESTION 10

Which two are true about duplicating pluggable databases (PDBs) with RMAN? (Choose two.)

- A. Two or more PDBs can be duplicated with the same RMAN DUPLICATE command.
- B. All tablespaces belonging to a PDB must be duplicated when duplicating the PDB.
- C. The auxiliary instance is automatically created with ENABLE_PLUGGABLE_DATABASE = TRUE.
- D. A user with SYSDBA or SYSBACKUP must be logged in with RMAN to the PDB to duplicate it.

E. CDB\$ROOT and PDB\$SEED are automatically duplicated.

Answer: CD

NEW QUESTION 10

Which two are true about creating pluggable databases (PDBs) using snapshots in Oracle 19c and later releases? (Choose two.)

- A. A PDB snapshot is always a full copy of the source PDB.
- B. A PDB snapshot is always a sparse copy of the source PDB.
- C. A snapshot copy PDB depends on a storage snapshot which can only be stored on specific file systems.
- D. A PDB snapshot depends on a storage snapshot which can be stored on any file system.
- E. A PDB snapshot depends on a storage snapshot which can only be stored on specific file systems.
- F. A snapshot copy PDB depends on a storage snapshot which can be stored on any file system.
- G. A snapshot copy PDB can be created from a stand-alone clone PDB.

Answer: AE

NEW QUESTION 11

Which two are true about RMAN encryption? (Choose two.)

- A. RMAN encryption keys are stored in a database keystore.
- B. RMAN can encrypt the Oracle Database password file.
- C. Dual-mode encrypted backups can be restored only if both the password and the keystore used for encryption are available.
- D. The SET ENCRYPTION command overrides encryption settings specified by the CONFIGURE ENCRYPTION command.
- E. Password encryption can be persistently configured using the CONFIGURE ENCRYPTION command.

Answer: CD

NEW QUESTION 15

Which four are true about performing Tablespace Point -In-Time Recovery (TSPITR) using Recovery Manager (RMAN)?

- A. It can be performed using an auxiliary instance managed by a DBA.
- B. It can be used to recover a truncated table.
- C. RMAN automatically adds any required tablespaces to the recovery set to make it self-contained.
- D. RMAN always includes tablespaces containing undo segments in the recovery set.
- E. It can be performed repeatedly until the correct time is found without using an RMAN catalog.
- F. flashback database must be enabled for it to work.
- G. It can be used to recover a dropped tablespace.
- H. It can be performed using an auxiliary instance managed by RMAN.

Answer: AEFH

NEW QUESTION 16

Which three are true about requirements for various FLASHBACK operations? (Choose three.)

- A. FLASHBACK transaction query requires undo to retrieve all versions of a row that existed between two points in time.
- B. FLASHBACK drop requires that the RECYCLEBIN parameter be set to ON.
- C. FLASHBACK version query requires that the RECYCLEBIN parameter be set to ON.
- D. FLASHBACK DATA ARCHIVE requires undo to store all versions of all rows of a table being tracked.
- E. FLASHBACK drop requires undo to retrieve all versions of a row that existed between two points in time.
- F. FLASHBACK version query requires undo to retrieve all versions of a row that existed between two points in time.

Answer: ABF

NEW QUESTION 21

Which two are true about OS groups and users for OracleGrid Infrastructure and the Oracle Relational Database Management System (RDBMS)? (Choose two.)

- A. By default, members of the OSASM group can access Automatic Storage Management and RDBMS instances.
- B. The primary group for the Oracle Grid Infrastructure and Oracle Database owners must be the Oracle Inventory group.
- C. The Oracle Grid Infrastructure installation must be owned by the grid user.
- D. The Oracle Grid Infrastructure owner owns Oracle Restart and Oracle Automatic Storage Management binaries.
- E. The Oracle Grid Infrastructure owner must have OSOPER, OSBACKUPDBA, and OSKMDBA as secondary groups.
- F. The same OSDBA group must be used for Automatic Storage Management and the Oracle Database.

Answer: EF

NEW QUESTION 23

Oracle Managed Files (OMF) is enabled in a CDB and this command is successfully executed:

```
CREATE PLUGGABLE DATABASE app1
  AS APPLICATION CONTAINER
  ADMIN USER admin1 IDENTIFIED BY app_123 ROLES=(CONNECT);
```

Which three are true? (Choose three.)

- A. Application PDBs that are subsequently created in the APP1 application container will be cloned from APP1\$SEED.
- B. An application seed PDB is created for APP1.
- C. An application root PDB is created for APP1.

- D. A default service is created for the application root APP1.
- E. Application PDBs that are subsequently created in the APP1 application container will be cloned from PDB\$SEED.
- F. APP1 can never be unplugged.

Answer: ABE

NEW QUESTION 24

Examine the command for creating pluggable database PDB2 in container database CDB2.

```
CREATE PLUGGABLE DATABASE pdb2  
  ADMIN USER pdb2_adm  
  IDENTIFIED BY 123pdb  
  ROLES=(CONNECT) ;
```

Select three options, any one of which is required for it to execute successfully. (Choose three.)

- A. Add the FILE_NAME_CONVERT clause to the statement and set the PDB_FILE_NAME_CONVERT parameter.
- B. Add only the CREATE_FILE_DEST clause to the statement.
- C. Set only the PDB_FILE_NAME_CONVERT parameter.
- D. Set the PDB_FILE_NAME_CONVERT parameter and enable OMF.
- E. Enable only OMF.
- F. Add the FILE_NAME_CONVERT clause to the statement and enable Oracle Managed Files (OMF)

Answer: BDE

NEW QUESTION 27

Which three are true about Audit policies In container databases (CDBs)?

- A. All audit records are written to the audit trail in CDB\$ROOT
- B. A common unified audit policy can be created at the application root level.
- C. A common unified audit policy can be created at the CDB level.
- D. An application PDB cannot have a local audit policy.
- E. Fine-grained auditing policies defined in an application root must be manually synchronized by each application PDB contained in the application root.
- F. Application-common unified audit policies defined In an application root must be manually synchronized by each application PDB contained in the application root.

Answer: DEF

NEW QUESTION 32

Which three actions are performed by the Oracle Preinstallation RPM, oracle-database-server-xxxx- preinstall, for Oracle Grid Infrastructure, where xxxx is the Oracle version and release? (Choose three.)

- A. performing checks to ensure minimum configuration requirements for Oracle Grid Infrastructure are met
- B. creating the oracle OS user
- C. creating the OSDBA (dba) group
- D. creating the oraInventory (oinstall) group
- E. creating the grid OS user
- F. configuring the OS for Oracle Automatic Storage Management shared storage access

Answer: BCD

NEW QUESTION 36

Which two are true about unplugging an application container from a container database and plugging it into a different container database?

- A. It requires local undo mode in both container databases.
- B. It requires only local undo mode in the database where the application container will be unplugged.
- C. Plugging the application root into a different CDB plugs In all its application PDBs.
- D. Application PDBs In the application container must be unplugged before the application root is unplugged.
- E. Unplugging the application root from a CDB unplugs all its application PDBs.
- F. The application root of an application container should be plugged Into the other CDB before its application PDBs are plugged in.

Answer: DE

NEW QUESTION 39

Which three are true In Oracle 19c and later releases?

- A. Tablespaces always remain In read/write mode during transportable tablespace operations.
- B. Simultaneous data pump jobs can be limited at the pluggable database (PDB) level.
- C. Tablespaces never remain In read/write mode during transportable tablespace operations.
- D. An ordinary data pump export of a table with encrypted columns will always encrypt the same columns when imported.
- E. A transportable data pump import can leave a plugged-in tablespace in read-only mode.
- F. A transportable data pump import can leave a plugged-in tablespace In read/write mode.

Answer: ADE

NEW QUESTION 44

Which three are true about upgrading Oracle Grid Infrastructure? (Choose three.)

- A. A direct upgrade can be performed only from the immediately preceding Oracle Grid Infrastructure version.
- B. The newer version is installed in a separate Oracle Grid Infrastructure home on the same server as the existing version.
- C. An existing Oracle base can be used.
- D. The upgrade process will automatically install all mandatory patches for the current version of Oracle Grid Infrastructure.
- E. Existing Oracle Database instances must be shut down before starting the upgrade.
- F. Only the grid user can perform the upgrade.

Answer: DEF

NEW QUESTION 47

Which three are true about an application seed pluggable database (PDB)? (Choose three.)

- A. It is automatically synchronized with its application root PDB when an application is upgraded.
- B. It cannot be added to an application container after the application container has already been created.
- C. A new application PDB created by cloning an application seed PDB can have an old version of the application installed after cloning completes.
- D. It is automatically synchronized with its application root PDB when an application is installed.
- E. It cannot be dropped from its application container.
- F. A new application PDB created by cloning an application seed PDB can have an up-to-date version of the application installed after cloning completes.
- G. It is not required in an application container.

Answer: DFG

NEW QUESTION 52

Which three are true about the SQL Tuning Advisor? (Choose three.)

- A. It checks each query being analyzed for stale statistics.
- B. It checks each query being analyzed for missing statistics.
- C. It only recommends syntactic changes to SQL statements.
- D. It can recommend semantic changes to SQL statements.
- E. It considers all SQL statements being analyzed by the advisor task as a group.
- F. It builds SQL profiles for each poorly performing SQL statement to prevent regressions.

Answer: ABF

NEW QUESTION 56

Which two are true about automatic block repair? (Choose two.)

- A. Automatic block repair can repair blocks with no standby database if DB_BLOCK_CHECKING = TRUE.
- B. Real-Time Query must be enabled on a physical standby database for automatic block repair to be done on that physical standby database.
- C. Real-Time Query must be enabled on a primary database for automatic block repair to be done on any of its physical standby databases.
- D. It is not possible for media corrupt blocks.
- E. Real-Time Query must be enabled on a physical standby database for automatic block repair to be done on its primary database.

Answer: BC

NEW QUESTION 61

You have configured RMAN SBT channels to write backups to media. You then take an RMAN backup by using this command:

```
RMAN> BACKUP AS COMPRESSED BACKUPSET
        DATABASE
        KEEP UNTIL TIME 'SYSDATE + 730'
        RESTORE POINT 'OLD_CONFIGURATION';
```

Which three are true? (Choose three.)

- A. The restore point is a label for the system change number (SCN) that will be saved two years after the archival backup was taken.
- B. The data file backups in the self-contained archive backup are not considered obsolete for two years regardless of the retention policy.
- C. All archive logs created after this backup are kept for two years.
- D. The SPFILE is included in the self-contained archival backup.
- E. The control file is included in the self-contained archival backup.
- F. The restore point is a label for the system change number (SCN) before the archival backup was taken.

Answer: CDE

NEW QUESTION 62

You plan to install Oracle Grid Infrastructure for a Standalone Server and Oracle Database for the first time on a server. Examine this command and its outcome:

```
# id oracle
uid=54321 (oracle) gid=54321(oinstall) groups=54321(oinstall), 54322 (dba)
```

Which two are true? (Choose two.)

- A. oracle will be an owner of the Oracle Inventory.
- B. oracle must be the owner of every Oracle Database installation.
- C. oracle can own an Oracle Database installation but not an Oracle Grid Infrastructure installation.
- D. oracle will be granted the SYSASM privilege when installing the Oracle Database software.
- E. The user account, oracle, and group, oinstall, can be used for all Oracle software installations.

Answer: CD

NEW QUESTION 65

Which two are true about diagnosing Oracle Database failure situations using Data Recovery Advisor? (Choose two.)

- A. Using the Data Recovery Advisor LIST FAILURE command always requires that the database for which failures are to be listed is in MOUNT state.
- B. A failure can be closed only when it has been repaired.
- C. Data Recovery Advisor can be used if a database is closed.
- D. The Data Recovery Advisor CHANGE FAILURE command can be used only to change failure priorities.
- E. Data Recovery Advisor can proactively check for failures.

Answer: DE

NEW QUESTION 66

Which three are true about performing an Oracle Database install on Linux? (Choose three.)

- A. The runfixup.sh script can install missing RPMs.
- B. The Oracle Preinstallation RPM must be used to configure the Oracle database installation owner, the Oracle Inventory group, and an Oracle administrative privileges group.
- C. It allows you to select the languages supported by the Oracle database server.
- D. It can be done before installing Grid Infrastructure for a Standalone Server.
- E. The Oracle Preinstallation RPM can be used to configure the Oracle database installation owner, the Oracle Inventory group, and an Oracle administrative privileges group.
- F. It can be done after installing Grid Infrastructure for a Standalone Server.
- G. The Oracle database administrator must be granted access to the root operating system account to run root privileged scripts.

Answer: CEG

NEW QUESTION 68

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 1z0-083 Exam with Our Prep Materials Via below:

<https://www.certleader.com/1z0-083-dumps.html>