



Amazon-Web-Services

Exam Questions ANS-C01

AWS Certified Advanced Networking Specialty Exam

NEW QUESTION 1

An IoT company sells hardware sensor modules that periodically send out temperature, humidity, pressure, and location data through the MQTT messaging protocol. The hardware sensor modules send this data to the company's on-premises MQTT brokers that run on Linux servers behind a load balancer. The hardware sensor modules have been hardcoded with public IP addresses to reach the brokers. The company is growing and is acquiring customers across the world. The existing solution can no longer scale and is introducing additional latency because of the company's global presence. As a result, the company decides to migrate its entire infrastructure from on premises to the AWS Cloud. The company needs to migrate without reconfiguring the hardware sensor modules that are already deployed across the world. The solution also must minimize latency. The company migrates the MQTT brokers to run on Amazon EC2 instances. What should the company do next to meet these requirements?

- A. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- B. Use Bring Your Own IP (BYOIP) from the on-premises network with the NLB.
- C. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- D. Create an AWS Global Accelerator accelerator in front of the NLB. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator.
- E. Place the EC2 instances behind an Application Load Balancer (ALB). Configure TCP listener
- F. Create an AWS Global Accelerator accelerator in front of the ALB
- G. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator
- H. Place the EC2 instances behind an Amazon CloudFront distribution
- I. Use Bring Your Own IP (BYOIP) from the on-premises network with CloudFront.

Answer: B

NEW QUESTION 2

A data analytics company has a 100-node high performance computing (HPC) cluster. The HPC cluster is for parallel data processing and is hosted in a VPC in the AWS Cloud. As part of the data processing workflow, the HPC cluster needs to perform several DNS queries to resolve and connect to Amazon RDS databases, Amazon S3 buckets, and on-premises data stores that are accessible through AWS Direct Connect. The HPC cluster can increase in size by five to seven times during the company's peak event at the end of the year. The company is using two Amazon EC2 instances as primary DNS servers for the VPC. The EC2 instances are configured to forward queries to the default VPC resolver for Amazon Route 53 hosted domains and to the on-premises DNS servers for other on-premises hosted domain names. The company notices job failures and finds that DNS queries from the HPC cluster nodes failed when the nodes tried to resolve RDS and S3 bucket endpoints. Which architectural change should a network engineer implement to provide the DNS service in the MOST scalable way?

- A. Scale out the DNS service by adding two additional EC2 instances in the VPC
- B. Reconfigure half of the HPC cluster nodes to use these new DNS servers
- C. Plan to scale out by adding additional EC2 instance-based DNS servers in the future as the HPC cluster size grows.
- D. Scale up the existing EC2 instances that the company is using as DNS servers
- E. Change the instance size to the largest possible instance size to accommodate the current DNS load and the anticipated load in the future.
- F. Create Route 53 Resolver outbound endpoint
- G. Create Route 53 Resolver rules to forward queries to on-premises DNS servers for on-premises hosted domain names
- H. Reconfigure the HPC cluster nodes to use the default VPC resolver instead of the EC2 instance-based DNS server
- I. Terminate the EC2 instances.
- J. Create Route 53 Resolver inbound endpoint
- K. Create rules on the on-premises DNS servers to forward queries to the default VPC resolver
- L. Reconfigure the HPC cluster nodes to forward all DNS queries to the on-premises DNS server
- M. Terminate the EC2 instances.

Answer: C

NEW QUESTION 3

A company has its production VPC (VPC-A) in the eu-west-1 Region in Account 1. VPC-A is attached to a transit gateway (TGW-A) that is connected to an on-premises data center in Dublin, Ireland, by an AWS Direct Connect transit VIF that is configured for an AWS Direct Connect gateway. The company also has a staging VPC (VPC-B) that is attached to another transit gateway (TGW-B) in the eu-west-2 Region in Account 2. A network engineer must implement connectivity between VPC-B and the on-premises data center in Dublin. Which solutions will meet these requirements? (Choose two.)

- A. Configure inter-Region VPC peering between VPC-A and VPC-B
- B. Add the required VPC peering route
- C. Add the VPC-B CIDR block in the allowed prefixes on the Direct Connect gateway association.
- D. Associate TGW-B with the Direct Connect gateway
- E. Advertise the VPC-B CIDR block under the allowed prefixes.
- F. Configure another transit VIF on the Direct Connect connection and associate TGW-B
- G. Advertise the VPC-B CIDR block under the allowed prefixes.
- H. Configure inter-Region transit gateway peering between TGW-A and TGW-B
- I. Add the peering routes in the transit gateway route table
- J. Add both the VPC-A and the VPC-B CIDR block under the allowed prefix list in the Direct Connect gateway association.
- K. Configure an AWS Site-to-Site VPN connection over the transit VIF to TGW-B as a VPN attachment.

Answer: BC

Explanation:

* B. Associate TGW-B with the Direct Connect gateway. Advertise the VPC-B CIDR block under the allowed prefixes. This will allow traffic from VPC-B to be sent over the Direct Connect connection to the on-premises data center via TGW-B. C. Configure another transit VIF on the Direct Connect connection and associate TGW-B. Advertise the VPC-B CIDR block under the allowed prefixes. This will enable the use of the Direct Connect connection for VPC-B's traffic by connecting TGW-B to the Direct Connect gateway.

NEW QUESTION 4

A company has hundreds of VPCs on AWS. All the VPCs access the public endpoints of Amazon S3 and AWS Systems Manager through NAT gateways. All the traffic from the VPCs to Amazon S3 and Systems Manager travels through the NAT gateways. The company's network engineer must centralize access to these

services and must eliminate the need to use public endpoints.
Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a central egress VPC that has private NAT gateway
- B. Connect all the VPCs to the central egress VPC by using AWS Transit Gateway
- C. Use the private NAT gateways to connect to Amazon S3 and Systems Manager by using private IP addresses.
- D. Create a central shared services VPC
- E. In the central shared services VPC, create interface VPC endpoints for Amazon S3 and Systems Manager to access
- F. Ensure that private DNS is turned off
- G. Connect all the VPCs to the central shared services VPC by using AWS Transit Gateway
- H. Create an Amazon Route 53 forwarding rule for each interface VPC endpoint
- I. Associate the forwarding rules with all the VPC
- J. Forward DNS queries to the interface VPC endpoints in the shared services VPC.
- K. Create a central shared services VPC
- L. In the central shared services VPC, create interface VPC endpoints for Amazon S3 and Systems Manager to access
- M. Ensure that private DNS is turned off
- N. Connect all the VPCs to the central shared services VPC by using AWS Transit Gateway
- O. Create an Amazon Route 53 private hosted zone with a full service endpoint name for Amazon S3 and Systems Manager
- P. Associate the private hosted zones with all the VPC
- Q. Create an alias record in each private hosted zone with the full AWS service endpoint pointing to the interface VPC endpoint in the shared services VPC.
- R. Create a central shared services VPC
- S. In the central shared services VPC, create interface VPC endpoints for Amazon S3 and Systems Manager to access
- T. Connect all the VPCs to the central shared services VPC by using AWS Transit Gateway
- U. Ensure that private DNS is turned on for the interface VPC endpoints and that the transit gateway is created with DNS support turned on.

Answer: B

Explanation:

Interface VPC endpoints enable private connectivity between VPCs and supported AWS services without requiring an internet gateway, NAT device, VPN connection, or AWS Direct Connect connection². Interface VPC endpoints are powered by AWS PrivateLink, a technology that enables private access to AWS services². Amazon S3 and AWS Systems Manager support interface VPC endpoints². By turning off private DNS, the interface VPC endpoints can be accessed by using their private IP addresses². By using Amazon Route 53 forwarding rules, DNS queries can be resolved to the interface VPC endpoints in the shared services VPC³.

NEW QUESTION 5

A real estate company is building an internal application so that real estate agents can upload photos and videos of various properties. The application will store these photos and videos in an Amazon S3 bucket as objects and will use Amazon DynamoDB to store corresponding metadata. The S3 bucket will be configured to publish all PUT events for new object uploads to an Amazon Simple Queue Service (Amazon SQS) queue.

A compute cluster of Amazon EC2 instances will poll the SQS queue to find out about newly uploaded objects. The cluster will retrieve new objects, perform proprietary image and video recognition and classification, update metadata in DynamoDB and replace the objects with new watermarked objects. The company does not want public IP addresses on the EC2 instances.

Which networking design solution will meet these requirements MOST cost-effectively as application usage increases?

- A. Place the EC2 instances in a public subnet
- B. Disable the Auto-assign Public IP option while launching the EC2 instance
- C. Create an internet gateway
- D. Attach the internet gateway to the VPC
- E. In the public subnet's route table, add a default route that points to the internet gateway.
- F. Place the EC2 instances in a private subnet
- G. Create a NAT gateway in a public subnet in the same Availability Zone
- H. Create an internet gateway
- I. Attach the internet gateway to the VPC
- J. In the public subnet's route table, add a default route that points to the internet gateway
- K. Place the EC2 instances in a private subnet
- L. Create an interface VPC endpoint for Amazon SQS
- M. Create gateway VPC endpoints for Amazon S3 and DynamoDB.
- N. Place the EC2 instances in a private subnet
- O. Create a gateway VPC endpoint for Amazon SQS. Create interface VPC endpoints for Amazon S3 and DynamoDB.

Answer: C

NEW QUESTION 6

A company's network engineer is designing a hybrid DNS solution for an AWS Cloud workload. Individual teams want to manage their own DNS hostnames for their applications in their development environment. The solution must integrate the application-specific hostnames with the centrally managed DNS hostnames from the on-premises network and must provide bidirectional name resolution. The solution also must minimize management overhead.

Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Use an Amazon Route 53 Resolver inbound endpoint.
- B. Modify the DHCP options set by setting a custom DNS server value.
- C. Use an Amazon Route 53 Resolver outbound endpoint.
- D. Create DNS proxy servers.
- E. Create Amazon Route 53 private hosted zones.
- F. Set up a zone transfer between Amazon Route 53 and the on-premises DNS.

Answer: ABE

NEW QUESTION 7

A software-as-a-service (SaaS) provider hosts its solution on Amazon EC2 instances within a VPC in the AWS Cloud. All of the provider's customers also have their environments in the AWS Cloud.

A recent design meeting revealed that the customers have IP address overlap with the provider's AWS deployment. The customers have stated that they will not share their internal IP addresses and that they do not want to connect to the provider's SaaS service over the internet.

Which combination of steps is part of a solution that meets these requirements? (Choose two.)

- A. Deploy the SaaS service endpoint behind a Network Load Balancer.
- B. Configure an endpoint service, and grant the customers permission to create a connection to the endpoint service.
- C. Deploy the SaaS service endpoint behind an Application Load Balancer.
- D. Configure a VPC peering connection to the customer VPC
- E. Route traffic through NAT gateways.
- F. Deploy an AWS Transit Gateway, and connect the SaaS VPC to it
- G. Share the transit gateway with the customer
- H. Configure routing on the transit gateway.

Answer: AB

Explanation:

NLB for creating the private link which solves the overlapping IP address issue and the SaaS service endpoint behind it. (the SaaS endpoint could be an ALB)
<https://aws.amazon.com/about-aws/whats-new/2021/09/application-load-balancer-aws-privatelink-static-ip>

NEW QUESTION 8

A customer has set up multiple VPCs for Dev, Test, Prod, and Management. You need to set up AWS Direct Connect to enable data flow from on-premises to each VPC. The customer has monitoring software running in the Management VPC that collects metrics from the instances in all the other VPCs. Due to budget requirements, data transfer charges should be kept at minimum.

Which design should be recommended?

- A. Create a total of four private VIFs, one for each VPC owned by the customer, and route traffic between VPCs using the Direct Connect link.
- B. Create a private VIF to the Management VPC, and peer this VPC to all other VPCs.
- C. Create a private VIF to the Management VPC, and peer this VPC to all other VPCs, enable source/destination NAT in the Management VPC.
- D. Create a total of four private VIFs, and enable VPC peering between all VPCs.

Answer: D

Explanation:

- creating VPC peering is free of charge - traffic costs ~0.01€/GB for VPC peering (IN + OUT) and ~0.02€/GB for direct connect (OUT only). As the communication involved in monitoring will never have IN == OUT, then $0.01 * (IN + OUT)$ will always be lower than $0.02 * OUT$, ergo VPC peering will be cheaper

NEW QUESTION 9

A company has two AWS accounts one for Production and one for Connectivity. A network engineer needs to connect the Production account VPC to a transit gateway in the Connectivity account. The feature to auto accept shared attachments is not enabled on the transit gateway.

Which set of steps should the network engineer follow in each AWS account to meet these requirements?

- A. * 1. In the Production account: Create a resource share in AWS Resource Access Manager for the transit gateway
- B. Provide the Connectivity account ID
- C. Enable the feature to allow external accounts* 2. In the Connectivity account: Accept the resource.* 3. In the Connectivity account: Create an attachment to the VPC subnets.* 4. In the Production account: Accept the attachment
- D. Associate a route table with the attachment.
- E. * 1. In the Production account: Create a resource share in AWS Resource Access Manager for the VPC subnet
- F. Provide the Connectivity account ID
- G. Enable the feature to allow external accounts.* 2. In the Connectivity account: Accept the resource.* 3. In the Production account: Create an attachment on the transit gateway to the VPC subnets.* 4. In the Connectivity account: Accept the attachment
- H. Associate a route table with the attachment.
- I. * 1. In the Connectivity account: Create a resource share in AWS Resource Access Manager for the VPC subnet
- J. Provide the Production account ID
- K. Enable the feature to allow external accounts.* 2. In the Production account: Accept the resource.* 3. In the Connectivity account: Create an attachment on the transit gateway to the VPC subnets.* 4. In the Production account: Accept the attachment
- L. Associate a route table with the attachment.
- M. * 1. In the Connectivity account: Create a resource share in AWS Resource Access Manager for the transit gateway
- N. Provide the Production account ID Enable the feature to allow external accounts.* 2. In the Production account: Accept the resource.* 3. In the Production account: Create an attachment to the VPC subnets.* 4. In the Connectivity account: Accept the attachment
- O. Associate a route table with the attachment.

Answer: A

Explanation:

step 1: In the Production account, create a resource share in AWS Resource Access Manager for the transit gateway and provide the Connectivity account ID. Enabling the feature to allow external accounts is also required to share resources between accounts. Step 2: In the Connectivity account, accept the shared resource. This action will allow the Production account to use the transit gateway in the Connectivity account. Step 3: In the Connectivity account, create an attachment to the VPC subnets. This attachment will enable communication between the VPC in the Production account and the transit gateway in the Connectivity account. Step 4: In the Production account, accept the attachment and associate a route table with the attachment. This will enable the VPC to route traffic through the transit gateway to other resources in the Connectivity account.

NEW QUESTION 10

You deploy an Amazon EC2 instance that runs a web server into a subnet in a VPC. An Internet gateway is attached, and the main route table has a default route (0.0.0.0/0) configured with a target of the Internet gateway.

The instance has a security group configured to allow as follows:

- Protocol: TCP
- Port: 80 inbound, nothing outbound

The Network ACL for the subnet is configured to allow as follows:

- Protocol: TCP

➤ Port: 80 inbound, nothing outbound

When you try to browse to the web server, you receive no response. Which additional step should you take to receive a successful response?

- A. Add an entry to the security group outbound rules for Protocol: TCP, Port Range: 80
- B. Add an entry to the security group outbound rules for Protocol: TCP, Port Range: 1024-65535
- C. Add an entry to the Network ACL outbound rules for Protocol: TCP, Port Range: 80
- D. Add an entry to the Network ACL outbound rules for Protocol: TCP, Port Range: 1024-65535

Answer: D

Explanation:

To enable the connection to a service running on an instance, the associated network ACL must allow both inbound traffic on the port that the service is listening on as well as allow outbound traffic from ephemeral ports. When a client connects to a server, a random port from the ephemeral port range (1024-65535) becomes the client's source port. The designated ephemeral port then becomes the destination port for return traffic from the service, so outbound traffic from the ephemeral port must be allowed in the network ACL. <https://aws.amazon.com/premiumsupport/knowledge-center/resolve-connection-sg-acl-inbound/>

NEW QUESTION 10

A company is building its website on AWS in a single VPC. The VPC has public subnets and private subnets in two Availability Zones. The website has static content such as images. The company is using Amazon S3 to store the content.

The company has deployed a fleet of Amazon EC2 instances as web servers in a private subnet. The EC2 instances are in an Auto Scaling group behind an Application Load Balancer. The EC2 instances will serve traffic, and they must pull content from an S3 bucket to render the webpages. The company is using AWS Direct Connect with a public VIF for on-premises connectivity to the S3 bucket.

A network engineer notices that traffic between the EC2 instances and Amazon S3 is routing through a NAT gateway. As traffic increases, the company's costs are increasing. The network engineer needs to change the connectivity to reduce the NAT gateway costs that result from the traffic between the EC2 instances and Amazon S3.

Which solution will meet these requirements?

- A. Create a Direct Connect private VIF
- B. Migrate the traffic from the public VIF to the private VIF.
- C. Create an AWS Site-to-Site VPN tunnel over the existing public VIF.
- D. Implement interface VPC endpoints for Amazon S3. Update the VPC route table.
- E. Implement gateway VPC endpoints for Amazon S3. Update the VPC route table.

Answer: D

NEW QUESTION 15

An IoT company sells hardware sensor modules that periodically send out temperature, humidity, pressure, and location data through the MQTT messaging protocol. The hardware sensor modules send this data to the company's on-premises MQTT brokers that run on Linux servers behind a load balancer. The hardware sensor modules have been hardcoded with public IP addresses to reach the brokers.

The company is growing and is acquiring customers across the world. The existing solution can no longer scale and is introducing additional latency because of the company's global presence. As a result, the company decides to migrate its entire infrastructure from on premises to the AWS Cloud. The company needs to migrate without reconfiguring the hardware sensor modules that are already deployed across the world. The solution also must minimize latency.

The company migrates the MQTT brokers to run on Amazon EC2 instances. What should the company do next to meet these requirements?

- A. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- B. Use Bring Your Own IP (BYOIP) from the on-premises network with the NLB.
- C. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- D. Create an AWS Global Accelerator accelerator in front of the NLB. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator.
- E. Place the EC2 instances behind an Application Load Balancer (ALB). Configure TCP listener
- F. Create an AWS Global Accelerator accelerator in front of the ALB
- G. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator
- H. Place the EC2 instances behind an Amazon CloudFront distribution
- I. Use Bring Your Own IP (BYOIP) from the on-premises network with CloudFront.

Answer: B

NEW QUESTION 16

A company has expanded its network to the AWS Cloud by using a hybrid architecture with multiple AWS accounts. The company has set up a shared AWS account for the connection to its on-premises data centers and the company offices. The workloads consist of private web-based services for internal use. These services run in different AWS accounts. Office-based employees consume these services by using a DNS name in an on-premises DNS zone that is named example.internal.

The process to register a new service that runs on AWS requires a manual and complicated change request to the internal DNS. The process involves many teams.

The company wants to update the DNS registration process by giving the service creators access that will allow them to register their DNS records. A network engineer must design a solution that will achieve this goal. The solution must maximize cost-effectiveness and must require the least possible number of configuration changes.

Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Create a record for each service in its local private hosted zone (serviceA.account1.aws.example.internal). Provide this DNS record to the employees who need access.
- B. Create an Amazon Route 53 Resolver inbound endpoint in the shared account VPC
- C. Create a conditional forwarder for a domain named aws.example.internal on the on-premises DNS server
- D. Set the forwarding IP addresses to the inbound endpoint's IP addresses that were created.
- E. Create an Amazon Route 53 Resolver rule to forward any queries made to onprem.example.internal to the on-premises DNS servers.
- F. Create an Amazon Route 53 private hosted zone named aws.example.internal in the shared AWS account to resolve queries for this domain.
- G. Launch two Amazon EC2 instances in the shared AWS account
- H. Install BIND on each instance
- I. Create a DNS conditional forwarder on each BIND server to forward queries for each subdomain under aws.example.internal to the appropriate private hosted zone in each AWS account

J. Create a conditional forwarder for a domain named aws.example.internal on the on-premises DNS server
K. Set the forwarding IP addresses to the IP addresses of the BIND servers.
L. Create a private hosted zone in the shared AWS account for each account that runs the service. Configure the private hosted zone to contain aws.example.internal in the domain (account1.aws.example.internal). Associate the private hosted zone with the VPC that runs the service and the shared account VPC.

Answer: ABD

Explanation:

To meet the requirements of updating the DNS registration process while maximizing cost-effectiveness and minimizing configuration changes, the network engineer should take the following steps:

- Create an Amazon Route 53 Resolver inbound endpoint in the shared account VPC. Create a conditional forwarder for a domain named aws.example.internal on the on-premises DNS servers. Set the forwarding IP addresses to the inbound endpoint's IP addresses that were created (Option B).
- Create an Amazon Route 53 private hosted zone named aws.example.internal in the shared AWS account to resolve queries for this domain (Option D).
- Create a record for each service in its local private hosted zone (serviceA.account1.aws.example.internal). Provide this DNS record to the employees who need access (Option A).

These steps will allow service creators to register their DNS records while keeping costs low and minimizing configuration changes.

NEW QUESTION 21

A network engineer must provide additional safeguards to protect encrypted data at Application Load Balancers (ALBs) through the use of a unique random session key.

What should the network engineer do to meet this requirement?

- A. Change the ALB security policy to a policy that supports TLS 1.2 protocol only
- B. Use AWS Key Management Service (AWS KMS) to encrypt session keys
- C. Associate an AWS WAF web ACL with the ALB
- D. and create a security rule to enforce forward secrecy (FS)
- E. Change the ALB security policy to a policy that supports forward secrecy (FS)

Answer: D

NEW QUESTION 25

A company has deployed an AWS Network Firewall firewall into a VPC. A network engineer needs to implement a solution to deliver Network Firewall flow logs to the company's Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster in the shortest possible time.

Which solution will meet these requirements?

- A. Create an Amazon S3 bucket
- B. Create an AWS Lambda function to load logs into the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster
- C. Enable Amazon Simple Notification Service (Amazon SNS) notifications on the S3 bucket to invoke the Lambda function
- D. Configure flow logs for the firewall
- E. Set the S3 bucket as the destination.
- F. Create an Amazon Kinesis Data Firehose delivery stream that includes the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster as the destination
- G. Configure flow logs for the firewall Set the Kinesis Data Firehose delivery stream as the destination for the Network Firewall flow logs.
- H. Configure flow logs for the firewall
- I. Set the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster as the destination for the Network Firewall flow logs.
- J. Create an Amazon Kinesis data stream that includes the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster as the destination
- K. Configure flow logs for the firewall
- L. Set the Kinesis data stream as the destination for the Network Firewall flow logs.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/networking-and-content-delivery/how-to-analyze-aws-network-firewall-logs-using-aws-lambda/>

NEW QUESTION 28

A global company operates all its non-production environments out of three AWS Regions: eu-west-1, us-east-1, and us-west-1. The company hosts all its production workloads in two on-premises data centers. The company has 60 AWS accounts and each account has two VPCs in each Region. Each VPC has a virtual private gateway where two VPN connections terminate for resilient connectivity to the data centers. The company has 360 VPN tunnels to each data center, resulting in high management overhead. The total VPN throughput for each Region is 500 Mbps.

The company wants to migrate the production environments to AWS. The company needs a solution that will simplify the network architecture and allow for future growth. The production environments will generate an additional 2 Gbps of traffic per Region back to the data centers. This traffic will increase over time.

Which solution will meet these requirements?

- A. Set up an AWS Direct Connect connection from each data center to AWS in each Region
- B. Create and attach private VIFs to a single Direct Connect gateway
- C. Attach the Direct Connect gateway to all the VPCs
- D. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- E. Create a single transit gateway with VPN connections from each data center
- F. Share the transit gateway with each account by using AWS Resource Access Manager (AWS RAM). Attach the transit gateway to each VPC
- G. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- H. Create a transit gateway in each Region with multiple newly commissioned VPN connections from each data center
- I. Share the transit gateways with each account by using AWS Resource Access Manager (AWS RAM). In each Region, attach the transit gateway to each VPC
- J. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- K. Peer all the VPCs in each Region to a new VPC in each Region that will function as a centralized transit VPC
- L. Create new VPN connections from each data center to the transit VPC
- M. Terminate the original VPN connections that are attached to all the original VPCs
- N. Retain the new VPN connection to the new transit VPC in each Region.

Answer: C

NEW QUESTION 30

A company has a hybrid cloud environment. The company's data center is connected to the AWS Cloud by an AWS Direct Connect connection. The AWS environment includes VPCs that are connected together in a hub-and-spoke model by a transit gateway. The AWS environment has a transit VIF with a Direct Connect gateway for on-premises connectivity.

The company has a hybrid DNS model. The company has configured Amazon Route 53 Resolver endpoints in the hub VPC to allow bidirectional DNS traffic flow. The company is running a backend application in one of the VPCs.

The company uses a message-oriented architecture and employs Amazon Simple Queue Service (Amazon SQS) to receive messages from other applications over a private network. A network engineer wants to use an interface VPC endpoint for Amazon SQS for this architecture. Client services must be able to access the endpoint service from on premises and from multiple VPCs within the company's AWS infrastructure.

Which combination of steps should the network engineer take to ensure that the client applications can resolve DNS for the interface endpoint? (Choose three.)

- A. Create the interface endpoint for Amazon SQS with the option for private DNS names turned on.
- B. Create the interface endpoint for Amazon SQS with the option for private DNS names turned off.
- C. Manually create a private hosted zone for sqs.us-east-1.amazonaws.co
- D. Add necessary records that point to the interface endpoint
- E. Associate the private hosted zones with other VPCs.
- F. Use the automatically created private hosted zone for sqs.us-east-1.amazonaws.com with previously created necessary records that point to the interface endpoint
- G. Associate the private hosted zones with other VPCs.
- H. Access the SQS endpoint by using the public DNS name sqs.us-east-1.amazonaws.com in VPCs and on premises.
- I. Access the SQS endpoint by using the private DNS name of the interface endpoint.sqs.us-east-1.vpce.amazonaws.com in VPCs and on premises.

Answer: ADF

NEW QUESTION 31

A company has two on-premises data center locations. There is a company-managed router at each data center. Each data center has a dedicated AWS Direct Connect connection to a Direct Connect gateway through a private virtual interface. The router for the first location is advertising 110 routes to the Direct Connect gateway by using BGP, and the router for the second location is advertising 60 routes to the Direct Connect gateway by using BGP. The Direct Connect gateway is attached to a company VPC through a virtual private gateway.

A network engineer receives reports that resources in the VPC are not reachable from various locations in either data center. The network engineer checks the VPC route table and sees that the routes from the first data center location are not being populated into the route table. The network engineer must resolve this issue in the most operationally efficient manner.

What should the network engineer do to meet these requirements?

- A. Remove the Direct Connect gateway, and create a new private virtual interface from each company router to the virtual private gateway of the VPC.
- B. Change the router configurations to summarize the advertised routes.
- C. Open a support ticket to increase the quota on advertised routes to the VPC route table.
- D. Create an AWS Transit Gateway
- E. Attach the transit gateway to the VPC, and connect the Direct Connect gateway to the transit gateway.

Answer: B

Explanation:

"If you advertise more than 100 routes each for IPv4 and IPv6 over the BGP session, the BGP session will go into an idle state with the BGP session DOWN." <https://docs.aws.amazon.com/directconnect/latest/UserGuide/limits.html>

NEW QUESTION 36

An organization is using a VPC endpoint for Amazon S3. When the security group rules for a set of instances were initially configured, access was restricted to allow traffic only to the IP addresses of the Amazon S3 API endpoints in the region from the published JSON file. The application was working properly, but now is logging a growing number of timeouts when connecting with Amazon S3. No internet gateway is configured for the VPC.

Which solution will fix the connectivity failures with the LEAST amount of effort?

- A. Create a Lambda function to update the security group based on AmazonIPSpaceChanged notifications.
- B. Update the VPC routing to direct Amazon S3 prefix-list traffic to the VPC endpoint using the route table APIs.
- C. Update the application server's outbound security group to use the prefix-list for Amazon S3 in the same region.
- D. Create an additional VPC endpoint for Amazon S3 in the same route table to scale the concurrent connections to Amazon.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/aws/subscribe-to-aws-public-ip-address-changes-via-amazon-sns/>

NEW QUESTION 40

A banking company is successfully operating its public mobile banking stack on AWS. The mobile banking stack is deployed in a VPC that includes private subnets and public subnets. The company is using IPv4 networking and has not deployed or supported IPv6 in the environment. The company has decided to adopt a third-party service provider's API and must integrate the API with the existing environment. The service provider's API requires the use of IPv6.

A network engineer must turn on IPv6 connectivity for the existing workload that is deployed in a private subnet. The company does not want to permit IPv6 traffic from the public internet and mandates that the company's servers must initiate all IPv6 connectivity. The network engineer turns on IPv6 in the VPC and in the private subnets.

Which solution will meet these requirements?

- A. Create an internet gateway and a NAT gateway in the VP
- B. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT gateway.
- C. Create an internet gateway and a NAT instance in the VP
- D. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT instance.
- E. Create an egress-only Internet gateway in the VPAdd a route to the existing subnet route tables to point IPv6 traffic to the egress-only internet gateway.
- F. Create an egress-only internet gateway in the VP

- G. Configure a security group that denies all inbound traffic.
- H. Associate the security group with the egress-only internet gateway.

Answer: C

NEW QUESTION 45

A company is deploying a new application in the AWS Cloud. The company wants a highly available web server that will sit behind an Elastic Load Balancer. The load balancer will route requests to multiple target groups based on the URL in the request. All traffic must use HTTPS. TLS processing must be offloaded to the load balancer. The web server must know the user's IP address so that the company can keep accurate logs for security purposes. Which solution will meet these requirements?

- A. Deploy an Application Load Balancer with an HTTPS listener
- B. Use path-based routing rules to forward the traffic to the correct target group
- C. Include the X-Forwarded-For request header with traffic to the targets.
- D. Deploy an Application Load Balancer with an HTTPS listener for each domain
- E. Use host-based routing rules to forward the traffic to the correct target group for each domain
- F. Include the X-Forwarded-For request header with traffic to the targets.
- G. Deploy a Network Load Balancer with a TLS listener
- H. Use path-based routing rules to forward the traffic to the correct target group
- I. Configure client IP address preservation for traffic to the targets.
- J. Deploy a Network Load Balancer with a TLS listener for each domain
- K. Use host-based routing rules to forward the traffic to the correct target group for each domain
- L. Configure client IP address preservation for traffic to the targets.

Answer: A

Explanation:

An Application Load Balancer (ALB) can be used to route traffic to multiple target groups based on the URL in the request. The ALB can be configured with an HTTPS listener to ensure all traffic uses HTTPS. TLS processing can be offloaded to the ALB, which reduces the load on the web server. Path-based routing rules can be used to route traffic to the correct target group based on the URL in the request. The X-Forwarded-For request header can be included with traffic to the targets, which will allow the web server to know the user's IP address and keep accurate logs for security purposes.

NEW QUESTION 50

A company operates its IT services through a multi-site hybrid infrastructure. The company deploys resources on AWS in the us-east-1 Region and in the eu-west-2 Region. The company also deploys resources in its own data centers that are located in the United States (US) and in the United Kingdom (UK). In both AWS Regions, the company uses a transit gateway to connect 15 VPCs to each other. The company has created a transit gateway peering connection between the two transit gateways. The VPC CIDR blocks do not overlap with each other or with IP addresses used within the data centers. The VPC CIDR prefixes can also be aggregated either on a Regional level or for the company's entire AWS environment.

The data centers are connected to each other by a private WAN connection. IP routing information is exchanged dynamically through Interior BGP (iBGP) sessions. The data centers maintain connectivity to AWS through one AWS Direct Connect connection in the US and one Direct Connect connection in the UK. Each Direct Connect connection is terminated on a Direct Connect gateway and is associated with a local transit gateway through a transit VIF.

Traffic follows the shortest geographical path from source to destination. For example, packets from the UK data center that are targeted to resources in eu-west-2 travel across the local Direct Connect connection. In cases of cross-Region data transfers, such as from the UK data center to VPCs in us-east-1, the private WAN connection must be used to minimize costs on AWS. A network engineer has configured each transit gateway association on the Direct Connect gateway to advertise VPC-specific CIDR IP prefixes only from the local Region. The routes toward the other Region must be learned through BGP from the routers in the other data center in the original, non-aggregated form.

The company recently experienced a problem with cross-Region data transfers because of issues with its private WAN connection. The network engineer needs to modify the routing setup to prevent similar interruptions in the future. The solution cannot modify the original traffic routing goal when the network is operating normally.

Which modifications will meet these requirements? (Choose two.)

- A. Remove all the VPC CIDR prefixes from the list of subnets advertised through the local Direct Connect connection
- B. Add the company's entire AWS environment aggregate route to the list of subnets advertised through the local Direct Connect connection.
- C. Add the CIDR prefixes from the other Region VPCs and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection
- D. Configure data center routers to make routing decisions based on the BGP communities received.
- E. Add the aggregate IP prefix for the other Region and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection.
- F. Add the aggregate IP prefix for the company's entire AWS environment and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection.
- G. Remove all the VPC CIDR prefixes from the list of subnets advertised through the local Direct Connect connection
- H. Add both Regional aggregate IP prefixes to the list of subnets advertised through the Direct Connect connection on both sides of the network
- I. Configure data center routers to make routing decisions based on the BGP communities received.

Answer: AD

NEW QUESTION 54

A bank built a new version of its banking application in AWS using containers that connect to an on-premises database over VPN connection. This application version requires users to also update their client application. The bank plans to deprecate the earlier client version. However, the company wants to keep supporting earlier clients through their on-premises version of the application to serve a small portion of the customers who haven't yet upgraded. What design will allow the company to serve both newer and earlier clients in the MOST efficient way?

- A. Use an Amazon Route 53 multivalue answer routing policy to route older client traffic to the on-premises application version and the rest of the traffic to the new AWS based version.
- B. Use a Classic Load Balancer for the new application
- C. Route all traffic to the new application by using an Elastic Load Balancing (ELB) load balancer DNS
- D. Define a user-agent-based rule on the backend servers to redirect earlier clients to the on-premises application.
- E. Use an Application Load Balancer for the new application
- F. Register both the new and earlier applications as separate target groups and use path-based routing to route traffic based on the application version.
- G. Use an Application Load Balancer for the new application
- H. Register both the new and earlier application backends as separate target groups
- I. Use header-based routing to route traffic based on the application version.

Answer: D

NEW QUESTION 59

A company is deploying a new application on AWS. The application uses dynamic multicasting. The company has five VPCs that are all attached to a transit gateway. Amazon EC2 instances in each VPC need to be able to register dynamically to receive a multicast transmission. How should a network engineer configure the AWS resources to meet these requirements?

- A. Create a static source multicast domain within the transit gateway
- B. Associate the VPCs and applicable subnets with the multicast domain
- C. Register the multicast senders' network interface with the multicast domain
- D. Adjust the network ACLs to allow UDP traffic from the source to all receivers and to allow UDP traffic that is sent to the multicast group address.
- E. Create a static source multicast domain within the transit gateway
- F. Associate the VPCs and applicable subnets with the multicast domain
- G. Register the multicast senders' network interface with the multicast domain
- H. Adjust the network ACLs to allow TCP traffic from the source to all receivers and to allow TCP traffic that is sent to the multicast group address.
- I. Create an Internet Group Management Protocol (IGMP) multicast domain within the transit gateway. Associate the VPCs and applicable subnets with the multicast domain
- J. Register the multicast senders' network interface with the multicast domain
- K. Adjust the network ACLs to allow UDP traffic from the source to all receivers and to allow UDP traffic that is sent to the multicast group address.
- L. Create an Internet Group Management Protocol (IGMP) multicast domain within the transit gateway. Associate the VPCs and applicable subnets with the multicast domain
- M. Register the multicast senders' network interface with the multicast domain
- N. Adjust the network ACLs to allow TCP traffic from the source to all receivers and to allow TCP traffic that is sent to the multicast group address.

Answer: C

NEW QUESTION 62

An organization is replacing a tape backup system with a storage gateway. There is currently no connectivity to AWS. Initial testing is needed. What connection option should the organization use to get up and running at minimal cost?

- A. Use an internet connection.
- B. Set up an AWS VPN connection.
- C. Provision an AWS Direct Connection private virtual interface.
- D. Provision a Direct Connect public virtual interface.

Answer: A

NEW QUESTION 65

A company's AWS architecture consists of several VPCs. The VPCs include a shared services VPC and several application VPCs. The company has established network connectivity from all VPCs to the on-premises DNS servers. Applications that are deployed in the application VPCs must be able to resolve DNS for internally hosted domains on premises. The applications also must be able to resolve local VPC domain names and domains that are hosted in Amazon Route 53 private hosted zones. What should a network engineer do to meet these requirements?

- A. Create a new Route 53 Resolver inbound endpoint in the shared services VPC
- B. Create forwarding rules for the on-premises hosted domain
- C. Associate the rules with the new Resolver endpoint and each application VPC
- D. Update each application VPC's DHCP configuration to point DNS resolution to the new Resolver endpoint.
- E. Create a new Route 53 Resolver outbound endpoint in the shared services VPC
- F. Create forwarding rules for the on-premises hosted domain
- G. Associate the rules with the new Resolver endpoint and each application VPC.
- H. Create a new Route 53 Resolver outbound endpoint in the shared services VPC. Create forwarding rules for the on-premises hosted domain
- I. Associate the rules with the new Resolver endpoint and each application VPC. Update each application VPC's DHCP configuration to point DNS resolution to the new Resolver endpoint.
- J. Create a new Route 53 Resolver inbound endpoint in the shared services VPC
- K. Create forwarding rules for the on-premises hosted domain
- L. Associate the rules with the new Resolver endpoint and each application VPC.

Answer: B

Explanation:

Creating a new Route 53 Resolver outbound endpoint in the shared services VPC would enable forwarding of DNS queries from the VPC to on-premises¹. Creating forwarding rules for the on-premises hosted domains would enable specifying which domain names are forwarded to the on-premises DNS servers². Associating the rules with the new Resolver endpoint and each application VPC would enable applying the rules to the VPCs². This solution would not affect the default DNS resolution behavior of Route 53 Resolver for local VPC domain names and domains that are hosted in Route 53 private hosted zones³.

NEW QUESTION 70

A company is migrating an application from on premises to AWS. The company will host the application on Amazon EC2 instances that are deployed in a single VPC. During the migration period, DNS queries from the EC2 instances must be able to resolve names of on-premises servers. The migration is expected to take 3 months. After the 3-month migration period, the resolution of on-premises servers will no longer be needed. What should a network engineer do to meet these requirements with the LEAST amount of configuration?

- A. Set up an AWS Site-to-Site VPN connection between on premises and AWS
- B. Deploy an Amazon Route 53 Resolver outbound endpoint in the Region that is hosting the VPC.
- C. Set up an AWS Direct Connect connection with a private VIF
- D. Deploy an Amazon Route 53 Resolver inbound endpoint and a Route 53 Resolver outbound endpoint in the Region that is hosting the VPC.
- E. Set up an AWS Client VPN connection between on premises and AWS
- F. Deploy an Amazon Route 53 Resolver inbound endpoint in the VPC.

- G. Set up an AWS Direct Connect connection with a public V
- H. Deploy an Amazon Route 53 Resolver inbound endpoint in the Region that is hosting the VP
- I. Use the IP address that is assigned to the endpoint for connectivity to the on-premises DNS servers.

Answer: A

Explanation:

Setting up an AWS Site-to-Site VPN connection between on premises and AWS would enable a secure and encrypted connection over the public internet¹. Deploying an Amazon Route 53 Resolver outbound endpoint in the Region that is hosting the VPC would enable forwarding of DNS queries for on-premises servers to the on-premises DNS servers². This would allow EC2 instances in the VPC to resolve names of on-premises servers during the migration period. After the migration period, the Route 53 Resolver outbound endpoint can be deleted with minimal configuration changes.

NEW QUESTION 74

A company delivers applications over the internet. An Amazon Route 53 public hosted zone is the authoritative DNS service for the company and its internet applications, all of which are offered from the same domain name. A network engineer is working on a new version of one of the applications. All the application's components are hosted in the AWS Cloud. The application has a three-tier design. The front end is delivered through Amazon EC2 instances that are deployed in public subnets with Elastic IP addresses assigned. The backend components are deployed in private subnets from RFC1918. Components of the application need to be able to access other components of the application within the application's VPC by using the same host names as the host names that are used over the public internet. The network engineer also needs to accommodate future DNS changes, such as the introduction of new host names or the retirement of DNS entries. Which combination of steps will meet these requirements? (Choose three.)

- A. Add a geoproximity routing policy in Route 53.
- B. Create a Route 53 private hosted zone for the same domain name Associate the application's VPC with the new private hosted zone.
- C. Enable DNS hostnames for the application's VPC.
- D. Create entries in the private hosted zone for each name in the public hosted zone by using the corresponding private IP addresses.
- E. Create an Amazon EventBridge (Amazon CloudWatch Events) rule that runs when AWS CloudTrail logs a Route 53 API call to the public hosted zon
- F. Create an AWS Lambda function as the target of the rul
- G. Configure the function to use the event information to update the privatehosted zone.
- H. Add the private IP addresses in the existing Route 53 public hosted zone.

Answer: BCD

NEW QUESTION 75

A company is hosting an application on Amazon EC2 instances behind a Network Load Balancer (NLB). A solutions architect added EC2 instances in a second Availability Zone to improve the availability of the application. The solutions architect added the instances to the NLB target group. The company's operations team notices that traffic is being routed only to the instances in the first Availability Zone. What is the MOST operationally efficient solution to resolve this issue?

- A. Enable the new Availability Zone on the NLB
- B. Create a new NLB for the instances in the second Availability Zone
- C. Enable proxy protocol on the NLB
- D. Create a new target group with the instances in both Availability Zones

Answer: A

Explanation:

When adding instances in a new Availability Zone to an existing Network Load Balancer (NLB), it is important to ensure that the new Availability Zone is enabled on the NLB. This will allow traffic to be routed to instances in both Availability Zones. This can be done by editing the settings of the NLB and selecting the new Availability Zone from the list of available zones.

NEW QUESTION 80

An Australian ecommerce company hosts all of its services in the AWS Cloud and wants to expand its customer base to the United States (US). The company is targeting the western US for the expansion. The company's existing AWS architecture consists of four AWS accounts with multiple VPCs deployed in the ap-southeast-2 Region. All VPCs are attached to a transit gateway in ap-southeast-2. There are dedicated VPCs for each application service. The company also has VPCs for centralized security features such as proxies, firewalls, and logging. The company plans to duplicate the infrastructure from ap-southeast-2 to the us-west-1 Region. A network engineer must establish connectivity between the various applications in the two Regions. The solution must maximize bandwidth, minimize latency and minimize operational overhead. Which solution will meet these requirements?

- A. Create VPN attachments between the two transit gateway
- B. Configure the VPN attachments to use BGP routing between the two transit gateways.
- C. Peer the transit gateways in each Regio
- D. Configure routing between the two transit gateways for each Region's IP addresses.
- E. Create a VPN server in a VPC in each Regio
- F. Update the routing to point to the VPN servers for the IP addresses in alternate Regions.
- G. Attach the VPCs in us-west-1 to the transit gateway in ap-southeast-2.

Answer: B

Explanation:

Peering the transit gateways in each region would establish a private network connection between the two regions, allowing the company to route traffic between the VPCs in different regions without going over the public internet. This would help minimize latency and maximize bandwidth while reducing the operational overhead of managing multiple VPN connections.

NEW QUESTION 83

A network engineer is designing the architecture for a healthcare company's workload that is moving to the AWS Cloud. All data to and from the on-premises

environment must be encrypted in transit. All traffic also must be inspected in the cloud before the traffic is allowed to leave the cloud and travel to the on-premises environment or to the internet.

The company will expose components of the workload to the internet so that patients can reserve appointments. The architecture must secure these components and protect them against DDoS attacks. The architecture also must provide protection against financial liability for services that scale out during a DDoS event. Which combination of steps should the network engineer take to meet all these requirements for the workload? (Choose three.)

- A. Use Traffic Mirroring to copy all traffic to a fleet of traffic capture appliances.
- B. Set up AWS WAF on all network components.
- C. Configure an AWS Lambda function to create Deny rules in security groups to block malicious IP addresses.
- D. Use AWS Direct Connect with MACsec support for connectivity to the cloud.
- E. Use Gateway Load Balancers to insert third-party firewalls for inline traffic inspection.
- F. Configure AWS Shield Advanced and ensure that it is configured on all public assets.

Answer: DEF

Explanation:

To meet the requirements for the healthcare company's workload that is moving to the AWS Cloud, the network engineer should take the following steps:

- Use AWS Direct Connect with MACsec support for connectivity to the cloud to ensure that all data to and from the on-premises environment is encrypted in transit (Option D).
- Use Gateway Load Balancers to insert third-party firewalls for inline traffic inspection to inspect all traffic in the cloud before it is allowed to leave (Option E).
- Configure AWS Shield Advanced and ensure that it is configured on all public assets to secure components exposed to the internet against DDoS attacks and provide protection against financial liability for services that scale out during a DDoS event (Option F).

These steps will help ensure that all data is encrypted in transit, all traffic is inspected before leaving the cloud, and components exposed to the internet are secured against DDoS attacks.

NEW QUESTION 85

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

ANS-C01 Practice Exam Features:

- * ANS-C01 Questions and Answers Updated Frequently
- * ANS-C01 Practice Questions Verified by Expert Senior Certified Staff
- * ANS-C01 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * ANS-C01 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The ANS-C01 Practice Test Here](#)